

# UT 2,5 - Feed-through terminal block



3044076

<https://www.phoenixcontact.com/pc/products/3044076>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 1000 V, nominal current: 24 A, number of connections: 2, connection method: Screw connection, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup> - 4 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: gray

## Your advantages

- Globally recognized: Internationally proven screw connection
- Maintenance-free and vibration-resistant thanks to the patented Reakdyn principle
- Space savings and flexibility with the connection of two identical conductors
- Long-term stable connections with the use of high-quality materials
- Low self-heating due to high contact forces
- Full flexibility thanks to the standardized CLIPLINE complete bridging, marking, and testing accessories
- Vibration-resistant and maintenance-free conductor connection

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3044076       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Product key                          | BE1111        |
| GTIN                                 | 4017918960377 |
| Weight per piece (including packing) | 7.933 g       |
| Weight per piece (excluding packing) | 7.441 g       |
| Customs tariff number                | 85369010      |
| Country of origin                    | DE            |

# UT 2,5 - Feed-through terminal block

3044076

<https://www.phoenixcontact.com/pc/products/3044076>



## Technical data

### Notes

#### General

|      |                                                                                                                                       |
|------|---------------------------------------------------------------------------------------------------------------------------------------|
| Note | With a free-hanging connection, an insulating foil has to be placed between the plug connection and electrically conductive surfaces. |
|      | Current and voltage are determined by the plug used                                                                                   |

### Product properties

|                       |                             |
|-----------------------|-----------------------------|
| Product type          | Feed-through terminal block |
| Product family        | UT                          |
| Area of application   | Railway industry            |
|                       | Machine building            |
|                       | Plant engineering           |
|                       | Process industry            |
| Number of connections | 2                           |
| Number of rows        | 1                           |
| Potentials            | 1                           |

#### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 0.77 W |

### Connection data

|                                                               |                                            |
|---------------------------------------------------------------|--------------------------------------------|
| Number of connections per level                               | 2                                          |
| Nominal cross section                                         | 2.5 mm <sup>2</sup>                        |
| Rated cross section AWG                                       | 12                                         |
| Connection method                                             | Screw connection                           |
| Screw thread                                                  | M3                                         |
| Tightening torque                                             | 0.5 ... 0.6 Nm                             |
| Stripping length                                              | 9 mm                                       |
| Internal cylindrical gage                                     | A3                                         |
| Connection in acc. with standard                              | IEC 60947-7-1                              |
| Conductor cross-section rigid                                 | 0.14 mm <sup>2</sup> ... 4 mm <sup>2</sup> |
| Cross section AWG                                             | 26 ... 12 (converted acc. to IEC)          |
| Conductor cross-section flexible                              | 0.14 mm <sup>2</sup> ... 4 mm <sup>2</sup> |
| Conductor cross-section, flexible [AWG]                       | 26 ... 12 (converted acc. to IEC)          |
| Conductor cross-section flexible ultrasound-compressed        | 0.34 mm <sup>2</sup> ... 4 mm <sup>2</sup> |
| Conductor cross-section, flexible [AWG] ultrasound-compressed | 22 ... 12 (converted acc. to IEC)          |

# UT 2,5 - Feed-through terminal block



3044076

<https://www.phoenixcontact.com/pc/products/3044076>

|                                                                                           |                                                                                                                              |
|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Conductor cross-section flexible (ferrule without plastic sleeve)                         | 0.14 mm² ... 2.5 mm²                                                                                                         |
| Flexible conductor cross-section (ferrule with plastic sleeve)                            | 0.14 mm² ... 2.5 mm²                                                                                                         |
| 2 conductors with same cross section, rigid                                               | 0.14 mm² ... 1.5 mm²                                                                                                         |
| 2 conductors with same cross section, flexible                                            | 0.14 mm² ... 1.5 mm²                                                                                                         |
| 2 conductors with same cross section, flexible, with ferrule without plastic sleeve       | 0.14 mm² ... 1.5 mm²                                                                                                         |
| 2 conductors with the same cross section, flexible, with TWIN ferrule with plastic sleeve | 0.5 mm² ... 1.5 mm²                                                                                                          |
| Nominal cross section                                                                     | 2.5 mm²                                                                                                                      |
| Nominal current                                                                           | 24 A                                                                                                                         |
| Maximum load current                                                                      | 32 A (with 4 mm² conductor cross-section)                                                                                    |
| Nominal voltage                                                                           | 1000 V                                                                                                                       |
| Note                                                                                      | Note: Product releases, connection cross sections and notes on connecting aluminum cables can be found in the download area. |

## Ex data

### Rated data (ATEX/IECEx)

|                                                                          |                                     |
|--------------------------------------------------------------------------|-------------------------------------|
| Identification                                                           | Ex II 2 GD Ex eb IIC Gb             |
| Operating temperature range                                              | -60 °C ... 110 °C                   |
| Ex-certified accessories                                                 | 3047028 D-UT 2,5/10                 |
|                                                                          | 3047167 ATP-UT                      |
|                                                                          | 1205053 SZS 0,6X3,5                 |
|                                                                          | 3022276 CLIPFIX 35-5                |
|                                                                          | 3022218 CLIPFIX 35                  |
| List of bridges                                                          | Plug-in bridge / FBS 2-5 / 3030161  |
|                                                                          | Plug-in bridge / FBS 3-5 / 3030174  |
|                                                                          | Plug-in bridge / FBS 4-5 / 3030187  |
|                                                                          | Plug-in bridge / FBS 5-5 / 3030190  |
|                                                                          | Plug-in bridge / FBS 10-5 / 3030213 |
|                                                                          | Plug-in bridge / FBS 20-5 / 3030226 |
| Bridge data                                                              | 21 A (2.5 mm²)                      |
| Ex temperature increase                                                  | 40 K (23.3 A / 2.5 mm²)             |
| for bridging with bridge                                                 | 690 V                               |
| - At bridging between non-adjacent terminal blocks                       | 352 V                               |
| - At bridging between non-adjacent terminal blocks via PE terminal block | 275 V                               |
| - At cut-to-length bridging with cover                                   | 220 V                               |
| - At cut-to-length bridging with partition plate                         | 275 V                               |
| Rated insulation voltage                                                 | 630 V                               |
| output                                                                   | (Permanent)                         |

### Ex level General

|                      |       |
|----------------------|-------|
| Rated voltage        | 690 V |
| Rated current        | 21 A  |
| Maximum load current | 28 A  |

# UT 2,5 - Feed-through terminal block



3044076

<https://www.phoenixcontact.com/pc/products/3044076>

|                    |         |
|--------------------|---------|
| Contact resistance | 0.41 mΩ |
|--------------------|---------|

## Ex connection data General

|                                                       |                      |
|-------------------------------------------------------|----------------------|
| Torque range                                          | 0.5 Nm ... 0.6 Nm    |
| Nominal cross section                                 | 2.5 mm²              |
| Rated cross section AWG                               | 14                   |
| Connection capacity rigid                             | 0.14 mm² ... 4 mm²   |
| Connection capacity AWG                               | 26 ... 12            |
| Connection capacity flexible                          | 0.14 mm² ... 2.5 mm² |
| Connection capacity AWG                               | 26 ... 14            |
| 2 conductors with same cross section, solid           | 0.14 mm² ... 1.5 mm² |
| 2 conductors with the same cross-section AWG rigid    | 26 ... 16            |
| 2 conductors with same cross section, stranded        | 0.14 mm² ... 1.5 mm² |
| 2 conductors with the same cross-section AWG flexible | 26 ... 16            |

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 5.2 mm  |
| End cover width    | 2.2 mm  |
| Height             | 47.7 mm |
| Depth              | 46.9 mm |
| Depth on NS 35/7,5 | 47.5 mm |
| Depth on NS 35/15  | 55 mm   |

## Material specifications

|                                                                  |                 |
|------------------------------------------------------------------|-----------------|
| Color                                                            | gray (RAL 7042) |
| Flammability rating according to UL 94                           | V0              |
| Insulating material group                                        | I               |
| Insulating material                                              | PA              |
| Static insulating material application in cold                   | -60 °C          |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C          |
| Fire protection for rail vehicles (DIN EN 45545-2) R22           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R23           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R24           | HL 1 - HL 3     |
| Fire protection for rail vehicles (DIN EN 45545-2) R26           | HL 1 - HL 3     |
| Surface flammability NFPA 130 (ASTM E 162)                       | passed          |
| Specific optical density of smoke NFPA 130 (ASTM E 662)          | passed          |
| Smoke gas toxicity NFPA 130 (SMP 800C)                           | passed          |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 9.8 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                   |                                |
|-----------------------------------|--------------------------------|
| Requirement temperature-rise test | Increase in temperature ≤ 45 K |
|-----------------------------------|--------------------------------|

# UT 2,5 - Feed-through terminal block



3044076

<https://www.phoenixcontact.com/pc/products/3044076>

|                                                  |             |
|--------------------------------------------------|-------------|
| Result                                           | Test passed |
|                                                  | Test passed |
| Short-time withstand current 2.5 mm <sup>2</sup> | 0.3 kA      |
| Result                                           | Test passed |
| Power-frequency withstand voltage                |             |
| Test voltage setpoint                            | 2.2 kV      |
| Result                                           | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 35       |
| Test force setpoint     | 1 N         |
| Result                  | Test passed |

### Test for conductor damage and slackening

|                                |                               |
|--------------------------------|-------------------------------|
| Rotation speed                 | 10 (+/- 2) rpm                |
| Revolutions                    | 135                           |
| Conductor cross-section/weight | 0.14 mm <sup>2</sup> / 0.2 kg |
|                                | 2.5 mm <sup>2</sup> / 0.7 kg  |
|                                | 4 mm <sup>2</sup> / 0.9 kg    |
| Result                         | Test passed                   |

## Environmental and real-life conditions

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Oscillation/broadband noise

|                        |                                                  |
|------------------------|--------------------------------------------------|
| Specification          | DIN EN 50155 (VDE 0115-200):2022-06              |
| Spectrum               | Long life test category 2, bogie-mounted         |
| Frequency              | f <sub>1</sub> = 5 Hz to f <sub>2</sub> = 250 Hz |
| ASD level              | 6.12 (m/s <sup>2</sup> ) <sup>2</sup> /Hz        |
| Acceleration           | 3.12g                                            |
| Test duration per axis | 5 h                                              |
| Test directions        | X-, Y- and Z-axis                                |
| Result                 | Test passed                                      |

# UT 2,5 - Feed-through terminal block



3044076

<https://www.phoenixcontact.com/pc/products/3044076>

## Shocks

|                                |                                     |
|--------------------------------|-------------------------------------|
| Specification                  | DIN EN 50155 (VDE 0115-200):2022-06 |
| Pulse shape                    | Half-sine                           |
| Acceleration                   | 5g                                  |
| Shock duration                 | 30 ms                               |
| Number of shocks per direction | 3                                   |
| Test directions                | X-, Y- and Z-axis (pos. and neg.)   |
| Result                         | Test passed                         |

## Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)                                                    |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# UT 2,5 - Feed-through terminal block

3044076

<https://www.phoenixcontact.com/pc/products/3044076>



## Drawings

Circuit diagram



# UT 2,5 - Feed-through terminal block



3044076

<https://www.phoenixcontact.com/pc/products/3044076>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/3044076>

### DNV

Approval ID: TAE00001S9



### CSA

Approval ID: 13631



### IECEE CB Scheme

Approval ID: DE1-63061\_M1

|       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------|-----------------------|-----------------------|-------------------|-----------------------------|
| keine |                       |                       |                   |                             |
|       | 1000 V                | 24 A                  | -                 | 0.2 - 2.5                   |



### cULus Recognized

Approval ID: E60425

|                            | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|----------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
| B                          |                       |                       |                   |                             |
|                            | 600 V                 | 20 A                  | 26 - 12           | -                           |
| Multi-conductor connection | 600 V                 | 20 A                  | 26 - 16           | -                           |
| C                          |                       |                       |                   |                             |
|                            | 600 V                 | 20 A                  | 26 - 12           | -                           |
| Multi-conductor connection | 600 V                 | 20 A                  | 26 - 16           | -                           |



### LR

Approval ID: LR24100022TA



### VDE Zeichengenehmigung

Approval ID: 40013658

|       | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------|-----------------------|-----------------------|-------------------|-----------------------------|
| keine |                       |                       |                   |                             |
|       | 1000 V                | 24 A                  | -                 | 0.2 - 2.5                   |



### CSA

Approval ID: 13631



# UT 2,5 - Feed-through terminal block



3044076

<https://www.phoenixcontact.com/pc/products/3044076>

|  <b>ATEX</b><br>Approval ID: KEMA04ATEX2048U |                       |                       |                   |                             |
|-------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                               | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| keine                                                                                                                         |                       |                       |                   |                             |
| Only flexible conductors                                                                                                      | 690 V                 | 21 A                  | -                 | 0.14 - 2.5                  |
| Only rigid conductors                                                                                                         | 690 V                 | 28 A                  | -                 | 0.14 - 4                    |

|  <b>EAC Ex</b><br>Approval ID: KZ 7500525010101950 |  |  |  |  |
|-------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|-------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|  <b>IECEx</b><br>Approval ID: IECEx KEM 06.0027U |                       |                       |                   |                             |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                                                                                                   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| keine                                                                                                                             |                       |                       |                   |                             |
| Only flexible conductors                                                                                                          | 690 V                 | 21 A                  | -                 | 0.14 - 2.5                  |
| Only rigid conductors                                                                                                             | 690 V                 | 28 A                  | -                 | 0.14 - 4                    |

|  <b>CCC</b><br>Approval ID: 2020322313000622 |  |  |  |  |
|---------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|---------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

|  <b>UKCA-EX</b><br>Approval ID: DEKRA 21UKEX0304U |  |  |  |  |
|--------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|
|--------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|

| <b>UL Comp Hazloc CA US</b><br>Approval ID: UL-US-2552444-2 |                       |                       |                   |                             |
|-------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                                             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| B                                                           |                       |                       |                   |                             |
|                                                             | 600 V                 | 20 A                  | 26 - 12           | -                           |
| C                                                           |                       |                       |                   |                             |
|                                                             | 600 V                 | 20 A                  | 26 - 12           | -                           |

# UT 2,5 - Feed-through terminal block



3044076

<https://www.phoenixcontact.com/pc/products/3044076>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27250101 |
| ECLASS-15.0 | 27250101 |

### ETIM

|           |          |
|-----------|----------|
| ETIM 10.0 | EC000897 |
|-----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# UT 2,5 - Feed-through terminal block



3044076

<https://www.phoenixcontact.com/pc/products/3044076>

## Environmental product compliance

### EU RoHS

|                                         |      |
|-----------------------------------------|------|
| Fulfills EU RoHS substance requirements | Yes  |
| Exemption                               | 6(c) |

### China RoHS

|                                        |                                                                                                                                                                                                                                   |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Environment friendly use period (EFUP) | EFUP-50                                                                                                                                                                                                                           |
|                                        | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |

### EU REACH SVHC

|                                     |                                      |
|-------------------------------------|--------------------------------------|
| REACH candidate substance (CAS No.) | Lead(CAS: 7439-92-1)                 |
| SCIP                                | de09f2d7-a4de-4956-bd20-4169c388eaaf |

### EF3.1 Climate Change

|         |              |
|---------|--------------|
| CO2e kg | 0.02 kg CO2e |
|---------|--------------|

Phoenix Contact 2026 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)