

```
mysql> CREATE DATABASE IF NOT EXISTS employeedb1;  
Query OK, 1 row affected (0.05 sec)
```

```
mysql> USE employeedb1;  
Database changed
```

```
mysql> CREATE TABLE IF NOT EXISTS employees (  
->     emp_id INT PRIMARY KEY,  
->     emp_name VARCHAR(50),  
->     dept_id INT,  
->     salary DECIMAL(10,2)  
-> );
```

```
Query OK, 0 rows affected (0.05 sec)
```

```
mysql> INSERT INTO employees VALUES
```

```
-> (101, 'Rahul', 1, 50000),  
-> (102, 'Priya', 2, 65000),  
-> (103, 'Anil', 1, 55000),  
-> (104, 'Sneha', 3, 70000),  
-> (105, 'Kiran', 2, 48000);
```

```
Query OK, 5 rows affected (0.01 sec)
```

```
Records: 5  Duplicates: 0  Warnings: 0
```

```
mysql> DROP PROCEDURE IF EXISTS GetEmployees  
-> ^C
```

```
mysql> DROP PROCEDURE IF EXISTS GetEmployees;
```

```
Query OK, 0 rows affected, 1 warning (0.01 sec)
```

```
mysql> DELIMITER $$
```

```
mysql> CREATE PROCEDURE GetEmployees()
```

```
-> BEGIN  
->     SELECT * FROM employees;  
-> END $$
```

```
Query OK, 0 rows affected (0.01 sec)
```

```

mysql>
mysql> DELIMITER ;
mysql> CALL GetEmployees();
+-----+-----+-----+-----+
| emp_id | emp_name | dept_id | salary |
+-----+-----+-----+-----+
|    101 | Rahul    |      1  | 50000.00 |
|    102 | Priya    |      2  | 65000.00 |
|    103 | Anil     |      1  | 55000.00 |
|    104 | Sneha    |      3  | 70000.00 |
|    105 | Kiran    |      2  | 48000.00 |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)

Query OK, 0 rows affected (0.04 sec)

mysql> DROP PROCEDURE IF EXISTS GetEmployeeById
Query OK, 0 rows affected, 1 warning (0.00 sec)

mysql>
mysql> DELIMITER $$
mysql>
mysql> CREATE PROCEDURE GetEmployeeById(IN eid
-> BEGIN
->     SELECT *
->     FROM employees
->     WHERE emp_id = eid;
-> END $$
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql>
mysql> CALL GetEmployeeById(102);
+-----+-----+-----+-----+
| emp_id | emp_name | dept_id | salary |
+-----+-----+-----+-----+
|    102 | Priya    |      2  | 65000.00 |
+-----+-----+-----+-----+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.01 sec)

```

Query OK, 0 rows affected (0.01 sec)

mysql> CALL GetEmployeeById(104);

| emp_id | emp_name | dept_id | salary   |
|--------|----------|---------|----------|
| 104    | Sneha    | 3       | 70000.00 |

1 row in set (0.00 sec)

Query OK, 0 rows affected (0.01 sec)

mysql> DROP PROCEDURE IF EXISTS IncreaseSalary;  
Query OK, 0 rows affected, 1 warning (0.00 sec)

```
mysql>
mysql> DELIMITER $$
mysql>
mysql> CREATE PROCEDURE IncreaseSalary(
    ->     IN eid INT,
    ->     IN amount DECIMAL(10,2)
    -> )
    -> BEGIN
    ->     UPDATE employees
    ->     SET salary = salary + amount
    ->     WHERE emp_id = eid;
    -> END $$
```

Query OK, 0 rows affected (0.01 sec)

```
mysql>
mysql> DELIMITER ;
mysql>
mysql> CALL IncreaseSalary(101, 5000);
Query OK, 1 row affected (0.00 sec)
```

```
mysql>
mysql> SELECT *
    -> FROM employees
    -> WHERE emp_id = 101;
```

| emp_id | emp_name | dept_id | salary   |
|--------|----------|---------|----------|
| 101    | Rahul    | 1       | 55000.00 |

1 row in set (0.00 sec)

mysql> DROP PROCEDURE IF EXISTS AvgSalary;

```
mysql>
mysql> DELIMITER ;
mysql>
mysql> CALL EmployeeDepartment();
```

| emp_name | dept_name | salary   |
|----------|-----------|----------|
| Rahul    | CSE       | 55000.00 |
| Priya    | ECE       | 65000.00 |
| Anil     | CSE       | 55000.00 |
| Sneha    | EEE       | 70000.00 |
| Kiran    | ECE       | 48000.00 |

5 rows in set (0.00 sec)

Query OK, 0 rows affected (0.03 sec)

```
mysql> DROP PROCEDURE IF EXISTS DepartmentAverageSalary;
Query OK, 0 rows affected, 1 warning (0.00 sec)
```

```
mysql>
mysql> DELIMITER $$
mysql>
mysql> CREATE PROCEDURE DepartmentAverageSalary()
-> BEGIN
->     SELECT d.dept_name,
->           COUNT(e.emp_id) AS EmployeeCount,
->           AVG(e.salary) AS AverageSalary
->     FROM employees e
->     JOIN departments d
->       ON e.dept_id = d.dept_id
->     GROUP BY d.dept_id, d.dept_name;
-> END $$
```

Query OK, 0 rows affected (0.01 sec)

```
mysql>
mysql> DELIMITER ;
mysql>
mysql> CALL DepartmentAverageSalary();
```

| dept_name | EmployeeCount | AverageSalary |
|-----------|---------------|---------------|
| CSE       | 2             | 55000.000000  |
| ECE       | 2             | 56500.000000  |
| EEE       | 1             | 70000.000000  |

```
MySQL 8.0 Command Line Cli X + v
3 rows in set (0.00 sec)

Query OK, 0 rows affected (0.01 sec)

mysql> DROP PROCEDURE IF EXISTS SalaryStatus;
Query OK, 0 rows affected, 1 warning (0.00 sec)

mysql>
mysql> DELIMITER $$
mysql>
mysql> CREATE PROCEDURE SalaryStatus(IN eid INT)
-> BEGIN
->     DECLARE sal DECIMAL(10,2);
->
->     SELECT salary INTO sal
->     FROM employees
->     WHERE emp_id = eid;
->
->     IF sal >= 60000 THEN
->         SELECT 'High Salary' AS Status;
->     ELSE
->         SELECT 'Low Salary' AS Status;
->     END IF;
-> END $$
Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> DELIMITER ;
mysql>
mysql> CALL SalaryStatus(102);
+-----+
| Status      |
+-----+
| High Salary |
+-----+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.00 sec)

mysql> CALL SalaryStatus(101);
+-----+
| Status      |
+-----+
| Low Salary  |
+-----+
1 row in set (0.00 sec)
```