

Markov Decision Processes

Chen-Yu Wei


Sequence of Actions



To win the game, the learner has to take a sequence of actions $a_1 \rightarrow a_2 \rightarrow \dots \rightarrow a_H$.
The effect of a particular action may not be revealed instantaneously.

- Some effect may be revealed instantaneously
- Some may be revealed later

Sequence of Actions



Deterministic World


$$R(a)$$


$$R(x, a)$$

$$\pi^* = \operatorname{argmax}_a R(a)$$

$$\pi^*(x) = \operatorname{argmax}_a R(x, a)$$

Which path gives us the highest **total reward**?






$V^*(s) :=$ maximum total reward starting from state s

$Q^*(s, a) :=$ maximum total reward starting from state s and taking action a **for one step**, and then following the optimal strategy

$\pi^*(s) :=$ optimal decision on state s



$$V^*(H_4) = 1 \quad Q^*(H_3, R) = 0 + 1 = 1 \quad V^*(H_3) = 2.5$$

$$Q^*(H_3, G) = -0.5 + 3 = 2.5$$

$$V^*(M_4) = 3 \quad Q^*(M_3, R) = 0 + 1 = 1 \quad V^*(M_3) = 4$$

$$Q^*(M_3, P) = -1 + 5 = 4$$

$$V^*(L_4) = 5 \quad Q^*(L_3, G) = -0.5 + 3 = 2.5 \quad V^*(L_3) = 4$$

$$Q^*(L_3, P) = -1 + 5 = 4$$

$$Q^*(H_2, R) = 0 + 2.5 = 2.5 \quad V^*(H_2) = 3.5$$


$$Q^*(H_2, G) = -0.5 + 4 = 3.5$$

$$Q^*(M_2, R) = \quad V^*(M_2) = ?$$

$$Q^*(M_2, P) =$$

$$Q^*(L_2, G) = \quad V^*(L_2) = ?$$

$$Q^*(L_2, P) =$$




Relation between Q^*, V^*, π^* :

$$Q^*(s, a) = R(s, a) + V^*(\text{next_state}(s, a))$$

$$V^*(s) = \max_a Q^*(s, a)$$

$$\pi^*(s) = \operatorname{argmax}_a Q^*(s, a)$$



General algorithm (Value Iteration) --- see next slide for a more detailed version

Repeat until Q, V no longer changes:

$$Q(s, a) \leftarrow R(s, a) + V(\text{next_state}(s, a)) \quad \text{for all } (s, a)$$

$$V(s) = \max_a Q(s, a) \quad \text{for all } s$$

$$\pi^*(s) = \operatorname{argmax}_a Q(s, a)$$

(for the last layer states. $Q(s, a) \leftarrow R(s, a)$)

Value Iteration:

Initialize $Q_0(s, a) \leftarrow 0$, $V_0(s) \leftarrow 0$ for all (s, a)

For $i = 1, 2, \dots$

$Q_i(s, a) \leftarrow R(s, a) + V_{i-1}(\text{next_state}(s, a))$ for all (s, a)

$V_i(s) = \max_a Q_i(s, a)$ for all s

If $Q_i(s, a) = Q_{i-1}(s, a)$ for all (s, a) : **break**


$\pi^*(s) = \operatorname{argmax}_a Q_{\text{final}}(s, a)$

If s is a terminal state, this line is simply $Q_i(s, a) \leftarrow R(s, a)$

If every path in the graph has length $\leq K$, then Value Iteration will terminate in $\leq K + 1$ iterations.


$$Q_0(s, a) = 0$$

$$V_0(s) = 0$$




$$Q_1(s, a) = R(s, a) + V_0(\text{next}(s, a))$$

$$V_1(s) = \max_a Q_1(s, a)$$




$$Q_2(s, a) = R(s, a) + V_1(\text{next}(s, a))$$

$$V_2(s) = \max_a Q_2(s, a)$$




$$Q_3(s, a) = R(s, a) + V_2(\text{next}(s, a))$$

$$V_3(s) = \max_a Q_3(s, a)$$




$$Q_4(s, a) = R(s, a) + V_3(\text{next}(s, a))$$

$$V_4(s) = \max_a Q_4(s, a)$$




$$Q_5(s, a) = R(s, a) + V_4(\text{next}(s, a))$$

$$V_5(s) = \max_a Q_5(s, a)$$



$$Q_6(s, a) = R(s, a) + V_5(\text{next}(s, a))$$


$$V_6(s) = \max_a Q_6(s, a)$$





Stochastic Worlds

Now, suppose taking an action does **not** lead to the desired state deterministically.

Instead, with probability 0.8, it goes to the state as specified in the figure;
with probability 0.1 each, it goes to the other two states.





$$V^*(H_4) = 1$$

$$Q^*(H_3, R) =$$

$$V^*(H_3) =$$

$$V^*(M_4) = 3$$

$$Q^*(H_3, G) =$$

$$Q^*(M_3, R) =$$

$$V^*(M_3) =$$


$$V^*(L_4) = 5$$

$$Q^*(M_3, P) =$$

$$Q^*(L_3, G) =$$

$$V^*(L_3) =$$

$$Q^*(L_3, P) =$$



$$V^*(H_3) =$$

$$Q^*(H_2, \text{Red}) =$$

$$V^*(H_2) =$$

$$Q^*(H_2, \text{Green}) =$$

$$V^*(M_3) =$$

$$Q^*(M_2, \text{Red}) =$$

$$V^*(M_2) =$$


$$Q^*(M_2, \text{Purple}) =$$

$$V^*(L_3) =$$

$$Q^*(L_2, \text{Green}) =$$

$$V^*(L_2) =$$

$$Q^*(L_2, \text{Purple}) =$$



Relation between Q^*, V^*, π^* :


$$Q^*(s, a) = R(s, a) + \sum_{s'} P(s'|s, a) V^*(s')$$

$$V^*(s) = \max_a Q^*(s, a)$$

$$\pi^*(s) = \operatorname{argmax}_a Q^*(s, a)$$

Transition probability $P(s'|s, a)$:

The probability of going to state s' if we take action a on state s



Value Iteration:

Repeat until Q, V no longer changes:

$$Q(s, a) \leftarrow R(s, a) + \sum_{s'} P(s'|s, a) V(s') \quad \text{for all } (s, a)$$

$$V(s) = \max_a Q(s, a) \quad \text{for all } s$$


$$\pi^*(s) = \operatorname{argmax}_a Q(s, a)$$


Infinite / Long-Horizon Case

What if there is no “terminal state”?

- Tasks with terminal states
 - Tic-Tac-Toe
 - Tetris
 - Robot doing housework
- Tasks without terminal states (or tasks with very **long horizon** or **loops**)
 - Driving
 - Inventory control

How to gain most reward **in the long run?** (or, in 1000 rounds)





Repeat until Q, V no longer changes? (Won't terminate)

$$Q(s, a) \leftarrow R(s, a) + \sum_{s'} P(s'|s, a) V(s') \quad \text{for all } (s, a)$$

$$V(s) = \max_a Q(s, a) \quad \text{for all } s$$

$$\pi^*(s) = \operatorname{argmax}_a Q(s, a)$$

Discounting

$$Q^*(s, a) = R(s, a) + \gamma \sum_{s'} P(s'|s, a) V^*(s')$$

$$V^*(s) = \max_a Q^*(s, a)$$

$$\pi^*(s) = \operatorname{argmax}_a Q^*(s, a)$$

To calculate Q^*, V^*, π^* --- see later slide for a more detailed version


Repeat until Q, V becomes stable:

$$Q(s, a) \leftarrow R(s, a) + \gamma \sum_{s'} P(s'|s, a) V(s') \quad \text{for all } (s, a)$$


$$V(s) = \max_a Q(s, a) \quad \text{for all } s$$

$$\pi^*(s) = \operatorname{argmax}_a Q(s, a)$$

Discounting: Equivalent View



Original Transition



Consider the Q^*, V^* in this modified graph.

Modified Transition: on any state, taking any action,

Next state = $\begin{cases} \text{terminal state} & \text{with probability } 1 - \gamma \\ \text{following } P(s'|s, a) & \text{with probability } \gamma \end{cases}$

Discounting

Effective horizon length (the expected length before going to the dummy terminal state) = $\frac{1}{1-\gamma}$

- Goal of discounting: Make V^*, Q^* finite even when there are positive loops
 - γ should be strictly smaller than 1
- The modification should still approximate the learner's goal well enough
 - γ should be sufficiently close to 1

Usually, γ is set to some value like 0.99, but it depends on the application

Discounting

Value Iteration with discounting

Initialize $Q_0(s, a) \leftarrow 0$, $V_0(s) \leftarrow 0$ for all (s, a)

For $i = 1, 2, \dots$

$Q_i(s, a) \leftarrow R(s, a) + \gamma V_{i-1}(\text{next_state}(s, a))$ for all (s, a)


$V_i(s) = \max_a Q_i(s, a)$ for all s

If $|Q_i(s, a) - Q_{i-1}(s, a)| \leq \epsilon$ for all (s, a) : **break**


$\pi^*(s) = \operatorname{argmax}_a Q_{\text{final}}(s, a)$

$$Q_0(s, a) = 0$$

$$V_0(s) = 0$$




$$\gamma = 0.95$$




$$\gamma = 1.0$$

$$Q_i(s, a) \leftarrow R(s, a) + \gamma \sum_{s'} P(s'|s, a) V_{i-1}(s')$$

$$V_i(s) \leftarrow \max_a Q_i(s, a)$$



$\gamma = 0.95$





$\gamma = 1.0$

Iteration $i = 1$

$$Q_i(s, a) \leftarrow R(s, a) + \gamma \sum_{s'} P(s'|s, a) V_{i-1}(s')$$



$$V_i(s) \leftarrow \max_a Q_i(s, a)$$



Iteration $i = 2$

$$Q_i(s, a) \leftarrow R(s, a) + \gamma \sum_{s'} P(s'|s, a) V_{i-1}(s')$$



$$V_i(s) \leftarrow \max_a Q_i(s, a)$$



Iteration $i = 3$

$$Q_i(s, a) \leftarrow R(s, a) + \gamma \sum_{s'} P(s'|s, a) V_{i-1}(s')$$



$$V_i(s) \leftarrow \max_a Q_i(s, a)$$



Iteration $i = 4$

$$Q_i(s, a) \leftarrow R(s, a) + \gamma \sum_{s'} P(s'|s, a) V_{i-1}(s')$$


$$V_i(s) \leftarrow \max_a Q_i(s, a)$$




Iteration $i = 5$

$$Q_i(s, a) \leftarrow R(s, a) + \gamma \sum_{s'} P(s'|s, a) V_{i-1}(s')$$

$$V_i(s) \leftarrow \max_a Q_i(s, a)$$



$\gamma = 0.95$




$\gamma = 1.0$


Iteration $i = 20$

$$Q_i(s, a) \leftarrow R(s, a) + \gamma \sum_{s'} P(s'|s, a) V_{i-1}(s')$$

$$V_i(s) \leftarrow \max_a Q_i(s, a)$$



$\gamma = 0.95$




$\gamma = 1.0$


Iteration $i = 21$

$$Q_i(s, a) \leftarrow R(s, a) + \gamma \sum_{s'} P(s'|s, a) V_{i-1}(s')$$

$$V_i(s) \leftarrow \max_a Q_i(s, a)$$



$\gamma = 0.95$





$\gamma = 1.0$

Iteration $i = 100$

$$Q_i(s, a) \leftarrow R(s, a) + \gamma \sum_{s'} P(s'|s, a) V_{i-1}(s')$$

$$V_i(s) \leftarrow \max_a Q_i(s, a)$$



Iteration $i = 101$