19 DHT11 temperature and humidity module

1 Project process:



2 Project source code:

```
pi@raspberrypi: ~/keyes_螺丝帮妈鹃琅编x增谦楠欢篮勤研/DHT11
#include <wiringPi.h>
#include <stdio.h>
#include <stdlib.h>
#include <stdint.h>
#define MAX_TIME 85
#define DHT11PIN 7
#define ATTEMPTS 5                  //retry 5 times when no response
int dht11_val[5]={0,0,0,0,0};

int dht11_read_val(){
    uint8_t laststate=HIGH;         //last state
    uint8_t counter=0;
    uint8_t j=0,i;
    for(i=0;i<5;i++)
        dht11_val[i]=0;

    //host send start signal
    pinMode(DHT11PIN,OUTPUT);       //set pin to output
    digitalWrite(DHT11PIN,LOW);     //set to low at least 18ms
    delay(18);
    digitalWrite(DHT11PIN,HIGH);    //set to high 20-40us
    delayMicroseconds(40);

    //start recieve dht response
    pinMode(DHT11PIN,INPUT);        //set pin to input
    for(i=0;i<MAX_TIME;i++)
"DHT11.c" 68L, 2396C                                1,1           Top
```

3 Project circuit connection

```
pi@raspberrypi: ~/keyes_螺丝帮妈鹃琅编x增谦楠欢篮勤研/DHT11
 +-----+-----+---------+------+---+--B Plus--+---+------+---------+-----+-----+
 | BCM | wPi |   Name  | Mode | V | Physical | V | Mode | Name    | wPi | BCM |
 +-----+-----+---------+------+---+----++----+---+------+---------+-----+-----+
 |     |     |    3.3v |      |   |  1 || 2  |   |      | 5v      |     |     |
 |   2 |   8 |   SDA.1 | ALT0 | 1 |  3 || 4  |   |      | 5V      |     |     |
 |   3 |   9 |   SCL.1 | ALT0 | 1 |  5 || 6  |   |      | 0v      |     |     |
 |   4 |   7 | GPIO. 7 |   IN | 1 |  7 || 8  | 1 | ALT0 | TxD     | 15  | 14  |
 |     |     |      0v |      |   |  9 || 10 | 1 | ALT0 | RxD     | 16  | 15  |
 |  17 |   0 | GPIO. 0 |   IN | 0 | 11 || 12 | 0 | IN   | GPIO. 1 | 1   | 18  |
 |  27 |   2 | GPIO. 2 |   IN | 0 | 13 || 14 |   |      | 0v      |     |     |
 |  22 |   3 | GPIO. 3 |   IN | 0 | 15 || 16 | 0 | IN   | GPIO. 4 | 4   | 23  |
 |     |     |    3.3v |      |   | 17 || 18 | 0 | IN   | GPIO. 5 | 5   | 24  |
 |  10 |  12 |    MOSI | ALT0 | 0 | 19 || 20 |   |      | 0v      |     |     |
 |   9 |  13 |    MISO | ALT0 | 0 | 21 || 22 | 0 | IN   | GPIO. 6 | 6   | 25  |
 |  11 |  14 |    SCLK | ALT0 | 0 | 23 || 24 | 1 | ALT0 | CE0     | 10  | 8   |
 |     |     |      0v |      |   | 25 || 26 | 1 | ALT0 | CE1     | 11  | 7   |
 |   0 |  30 |   SDA.0 |   IN | 1 | 27 || 28 | 1 | IN   | SCL.0   | 31  | 1   |
 |   5 |  21 | GPIO.21 |   IN | 1 | 29 || 30 |   |      | 0v      |     |     |
 |   6 |  22 | GPIO.22 |   IN | 1 | 31 || 32 | 0 | IN   | GPIO.26 | 26  | 12  |
 |  13 |  23 | GPIO.23 |   IN | 0 | 33 || 34 |   |      | 0v      |     |     |
 |  19 |  24 | GPIO.24 |   IN | 0 | 35 || 36 | 0 | IN   | GPIO.27 | 27  | 16  |
 |  26 |  25 | GPIO.25 |   IN | 0 | 37 || 38 | 0 | IN   | GPIO.28 | 28  | 20  |
 |     |     |      0v |      |   | 39 || 40 | 0 | IN   | GPIO.29 | 29  | 21  |
 +-----+-----+---------+------+---+----++----+---+------+---------+-----+-----+
 | BCM | wPi |   Name  | Mode | V | Physical | V | Mode | Name    | wPi | BCM |
 +-----+-----+---------+------+---+--B Plus--+---+------+---------+-----+-----+
pi@raspberrypi ~/keyes_树莓派高级版套件资料/DHT11 $
```

Connection diagram

```
        VCC--------3.3V
        GND--------GND
        S----------7
~
~
~
```



4 Result