```
lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git init
Initialized empty Git repository in C:/Users/lenovo/Documents/gomycode/learn_gi
_again/.git/

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git status
On branch master

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        third.txt

nothing added to commit but untracked files present (use "git add" to track)

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git add .

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git commit -m 'adding third.txt'
[master (root-commit) 043521d] adding third.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 third.txt

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git log
commit 043521d48a487b36e3f2c6496e5b7f0a4e236afe (HEAD -> master)
Author: BAHRI Mekki <mekkibahri15@gmail.com>
Date:   Wed Feb 17 02:37:04 2021 +0100

        adding third.txt

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git add fourth.txt

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git commit -m 'adding fourth.txt'
[master 1c5f9d6] adding fourth.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 create mode 100644 fourth.txt

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git rm --cached third.txt
rm 'third.txt'

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git status
On branch master
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        deleted:    third.txt

Untracked files:
  (use "git add <file>..." to include in what will be committed)
        third.txt

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git commit -m 'removing third.txt'
[master e528579] removing third.txt
 1 file changed, 0 insertions(+), 0 deletions(-)
 delete mode 100644 third.txt

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git log
commit e528795f29af0a95bff152e56c06d5643c6bdad (HEAD -> master)
Author: BAHRI Mekki <mekkibahri15@gmail.com>
Date:   Wed Feb 17 02:51:08 2021 +0100

        removing third.txt

commit 1c5f9d62e9e46795d95e07370dd69b1d25a04bbc
Author: BAHRI Mekki <mekkibahri15@gmail.com>
Date:   Wed Feb 17 02:41:25 2021 +0100

        adding fourth.txt

commit 043521d48a487b36e3f2c6496e5b7f0a4e236afe
Author: BAHRI Mekki <mekkibahri15@gmail.com>
Date:   Wed Feb 17 02:37:04 2021 +0100

        adding third.txt

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git config --global core.pager 'cat'

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git config --list
diff.astextplain.textconv=astextplain
filter.lfs.clean=git-lfs clean -- %f
filter.lfs.smudge=git-lfs smudge -- %f
filter.lfs.process=git-lfs filter-process
filter.lfs.required=true
http.sslbackend=openssl
http.sslcainfo=C:/Program Files/Git/mingw64/ssl/certs/ca-bundle.crt
core.autocrlf=true
core.fscache=true
core.symlinks=false
pull.rebase=false
credential.helper=manager-core
credential.https://dev.azure.com.usehttppath=true
init.defaultbranch=master
user.name=BAHRI Mekki
user.email=mekkibahri15@gmail.com
core.pager=cat
core.repositoryformatversion=0
core.filemode=false
core.bare=false
core.logallrefupdates=true
core.symlinks=false
core.ignorecase=true

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git remote add origin https://github.com/bahrimekki/first-repo.git

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$ git push -u origin master
Enumerating objects: 7, done.
Counting objects: 100% (7/7), done.
Delta compression using up to 4 threads
Compressing objects: 100% (4/4), done.
Writing objects: 100% (7/7), 664 bytes | 221.00 KiB/s, done.
Total 7 (delta 0), reused 0 (delta 0), pack-reused 0
To https://github.com/bahrimekki/first-repo.git
 * [new branch]      master -> master
Branch 'master' set up to track remote branch 'master' from 'origin'.

lenovo@DESKTOP-LAEUI7F MINGW64 ~/Documents/gomycode/learn_git_again (master)
$
```