

Assignment 1

Bailey Rosato

2023-10-05

Chapter 8

Question 1

1. Create a vector of three elements (2,4,6) and name that vector `vec_a`. Create a second vector, `vec_b`, that contains (8,10,12). Add these two vectors together and name the result `vec_c`.

```
vec_a <- c(2,4,6)

vec_b <- c(8,10,12)

vec_c <- vec_a + vec_b

vec_c
```

```
## [1] 10 14 18
```

Question 2

2. Create a vector, named `vec_d`, that contains only two elements (14,20). Add this vector to `vec_a`. What is the result and what do you think R did (look up the recycling rule using Google)? What is the warning message that R gives you?

```
vec_d <- c(14, 20)

vec_a <- vec_a + vec_d
```

```
## Warning in vec_a + vec_d: longer object length is not a multiple of shorter
## object length

vec_a
```

```
## [1] 16 24 20
```

The result for adding `vec_a` to `vec_c` is [16 24 20]. Because the `vec_d` is not the same size as `vec_a`, it recycles elements from the larger vector. The warning message states : “Warning: longer object length is not a multiple of shorter object length”.

Question 3

3. Next add 5 to the vector `vec_a`. What is the result and what did R do? Why doesn't it give you a warning message similar to what you saw in the previous problem?

```
vec_a <- vec_a + 5

vec_a
```

```
## [1] 21 29 25
```

The result is `[21 29 25]`. R does not give a warning message because it is not trying to add vectors of different sizes, it is only adding a constant to every element.

Question 4

4. Generate the vector of integers $\{1, 2, \dots, 5\}$ in two different ways.
- First using the `seq()` function
 - Using the `a:b` shortcut.

```
seq(from=1, to=5, by=1)
```

```
## [1] 1 2 3 4 5
```

```
1:5
```

```
## [1] 1 2 3 4 5
```

Question 5

5. Generate the vector of even numbers $\{2, 4, 6, \dots, 20\}$
- Using the `seq()` function and
 - Using the `a:b` shortcut and some subsequent algebra. *Hint: Generate the vector 1-10 and then multiple it by 2.*

```
seq(from=2, to=20, by=2)
```

```
## [1] 2 4 6 8 10 12 14 16 18 20
```

```
2 * 1:10
```

```
## [1] 2 4 6 8 10 12 14 16 18 20
```

Question 6

6. Generate a vector of 21 elements that are evenly placed between 0 and 1 using the `seq()` command and name this vector `x`.

```
x <- seq(0,1, length.out = 21)
x
```

```
## [1] 0.00 0.05 0.10 0.15 0.20 0.25 0.30 0.35 0.40 0.45 0.50 0.55 0.60 0.65 0.70
```

```
## [16] 0.75 0.80 0.85 0.90 0.95 1.00
```

Question 7

7. Generate the vector $\{2, 4, 8, 2, 4, 8, 2, 4, 8\}$ using the `rep()` command to replicate the vector `c(2,4,8)`.

```
rep( c(2,4,8), 3 )
```

```
## [1] 2 4 8 2 4 8 2 4 8
```

Question 8

8. Generate the vector $\{2, 2, 2, 2, 4, 4, 4, 4, 8, 8, 8, 8\}$ using the `rep()` command. You might need to check the help file for `rep()` to see all of the options that `rep()` will accept. In particular, look at the optional argument `each=`.

```
##?rep
rep(c(2,4,8), each=4)
```

```
## [1] 2 2 2 2 4 4 4 4 8 8 8 8
```

Question 10

10. In this problem, we will work with the matrix

$$\begin{bmatrix} 2 & 4 & 6 & 8 & 10 \\ 12 & 14 & 16 & 18 & 20 \\ 22 & 24 & 26 & 28 & 30 \end{bmatrix}$$

- a) Create the matrix in two ways and save the resulting matrix as M.
- Create the matrix using some combination of the `seq()` and `matrix()` commands.

```
M <- matrix(seq(from=2, to=30, by=2), nrow=3, ncol=5, byrow=TRUE)
```

M

```
##      [,1] [,2] [,3] [,4] [,5]
## [1,]    2    4    6    8   10
## [2,]   12   14   16   18   20
## [3,]   22   24   26   28   30
```

- Create the same matrix by some combination of multiple ``seq()`` commands and either the ``rbind()``

```
##?rbind
```

```
row_1 <- seq(from=2, to=10, by=2)
row_2 <- seq(from=12, to=20, by=2)
row_3 <- seq(from=22, to=30, by=2)

rbind(row_1, row_2, row_3)
```

```
##      [,1] [,2] [,3] [,4] [,5]
## row_1    2    4    6    8   10
## row_2   12   14   16   18   20
## row_3   22   24   26   28   30
```

- b) Extract the second row out of ``M``.

```
M[2, ]
```

```
## [1] 12 14 16 18 20
```

- c) Extract the element in the third row and second column of ``M``.

```
M[3,2]
```

```
## [1] 24
```

Question 12

12. The following code creates a `data.frame` and then has two different methods for removing the rows with NA values in the column `Grade`. Explain the difference between the two.

```
df <- data.frame(name= c('Alice', 'Bob', 'Charlie', 'Daniel'),
                  Grade = c(6,8,NA,9))

df[ -which( is.na(df$Grade) ), ]
df[  which( !is.na(df$Grade) ), ]
```

The first example is not selecting elements that is a NA in the grade and the second example is logically checking that the grade is not NA before selecting them.

Question 14

14. Create and manipulate a list.

a) Create a list named my.test with elements

- `x = c(4,5,6,7,8,9,10)`
- `y = c(34,35,41,40,45,47,51)`
- `slope = 2.82`
- `p.value = 0.000131`

```
x <- c(4,5,6,7,8,9,10)
y <- c(34,35,41,40,45,47,51)
slope <- 2.82
p.value <- 0.000131
my.test <- list(Xvalues=x,Yvalues=y, Slope=slope, Pvalue=p.value)
str(my.test)
```

```
## List of 4
## $ Xvalues: num [1:7] 4 5 6 7 8 9 10
## $ Yvalues: num [1:7] 34 35 41 40 45 47 51
## $ Slope : num 2.82
## $ Pvalue : num 0.000131
```

b) Extract the second element in the list.

```
my.test[[2]]
```

```
## [1] 34 35 41 40 45 47 51
```

c) Extract the element named `p.value` from the list.

```
my.test['Pvalue']
```

```
## $Pvalue
## [1] 0.000131
```

Chapter 9

Question 1

1. Download from GitHub the data file Example_5.xls. Open it in Excel and figure out which sheet of data we should import into R. At the same time figure out how many initial rows need to be skipped. Import the data set into a data frame and show the structure of the imported data using the `str()` command. Make sure that your data has $n = 31$ observations and the three columns are appropriately named. If you make any modifications to the data file, comment on those modifications.

```
RawData <- read_excel('Example_5.xls', sheet="RawData", skip=4, range='A5:C36')
```

```
str(RawData)
```

```
## tibble [31 x 3] (S3: tbl_df/tbl/data.frame)
## $ Girth : num [1:31] 8.3 8.6 8.8 10.5 10.7 10.8 11 11 11.1 11.2 ...
## $ Height: num [1:31] 70 65 63 72 81 83 66 75 80 75 ...
## $ Volume: num [1:31] 10.3 10.3 10.2 16.4 18.8 19.7 15.6 18.2 22.6 19.9 ...
```

Question 2

2. Download from GitHub the data file `Example_3.xls`. Import the data set into a data frame and show the structure of the imported data using the `tail()` command which shows the last few rows of a data table. Make sure the Tesla values are NA where appropriate and that both `-9999` and NA are imported as NA values. If you make any modifications to the data file, comment on those modifications.

```
data <- read_excel('Example_3.xls', sheet="data", range="A1:L34",
                  na = c("-9999", "NA"))
tail(data)
```

```
## # A tibble: 6 x 12
##   model      mpg   cyl  disp    hp  drat    wt   qsec    vs  am  gear  carb
##   <chr>    <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl> <dbl>
## 1 Lotus Europa 30.4     4  95.1   113  3.77  1.51  16.9     1   1     5     2
## 2 Ford Panter~ 15.8     8 351    264  4.22  3.17  14.5     0   1     5     4
## 3 Ferrari Dino 19.7     6 145    175  3.62  2.77  15.5     0   1     5     6
## 4 Maserati Bo~ 15      8 301    335  3.54  3.57  14.6     0   1     5     8
## 5 Volvo 142E   21.4     4 121    109  4.11  2.78  18.6     1   1     4     2
## 6 Tesla Model~ 98      NA  NA    778  NA    4.94  10.4    NA   0     1    NA
```