

# *computer Network*

**Gate Notes**

For more visit [www.gatenotes.in](http://www.gatenotes.in)

Name: Rakesh Nama


Standard: Division: Roll:

Subject: Computer Network.

# INDEX

www.GateNotes.in

Serial Number	Date	Title	Page Number	Teacher's Sign/Remarks
✓ 1.		<u>IP address Subnetting Super netting.</u>		
✓ 2.		<u>Flow control method.</u>		
✓ 3.		<u>Error control method.</u>		
✓ 4.		<u>ISO OSI stack.</u>		
✓ 5.		<u>LAN Technology.</u>		
✓ 6.		<u>switching</u>		
✓ 7.		<u>Internet protocol</u>		
✓ 8.		<u>Fragmentation.</u>		
✓ 9.		<u>protocols and concepts of at network layers</u>		
✓ 10.		<u>Routing.</u>		
✓ 11.		<u>TCP</u>		
✓ 12.		<u>UDP</u>		
✓ 13.		<u>Hardware and various devices used in networking.</u>		
✓ 14.		<u>Application protocols.</u>		
✓ 15.		<u>Problems on IP addressing.</u>		
✓ 16.		<u>problems on sliding window protocol.</u>		

IP address Subnetting & SupernettingINTRODUCTION TO COMPUTER NETWORK AND IP ADDRESS:

→ www.google.com (using this domain name we can identify destination N/w, destination host and destination process)

→ www.google.com (this Domain name convert into some numbers so that it can identify N/w, host, process)

www.google.com



IP address.

N/w ID	Host ID
--------	---------

(port num)

→ here, N/w ID to identify destination N/w and Host ID to identify destination Host.

→ port number (80) used to reach in destination process. (most of the port numbers fixed)

- ISP (Internet Service provider) provide DNS (Domain name server) Inside the Net N/w <sup>it</sup> provide the IP address of google.com.
- By using DNS converting domain name into IP address, it called DNS overhead.

### • Number system —

→ If the base of a number system 'n', then we have 'n' symbol in the number system.  
 $0, 1, 2, \dots, (n-1)$

Unary — 0


\*Binary — 0, 1

Octa — 0, 1, 2, 3, 4, ..., 7.

Decimal — 0, 1, 2, 3, ..., 9.

Hexadecimal — 0, 1, 2, ..., 9, A, B, ..., F  
 $10 \quad 11 \quad 15$   
 $1 \quad 1 \quad 1$


$(2^1)$ 1bit	$(2^2)$ 2bit	$(2^3)$ 3bit
$2^{10} - K$	0 0	0 0 0
$2^{20} - M$	1	0 1
$2^{30} - Gc$		1 0
$2^{40} - T$		0 1 1
		1 0 0
1 - 2		1 0 1
2 - 2 <sup>2</sup> = 4 part		1 1 0
3 - 2 <sup>3</sup> = 8 part		1 1 1

$n$  bit

$2^n$

# of choose,  $K \rightarrow 2^K$  (devide) $2^K$  parts  $\rightarrow 2^n$  numbers.

1 part  $\rightarrow \frac{2^n}{2^K} = 2^{n-K}$ .

 $\rightarrow$  In computer network IP address is 32 bits.

8	24
---	----

N ID      H ID  
 $2^8 = 256$      $2^{24} = 16M$ .

here N/W are very less than Host.

- Classfull IP address -

32 bit  $= 2^{32}$




Class-A	Class-B	Class-C	Class-D	Class-E
0	10	110	1110	
$2^{31}$	$2^{30}$	$2^9$	$2^8$	
0	10	110	1110	
0	10	110	1110	
:	10	110	1110	
1	11	111	1111	
$2^{31}$	$2^{30}$	$2^9$	$2^8$	
1	11	111	1111	
1	11	111	1111	
1	11	111	1111	

$\downarrow$   
Total add space  $= 2^{32}$

choose bit = 1

size of each part  $= \frac{2^{32}}{2^1} = \frac{31}{2}$



IP Address Representation -

→ IP add represent in three way's

(A) **BINARY REPRESENTATION**: 0's & 1's of 32 bits.

(B) Convert the entire 32 bit in it decimal numbers.

\* (C) Dotted Decimal Representation: 32 bit are divided into 4 bytes and every byte is converted into decimal number.


ex -



10 . 20 . 30 . 40

Class-A:

→ # IP in class-A is  $2^{24}$ .



with 7 bits,  $2^7 = 128$  N/W of class A.

$$2^{24} = 16M \text{ IP/N/W}, \text{ so total IP add present} \\ = 2^{24} \times 2^7 \\ = 2^{31}$$

0 0 0 0 0 0 0 - 0 X

0 0 0 0 0 0 1 - 2

0 0 0 0 0 1 0 - 2


1 1 1 1 1 1 1 - 126

$$(1-126) [2^8 - 2^7] = 128$$

range = B/W  $[1-126] \Rightarrow$  class A.

## class - B:

Total IP address =  $2^{30}$ .



$$\# N/W \cdot 2^{14} \cong 16K$$

~~2<sup>16</sup> IP / NW~~

So, Total IP address present in class-B =  $2^{14} \times 2^{16} = 2^{30}$

Rang of class-B B/W [128-191]

$$\begin{array}{r}
 10\bar{0}\bar{0}\bar{0}\bar{0}\bar{0} - 128 \\
 000001 - 129 \\
 000010 - 130 \\
 \vdots \\
 11111 - 191
 \end{array}
 \left| \begin{array}{l}
 2^8 - 2^6 \\
 = 192
 \end{array} \right.$$

## Class - c

$$\text{Total IP address} = 2^{29}$$



$$\# N(w) 2^{2^1} \cong 2M$$

2<sup>8</sup> 1P/n/w

So, Total IP add present in class C =  $2^8 \times 2^2 = 2^{10}$

team of class-c B/w T192-223

$$\begin{array}{r} 28 \\ - 25 \\ \hline = 229 \end{array}$$

00000 - 192  
00001 - 193  
00010  
11111 - 22

Class-D

total number of IP address present =  $2^{28}$ , later

and range =  $(224 - 239)$

1110---

0000 - 224

0001 - 225

0010 - 226

$(2^8 - 2^4)$

$224 + 2^4$

$\Rightarrow 240$

224

16

240

Class-E

range =  $(240 - 255)$

$240 + 2^4$

$\Rightarrow 256$

- Type of casting - (Unicast, Limited Broadcast, Directed Broadcast)

→ Sending one packet to another, is called casting.

→ casting '2' types :

(1) unicast : means sending a packet from one host to only one particular host.

(2) Broadcast : means sending a packet from one host to many hosts.


Range - A - (1 - 126)

C B - (127 - 191)

C C - (192 - 223)

C D - (224 - 239)

C E - (240 - 255)




(I) Unicasting

(II)

Broadcasting

Limited BC

Directed BC





$\rightarrow$  att means sending to all the host.

this Host creat  $\uparrow$  packet

Limited BC : sending from one host to many host in same N/W is called limited Broadcasting.

N/W ( $11.0.0.0$ )

N/W ( $20.0.0.0$ )



$\rightarrow$  packet

from

Directed Broadcast: means sending one host to many other host in others network.

→ If in a Network having  $2^n$  IP address then, ~~2<sup>n</sup>-1~~ host total host present ( $2^n - 2$ ).

# IP add # host

	$2^m$	$2^n - 2$
CA →	$2^{24}$	$2^{24} - 2$
CB →	$2^{16}$	$2^{16} - 2$
CC →	$2^8$	$2^8 - 2$

$$CA = (1-126), CB = (128-191), CC = (192-223)$$

	IP address	N/W ID	Direct Broadcast Address	Limited Broadcast Address
CA -	<u>1.2.3.4</u>	1.0.0.0	1.255.255.255	255.255.255.255
	<u>10.15.20.60</u>	10.0.0.0	10.255.255.255	255.255.255.255
CB -	<u>130.1.0.0</u>	130.1.0.0	130.1.255.255	"
	<u>150.0.0.0</u>	150.0.0.0	150.1.255.255	"
CC -	<u>200.1.10.100</u>	200.1.10.0	200.1.10.255	"
	<u>220.15.1.10</u>	220.15.1.0	220.15.1.255	"
CE	250.0.1.2	X	X	X
	(360).1.2.3X			
	X not valid			

## • Subnets, Subnet Mask, Routing:

### Subnetting:

→ Dividing a big network in to many small networks, is called subnetting.

### Adv:

(i) Maintenance of smallest network is easy as compare to big network.

(ii) security can be improved.

### disadv:

(i) Now 4 steps required to identification -


a. Identify network

b. " " subnet

c. " " host

d. " " process.

[normally 3 steps needed]



Class-C

200.1.2.0

---

Subnet ID  
00000000-0

Subnet (1)  
Subnet (2)

Subnet Id | Block Id | Nid.

00000000-128

111111-127

(0-127)

111111-255

(128-255)

200.1.2.0


200.1.2.127

200.1.2.128


200.1.3.255

200.1.2.0

200.1.2.0 ---




→ here wasted  $2 \times 4 = 8$  IP addresses. (to 4 subnet)



Subnet Mask: 32 bit (contain)

1's - NID & Subnet ID (part)

0's - Host ID (part)



200.1.2.130

255

255 . 255 . 192

Subnet mask - 11111111 . 11111111 . 111111 . 11000000

IP add - 11001000 . 00000001 . 00000010 . 10000000

11001000 . 00000001 . 00000010 . 10000000

terminal 22.21.9.612, host 260 . 1 . 2 . 128

(0.2.4.5) below of it

terminal prompt 200&gt; [200 . 1 . 2 . 128]

→ given an IP add and subnet mask we can find out

the network id of network to which the IP address  
belongs.

Ex - Subnet mask : 255.255.255.192

IP add : 200 . 1 . 2 . 10

[200 . 0 . 1 . 8 . 12 . 0 ]


→ It belongs to subnet ( $S_1$ )→ Router will used the subnet mask in order  
to find out what is the interface we should  
forward the packet to.Routing table

N ID	Subnet M	Interface
200 . 1 . 2 . 0	255 . 255 . 255 . 192	a
200 . 1 . 2 . 64	255 . 255 . 255 . 192	b
200 . 1 . 2 . 128	255 . 255 . 255 . 192	c
200 . 1 . 2 . 192	"	d
0 . 0 . 0 . 0	0 . 0 . 0 . 0	e

If coming packet-(IP add + subnet mask) is match with any one N ID then the packet send over (a,b,c,d). If doesn't match then next packet sent out (Default entry)

variable length subnet masking →

CC - 200.1.2.0



→ subnet size is different  
it is called (VLSM)

variable length subnet  
masking.

→ 200.1.2.0 → NID + SID

NID      SID

choose 1 bit.

3 bit remaining

SM [255.255.255.192]

SNID  
 $(2^7 = 128)$

64

6 bit remaining ( $2^6 = 64$ )

200.1.2.0  
0.0.0.0000-0  
0.0.0.001-1

128

200.1.2.10----- (200.1.2.128)

64

6 ( $2^6 = 64$ )

200.1.2.0  
128 IP odd

111111-127

200.1.2.11----- (200.1.2.191)

111111-127

111111-127 (200.1.2.191)

SID

DBA

Subnet mask

255.255.255.128

255.255.255.192

→ subnet having same size have same subnet mask.  
→ if subnet's have same size, then they have same subnet mask.

Routing table

NID	SM	Interface
200.1.2.0	255.255.255.128	b
200.1.2.128	255.255.255.192	c
200.1.2.192	255.255.255.192	d
0.0.0.0	0.0.0.0	

## Subnet mask

255.255.255.192

Binary: 11111111.11111111.11111111.11000000

here, 26 is  
 $(NID + SID)$   
 Class-A,  $8 + SID = 26$   
 $SID = 18$   
 $\# \text{subnets} = 2^{18}$

6 is  
 $(HID)$   
 $2^6 = 64 \text{ IP/SN}$

C-B,  $16 + SID = 26$

$SID = 10$   
 $\# \text{subnets} = 2^{10}$

C-C,  $24 + SID = 26$

$SID = 2$   
 $\# \text{SN} = 2^2 = 4$

(Question) — given 1225.255.255.15 (SM), how many subnet, possible. If it is class-C.

$\rightarrow 1225.225.255.15$   
 Binary: 11111111.11111111.11111111.11111111  
 $2^{15}$   
 $2^{17-1}$   
 $2^{13-1}$   
 $2^{11-1}$   
 $0-1$

Network ID + subnet = 28

$\Rightarrow 24 + SID = 28$

$SID = 2^4$

$\Rightarrow 2^4 \text{ (subnets)}$

Date \_\_\_\_\_  
Page \_\_\_\_\_

~~• Questions on Subnet masking:~~

00000000 - 0

10000000 - 128

11000000 - 192

11100000 - 224

11110000 - 240

11111000 - 248

11111100 - 252

11111110 - 254

11111111 - 255

2<sup>8</sup> = 256 sub

(128+64)

2<sup>8</sup> = 256 = 128 + 642<sup>8</sup> = 2562<sup>8</sup> = 256 sub2<sup>8</sup> = 256 for the given subnetmask how many  
subnet possible.

Subnet mask	No of Hosts	Subnet in class A	Subnet in class B	Subnet in class C	NID is 10 bit
255.0.0.0	2 <sup>4</sup> -2	2 <sup>0</sup>	—	—	X
255.128.0.0	2 <sup>7</sup> -2	2 <sup>1</sup>	—	—	X
255.192.0.0	2 <sup>6</sup> -2	2 <sup>2</sup>	—	—	2 <sup>0</sup>
255.240.0.0	2 <sup>5</sup> -2	2 <sup>3</sup>	—	—	2 <sup>2</sup>
255.255.0.0	2 <sup>16</sup> -2	2 <sup>8</sup>	2 <sup>8</sup>	—	2 <sup>6</sup>
255.255.254.0	2 <sup>9</sup> -2	2 <sup>5</sup>	2 <sup>3</sup>	—	2 <sup>3</sup>
255.255.255.0	2 <sup>8</sup> -2	2 <sup>6</sup>	2 <sup>8</sup>	2 <sup>0</sup>	2 <sup>14</sup>
255.255.255.224	2 <sup>5</sup> -2	2 <sup>19</sup>	2 <sup>11</sup>	2 <sup>5</sup>	2 <sup>17</sup>
255.255.255.240	2 <sup>4</sup> -2	2 <sup>20</sup>	2 <sup>12</sup>	2 <sup>4</sup>	2 <sup>18</sup>

(a) 1's + 0's = 2<sup>8</sup>

8 24

$$\text{NID} + \text{S-ID} = 2^8$$

$$8 \quad 8$$

$$\text{S-ID} = 0$$

Q. Given subnet mask as 255.255.255.192 and IP address PS: 200.1.2.3 ? find the Subnet ID and how many subnet there is.

SM - 255.255.255.192 ~~255.255.255.192~~

IP - 200. 1 . 2 . 3 ,

$\hookrightarrow$  (classical network)

SID = 200-1-2-0


# mask of subnet → 11111111.11111111.11111111.11000000  
mask NID SID SSID

$$\underline{NID + SID = 26}$$

$$\# SID = 2^6 - 24 \Rightarrow 2 \text{ bit}$$

$$\text{So, no of subnet} = 2^2 \Rightarrow 4.$$

## CLASSES INTER DOMAIN ROUTING (CIDR) :



→ hence  $m$  represent what are the bits in Block ID (NID).

## CIDR representation

Ex- 20.10.50.100/20 $(m=20 \text{ bit in Network ID})$   
part

total bit = 32

NID = 20

HID =  $32 - 20$  $= 12$ contains  $2^{12}$  IP addresses  
 $= 2^{12} - 2$  host

## Rules for forming CIDR blocks

I) All IP Addresses should continue be contiguous.

II) The Block size should always be a power of 2. ( $2^n$ )  
(easy to divide IP add into SID and HID)

III) First IP address in the block should be evenly divisible by size of the block.

## Examples:

Given a block of IP addresses are CIDR Block or not?

100.1.2.32

100.1.2.33

100.1.2.47

no gaps (so 1<sup>st</sup> rule satisfied)

$16 = 2^4$

Block size is power of 2  
(2<sup>nd</sup> rule satisfied).

100.1.2.00100000

$2^4$

reminders

So first IP add divisible by  $2^4$ .  
(3<sup>rd</sup> rule satisfied)

→ This block are CIDR Block.

### Example -

Whether this IP address form the CIDR Block or not.

<u>20. 30. 30. 32</u>	and $\rightarrow$ explanation
20. 10. 30. 33	$32 = 2^5$ size of the block power of '2'.
20. 10. 30. 34	<del>20. 10. 30. 33 - 0100001</del>
:	<del>11110101</del>
20. 10. 30. 63	20. 30. 30. 00100000

→ this block also qualify to form GDR block.

$$\rightarrow \text{No of IP add } 2^5, \text{ HID} = 5, \text{ BID} = 32 - 5 = 27 \quad [20, 10, 30, 32/1]$$

Example → structure & function of a protein

find out whether this block are EIDR or not.

$150 \cdot 10 \cdot 20 \cdot 64$	$64 = 2^6$ (2 <sup>nd</sup> rule followed)
$150 \cdot 10 \cdot 20 \cdot 65$	
$150 \cdot 10 \cdot 20 \cdot 66$	
$150 \cdot 10 \cdot 20 \cdot 127$	$150 \cdot 10 \cdot 20 \cdot 01   000000$

→ to this block are also CIDR block.

→ In this block,  $2^6$  IP addresses and 6 host ID.

H1D = 6

$$\overline{HID + BID} = 32$$

$$-BID = -28$$

150.10.20.64 /28

### Example -

Given CIDR Block find the range.

10091.2.35 / 20

BID size = 20 bits

range -

100.1.0.0

100-1015-365

150.10.20.01000000

BID

## Subnetting in CIDR -

example: In 20.30.40.10/25 → here NID = 25 and Host ID = 7 bit.

$$20.30.40.10/25 \rightarrow \text{here NID} = 25 \text{ and Host ID} = 7 \text{ bit.}$$

20.30.40.0 0001010

↓ NID

↓ 7 bit Host ID.

We will choose bits from Host ID part for subnetting.

If we choose 1 bits from Host ID then we are going to divide the we will get 2 subnets.

20.30.40.0 0001010

NID ↓ 000000

HID

20.30.40.0 0001010

NID ↓ 1100000

HID

20.30.40.0 0001010

0000000 - 0

0000001 - 1

0000100 - 2

20.30.40.0 0001010

1100000 - 64

0000001 - 65

0000100 - 66

0001000 - 67

0001100 - 68

0010000 - 69

0010100 - 70

0011000 - 71

0011100 - 72

0100000 - 73

0100100 - 74

0101000 - 75

0101100 - 76

0110000 - 77

0110100 - 78

0111000 - 79

Block ID 20.30.40.0/26

to 20.30.40.63

→ for one subnet.

Range

20.30.40.64/26


to 20.30.40.127

→ for another subnet.

Example -

120.30.40.10/25

dividing the entire network into 4 subnets



If you choose 2 bits from HID part, then you get the entire network will be divide into 4 parts.

Subnet 1 ID (00)

Subnet 2 ID

First IP add

Last IP add

Subnet 1 ID  $\rightarrow$  20.30.40.0/27

20.30.40.31/27

Subnet 2 ID  $\rightarrow$  20.30.40.32/27

20.30.40.63/27

Subnet 3 ID  $\rightarrow$  20.30.40.64/27

20.30.40.95/27



Subnet 4 ID  $\rightarrow$  20.30.40.96/27

20.30.40.127/27

NID

Directed Broadcast add

/25 - NID (HID=7) ( $2^7$  IP address)



→ Variable length subnet masking.

### VLSM in CIDR blocks:

Example

20.30.40.10/25

here in this block 25 bit Network ID and (32-25) = 7 bits HID, means  $2^7$  IP addresses.

00100010.00110000.01101010.00000000

Internet service provider (ISP)

[ISP] -  $2^7$  IP add

↓ ↓ ↓

2<sup>6</sup> 2<sup>6</sup>

(for company A)

1 2<sup>5</sup> 2<sup>5</sup>


(for company) (to individual customers)

25 bits NID

HID

site in at 20.30.40.00001010

00000000000000000000000000000000



((S) 25))

Example — Subclass A and C IP address allocation

(M1)  $40 \cdot 30 \cdot 10 \cdot 10 / 20$  CIDR (M2) Network block

hence block size 20 bits BID(NID) and  $(32-20)$  bits = 12 bits Host ID (HID) so, total number of IP address possible  $2^{12}$ .

$40 \cdot 30 \cdot 000001010 \cdot 00001010.0.0.0$


20 bit Block ID      Host ID

~~0000000000000.0.0.0~~ — 1<sup>st</sup> IP add ( $40 \cdot 30 \cdot 0 \cdot 0$ )

10th network address  $11110 \cdot 11111111$  — last IP add ( $40 \cdot 30 \cdot 15 \cdot 225$ )


first & last address of  $n-12$  subnet

different first 12 bits same as ISP.



first — ( $40 \cdot 30 \cdot 0 \cdot 0 / 21$ ) ←  
last IP add block

last IP — ( $40 \cdot 30 \cdot 15 \cdot 255 / 21$ ) →  
first IP add block



For II block cannot belong any host. taking a look at the existing no effect and AD go into host portion.

### Some problems on Subnet masking -

→ subnet mask (sm) also called network mask (nm) .

~~and so = 2 sin(0.5 - 30) from (c)(ii) and this is minimum and~~

The following table gives the maintenance factors of (1914) at first.

TP

SUN

Subnet ID of subnet where IP belongs to.



→ subnet masking used by the

→ router. Router to which find out which way direct to the packet.

$\Rightarrow$  IPv4 means 32 bit IP address.

Internet service provider (ISP) provides – (a) IP v4

(11) D (EW)

(Default gateway IP add)

(iii) SM (subnet mask)

#### (iv) DNS (Pomme.mysite)

A diagram showing three rectangular blocks labeled A, B, and C arranged horizontally inside a large circle. Block A is on the left, block B is in the middle, and block C is on the right. Each block has a small vertical line extending downwards from its center.

(↓)  $\beta \in \omega$ )

A hand-drawn diagram of a brain-like shape on lined paper. Inside the head, there is a small rectangle with the letter 'B' written below it.

→ To send a packet, first you should know that IP address Destination and also IP DA are Inside or outside.

Example -


200.1.2.0

a host A : IP<sub>A</sub> : 200.1.2.10

SMA : 255.255.255.128. And a host

8.8.8.88. IP<sub>B</sub> : 200.1.2.130

(0.0.0.0) default route 200.1.2.128

B : IP<sub>B</sub> : 200.1.2.130 facing number

To send packet from host A, A first take its own IP add and SMA.

IP<sub>A</sub> : 11001000 . 00000001 . 00000010 . 00001010

SMA : 11111111 . 11111111 . 11111111 . 10000000

Network ID : 11001000 . 00000001 . 00000010 . 00000000  
Host ID : AA : 200 . 1 . 0 . 2 . 0

(Network ID according to A)  
(Host ID according to A)

IP<sub>B</sub> : 11001000 . 00000001 . 00000010 . 10000010

SMA : 11111111 . 11111111 . 11111111 . 10000000

Network ID : 11001000 . 00000001 . 00000010 . 10000000  
Host ID : BA : 200 . 0 . 0 . 1 (8.8.8.88) . 128

(Network ID according to B)  
(Host ID according to B)

In this case, we can see that Network ID of A and B are different so,

A ~~can't send~~ A first send the packet to router (Router know that where its Destination) and router send the packet to Destination address.

Example-

Q. 3.1.3.3


$(1 \cdot 5) \rightarrow$  belongs belongs to (200.1.2.0)

Ans: a host A:  $IPA: 200 \cdot 1 \cdot 2 \cdot 10$

$SMA: 255.255.255.128$

$7 \cdot 1 \cdot 1 \rightarrow$  this IP belongs to (200.1.2.0)

another host B:  $IP_B: 200 \cdot 1 \cdot 2 \cdot 126$



$IPA: 11001000 \cdot 00000001 \cdot 00000010 \cdot 00001010$

$SMA: 1111111 \cdot 1111111 \cdot 1111111 \cdot 10000000$

$NID: 11001000 \cdot 00000001 \cdot 00000010 \cdot 00000000$

AA

200 . 1 . 2 . 0

$IPA: 11001000 \cdot 00000001 \cdot 00000010 \cdot 00001010$

$SMA: 1111111 \cdot 1111111 \cdot 1111111 \cdot 10000000$

$NID: 11001000 \cdot 00000001 \cdot 00000010 \cdot 00000000$

200 . 1 . 2 . 0

so, A and B both are in same <sup>in network</sup> so, A send the packet


Diretly to B.

Ex-


$SMA (subnet mask): 255.255.255.255$

here, no of 1's (32), means  $(NID+ID)=32$ .

so transmit from A to no of 0's (0), means  $ID=0$ .



Combining all subnet mask (SM) and IP address (IPA)



~~Explain how to find network ID & subnet mask.~~

given a Directed Broadcast Address (DBA) can you find out network ID and subnet mask.



DBA: 200.1.15.255 (if in host ID part put all 1's then it is DBA)

~~11001000.00000001.00001111.11111111  
8 bit 8 bit Host ID~~


many NID =  $2^{24 - 4} = 2^{20}$  million (Because all 1's are in this part)

$$= 1048576$$

$$= 1024$$

• Supernetting or Aggregation:

→ Combining many small networks into one big network.



rules: (to aggregation)

- 1) all the network should be contiguous. (means NID)
- 2) size of all network same ( $2^n$ )
- 3) First network ID should divisible by ( $2^n$ )

Example - How Aggregate all this 4 network.

① 200.1.0.0 /24

② 200.1.1.0 /24

③ 200.1.2.0 /24

④ 200.1.3.0 /24

→ (possible)

(Ans 4 IP subnets)

→ (i) all the addresses are contiguous form.

(ii) here, size of all network is same ( $2^8$ ,  $2^8$ ,  $2^8$ ,  $2^8$ )

(iii) first IP address should be divisible by size of the total supernet.

$$(4 \times 2^8 = 2^{10})$$

200.1.0.0

200.1.0.000000|00, 00000000

so, When you divisible the 1<sup>st</sup> network then remainder will be '0'.




Table for Router (R2) -

N ID	SM	Interface
200.1.0.0	255.255.255.0	a.1
200.1.1.0	255.255.255.0	a.2
200.1.2.0	255.255.255.0	a.3
200.1.3.0	255.255.255.0	a.4

Subnet mask:

~~Subnet~~ → If we change mask then it becomes supernet.

SuperNet Mask: 32 bit number.

→ In superNet mask 1's represent fixed part and no. of 0's represent variable part.

fixed	fixed	fixed	variable
200	.	1	00000000
200	.	1	00000001
200	.	1	00000010
200	.	1	00000011
255	.	255	00000000
255	.	255	252

$255 \cdot 255 \cdot 252 \cdot 0$  → SuperNet mask. For this enter SuperNet.

SuperNet ID:  $\frac{IP}{SM}$  → SuperNet ID

$200 \cdot 1 \cdot 0 \cdot 0$  → SuperNet ID

$255 \cdot 255 \cdot 252 \cdot 0$

$200 \cdot 1 \cdot 0 \cdot 0$

→ SuperNet ID.

Routing Table.

NID	IP	SM	Interface
200.1.0.0		255.255.252.0	a

→ by the one

entry, it represents all '9' networks.

→ SuperNet ID: (1) IP (2) subnet mask (3) interface.

→ Subnet mask is always 32 bits.

Example - How aggregate all this network.

It possible not to give block.

Four	$200 \cdot 1 \cdot 32 \cdot 0 / 24$	→ valid networks for super-
	$200 \cdot 1 \cdot 33 \cdot 0 / 24$	networking.
	:	
	$200 \cdot 1 \cdot 47 \cdot 0 / 24$	

(i) contiguous.

(ii) size of all networks ( $2^8$ ) same. ( $2^8$ )

(iii)  $200 \cdot 1 \cdot 32 \cdot 0$  should divisible by ( $2^8 \cdot 2^4 = 2^{12}$ )

$200 \cdot 1 \cdot 00100000 \cdot 00000000$


~~$200 \cdot 1 \cdot 32 \cdot 00000000$~~

Yes, it possible to convert into supernet.

Total Network =  $16 \cdot 2^8$

So, entire size of the entire Network =  $2^4 \times 2^8$   
 $= 2^{12}$

→ If all '3' networks are satisfied then, 1st NID will be SuperNet ID. =  $200 \cdot 1 \cdot 32 \cdot 0 / 20$



SuperNet mask:  $255.255.240.0$

Example- (many possible 2, 4, 8, 16, 32 ...)

①  $100 \cdot 1 \cdot 2 \cdot 0 / 25$

②  $100 \cdot 1 \cdot 2 \cdot 128 / 26$

③  $100 \cdot 1 \cdot 2 \cdot 192 / 26$

→ In this case first merge ② and ③ then merge ① with new supernet.

atlantis

Date \_\_\_\_\_

Page \_\_\_\_\_

## FLOW CONTROL METHODS

atlantis

Date \_\_\_\_\_


Page \_\_\_\_\_

[www.GateNotes.in](http://www.GateNotes.in)

- DELAYS in Computer networks:

Transmission delay: ( $T_f$ )

The time taken to transmit a data packet from a host on to an outgoing link is called transmission delay.



Ex -  $BW = 1 \text{ bps}$

Data size = 1 bit

so, what is the transmission delay of the data.

$\rightarrow 1 \text{ sec} - 1 \text{ bit}$

$10 \text{ bit} - 10 \text{ sec}$

If the size of Data packet = 1 bits and BW is 'B' bps.

then time taken to transmit this data 1 is,

$$T_f = (1/B) \text{ sec.}$$

Ex -  $L$  (length of the data) is 1000 bits

$BW = 1 \text{ Kbps}$

What is the transmission delay of the data.

$$\rightarrow T_f = \frac{L}{B} \Rightarrow \frac{1000 \text{ bits}}{1000} = 1 \text{ sec.}$$

Ex -  $L = 1 \text{ Kbytes}$ ,  $BW = 1 \text{ Kbps}$

$$T_f = ?$$

$$\rightarrow T_f = \frac{1024}{1000} = 1.024 \text{ sec.}$$

✓ Data → powers of 2 | BW → powers of 10.

$$K = 1024$$

$$M = 1024 \times 1024$$


$$G = 1024 \times 1024 \times 1024$$

$$K = 1000$$

$$M = 10^6$$

$$G = 10^9$$

propagation delay — Time taken by the signal to reach from one link to other link is called propagation delay.



$$T_p = \frac{d}{v} = \frac{\text{distance}}{\text{velocity}}$$

$$\begin{aligned} v &= 3 \times 10^8 \times 0.7 \\ &= 2.1 \times 10^8 \text{ m/s} \end{aligned}$$

Ex-

$$d = 2.1 \text{ km}$$

$$v = 2.1 \times 10^8 \text{ m/s}$$

What is  $T_p = ?$

$$\rightarrow T_p = \frac{d}{v} \Rightarrow \frac{2.1 \text{ km}}{2.1 \times 10^8 \text{ m/s}}$$

$$\Rightarrow \frac{2.1 \times 10^3 \text{ m}}{2.1 \times 10^8 \text{ m/s}} \quad \boxed{\text{Micro sec} = 10^{-6}}$$

$$T_p \Rightarrow 10^{-5} \text{ seconds}$$

$$\boxed{\text{msec} = 10^{-3}}$$


✓ Convert into msec =  $10^{-5} \times 10^3$

$$= 10^{-2} \text{ msec}$$

✓ Convert microsecond =  $(10^{-5}) \times \frac{10^6}{10^6}$


$$= 10 \mu\text{sec.}$$

$$T_f = \frac{1}{B}$$



$$T_p = \frac{d}{V}$$

processing delay



queuing  
delay

Queuing delay) — The amount of time any packet sits in the buffer and wait before being process is called queuing delay.

Packet

processing delay) — The will be taken by the machine and then it will be processed that is called processing delay.

~~for best time (or min. to traverse off grid) for wind power, based on wind speed~~

Some countries will not allow it. And probably it's better to do it because it's good for the environment.

To Get Full Content

Click of the below link given  
in this page



[www.GateNotes.in](http://www.GateNotes.in)

or

visit:[www.gatenotes.in](http://www.gatenotes.in)