

COMP10002 Workshop Week 9

Structs

Struct, pointers to struct, arrays of struct.

Discuss: 8.02,8.03

Discuss: Ex1,2,3 of lec07

Lab Time:

- Exercises 8.02, **8.03**, 8.05, and 8.07.
- Exercises 1, 2, and 3 in lec07.pdf
- Then, if you still have time, start looking at Exercises 4, 5, 6, and 7 in lec07.pdf

Warnings on Assignment 2 (due Friday Week 11) :

- likely challenging
- be prepared before Workshop Week 10 [at least understand & finish the 1st stage]

struct: a group of related variables

isolated variables

```
char hName[20]= "Harry Potter",  
    dName[20]= "Draco Malfoy";  
int  hId = 10001, dId = 10108;  
float hScore= 7.5, dScore= 8.0;  
  
printf("Student Harry:\n");  
printf("name = %s\n", hName);  
printf("id  = %d\n", hId);  
printf("score= %f\n", hScore);
```

grouped into a struct

```
typedef struct {  
    char name[20];  
    int id;  
    float score;  
} student_t;  
  
student_t  
    harry= {"Harry Potter", 10001, 7.5},  
    draco= {"Draco Malfoy", 10108, 8.0};  
  
printf("Student Harry:\n");  
printf("name = %s\n", harry.name);  
printf("id  = %d\n", harry.id);  
printf("score= %f\n", harry.score);
```

How best to organise collections of data?

Scenario

Data:

<= 1000 student records, each has ID, name, MST score.

Some of the tasks:

1. **searching**: find a student and score, knowing the ID
2. **sorting**: sort data in ID order
3. ...

Data structure Design 1: 3 Parallel Arrays

```
char names[SIZE][MAX_NAME+1];
```

```
int ids[SIZE];
```

```
float scores[SIZE];
```

```
int n= 0; // current length
```

- How to do the searching/sorting?
- Is that a *good* design?

n	names	ids	scores
4	James Bond	10007	8.5
	Harry Potter	30030	7.5
	Luna Lovegood	10000	7.0
	Draco Malfoy	40004	7.5

struct

student_t

name

id

score

James Bond

10007

8.5

Harry Potter

30030

7.5

Luna Lovegood

10000

7.0

Draco Malfoy

40004

7.5

n

4

Data structure Design 2: 1 array of structs

```
typedef struct {  
    char name[MAX_NAME+1];  
    int id;  
    double score;  
    // other fields  
} student_t;  
  
student_t studs[SIZE] = {...};  
int n = 0; // current length
```

Searching: operates in just one array, return one data!

```
student_t search(student_t A[], int n, int id) {  
    ...if (A[i].id == id) return A[i];  
}
```

Sorting: operates in a single array, need a single swap each time

```
void sort_by_name(student_t A[], int n) {  
    ... if ( strcmp(A[j].name, A[j-1].name) < 0 ) {  
        tmp = A[j]; A[j] = A[j-1]; A[j-1] = tmp; // swap  
    }  
    ...  
}
```

Memo 1: Processing structs

```
typedef struct {  
    char name [MAX_NAME+1]; // note that "name" is an array  
    int id;  
    float score;  
} student_t;
```

Initialising :

```
student_t bob= { "Bob Taylor" , 1234 , 97.75 };
```

Processing `struct` by processing each member, using the dot operator:

```
scanf("%s %d %f", bob.name, &bob.id, &bob.score);  
printf("name= %s, id= %d, score= %.1f\n",  
       bob.name, bob.id, bob.score);
```

But, unlike arrays, we can:

- make assignment: `s= bob;`
- and hence, `struct` can be the output of a function:
 `student_t best_student(student_t s[], int n)`
- Note: we cannot compare 2 struct-s : `if (s==bob)` is invalid

Discuss HOW-TO: Exercises 8.2 and 8.3

Define a structure `vector_t` that could be used to store points in two dimensions `x` and `y` (such as on a map).

8.02: Write `double distance(vector_t p1, vector_t p2)` that returns the Euclidean distance between `p1` and `p2`.

Give suitable declarations for a type `poly_t` that could be used to store a closed polygon, which is represented as a sequence of points in two dimensions (in counter-clockwise order). Assume that no polygon contains more than 100 points.

Memo 2: Pointers to structs

```
typedef struct {  
    char name[31];  
    int id;  
    float score;  
} student_t;
```

```
student_t s, *ps;  
ps = &s;      // now *ps and s are equivalent
```

The following 2 lines are equivalent:

```
scanf("%s %d %f", s.name, &s.id, &s.score);  
scanf("%s %d %f", (*ps).name, &ps->id, &ps->score);
```

`ps->name` is just a shorthand for `(*ps).name`, a great shorthand!

Discuss HOW-TO: The Task (**adapted** from Exercises 8.3)

*Define a structure **vector_t** that could be used to store points in two dimensions **x** and **y** (such as on a map).*

*Give suitable declarations for a type **poly_t** that could be used to store a closed polygon, which is represented as a sequence of points in two dimensions (in counter-clockwise order). Assume that no polygon contains more than 100 points. Then:*

*8.03: Write **double perimeter(poly_t P)** that returns the length of the perimeter of a polygon.*

8.03-Extended:

- how many bytes passed around when we make a call*

```
per_i = perimeter(poly_t P);      ?
```

- can we reduce that amount?*

Discuss HOW-TO: The Task (**adapted** from Exercises 8.2 and 8.3)

Define a structure `vector_t` that could be used to store points in two dimensions `x` and `y` (such as on a map).

Give suitable declarations for a type `poly_t` that could be used to store a closed polygon, which is represented as a sequence of points in two dimensions (in counter-clockwise order). Assume that no polygon contains more than 100 points. Then:

- a) 8.02: Write `double distance(vector_t p1, vector_t p2)` that returns the Euclidean distance between `p1` and `p2`.
- b) 8.03: Write `double perimeter(poly_t P)` that returns the length of the perimeter of a polygon.
- c) 8.03-improved: Write a function that returns the length of the perimeter of a polygon, but avoiding copying a whole struct. What the advantages in comparison with soln of b)?
- d) *[Homework, need Internet exploring]* Write a function that returns the area of a polygon.

$$A = \frac{1}{2} (x_0 y_1 - x_1 y_0 + \dots + x_{n-2} y_{n-1} - x_{n-1} y_{n-2} + x_{n-1} y_0 - x_0 y_{n-1}).$$

Memo 3: Passing/returning large struct-s in functions is INNEFFICIENT!

Use pointers instead!

Compare:

```
#define MAX_NAME 50
typedef struct {
    char name [MAX_NAME+1];
    int id;
    float score;
} student_t;
```

```
student_t best_student(student_t A[], int n) {
    ...
    return A[i];
}
```

and:

```
student_t *best_student(student_t A[], int n) {
    ...
    return &A[i];
}
```

In each case, how many bytes is passed by one function call:

`best_student(A, n)` ?

Ed 8.X1: from lec07.pdf: Scenario for ex 1-3

People have titles, a given name, a middle name, and a family name, all of up to 50 characters each. People also have dates of birth (dd/mm/yyyy), dates of marriage and divorce (as many as 10 of each), and dates of death (with a flag to indicate whether or not they are dead yet). Each date of marriage is accompanied by the name of a person.

Assuming that people work for less than 100 years each, people also have, for each year they worked, a year (yyyy), a net income and a tax liability (both rounded to whole dollars), and a date when that tax liability was paid.

Countries are collections of people. Australia is expected to contain as many as 30,000,000 people; New Zealand as many as 6,000,000 people.

a person:

```
name (title, given, middle, family),
dob (dd/mm/yy),
dod,
is_dead,
number_of_marriages,
marriages= {d_start, d_end, spouse(...)} x 10
number_of_work_years
work_years= {yyyy, income, tax, d_tax} x 100
```

Ed 8.X1: from lec07.pdf: Scenario for ex 1-3

People have titles, a given name, a middle name, and a family name, all of up to 50 characters each. People also have dates of birth (dd/mm/yyyy), dates of marriage and divorce (as many as 10 of each), and dates of death (with a flag to indicate whether or not they are dead yet). Each date of marriage is accompanied by the name of a person. Assuming that people work for less than 100 years each, people also have, for each year they worked, a year (yyyy), a net income and a tax liability (both rounded to whole dollars), and a date when that tax liability was paid.

Countries are collections of people. Australia is expected to contain as many as 30,000,000 people; New Zealand as many as 6,000,000 people.

```
typedef struct {  
    name  
    dob, dod  
    is_dead  
    number_of_marriages  
    marriages[10]  
    number_of_work_years  
    works[100]  
} person_t;
```

lec07.E1: Give declarations that reflect :

People have titles, a given name, a middle name, and a family name, all of up to 50 characters each. People also have **dates of birth** (dd/mm/yyyy), **dates of marriage and divorce** (as many as 10 of each), and **date of death** (with a flag to indicate whether or not they are dead yet). Each **date of marriage** is accompanied by the name of a person. Assuming that people work for less than 100 years each, people also have, for each year they worked, a year (yyyy), a net income and a tax liability (both rounded to whole dollars), and a date when that tax liability was paid.

```
typedef struct {
    name,
    dob, dod
    is_dead
    number_of_marriages
    marriages[10]
    number_of_work_years
    works[100]
} person_t;
```

```
#define MAXL 50
typedef char nstr[MAXL+1];

typedef struct {
    nstr title, given, mid, fam;
} name_t;

typedef struct {
    int dd, mm, yyyy;
} date_t;

typedef struct {
    name_t spouse;
    date_t start, end;
} mary_t;

typedef struct {
    int yyyy;
    int income, tax;
    date_t taxdate;
} work_t;
```

```
typedef char  
    nstr[MAXL+1];
```

```
typedef struct {  
    nstr giv, mid,  
        fam;  
} name_t;
```

```
typedef struct {  
    int dd,mm,yyyy;  
} date_t;
```

```
typedef struct {  
    name_t name;  
    date_t dob;  
    date_t dod;  
    int is_dead;  
    mary_t marys[10]; //need #define for 10  
    int nmary;  
    work_t works[100]; //need #define for 100  
    int nwork;  
} person_t;
```

```
typedef struct {  
    name_t spouse;  
    date_t start, end;  
} mary_t;
```

```
typedef struct {  
    int yyyy;  
    int income, tax;  
    date_t taxdate;  
} work_t;
```

lec07.E2: Write a function that calculates the average age of death for a country. Do not include people that are not yet dead.

Countries are collections of people. Australia is expected to contain as many as 30,000,000 people;

```
#define MAX_PEOPLE 30000000  
persont_t aus[MAX_PEOPLE];
```

New Zealand as many as 6,000,000 people.

```
??? avg_longevity(??? ) {  
  
}
```

E3: Write a function that calculates, for a country, the total taxation revenue in a specified year.

```
typedef char nstr[MAXL+1];
typedef struct {
    nstr given, mid, fam;
} name_t;
typedef struct {
    int dd,mm,yyyy;
} date_t;
typedef struct {
    name_t spouse;
    date_t start, end;
} mary_t;
typedef struct {
    int yyyy;
    int income, tax;
    date_t taxdate;
} work_t;
typedef struct {
    name_t name;
    date_t dob;
    date_t dod;
    int is_dead;
    mary_t mary[10]; //change!
    int nm;
    work_t work[100]; //change!
    int nw;
} person_t;
```

```
???    tax_revenue(    ) {

}
```

LAB TIME

Lab Time:

- Exercises 8.02, **8.03 (using pointer parameter!)**, 8.05, and 8.07.
- Exercises 1, 2, and 3 in lec07.pdf (same as [Ed exercise 8.X1](#))
- Then, if you still have time, start looking at Exercises 4, 5, 6, and 7 in lec07.pdf
- **Questions, including questions on dynamic memory**

Warnings on Assignment 2 (due Friday Week 11) :

- likely challenging
- be prepared before Workshop Week 10 [perhaps *at least* finish the first stage?]
- depending on your study plan, you might want to finish A2 during the break!

Additional Slides

Toward using multi-component objects...

Scenario

Data:

<= 1000 student records, each has ID, given name, MST score (and possibly some other fields).

Some of the tasks:

1. **input:** input all the data
2. **searching:** find a student knowing the ID
3. **sorting:** sort data in ID order
4. ...

Data structure Design 1: Parallel Arrays

```
char names[SIZE][MAX_NAME+1];
int ids[SIZE];
float scores[SIZE];
// arrays for other fields
int n= 0;    // current length
```

Searching: how to return name, id, score?

```
? search( <the 3 arrays>, int n, int id ) {
    ...
}
```

Sorting: how to simplify the swaps?

```
void sort( <the 3 arrays>, int n) {
    ...
    swap names[?] with names[??]
    swap ids{?] with ids[??]
    swap scores[?] with scores[??]
    ...
}
```

example: insertion sort for an array of struct

```
// insertion sort: sorting elements A[] in ascending order
void ins_sort(int A[], int n) {
    int i;
    for (i= 1; i<n ; i++) {
        // swap A[i] left into correct position
        for (j= i-1; j>=0 && A[j+1]<A[j]; j--) {
            int_swap( &A[j] , &A[j+1] );
        }
    }
}
```

```
void int_swap( int *a, int *b ) {
    int tmp= *a;
    *a= *b;
    *b= tmp;
}
```

```
// insertion sort: A[] in ascending order of student id
void ins_sort_stud(student_t A[], int n) {
    int i;
    for (i= 1; i<n ; i++) {
        // swap A[i] left into correct position
        for (j= i-1; j>=0 && A[j+1]<A[j]; j--) {
            int_swap( &A[j] , &A[j+1] );
        }
    }
}
```

```
void swap( ?? a, ?? b ) {
}
}
```