

code jam

print "hello, world!"

Practice Mode

[Contest scoreboard](#) | [Sign in](#)

Round 1A 2010

[A. Rotate](#)**B. Make it Smooth**[C. Number Game](#)[Contest Analysis](#)[Questions asked](#) 1**Problem B. Make it Smooth**

This contest is open for practice. You can try every problem as many times as you like, though we won't keep track of which problems you solve. Read the [Quick-Start Guide](#) to get started.

Small input  
12 points

Solve B-small

Large input  
24 points

Solve B-large

## - Submissions

## Rotate

11pt Not attempted  
2076/2436 users correct (85%)

12pt Not attempted  
1855/2071 users correct (90%)

## Make it Smooth

12pt Not attempted  
509/954 users correct (53%)

24pt Not attempted  
319/482 users correct (66%)

## Number Game

16pt Not attempted  
680/1091 users correct (62%)

25pt Not attempted  
244/450 users correct (54%)

## Problem

You have a one-dimensional array of **N** pixels. Each pixel has a value, represented by a number between 0 and 255, inclusive. The *distance* between two pixels is the absolute difference of their numbers.

You can perform each of the following operations zero or more times:

1. With cost **D**, delete any pixel, so its original neighbors become neighboring pixels.
2. With cost **I**, insert one pixel of any value into any position -- either between two existing pixels, or before the first pixel, or after the last pixel.
3. You can change the value of any pixel. The cost is the absolute difference of the old value of the pixel and the new value of the pixel.

The array is *smooth* if any neighboring pixels have distance at most **M**. Find the minimum possible cost of a sequence of operations that makes the array smooth.

Note: The empty array -- the array containing no pixels -- is considered to be smooth.

## Input

The first line of the input gives the number of test cases, **T**. **T** test cases follow, each with two lines. The first line is in the form "**D I M N**", the next line contains **N** numbers **a<sub>i</sub>**; the values of the pixels from left to the right.

## Output

For each test case, output one line containing "Case #x: y", where x is the case number (starting from 1), and y is the minimum cost to make the input array smooth.

## Limits

All the numbers in the input are integers.  
 $1 \leq T \leq 100$   
 $0 \leq D, I, M, a_i \leq 255$

## Small dataset

$1 \leq N \leq 3$ .

## Large dataset

$1 \leq N \leq 100$ .

## - Top Scores

rng..58	100
Pipi	100
cgy4ever	100
rem	100
XiaoZiqian	100
qizichao	100
exod40	100
GarnetCrow	100
hos.lyric	100
ACRush	100

## Sample

Input	Output
2	Case #1: 4
6 6 2 3	Case #2: 17
1 7 5	
100 1 5 3	
1 50 7	

## Explanation

In Case #1, decreasing the 7 to 3 costs 4 and is the cheapest solution. In Case #2, deleting is extremely expensive; it's cheaper to insert elements so your final array looks like [1, 6, 11, 16, 21, 26, 31, 36, 41, 46, 50, 45, 40, 35, 30, 25, 20, 15, 10, 7].

---

All problem statements, input data and contest analyses are licensed under the [Creative Commons Attribution License](#).

© 2008-2013 Google [Google Home](#) - [Terms and Conditions](#) - [Privacy Policies and Principles](#)

