API Telemetry: Custom Transcript Override Initiated

Top-Level Status Bar

- OPERATION: Smoke Test
- TARGET_NODE: API Ingestion
- STATUS: Ping Sent

Payload Box

```
Payload Data: "This is a tiny transcript
to confirm the API accepts a custom
transcript and uses it instead of the
sample."
```

Objective Panel

- [ ] **Objective 01:** Confirm API accepts custom transcript.
- [ ] **Objective 02:** Confirm API bypasses default sample.

Topic: testing custom transcripts.

NotebookLM

Routing Architecture for Payload Injection



NotebookLM

System State Diagnostic Comparison

Payload Processing Matrix

System State	Data Origin	Data Origin	API Routing Path	Validation Status
Baseline	Default Fallback	Internal Sample	Standard (No Override)	BYPASSED
Smoke Test Target	Custom Ingestion	Tiny Transcript	Active Override	CONFIRMED

The custom transcript is utilized exclusively.

NotebookLM

Validation Confirmed for Custom Data Ingestion

"System Readiness" Checklist UI

- ✓ CHECK_01 Custom Payload Acceptance
- ✓ CHECK_02 Default Sample Override
- ✓ CHECK_03 API Processing Continuity

The succissful ingestion of the tiny transcript verifies total architectural readiness. The API is now cleared to bypass default samples and process external custom transcripts at scale.

STATUS: PASSED // END_TEST

NotebookLM