

Chess position difficulty estimation

Zala Urh
@student.uni-lj.si
Faculty of Computer and
Information Science,
University of Ljubljana
Večna pot 113
SI-1000 Ljubljana, Slovenia

Matej Belšak
mb4390@student.uni-lj.si
Faculty of Computer and
Information Science,
University of Ljubljana
Večna pot 113
SI-1000 Ljubljana, Slovenia

Luka Bajić
lb4129@student.uni-lj.si
Faculty of Computer and
Information Science,
University of Ljubljana
Večna pot 113
SI-1000 Ljubljana, Slovenia

ABSTRACT

In this paper we implement compare various procedures for assigning an ELO estimate to any chess position and for ranking the positions without providing numerical outputs.

KEYWORDS

chess, classification, regression, ranking

1 INTRODUCTION

In this paper we compare various methods for determining the difficulty of a given chess position for human players, using chess engine evaluations and other attributes of the position. This problem can be defined in the following three ways:

- classification: the model classifies positions into pre-defined classes (e.g. easy/medium/hard), or binned ELO ratings.
- regression: the model directly predicts an estimated ELO rating of the position.
- ranking: the model orders a set of positions from easiest to hardest, or ranks a single position in relation to all positions in the training set.

All the developed methods are available at ¹.

2 RELATED WORK

Recent approaches for estimating the difficulty of a chess position, e. g. [3] are largely based on the deep learning paradigm and the input of these models consists of some encoding of the chess position, but no information that would provide interpretability for human players. In this paper we therefore focus on finding features that achieve good classification score, but also provide a meaningful interpretation regarding the reasons why a position is considered difficult or easy for human players.

Our approaches are based on insights provided by [2] [1] [4]. These studies developed numerous attributes that can be obtained by performing a chess engine search of certain depth, starting in the initial position we wish to evaluate. The search is constrained in such a way that only moves which human players would typically assess as meaningful are explored, which aims to provide an estimate of how complex the search tree around the position is.

3 METHODOLOGY

To train and evaluate our models, we use a subset of the Lichess puzzle dataset ².

¹<https://github.com/bajicluka01/chess-puzzle-evaluation/tree/main>

²<https://database.lichess.org/#puzzles>

3.1 Hierarchical Model

We propose a hierarchical classification/regression model, consisting of a main model, which classifies the position into one of the predetermined equidistant rating bins and a dedicated, more precise, separately trained model for each of the bins.

4 RESULTS

Table 1: Classification accuracies.

model	CA
XGBoost	0.485
Logistic regression	0.705

Table 2: Regression accuracies.

model	MAE
XGBoost	0.485
Logistic regression	0.705

Table 3: Ranking accuracies.

model	NDCG	τ
XGBRanker	0.485	0
Logistic regression	0.705	0

5 CONCLUSIONS

Future work would consist of checking if these approaches are suitable also for strategic/nondescript positions, rather than just puzzles. Here, the main challenge is in assigning the ground truth ELO to these positions, since consensus among human players is more difficult to reach.

REFERENCES

- [1] Ivan Bratko, Dayana Hristova, and Matej Guid. 2016. *Search Versus Knowledge in Human Problem Solving: A Case Study in Chess*. Vol. 27. 569–583. https://doi.org/10.1007/978-3-319-38983-7_32
- [2] Ivan Bratko, Dayana Hristova, and Matej Guid. 2021. Predicting Problem Difficulty in Chess. In *Human-Like Machine Intelligence*, Stephen Muggleton and Nicholas Chater (Eds.). Oxford University Press. <https://doi.org/10.1093/oso/9780198862536.003.0024>
- arXiv:<https://academic.oup.com/book/0/chapter/350718010/chapter-pdf/43431216/oso-9780198862536-chapter-24.pdf>
- [3] Szymon Miłosz and Paweł Kapusta. 2024. Predicting Chess Puzzle Difficulty with Transformers. arXiv:2410.11078 [cs.LG] <https://arxiv.org/abs/2410.11078>
- [4] Simon Stoiljković, Ivan Bratko, and Matej Guid. 2015. A Computational Model for Estimating the Difficulty of Chess Problems. <https://api.semanticscholar.org/CorpusID:204857616>