



- 1) ALL BUILDING DIMENSIONS TO BE CHECKED ON SITE AND VERIFIED WITH DRAWING LAYOUT PRIOR TO ANY ERECTION OF COMPONENTS. PROJECT ENGINEER TO AUTHORISE ANY CHANGES REQUIRED TO LAYOUT DIMS.
- 2) ONE MASONRY ANCHOR REQUIRED PER STANDARD CONVEYOR LEG.
- 3) FOUR MASONRY ANCHORS REQUIRED PER TALL CONVEYOR LEG.
- 4) CONVEYOR GUIDE RAIL TO BE CUT AND BENT ONSITE TO ALIGN PRODUCT
- 5) BOLT-ON PAN GUARDING TO BE SPICED ONSITE WITH SPICE PLATE AND HARDWARE SUPPLIED

ALL BUILDING DIMENSIONS TO BE CHECKED ON SITE AND  
CLARIFIED WITH DRAWING LAYOUT PRIOR TO ANY  
ERECTION OF COMPONENTS.  
PROJECT ENGINEER TO AUTHORISE ANY CHANGES  
REQUIRED TO LAYOUT DIMENSIONS.

M:\mh\JOB\PO6418 - Toll Fashion GTP\Drawings\Layouts\L100-199 Conveyor\PO6418L140C.dwg