ARRAYS/STRINGS
TWO POINTERS
SLIDING WINDOW
PREFIX SUM
HASHING
(SETS&DICTIONARIES)
ANAGRAM GROUPING
FREQUENT ITEMS
COUNTING
STACKS/QUEUES
QUEUE
FIFO
ENQUEUE(4)
ENQUEUE(3)
ENQUEUE(2)
DEQUEUE()
front
rear
DEQUEUE()
4
DEQUEUE()
USE CASES
BUFFERED PRINTING
- CPU JOB SCHEDULING
- UNDO LIST (WEB)
BFS TRAVERSAL
FIRST-PUSHED
PROCESSED FIRST
STACK
LIFO
PUSH(1)
PUSH(2)
PUSH(3)
POP()
POP()
PUSH(4)
ONE SQUARE
top
stack
USE CASES
- UNDO/REDO
- BACKTRACKING
- DFS TRAVERSAL
RECURSION
PYTHON
LAST[]
O(1)
LEN()
TOP ITEM
BOTTOM ITEM
O(n)
REMOVE
LEAST
ADD
RECENT
REMOVE
PUSH(x)
APPEND(x)
STACK
QUEUE
LEN()
EMPTY
PUSH ONTO
POP FROM
ADD[-1]
REMOVE
BOTTOM ITEM
TOP ITEM
ADD[0]
REMOVE
1 START
2 PUSH 4
3 POP → RETURN 4
TOP
OUT
4
8
2
5
4
8
2
5
8
2
5
Only the top item can be pushed or popped.
1. START
STACK: 9, 7, 4, 2
2. INCOMING 5
INCOMING: 5
OUT
2
4
3. POP 2, POP 4
POP: 2, 4
5
4. PUSH 5
STACK: 9, 7, 5
A new plate removes all smaller plates from the top.
When to think of it
I need to restore the most recently saved state first.
I need undo / backtracking behavior.
I need to return to the latest unfinished or previous context.
The natural processing order is last-in, first-out.
Only the top item can be pushed or popped.
When to think of it
The problem asks for the first / nearest later value that is greater or smaller.
I scan left to right while some previous values are still waiting for an answer.
One new value can resolve several previous values at once.
Once a value gets its answer, I can remove it permanently.
1. START
QUEUE: [2, 4, 7]
NEXT OUT: 2
2. ENQUEUE 9
QUEUE: [2, 4, 7, 9]
add at REAR
9 enters
3. DEQUEUE 2
QUEUE: [4, 7, 9]
REMOVE: 2
OUT
4. FINAL
QUEUE: [4, 7, 9]
NEXT OUT: 4
FIFO: FIRST IN, FIRST OUT.
VIDEO
MONO STACK
2.9K likes, 90 comments. "Monotonic Stack Data Structure Explained"
Algobanster
youtu.be
GAME
Algo Arcade
bayar.github.io