

3ART13 LED Fabrication Document


Layer Stack Legend

	Material	Layer	Thickness	Dielectric	Type	Gerber
		F.Paste			Paste Mask	
		F.Silkscreen		Direct Printing	Legend	GBR
		F.Mask	0.02mm	Solder Resist	Solder Mask	GBR
	Copper	T.Cu (Sig, PWR)	0.035mm (1.00oz)		Signal	GBR
	Core		1.5mm	FR4_7628	Dielectric	
	Copper	B.Cu (Sig, PWR)	0.035mm (1.00oz)		Signal	GBR
		B.Mask	0.02mm	Solder Resist	Solder Mask	GBR
		B.Silkscreen		Direct Printing	Legend	GBR
		B.Paste			Paste Mask	
Total thickness: 1.61mm						
Note: external layer thicknesses are specified after plating						

Impedance Table

Transmission Line	Impedance [ohms]	Tolerance [ohms]	Layer	Trace Width [mm]	Gap [mm]	Ref. Layers
Edge-Coupled Coated Microstrip	100	±10 %	L1	0.2032	0.28	L2

Top Fabrication (Scale 1:1)



FABRICATION NOTES (UNLESS OTHERWISE SPECIFIED)

- 1) FABRICATE PER IPC-6012A CLASS 2.
- 2) OUTLINE DEFINED IN SEPARATE GERBER FILE WITH "Edge_Cuts.GBR" SUFFIX.

DIMENSIONS OF CIRCUMSIZED RECTANGLE SHOWN ON THIS DRAWING FOR REFERENCE ONLY.
- 3) SEE SEPARATE DRILL FILES WITH ".DRL" SUFFIX FOR HOLE LOCATIONS.

SELECTED HOLE LOCATIONS SHOWN ON THIS DRAWING FOR REFERENCE ONLY.
- 4) SURFACE FINISH: IMMERSION GOLD
- 5) SOLDERMASK ON BOTH SIDES OF THE BOARD SHALL BE LPI, COLOR BLACK.
- 6) SILK SCREEN LEGEND TO BE APPLIED PER LAYER STACKUP USING YELLOW NON-CONDUCTIVE EPOXY INK.
- 7) ALL VIAS ARE TENTED ON BOTH SIDES UNLESS SOLDERMASK OPENED IN GERBER.
- 8) VENDOR SHOULD FOLLOW ROHS COMPLIANT PROCESS AND Pb FREE FOR MANUFACTURING
- 9) PCB MATERIAL REQUIREMENTS:

A. FLAMMABILITY RATING MUST MEET OR EXCEED UL94V-0 REQUIREMENTS.

B. Tg 170 C OR EQUIVALENT.

C. EQUIVALENT MATERIAL SHALL BE RoHS COMPLIANT, HALOGEN FREE AND APPROVED BY BAJRAN IMGAGINARY INDUSTRIES.
- 10) DESIGN GEOMETRY MINIMUM FEATURE SIZES:

BOARD SIZE38.000 × 38.000 mm

BOARD THICKNESS1.610 mm

TRACE WIDTH0.200 mm

TRACE TO TRACE0.200 mm

MIN. HOLE (PTH)0.250 mm

MIN. HOLE (NPTH)N/A mm

ANNULAR RING0.150 mm

COPPER TO HOLE0.254 mm

COPPER TO EDGE0.250 mm

HOLE TO HOLE0.254 mm
- 11) REFER TO IMPEDANCE TABLE FOR IMPEDANCE CONTROL REQUIREMENTS.
- 12) CONFIRM SPACE WIDTHS AND SPACINGS.

All dimensions are in millimeters unless otherwise specified.

	Comments:	Company: BaJRan 		Variant: CHECKED	Git Hash: c7cddf3	
		Board Name: 3ART13 LED		Project Name: Sienkiewicz		
	Sheet Title: Top Fabrication (Scale 1:1)	File Name: Sienkiewicz_LED.kicad_pcb	Designer: Pawel Baran	Date: 2024-04-13	Revision: 2.1.1+ (Unreleased)	
	Sheet Path:		Reviewer:	Size: A4	Sheet: 1 of 7	