

|       |      |             |       |          |
|-------|------|-------------|-------|----------|
| ISSUE | INFO | CHANGE REF. | DRAWN | DATE     |
|       |      |             |       | 24-04-26 |

BSH SPRING – LONG

CODE: QDBJ2020060502-1  
ø23.8

BSH SPRING – SHORT

CODE: QDBJ2020060502-2

NOTES:

1. END TYPE: CLOSED & NOT GROUND
2. COILING DIRECTION: RIGHT
3. TOTAL COILS: 12.5 | ACTIVE: 10.5
4. SPRING CONSTANT:  
  
SP1: ~1.97 N/mm SP2: ~1.97 N/mm
5. MATERIAL: SPRING STEEL WIRE Gr. SH  
  
ZINC PLATED, CHROME VI FREE 5-8µm  
  
SMOOTH & CONTINUOUS, FREE FROM  
  
SURFACE IMPERFECTIONS
6. COLOR: WHITE COATING
7. AFTER 24HRS FULL COMPRESSION:  
  
LENGTH CHANGE < 1.5mm
8. TOLERANCE: ±1.5mm ON FREE LENGTH
9. GEOMETRIC TOL: ANSI/ASME Y14.5M

|                |                               |                       |          |
|----------------|-------------------------------|-----------------------|----------|
| NAME           | DRAWN                         | CHECKED               | APPROVED |
| DATE           | 24/04/2026                    |                       |          |
| COMPANY        | CABE SPRINGS & FASTENERS, GOA |                       |          |
| SCALE          | 1.000                         | PROJECTION: 1ST ANGLE |          |
| TITLE          | COMPRESSION SPRINGS (2 TYPES) |                       |          |
| MATERIAL (CCT) | SPRING STEEL                  | WT: -                 |          |

| ITEM | CODE      | FREE LEN (mm) | OD (mm) | WIRE ø | COILS (T/E) | LOAD 1   | LOAD 2     | QTY |
|------|-----------|---------------|---------|--------|-------------|----------|------------|-----|
| 1    | QDBJ...-1 | 93.5±1.5      | 23.8    | 2.3    | 12.5 / 10.5 | 69N@35mm | 35.5N@18mm | 2   |
| 2    | QDBJ...-2 | 86.5±1.5      | 23.8    | 2.3    | 12.5 / 10.5 | 79N@40mm | 35.5N@18mm | 2   |