

# jodliterate Group

John D. Baker

<https://github.com/bakerjd99/jacks/blob/master/jodliterate/jodliterate.ijs>

SHA-256: 70d39e3f637fcc6d047d151ac3a5c53111669ae5ab332eb6039d9ae596a0fd52

December 2, 2020

## Contents

<b>jodliterate Overview</b>	<b>2</b>
jodliterate Interface . . . . .	2
jodliterate and JOD . . . . .	2
Running jodliterate . . . . .	3
<b>jodliterate Source Code</b>	<b>6</b>
<b>=: Index</b>	<b>68</b>

## jodliterate Overview

jodliterate is a J utility script that generates [literate](#) documents directly from [JOD dictionary](#) groups.

See the following for details:

1. [Using jodliterate notebook](https://github.com/bakerjd99/jacks/blob/master/jodliterate/Using%20jodliterate.ipynb). <https://github.com/bakerjd99/jacks/blob/master/jodliterate/Using%20jodliterate.ipynb>
2. [Using jodliterate PDF](https://github.com/bakerjd99/jacks/blob/master/jodliterate/UsingJodliterate.pdf). <https://github.com/bakerjd99/jacks/blob/master/jodliterate/UsingJodliterate.pdf>

## jodliterate Interface

THISPANDOC	[25]	<i>full pandoc path - use (pandoc) if on shell path</i>
formifacetex	[32]	<i>formats hyperlinked and highlighted interface words</i>
grplit	[37]	<i>make latex for group (y)</i>
ifacesection	[40]	<i>interface section summary string</i>
ifc	[41]	<i>format interface comment text</i>
setjodliterate	[57]	<i>prepare LaTeX processing - sets out directory writes preamble</i>
uwllatexfrwords	[60]	<i>unwrapped latex from words: uwllatexfrwords ;:'we wrap ugly'</i>
wordlit	[61]	<i>make latex from word list (y)</i>

## jodliterate and JOD

jodliterate makes some assumptions about the J code and document text it processes. It assumes:

1. All source code is stored in JOD dictionaries.

2. jodliterate document fragments are either:

- Markdown group long documents: 2 9 disp 'groupname'
- L<sup>A</sup>T<sub>E</sub>X suffixed macros: 4 disp 'groupname', '\_oview\_tex'

## Running jodliterate

jodliterate runs on Windows, Linux and Mac versions of J.<sup>1</sup>

To use jodliterate you must:

1. Install JOD. JOD is a J addon. It is usually installed with [pacman](#).
2. Install JODSOURCE. JODSOURCE is also a J addon. Install it with [pacman](#). It contains the JOD dictionaries required to build JOD. JODSOURCE also contains jodliterate.
3. Install a current version of [pandoc](#). pandoc version 2.9.1.1 and beyond supports J syntax highlighting. Prior versions required modification. The following blog posts provide more information:
  - (a) [More J Pandoc Syntax HighLighting](https://analyzethedatanotthedrive1.org/2020/02/19/more-j-pandoc-syntax-highlighting/) <https://analyzethedatanotthedrive1.org/2020/02/19/more-j-pandoc-syntax-highlighting/>
  - (b) [Pandoc based J Syntax Highlighting](https://analyzethedatanotthedrive1.org/2012/09/20/pandoc-based-j-syntax-highlighting/) <https://analyzethedatanotthedrive1.org/2012/09/20/pandoc-based-j-syntax-highlighting/>
  - (c) [Semi-Literate JOD](https://analyzethedatanotthedrive1.org/2012/10/01/semi-literate-jod/). <https://analyzethedatanotthedrive1.org/2012/10/01/semi-literate-jod/>
4. Build jodliterate. jodliterate is a J group. JOD makes J scripts from groups. To make jodliterate do:

```
require 'general/jod'
od ;:'joddev jod utils' [ 3 od ''
mls 'jodliterate'
```

---

<sup>1</sup>jodliterate will run on J 8.01 and beyond.

- Open the JOD dictionaries containing the group you want to document.

```
od ;:'joddev jod utils' [ 3 od ''
```

- Load jodliterate. After making jodliterate it can be loaded like any J script.

```
load 'jodliterate'
```

- Set a working directory. jodliterate generates L<sup>A</sup>T<sub>E</sub>X files. All such files are written to the directory specified by setjodliterate.

```
setjodliterate '' NB. current JOD put dictionary document directory
```

```
setjodliterate 'c:\temp' NB. windows
```

```
setjodliterate '/home/john/temp' NB. linux
```

- Set optional author(s) with dyadic setjodliterate.

```
'Batman' setjodliterate 'c:\batcave' NB. set LaTeX author(s) text and directory
```

- Run grplit on the group you want to document. grplit generates L<sup>A</sup>T<sub>E</sub>X files in the working directory. The root L<sup>A</sup>T<sub>E</sub>X file is given the group name.

```
grplit 'jodliterate' NB. makes jodliterate.tex
```

- Use L<sup>A</sup>T<sub>E</sub>X to compile the files generated by grplit.

A batch bat script is written to the setjodliterate directory that shows the sequence of L<sup>A</sup>T<sub>E</sub>X compilation commands. Files may be processed with pdf<sub>l</sub>atex, xelatex or lualatex. Your choice will be dictated by the presence of Unicode characters. For more details see the preamble file JODLiteratePreamble.tex in the working directory.

There are some  $\text{\LaTeX}$  settings you may want to adjust.

1. Edit `JODLiteratePreamble.tex` to change the number of index columns. The default is three but this may result in very long names running together. To decrease or increase index columns change:

```
\begin{multicols}{3}[\section*{\indexname}]
```

2. `jodliterate` wraps long source code lines. Wrapping is controlled by `WRAPLIMIT`. The default is 110 characters. Change this value if you change font or page size. Wrapped lines are preceded with the string `WRAPLEAD` with default `>...>`.
3. `jodliterate` may incorrectly highlight *wrapped* boxed J nouns that contain mixtures of strings and other other types. This also holds for wrapped nonnouns that contain long embedded strings. The verb `uwlaterxfrwords`, see page 60, can be used to generate *unwrapped*  $\text{\LaTeX}$  for such words that can be manually wrapped and inserted in the files generated by `jodliterate`. Try as we might some manual editing is always necessary with  $\text{\LaTeX}$ .

## jodliterate Source Code

```
NB. *jodliterate s-- generates literate source code documents directly from JOD groups.
NB.
NB. verbatim: see the following blog posts and github files
NB.
NB. https://analyzethedatanotthedrivel.org/2012/10/01/semi-literate-jod/
NB. https://analyzethedatanotthedrivel.org/2020/02/19/more-j-pandoc-syntax-highlighting/
NB. https://github.com/bakerjd99/jacks/blob/master/jodliterate/UsingJodliterate.pdf
NB. https://github.com/bakerjd99/jacks/blob/master/jodliterate/Using%20jodliterate.ipynb
NB.
NB. interface word(s):
NB. -----
NB. THISPANDOC      - full pandoc path - use (pandoc) if on shell path
NB. formifacetex    - formats hyperlinked and highlighted interface words
NB. grplit          - make latex for group (y)
NB. ifacesection    - interface section summary string
NB. ifc            - format interface comment text
NB. setjodliterate - prepare LaTeX processing - sets out directory writes preamble
NB. uwlaterfrwords - unwrapped latex from words: uwlaterfrwords ;:'we wrap ugly'
NB. wordlit        - make latex from word list (y)
NB.
NB. author: John D. Baker
NB. created: 2012oct01
NB. -----
NB. 12oct03 (x) grplit argument added to suppress root tex overwrites
NB. 12oct04 group IFACEWORDSgroupname hyperlinked
```

NB. 12oct05 replaced `::` parsing with `(wfl)` - handles bad `j` code  
NB. 12oct08 added error handling - replaced `(write)` with `(writeas)`  
NB. 12oct11 adjusted LaTeX preamble - changing monofonts  
NB. 12oct12 added `(sbtokens)` - useful for analyzing code text  
NB. 12oct17 added `(wrapvrblong)` - long source lines now wrapped  
NB. 13dec29 added to `(jacks)` GitHub repository  
NB. 20may07 adjusted word formation `(wfl)` for J 9.01  
NB. 20may08 updated for current `(pandoc)` versions  
NB. 20jun07 added `(formifacetex)` to interface words  
NB. 20nov01 added `graphics` and `inclusions` subdirectory to preamble  
NB. 20nov01 `\begin{document}` moved to root file for OverLeaf.com  
NB. 20nov04 `(setjodliterate)` cleaner script, author(s), email added  
NB. 20nov12 `(ppcodelatex)` added to adjust coloring of wrapped lines  
NB. 20dec01 `(uwlaterxfrwords)` added

```
coclass 'ajodliterate'  
coinert 'ijod'
```

NB. *\*dependents*

NB. declared global here to avoid confusing LaTeX names with J names  
NB. `(*)=: JLTITLETEX JLOVIEWTEX JLBUILDTEX JLGRPLITTEX JLWORDLITTEX`  
NB. `(*)=: JODLiteratePreamble JLCLEANTEX`

NB. Roger Hui's word formation state machine - similar to `::` but  
NB. parses text with LFs, retains whitespace and handles open quotes.  
NB.  
NB. *verbatim: note difference*

```

NB.
NB.      wfl'+/ i. 23 5, ''OPEN QUOTE'
NB.      ;:'+/ i. 23 5, ''OPEN QUOTE'

NB. hide script locals !(*)=. mfl sfl
mfl=. 256$0                      NB. X other
mfl=. 1 (9,a.i.' ')              }mfl NB. S whitespace (space and horizontal tab)
mfl=. 2 (,(a.i.'Aa')+/i.26) }mfl NB. A A-Z a-z excluding N B
mfl=. 3 (a.i.'N')                }mfl NB. N the letter N
mfl=. 4 (a.i.'B')                }mfl NB. B the letter B
mfl=. 5 (a.i.'0123456789_') }mfl NB. 9 digits and _
mfl=. 6 (a.i.'.'')              }mfl NB. D .
mfl=. 7 (a.i.'::')              }mfl NB. C :
mfl=. 8 (a.i.'''')             }mfl NB. Q quote
mfl=. 9 (13)                    }mfl NB. CR
mfl=. 10 (10)                   }mfl NB. LF

sfl=. _2]\ "1 }. ". ;. _2 (0 : 0)
' X      S      A      N      B      9      D      C      Q      CR      LF  ' ]0
1 1 12 1 2 1 3 1 2 1 6 1 1 1 1 7 1 10 1 1 1 NB. 0 initial
1 2 12 2 2 2 3 2 2 2 6 2 1 0 1 0 7 2 10 2 1 2 NB. 1 other
1 2 12 2 2 0 2 0 2 0 2 0 1 0 1 0 7 2 10 2 1 2 NB. 2 alp/num
1 2 12 2 2 0 2 0 4 0 2 0 1 0 1 0 7 2 10 2 1 2 NB. 3 N
1 2 12 2 2 0 2 0 2 0 2 0 5 0 1 0 7 2 10 2 1 2 NB. 4 NB
9 0 9 0 9 0 9 0 9 0 9 0 1 0 1 0 9 0 10 2 1 2 NB. 5 NB.
1 4 13 0 6 0 6 0 6 0 6 0 6 0 1 0 7 4 10 2 1 2 NB. 6 num
7 0 7 0 7 0 7 0 7 0 7 0 7 0 8 0 10 2 1 2 NB. 7 '

```



```
1 2 11 2 2 2 3 2 2 2 6 2 1 2 1 2 7 0 10 2 1 2 NB. 8 ''
9 0 9 0 9 0 9 0 9 0 9 0 9 0 9 0 10 2 1 2 NB. 9 comment
1 2 11 2 2 2 4 2 2 2 6 2 1 2 1 2 7 2 10 2 11 0 NB. 10 CR
1 2 11 2 2 2 4 2 2 2 6 2 1 2 1 2 7 2 10 2 1 2 NB. 11 CRLF
1 2 12 0 2 2 3 2 2 2 6 0 1 2 1 2 7 2 10 2 1 2 NB. 12 space
1 2 13 0 2 2 3 2 2 2 6 0 1 2 1 2 7 2 10 2 1 2 NB. 13 space after num
)
```

*NB. word formation for lines*

```
wfl=: (0;sfl;mfl) & ;:
```

```
JLDIRECTORY=: ''
```

*NB. wrapped line prefix*

```
WRAPLEAD=: '>..>'
```

*NB. pandoc transformed wrapped line lead token*

```
ALERTTOKWRAP=: '\AlertTok{' , WRAPLEAD , '}'
```

*NB.\*enddependents*

*NB.<<~~~~ { . bat }*

*NB. shell script that erases temporary LaTeX files*

*NB. NIMP: generalize for linux/macOS*

```
JLCLEANTEX=: 0 : 0
```

```
rem remove latex/tex temp files
del *.aux
del *.bbl
del *.dvi
del *.ps
del *.idx
del *.out
del *.log
del *.toc
del *.lof
del *.lol
del *.lot
del *.ind
del *.ilg
del *.blg
del *.gz
del *.gz(busy)
)
NB.>>~~~~
```

```
NB.<<~~~~ { .latex }
```

```
NB. group title and author - standard \maketitle
JLTITLETEX=: 0 : 0
```

```
% latex author, title, optional url and hash
\author{~#~author~#~ %\\
%\\
%\small \url{~#~ijsurl~#~} \\
%\footnotesize \texttt{SHA-256: ~#~sha256~#~} \normalsize
}
\title{\texttt{~#~group~#~} Group}
)
```

*NB. group overview header*

```
JLOVIEWTEX=: 0 : 0
```

```
% this jodliterate overview
\section{\texttt{~#~group~#~} Overview}
)
```

*NB. latex group build script*

```
JLBUILDTEx=: 0 : 0
```

```
rem sequence of latex commands that generate PDF
rem assumes latex exes are on the working path
setlocal
cd /d %~dp0
lualatex ~#~group~#~
makeindex ~#~group~#~
lualatex ~#~group~#~
lualatex ~#~group~#~
```

```
endlocal
)
```

*NB. group root tex - columns may need adjusting*

```
JLGRPLITTEX=: 0 : 0
```

```
% Main jodliterate (grplit) latex file. (grplit) generates "group"
% named versions of this file for each JOD group it processes.
```

```
\input{JODLiteratePreamble.tex}
```

```
\begin{document}
```

```
\input{~#~group~#~title.tex}
```

```
\maketitle
```

```
\tableofcontents
```

```
\newpage
```

```
% commands for adjusting distance
```

```
% between columns and inserting a rule
```

```
%\setlength{\columnsep}{3em}
```

```
%\setlength{\columnseprule}{0.5pt}
```

```
%\twocolumn
```

```
\input{~#~group~#~oview.tex}
```

```
\newpage
```

```
%\onecolumn
```

```
\input{~#~group~#~code.tex}

\newpage
\phantomsection
\addcontentsline{toc}{section}{\texttt{=:} Index}
\printindex

\end{document}
)

NB. word lit root tex
JLWORDLITTEX=: 0 : 0

% Main jodliterate (wordlit) latex file.

\input{JODLiteratePreamble.tex}

\begin{document}

\newpage

% commands for adjusting distance
% between columns and inserting a rule
%\setlength{\columnsep}{3em}
%\setlength{\columnseprule}{0.5pt}
%\twocolumn
```

```
%\onecolumn
\input{~#~texname~#~code.tex}

\newpage
\phantomsection
\addcontentsline{toc}{section}{\texttt{=:} Index}
\printindex

\end{document}
)

NB. main jodliterate LaTeX preamble
JODLiteratePreamble=: 0 : 0

% jodliterate latex preamble.
%
% This file is a highly customized version of the preamble
% material generated by pandoc's -s option when producing
% .tex output. pandoc highlighting is overridden and
% the standard index is redefined.

\documentclass[12pt]{article}

\usepackage[landscape]{geometry}
\usepackage[headings]{fullpage}
\usepackage{lmodern}
```

```
\usepackage{amssymb,amsmath}
\usepackage{ifxetex,ifluatex}

% provides \textsubscript
\usepackage{fixltx2e}

% graphics inclusions
\usepackage{graphicx,subfigure}
\graphicspath{{./inclusions/}}

% use microtype if available
\IfFileExists{microtype.sty}{\usepackage{microtype}}{}
\ifnum 0\ifxetex 1\fi\ifluatex 1\fi=0 % if pdftex
  \usepackage[utf8]{inputenc}
\else % if luatex or xelatex
  \usepackage{fontspec}
  \ifxetex
    \usepackage{xltxtra,xunicode}
  \fi
  \defaultfontfeatures{Mapping=tex-text,Scale=MatchLowercase}
  % replace EUROUC with unicode euro character
  % if you need this character - the presence of
  % this single character in the preamble forces use of xelatex, lualated
  %\newcommand{\euro}{EUROUC}
  % can set other monospace fonts if they're available
  % I rather like Source Code Pro see:
  % http://blogs.adobe.com/typblography/2012/09/source-code-pro.html
```

```
%\setmonofont{FreeMono}
%\setmonofont{Source Code Pro}
\fi

% Redefine labelwidth for lists; otherwise, the enumerate package will cause
% markers to extend beyond the left margin.
\makeatletter\AtBeginDocument{%
  \renewcommand{\@listi}{
    {\setlength{\labelwidth}{4em}}
  }\makeatother
\usepackage{enumerate}

% tightlist command for list spacing
\providecommand{\tightlist}{%
  \setlength{\itemsep}{0pt}\setlength{\parskip}{0pt}}

% build document index
\usepackage{makeidx}

% colors
\usepackage{color}
\definecolor{shadecolor}{RGB}{248,248,248}
% j control structures
\definecolor{keywcolor}{rgb}{0.13,0.29,0.53}
% j explicit arguments x y m n u v
\definecolor{datacolor}{rgb}{0.13,0.29,0.53}
% j numbers - all types see j.xml
```



```
\definecolor{decvcolor}{rgb}{0.00,0.00,0.81}
\definecolor{basencolor}{rgb}{0.00,0.00,0.81}
\definecolor{floatcolor}{rgb}{0.00,0.00,0.81}
% j local assignments
\definecolor{charcolor}{rgb}{0.31,0.60,0.02}
\definecolor{stringcolor}{rgb}{0.31,0.60,0.02}
\definecolor{commentcolor}{rgb}{0.56,0.35,0.01}
% primitive adverbs and conjunctions
%\definecolor{othercolor}{rgb}{0.56,0.35,0.01}
\definecolor{othercolor}{RGB}{0,0,255}
% global assignments
\definecolor{alertcolor}{rgb}{0.94,0.16,0.16}
% primitive J verbs and noun names
\definecolor{funccolor}{rgb}{0.00,0.00,0.00}

\usepackage{fancyvrb}
\DefineShortVerb[commandchars=\\\{\}\|\}
\DefineVerbatimEnvironment{Highlighting}{Verbatim}{commandchars=\\\{\}\}
% Add ',fontsize=\small' for more characters per line

% pandoc generated syntax coloring commands - names
% are fixed in generated code but definitions may
% be set to any valid text formatting command
\usepackage{framed}
\newenvironment{Shaded}{}{}
\newcommand{\KeywordTok}[1]{\textcolor{keywcolor}{\textbf{#1}}}}
% works better with Source Code Pro
```

```
%\newcommand{\KeywordTok}[1]{\textcolor{keywcolor}{\#1}}
\newcommand{\DataTypeTok}[1]{\textcolor{datacolor}{\#1}}
%\newcommand{\DecValTok}[1]{\textcolor{decvcolor}{\#1}}
\newcommand{\DecValTok}[1]{\#1}
\newcommand{\BaseNTok}[1]{\textcolor{basencolor}{\#1}}
\newcommand{\FloatTok}[1]{\textcolor{floatcolor}{\#1}}
\newcommand{\CharTok}[1]{\textcolor{charcolor}{\textbf{\#1}}}
\newcommand{\StringTok}[1]{\textcolor{stringcolor}{\#1}}
\newcommand{\CommentTok}[1]{\textcolor{commentcolor}{\textit{\#1}}}
\newcommand{\OtherTok}[1]{\textcolor{othercolor}{\#1}}
\newcommand{\AlertTok}[1]{\textcolor{alertcolor}{\textbf{\#1}}}
%\newcommand{\FunctionTok}[1]{\textcolor{funccolor}{\#1}}
\newcommand{\FunctionTok}[1]{\#1}
\newcommand{\RegionMarkerTok}[1]{\#1}
\newcommand{\ErrorTok}[1]{\textbf{\#1}}
\newcommand{\NormalTok}[1]{\#1}

% JOD oriented auxiliary commands for post processing pandoc generated latex
\newenvironment{JODGroupHeader}{}{}
\newenvironment{JODPostProcessor}{}{}

\usepackage{fancyhdr}
\pagestyle{fancy}

% date each page
\rfoot{\emph{\today}}
```

```
\ifxetex
  \usepackage[setpagesize=false, % page size defined by xetex
              unicode=false,      % unicode breaks when used with xetex
              xetex]{hyperref}
\else
  \usepackage[unicode=true]{hyperref}
\fi

\hypersetup{breaklinks=true,
            bookmarks=true,
            pdfauthor={},
            pdftitle={},
            colorlinks=true,
            urlcolor=blue,
            linkcolor=magenta,
            pdfborder={0 0 0}}

\setlength{\parindent}{0pt}
\setlength{\parskip}{6pt plus 2pt minus 1pt}
\setlength{\emergencystretch}{3em} % prevent overfull lines
\setcounter{secnumdepth}{0}

% reset latex index to use three columns - default is two
% which results in lots of wasted page space in landscape
% NOTE: adjust if index names run together
% from: http://www.latex-community.org/viewtopic.php?f=4&t=1735
\usepackage{multicol}
\makeatletter
```

```
\renewenvironment{theindex}
  {\if@twocolumn
    \@restonecolfalse
  \else
    \@restonecoltrue
  \fi
  \setlength{\columnseprule}{0pt}
  \setlength{\columnsep}{35pt}
  % change 3 to desired number of index columns
  \begin{multicols}{3}[\section*{\indexname}]
  \markboth{\MakeUppercase\indexname}%
            {\MakeUppercase\indexname}%
  \thispagestyle{plain}
  \setlength{\parindent}{0pt}
  \setlength{\parskip}{0pt plus 0.3pt}
  \relax
  \let\item\@idxitem}%
  {\end{multicols}\if@restonecol\onecolumn\else\clearpage\fi}
\makeatother

\makeindex

)
NB.>>~~~~

NB.*end-header

NB. pandoc LaTeX alert token prefix
```

ALERTTOKPFX=: '\AlertTok{'

*NB. string marking start of LaTeX indexed word - see FAKETOKENS*

BEGININDEX=: '\KeywordTok{=.:.:.}'

*NB. marks start of JOD group header in pandoc latex*

BEGINJODHEADER=: '\begin{JODGroupHeader}'

*NB. marks start of JOD group postprocessor in pandoc latex*

BEGINJODPOSTP=: '\begin{JODPostProcessor}'

*NB. marks the start of J script text that is not J*

BEGINNOTJ=: 'NB.<<~~~~'

*NB. pandoc LaTeX comment token prefix*

COMMENTTOKPFX=: '\CommentTok{'

*NB. carriage return character*

CR=: 13{a.

*NB. default pandoc install location*

DEFAULTPANDOC=: '"C:\Program Files\Pandoc\pandoc"'

*NB. string marking end of LaTeX indexed word - see FAKETOKENS*

ENDINDEX=: '\KeywordTok{=..=.}'

*NB. marks end of JOD group header in pandoc latex*

ENDJODHEADER=: '\end{JODGroupHeader}'

*NB. marks end of JOD group postprocessor in pandoc latex*

ENDJODPOSTP=: '\end{JODPostProcessor}'

*NB. marks the end of J script text that is not J*

ENDNOTJ=: 'NB.>>~~~'

*NB. 2 and 3 j (wfl) tokens - the trailing blank of (;1{FAKETOKENS) matters!*

FAKETOKENS=: <;.\_1 ' |=::=::|=..=.. '

*NB. interface word list name prefix*

IFACEWORDSPFX=: 'IFACEWORDS'

*NB. interface words for (jodliterate) group*

IFACEWORDSjodliterate=: <;.\_1 ' THISPANDOC formifacetex grplit ifacesection ifc setjodliterate uwlatexfrwor  
>..>ds wordlit'

*NB. interface words \pageref \label prefix*

IFCPFX=: 'ifc:'

*NB. jodliterate author - inserted in latex \author{}*

JLAUTHOR=: 'John D. Baker'

*NB. suffix of jodliterate code file*

JLCODEFILE=: 'code.tex'

*NB. default LaTeX \author{ ... } text*

JLDEFAULTAUTHORS=: ''

*NB. markdown text string that marks where generated group interface inserted*

JLINSERTIFACEMD=: '`{~{insert\_interface\_md\_}~}`'

*NB. suffix of jodliterate overview file*

JLOVIEWFILE=: 'oview.tex'

*NB. name suffix of markdown overview text*

JLOVIEWSUFFIX=: '\_oview\_tex'

*NB. suffix of jodliterate title file*

JLTITLEFILE=: 'title.tex'

*NB. temporary latex file*

LATEXTMP=: 'jltemp.tex'

*NB. line feed character*

LF=: 10{a.

*NB. regex for start of long LaTeX encoded J (0 : 0) strings*

LONGCHRBEGPAT=: '\DecValTok\{0\}[ ]\*\RegionMarkerTok\{:[ ]\*0[ \)]\*\}'

*NB. regex for end of long LaTeX encoded J (0 : 0) strings*

LONGCHRENDPAT=: '^\\RegionMarkerTok{[ ]\*\)[ ]\*}\$'

*NB. marks start of J code for pandoc -- requires pandoc with j syntax coloring*

MARKDOWNHEAD=: '~~~~ { .j }'

*NB. marks end J code for pandoc*

MARKDOWNTAIL=: '~~~~'

*NB. temporary markdown file*

MARKDOWNTMP=: 'jltmp.markdown'

*NB. regex matching pandoc LaTeX token commands*

PANDOCTOKPAT=: '\\[[:alpha:]]\*Tok{'

*NB. root words for (jodliterate) group*

ROOTWORDSjodliterate=: <;.\_1 ' DEFAULTPANDOC IFACEWORDSjodliterate ROOTWORDSjodliterate grplit setjodlitera  
>..>te wordlit'

*NB. pandoc LaTeX string token prefix*

STRINGTTOKPFX=: '\\StringTok{'

*NB. pandoc transformed LaTeX single quote*

TEXTQUOTESINGLE=: '\\textquotesingle{'



*NB. interface word \_ character replacement*

*NB. white space characters*

*NB. maximum number of code listing characters - adjust for given LaTeX pagesize*

*NB. invalid j string starting wrapped line - exclude '=' - trailing blank matters*

*NB. pandoc LaTeX fragment from (WRAPPREFIX) - these strings must correspond*

*NB. jodliterate version make and date*

*NB. retains string after first occurrence of (x)*

*NB. trims all leading and trailing blanks*

December 2, 2020

*NB. retains string before first occurrence of (x)*

```
beforestr=: ] {~ 1&(i.~)@([ E. ])
```

```
betweenstrs=: 4 : 0
```

*NB.\*betweenstrs v-- select sublists between nonnested delimiters*

*NB. discarding delimiters.*

*NB.*

*NB. dyad: blcl =. (clStart;clEnd) betweenstrs cl*

*NB. blnl =. (nlStart;nlEnd) betweenstrs nl*

*NB.*

*NB. ('start';'end') betweenstrs 'start yada yada end boo hoo start ahh end'*

*NB.*

*NB. NB. also applies to numeric delimiters*

*NB. (1 1;2 2) betweenstrs 1 1 66 666 2 2 7 87 1 1 0 2 2*

```
's e'=. x
```

```
llst=. ((-#s) (|.!.0) s E. y) +. e E. y
```

```
mask=. ~:/\ llst
```

```
(mask#llst) <|.1 mask#y
```

```
)
```

*NB. boxes open nouns*

```
boxopen=: <^(L. = 0:)
```

```
changestr=: 4 : 0
```

```

NB.*changestr v-- replaces substrings - see long documentation.
NB.
NB. dyad:  clReps changestr cl
NB.
NB.  NB. first character delimits replacements
NB.  '/change/becomes/me/ehh' changestr 'blah blah ...'

pairs=. 2 {."(1) _2 [\ <; _1 x      NB. change table
cnt=. _1 [ lim=. # pairs
while. lim > cnt=.>:cnt do.        NB. process each change pair
  't c'=. cnt { pairs              NB. /target/change
  if. +./b=. t E. y do.            NB. next if no target
    r=. I. b                       NB. target starts
    'l q'=. #&> cnt { pairs         NB. lengths
    p=. r + 0,+/\(<:# r)$ d=. q - 1 NB. change starts
    s=. * d                        NB. reduce < and > to =
    if. s = _1 do.
      b=. 1 #~ # b
      b=. ((1 * # r)$ 1 0 #~ q,l-q) (,r +/ i. l)} b
      y=. b # y
      if. q = 0 do. continue. end. NB. next for deletions
    elseif. s = 1 do.
      y=. y #~ >: d r} b           NB. first target char replicated
    end.
    y=. (c $~ q *# r) (,p +/i. q)} y NB. insert replacements
  end.
end. y                             NB. altered string

```

```
)

charsub=: 4 : 0

NB.*charsub v-- single character pair replacements.
NB.
NB. dyad: clPairs charsub cu
NB.
NB.   '-_$ ' charsub '$123 -456 -789'

'f t'=. ((#x)$0 1)<@,&a./x
t {~ f i. y
)

NB. character table to newline delimited list
ctl=: }.@(@1&(",1)@(-.@(*./\."1@(&' '0]))) # ,@((10{a.)&(",1)@])

cutnestidx=: 4 : 0

NB.*cutnestidx v-- cut list into nested runs and other.
NB.
NB. Nested runs are delimited by begin and end tags. This verb is
NB. oriented toward XML parsing where typical begin end tags are
NB. <ul> </ul> and tags with attributes like: <hoo boy="2">
NB. </hoo>
NB.
NB. This verb can process numeric lists but care must be taken to
```

```
NB. insure the pad item (1{.0$y) does not match begin and end
NB. values.
NB.
NB. dyad: (ilIdx ;< blcl) =. (clStart;clEnd) cutnestidx cl
NB.      (ilIdx ;< blnl) =. (nlStart;nlEnd) cutnestidx nl
NB.
NB. xml=. 'yada <ol><li>one</li><ol><li>sub one</li></ol></ol> boo'
NB. ('<ol';'</ol>') cutnestidx xml
NB.
NB. 88 99 cutnestidx (i.5),88,(10?10),99 88 5 5 5 5 5 99

if. #y do.
  's e'=. ,&.> x          NB. start end lists
  ut=. 1{.0$y             NB. padding
  assert. -.s -: e        NB. they must differ
  assert. -. (s -:ut) +. e -:ut
  sp=. s E. ut=.y,ut      NB. start mask

  NB. quit if no delimiters
  if. -.1 e. sp do. (i.0);<<y return. end.

  ep=. e E. ut            NB. end mask
  assert. (+/sp) = +/ep    NB. basic balance
  dp=. sp + - ep          NB. start end marks
  assert. 0 *./ . <: +/\ dp NB. nested balance
  ep=. I. _1=dp [ sp=. I. 1=dp NB. start end indexes
  ut=. +/\dp -. 0         NB. scanned marks
```

```

dp=. /:~ sp,ep          NB. all indexes
sp=. (firstones 1<:ut)#dp  NB. starts of nested
ep=. (#e)+(0=ut)#dp      NB. starts of other
dp=. /:~ ~.0,sp,ep       NB. cut starts
ut=. }: 1 dp} (>:#y)#0    NB. cut mask
(dp i. sp);<ut <;.1 y    NB. nest indexes cut list
else.
  (i.0);<<y              NB. empty arg result
end.
)

cutpatidx=: 4 : 0

NB.*cutpatidx v-- cut character list into begin/end patterns and non-pattern.
NB.
NB. dyad: (ilIdx ;< blcl) =. (clBeginpat;clEndpat) cutpatidx cl
NB.
NB. (;:'<>') cutpatidx 'no matches'
NB. ('begin[ ]*';'end') cutpatidx ' begin end begin end begin end'
NB. ('\{([ yad012]*';'\)\}') cutpatidx 'boo hoo {( yada yada yada )} {( 1 0 22222 )}'
NB.
NB. NB. starts without ends
NB. (;:'@;') cutpatidx '@@@;@@@@@;@;'

NB. require 'regex' !(*)=. rxmatches rxmatch
if. #y do.
  's e'=. ,&.> x NB. start/end patterns

```

---

```

NB. quit if no start patterns
if. 0=#h=. s rxmatches y do. (i.0);<<y return. end.

sp=. srxm h NB. start positions

NB. first end pattern within started
ep=. srxm (1 sp} 0 #~ #y) e&rxmatch;.1 y

NB. remove starts without end patterns
NB. HARDCODE: _1 is the (rxmatch) for not found
if. 0=#cp=. (ep ~: _1) # sp ,. ep do. (i.0);<<y return. end.

cp=. +/\&. |: cp NB. convert ends to (y) indexes

NB. cut list into start/end pattern and non-pattern
sp=. (0={.,cp) }. 0,,cp
idx=. (sp i. {"1 cp) -. #sp
idx;<(1 sp} 0 #~ #y) <|.1 y
else.
  (i.0);<<y NB. empty arg result
end.
)

NB. double quotes - doubles internal " quotes like (quote)
dbquote=: '""&,@(&""')@(#~ >:@(=&""'))

NB. quote unquoted strings containing blanks: dbquoteuq 'c:\blanks in\paths bitch'
dbquoteuq=: ]`dbquote@.(([: -. '""'&-:@({: , {.)) *. ' ' e. ])

```

*NB. boxes UTF8 names*

`fboxname=: ([: < 8 u: >) ::]`

*NB. erase files - cl / blcl of path file names*

`ferase=: 1!:55 ::(_1:)@(fboxname&>)@boxopen`

*NB. 1 if file exists 0 otherwise*

`fexist=: 1:@(1!:4) ::0:@(fboxname&>)@boxopen`

*NB. 0's all but first 1 in runs of 1's - like (firstone) but differs for nulls*

`firstones=: > (0: , }:)`

`formifacetex=: 3 : 0`

*NB.\*formifacetex v-- formats hyperlinked and highlighted interface words.*

*NB.*

*NB. monad: cl =. formifacetex blclIwords*

*NB.*

*NB. NB. inteface latex*

*NB. formifacetex IFACEWORDSjodliterate*

*NB. require 'jod' !(\*)=. get*

`head=. '\begin{Shaded}',LF,'\begin{Highlighting}[]',LF`

`tail=. '\end{Highlighting}',LF,'\end{Shaded}',LF`

`ctok=. '\CommentTok{'`

`ntok=. '\NormalTok{'`

`href=. '\hyperlink{'`



*NB. using [] brackets for page references*

```
pgrefhd=. '[\pageref{' ,IFCPFX
pgreftl=. '}] '
```

*NB. fetch current short descriptions !(\*)=. WORD\_ajod\_ EXPLAIN\_ajod\_*

```
'rc tab'=. (WORD_ajod_,EXPLAIN_ajod_) get y
words=. 0 {"1 tab
desc=. 1 {"1 tab
```

*NB. \_ chars create problems with page and hyperref*

```
hlwords=. UBARSUB&charsub&.> words
```

*NB. page references*

```
pgref=. (<pgrefhd) ,&.> hlwords ,&.> <pgreftl
```

*NB. set hyperlinks on words - colors on comments*

```
words=. (<href) ,&.> hlwords ,&.> (<' }{' ,ntok) ,&.> (<"1 (>words),"1 ' ' ) ,&.> <' } }'
desc=. (<ctok) ,&.> (alltrim&.> desc) ,&.> '}'
tex=. ;words ,&.> pgref ,&.> desc ,&.> LF
head,tex,tail
)
```

```
formtexindexes=: 3 : 0
```

*NB.\*formtexindexes v-- format latex index commands from global marks.*

*NB.*

*NB. monad: blcl =. formtexindexes blclMarked*

*NB. extract ::= =. marked text*

```
inames=. ;@({'&betweenstrs)&.> (-#ENDINDEX) }.&.> (#BEGININDEX) }.&.> y
```

*NB. find any indirect ()=: and multiple '=: assignments*

```
'pma pia'=. I.&.> <"1 ''')' =/ {:@(-.&' ')&> inames
```

*NB. form latex index commands*

```
indexes=. (<'\\AlertTok{=:}\\index{'} ,&.> inames ,&.> (<'@\\texttt{'} ,&.> inames ,&.> <'}}'
```

*NB. replace indirect and multiple assignments with fixed proxies*

```
indexes=. ((#pma) # <'\\AlertTok{=:}\\index{00multiple@\\texttt{'...'=:}}') pma} indexes
```

```
indexes=. ((#pia) # <'\\AlertTok{=:}\\index{01indirect@\\texttt{(...)=:}}') pia} indexes
```

*NB. adjust j locative chars \_ they give latex indexing grief*

*NB. later versions of pandoc handle this case*

*NB. if. #pos=. I. '\_'&e.&> indexes do.*

*NB. indexes=. ('#\_#\\_ ' &changeStr&> pos{indexes) pos} indexes*

*NB. end.*

```
indexes
```

```
)
```

*NB. size of file in bytes*

```
fsize=: 1!:4 ::(_1:)@fboxname&>@boxopen
```

*NB. opens and catenates boxed lists on the last axis*

```
fuserows=: >@(>@[ , "1 >@])
```

```
gbodylatex=: 3 : 0
```

```
NB.*gbodylatex v-- group body latex.
```

```
NB.
```

```
NB. monad: clTex =. gbodylatex clGroupname
```

```
if. #mtxt=. markdfrgroup y do. latexfrmarkd mtxt else. '' end.  
)
```

```
gheadlatex=: 3 : 0
```

```
NB.*gheadlatex v-- group header latex.
```

```
NB.
```

```
NB. monad: clTex =. gheadlatex clGroupname
```

```
if. #mtxt=. markdfrghead y do.  
    BEGINJODHEADER,LF,(tlf latexfrmarkd mtxt),ENDJODHEADER,2#LF  
else.  
    ''  
end.  
)
```

```
gpostlatex=: 3 : 0
```

```
NB.*gpostlatex v-- group post processor latex.
```

```
NB.
```

```
NB. monad: clTex =. gpostlatex clGroupname
```

```
if. #mtxt=. markdfrgpost y do.
  BEGINJODPOSTP,LF,(tlf latexfrmarkd mtxt),ENDJODPOSTP
else.
  ''
end.
)

grouplatex=: 3 : 0

NB.*grouplatex v-- group latex with pandoc syntax highlighting.
NB.
NB. monad: clTex =. grouplatex clGroupname
NB.
NB. NB. requires open JOD dictionary with a 'jod' group
NB. gtex=. grouplatex 'jod'
NB.
NB. dyad: clTex =. paIndex grouplatex clGroupname
NB.
NB. 0 grouplatex 'jod' NB. do not replace marks with index

1 grouplatex y
:
NB. require 'jod' !(*). badrc_ajod_ grp jderr_ajod_
if. badrc_ajod_ gnames=. grp y do. gnames return. end.

ltx=. x indexwraplatex (gheadlatex ; gbodylatex ; gpostlatex) y
```

```
ppcodelatex '\section{\texttt{'',(alltrim y),'} Source Code}','LF,LF,ltx
)

grplit=: 3 : 0

NB.*grplit v-- make latex for group (y).
NB.
NB. monad: (paRc ; blclTeXfiles) =. grplit clGroupname
NB.
NB.   grplit 'jodliterate' NB. document self
NB.
NB. dyad: (paRc ; blclTeXfiles) =. paOw grplit glGroupname
NB.
NB.   NB. do not overwrite root tex - allows for latex tweaking
NB.   0 grplit 'jodliterate'

1 grplit y
:
NB. require 'jod' !(*)=. badrc_ajod_ get grp jderr_ajod_ ok_ajod_
try.

if. 3~:(4!:0) <'badrc_ajod_' do. 0;!'error: jod is not loaded' return. end.
if. 0=#JLDIRECTORY do. 0;!'error: working directory is not set' return. end.

NB. group must exist
if. badrc_ajod_ glist=. GROUP_ajod_ grp group=. y -. ' ' do. glist return. end.

NB. default overview
```

```
ohd=. ('/~#~group~#~/',alltrim y) changestr JLOVIEWTEX [ gdoc=. ''
iwords=. ifacewords group

NB. overviews are either markdown/latex group long documents or stored LaTeX macros
if. badrc_ajod_ gdoc=. MACRO_ajod_ get group,JLOVIEWSUFFIX do.
  NB. no stored LaTeX generate LaTeX from group document markdown/latex
  if. badrc_ajod_ gdoc=. (GROUP_ajod_,DOCUMENT_ajod_) get group do. gdoc return. end.
  if. #gdoc=. ;{:,>1{gdoc do.
    NB. insert interface md based on IFACEWORDSgroup
    if. +./JLINSERTIFACEMD E. gdoc do.
      gdoc=. group setifacesummary gdoc
    end.
    gdoc=. latexfrmard gdoc
    ifstr=. ifacesection group
    if. (+./ifstr E. gdoc) *. (<IFACEWORDSPFX,group) e. glist do.
      gdoc=. iwords setifacelinks ifstr;gdoc
    end.
  end.
else.
  NB. stored macro LaTeX - no adjustments
  gdoc=. ;{:,>1{gdoc
end.

NB. root .tex file - gets group name
wdir=. JLDIRECTORY
jlroot=. wdir,group,'.tex'
if. chroot=. x -: 1 do.
```

```
    root=. ('/~#~group~#~/',group) changestr JLGRPLITTEX
    (toJ root) writeas jlroot
end.

NB. author title .tex file
tittex=. JLTITLETEX seturlsha256 y
agstrs=. ('/~#~author~#~/',(alltrim JLAUTHOR),'/~#~group~#~/',alltrim y
(toJ agstrs changestr tittex) writeas jlttitle=. wdir,group,JLTITLEFILE

NB. group overview .tex file
ohd=. ohd,LF,gdoc
(toJ ohd) writeas jloverview=. wdir,group,JLOVIEWFILE

NB. group build batch script - latex utils that compile generated files
jlbuildtex=. ('/~#~group~#~/',alltrim y) changestr JLBUILDTEX
(toJ jlbuildtex) writeas jlbuildbat=. wdir,group,'.bat'

NB. group source code .tex - return file names
gltx=. grouplatex group
gltx=. iwords setifacetargs gltx
(toJ gltx) writeas jlcode=. wdir,group,JLCODEFILE
ok_ajod_ (-.chroot) }. jlroot;jlttitle;jloverview;jlcode;jlbuildbat

catchd.
    0;!'error: (grplit) failure - last J error ->';13!:12 ''
end.
)
```

```
ifacemarkd=: 3 : 0
```

```
NB.*ifacemarkd v-- generate word interface markdown section.
```

```
NB.
```

```
NB. monad: clMd =. ifacemarkd clGroupName
```

```
NB.
```

```
NB. ifacemarkd 'jodliterate'
```

```
LF,'~~~{ .j }',LF,(2 ifc y),LF,'~~~',LF  
)
```

```
ifacesection=: 3 : 0
```

```
NB.*ifacesection v-- interface section summary string.
```

```
NB.
```

```
NB. This verb produces the interface section summary string. For
```

```
NB. (jodliterate) to include an updated hyperlinked interface
```

```
NB. summary it must find this string in generated latex. Edit
```

```
NB. this verb if you change the section layout.
```

```
NB.
```

```
NB. monad: cl =. ifacesection clGroupname
```

```
'\subsection{\texttt{' ,y,'} Interface}'  
)
```

```
ifacewords=: 3 : 0
```



```
NB.*ifacewords v-- return interface word list.
NB.
NB. Assume the interface is out of date fetch current definition
NB. from dictionary. We need the value not the storage
NB. representation so define it in the JOD scratch object.
NB.
NB. monad: blcl =. ifacewords clGroupname

NB. require 'jod' !(*)=. get
iname=. (IFACEWORDSPFX,y) -. ' '
(;SO__JODobj) get iname
iname=. iname, '__SO__JODobj'
words=. ". iname
words [ (4!:55) <iname
)

ifc=: 3 : 0

NB.*ifc v-- format interface comment text.
NB.
NB. Looks up interface words of a group and formats text for
NB. insertion into group headers and postprocessors.
NB.
NB. monad: ifc clGroupName
NB. dyad: iaOption ifc clGroupName

1 ifc y
:
```

---

```

NB. require 'jod' !(*)=. badrc_ajod_ get jderr_ajod_ badcl_ajod_ badil_ajod_
if. badcl_ajod_ y do. jderr_ajod_ 'invalid group name' return.
else.
  iface=. 'IFACEWORDS',alltrim y
end.

x=. {. ,x [ msg=. 'invalid ifc options'
if. badil_ajod_ x do. jderr_ajod_ msg return. end.
if. -.x e. i.3 do. jderr_ajod_ msg return. end.

NB. set comment style (header, postprocessor)
cpx=. ; x { (<'NB. ' ;' - '),(<'NB. ' ;' NB. '),<' ;' NB. '

NB. define interface list in jod scratch locale
NB. !(*)=. SO__JODobj erase__SO__JODobj locsfx_ajod_ nl__SO__JODobj
if. badrc_ajod_ rc=. (;SO__JODobj) get iface do. rc return.
elseif. ilist=. ".iface , ;locsfx_ajod_ ;SO__JODobj
  erase__SO__JODobj nl__SO__JODobj i. 4
  badrc_ajod_ rc=. 0 8 get /:~ ~.ilist do. rc return.
elseif. 0=#txt=. >1{rc do. jderr_ajod_ 'no interface words' return.
elseif.do.
  ctl fuserows >&.> <"1 |: ((#txt)#,:cpx) ,&.> txt
end.
)

indexgrouptex=: 3 : 0

NB.*indexgrouptex v-- insert index commands in pandoc highlight group latex.

```

```
NB.
NB. dyad:  cl =. clGroupName indexgrouptex clTex

'pos ltx'=. (BEGININDEX;ENDINDEX) cutnestidx y
if. #pos do. ; (formtexindexes pos{ltx} pos} ltx else. y end.
)

indexwraplatex=: 4 : 0

NB.*indexwraplatex v-- insert index commands and handle spurious blanks.
NB.
NB. dyad:  clLatex =. paIndex indexwraplatex clLatex

ltx=. ]`indexgrouptex@.(1 -: x) ; tlf&.> y -. a:

NB. wrap prefix final LaTeX
wpfx=. '\AlertTok{' ,WRAPLEAD, '}'

NB. convert wrap marks to LaTeX fragments - handle trailing blank first
ltx=. ('#',WRAPPREFIXTEX,' ', '#',wpfx) changestr ltx
ltx=. ('#',WRAPPREFIXTEX,'#',wpfx) changestr ltx

NB. remove spurious normal token blanks
sprb=. wpfx, '\NormalTok{'
('#',sprb,' #',sprb) changestr ltx
)

NB. standarizes J path delimiter to unix/linux forward slash
```

```
jpathsep=: '/'&(('\ ' I.@:= ])) }
```

```
jtokenize=: 3 : 0
```

*NB.\*jtokenize v-- tokenizes j text with (wfl).*

*NB.*

*NB. Similar to (;&.>)@(<.<.2) but preserves whitespace and is*

*NB. able to parse invalid j text containing open quotes. When an*

*NB. open quote is encountered it is treated like an unterminated*

*NB. string.*

*NB.*

*NB. monad: bblcl =. jtokenize clJtext*

*NB.*

*NB. jtokenize 5!:5 <'jtokenize'*

```
ct=. wfl y,LF
```

```
(ct -:&> <,LF) <.<.2 ct
```

```
)
```

```
latexfrmarkd=: 3 : 0
```

*NB.\*latexfrmarkd v-- latex from markdown using pandoc.*

*NB.*

*NB. monad: clTex =. latexfrmarkd clMarkdown*

*NB. require 'task' !(\*)=. shell*

*if. #y do.*

```
ferase mrktmp=. JLDIRECTORY,MARKDOWNTMP
ferase ltxtmp=. JLDIRECTORY,LATEXTMP
(toJ y) writeas mrktmp
NB. highlighting style is overridden in latex preamble
shell THISPANDOC,' --highlight-style=tango ',(dbquoteuq mrktmp),' -o ',dbquoteuq ltxtmp
assert. 0 < fsize ltxtmp
tex=. read ltxtmp
tex [ ferase ltxtmp [ ferase mrktmp
else.
  y
end.
)

long0d0latex=: 3 : 0

NB.*long0d0latex v-- adjust long 0 : 0 encoded LaTeX.
NB.
NB. monad: clNewTeX =. long0d0latex clTex

NB. exclude first line from token replacements
(LF beforestr y),LF,(STRINGTTOKPFX;ALERTTOKPFX) replacetoks LF afterstr y
)

markdfrghead=: 3 : 0

NB.*markdfrghead v-- markdown text from group header.
NB.
```

```
NB. monad: cl =. markdfrghead clGroupname
NB.
NB.  txt=. markdfrghead 'jod'
NB.  (toHOST txt) write 'c:/temp/jodhdr.markdown'

NB. require 'jod' !(*)=. badrc_ajod_ get HEADEND_ajodmake_ GROUP_ajod_
if. badrc_ajod_ hdr=. GROUP_ajod_ get y do. hdr return. end.
if. 0=#hdr=. ;1{,>1{hdr      do. '' return. end.
hdr=. hdr,LF,HEADEND_ajodmake_

NB. handle any non j code regions
'idx chd'=. (BEGINNOTJ;ENDNOTJ) cutnestidx hdr

if. #idx do.
  psj=. idx -.~ i.#chd
  chd=. (markgnonj&.> idx{chd) idx} chd
  chd=. (markgassign&.> psj{chd) psj} chd
  hdr=. ;chd
else.
  hdr=. markgassign hdr
end.

if. #hdr do. markdj hdr else. '' end.
)

markdfrgpost=: 3 : 0

NB.*markdfrgpost v-- markdown from group post processor.
```

```
NB.
NB. monad: clMarkdown =. markdfrgpost clGroupname

NB. require 'jod' !(*)=. get MACRO_ajod_
'rc post'=. 2 {. MACRO_ajod_ get 'POST_',y -. ' '
if. rc do. markdj markgassign ; {: , post else. '' end.
)

markdfrgroup=: 3 : 0

NB.*markdfrgroup v-- markdown text from group.
NB.
NB. monad: cl =. markdfrgrp clGroupname
NB.
NB.   txt=. markdfrgroup 'jod'
NB.   (toHOST txt) write 'c:/temp/jcode.markdown'

NB. require 'jod' !(*)=. badrc_ajod_ get gdeps grp
if. badrc_ajod_ gnl=. grp y do. gnl return. end.
if. badrc_ajod_ gdp=. gdeps y do. gdp return. end.
if. #gnl=. (gnl -. gdp) -. a: do. markdfrwords gnl else. '' end.
)

markdfrwords=: 3 : 0

NB.*markdfrwords v-- markdown text from word list.
NB.
```

```
NB. This verb takes a blcl of JOD word names and returns a UTF-8
NB. encoded cl of word source code in markdown format. Markdown
NB. is a simple but versatile text markup format that is almost
NB. ideal for documenting program source code, see:
NB.
NB. http://daringfireball.net/projects/markdown/
NB.
NB. monad: clMarkdown =. markdfrwords blclWords
NB.
NB.   markdfrwords ;:'go ahead mark us up'
NB.
NB.   NB. markdown text from JOD group words
NB.   mtxt=. markdfrwords }. grp 'jod'
NB.
NB. dyad: clMarkdown =. paWrap markdfrwords blclWords
NB.
NB.   mtxt=. 0 markdfrwords }. grp 'jod' NB. suppress wrapping

1 markdfrwords y
:
NB. require 'jod' !(*)=. WORD_ajod_ NVTABLE_ajod_ badrc_ajod_ get wtext__MK__JODobj
if. badrc_ajod_ src=. (WORD_ajod_,NVTABLE_ajod_) get y do. src return. end.

NB. commented source code (name,source) table.
if. badrc_ajod_ src=. 0 0 1 wtext__MK__JODobj >1{src do. src
else.
  src=. x&markgassign&.> {:"1 >1{src
```



```
NB. similar to (markdj) but faster here
utf8 ; (<LF,MARKDOWNHEAD,LF) ,&.> src ,&.> <LF,MARKDOWNTAIL,LF
end.
)
```

```
markdj=: 3 : 0
```

```
NB.*markdj v-- mark j code for markdown.
```

```
NB.
```

```
NB. monad: clM =. markdj clJ
```

```
utf8 (LF,MARKDOWNHEAD,LF),(tlf y),MARKDOWNTAIL,LF
)
```

```
markgassign=: 3 : 0
```

```
NB.*markgassign v-- mark j code for latex indexing.
```

```
NB.
```

```
NB. This verb tokenizes j code and replaces all global
```

```
NB. assignments with syntactically incorrect j strings that will
```

```
NB. be transformed by pandoc into easily located latex strings
```

```
NB. that will then be converted by a post pandoc processor into
```

```
NB. valid latex index commands. This works because regex based
```

```
NB. pandoc coloring does not "understand" j's parsing rules.
```

```
NB.
```

```
NB. monad: cl =. markgassign clJcode
```

```
NB.
```

```
NB. jcode=. 'markgassign=: ' , 5!:5 <'markgassign'
NB. markgassign jcode
NB.
NB. dyad: cl =. paWrap markgassign clJcode
NB.
NB. 0 markgassign jcode NB. suppress long line wrapping
```

```
1 markgassign y
:
if. 0=#jcode=. y -. CR do. y return. end.
if. 1-:x do. jcode=. WRAPLIMIT wrapvrblong jcode end.
jtokens=. jtokenize jcode
```

```
NB. only interested in global assignment lines
if. #gix=. I. ; (<'=:') e. L: 1 jtokens do.
  jgl=. gix{jtokens
  jshp=. $jat=. >jgl
  jix=. I. jat = <'=: ' [ jat=. ,jat
  NB. extract global assignments
  NB. ignoring interleaving blanks
  jat2=. (jat -.&.> ' ') -. a:
  anames=. (<:I.(<'=:') -:&> jat2){jat2
  NB. (0{FAKETOKENS) and (1{FAKETOKENS) are invalid in j
  faketoks=. (0{FAKETOKENS) ,&.> anames ,&.> 1{FAKETOKENS
  jat=. <"1 jshp $ faketoks jix} jat
  jat=. (#&> jgl) {.&.> jat
  NB. adjust last LF
```

```
(-LF={:y) }. ;;jat gix} jtokens
else.
  y
end.
)
```

```
markgnonj=: 3 : 0
```

```
NB.*markgnonj v-- mark non j code region global assignments.
```

```
NB.
```

```
NB. Non J code is often inserted in J scripts as character nouns
```

```
NB. using explicit multi-line '0 : 0' definitions. This verb
```

```
NB. marks the assigned noun name. Only '=: 0 : 0' will be found
```

```
NB. and marked.
```

```
NB.
```

```
NB. verbatim:
```

```
NB.
```

```
NB. IamFound =: 0 : 0
```

```
NB. .... non j code ...
```

```
NB. )
```

```
NB.
```

```
NB. monad: cl =. markgnonj clNonj
```

```
ct=. <|.2 tlf y
```

```
mrk=. '=:0:0'
```

```
pos=. I. mrk&-:&> (-#mrk)&{.&.> ct -.&.> <WHITESPACE
```

```
ct=. ;(LF ,&.>~ markgassign&.> pos{ct) pos} ct
```

```
(-LF={:y}) }. ct
)

patpartstr=: 4 : 0

NB. *patpartstr v-- split list into sublists of pattern and non-pattern.
NB.
NB. dyad: (ilIdx ;< blcl) =. clPattern patpartstr clStr
NB.
NB. 'hoo' patpartstr 'hooohoo'
NB. 'ab.c' patpartstr 'abh c yada yada abNcabuc boo freaking hoo'
NB. 'nada' patpartstr 'nothing to match'
NB.
NB. NB. result pattern indexes and split list
NB. 'idx substrs'=. 'yo[a-z]*' patpartstr 'yo yohomeboy no no yoman'
NB. idx{substrs NB. patterns

NB. require 'regex' !(*)=. rxmatches
if. #pat=. , "2 x rxmatches y do.
  mask=. (#y)#0
  starts=. 0 {"1 pat
  ends=. starts + <: 1 {"1 pat
  m1=. 1 (0, starts)} mask
  m2=. _1 (|.!. 0) 1 ends} mask
  m2=. m1 +. m2
  mask=. 1 starts} mask
  idx=. (m2 {.;. 1 mask) # i. +/m2
  idx;< m2 <;. 1 y
```

```
else.  
  (i.0);<<y  
end.  
)  
  
ppcodelatex=: 3 : 0  
  
NB.*ppcodelatex v-- post process generated source code latex.  
NB.  
NB. This verb applies final adjustments to generated LaTeX source  
NB. code In particular it alters the syntax coloring of long J (0  
NB. : 0) character nouns, long wrapped quoted 'long ....' strings  
NB. and wrapped comment lines.  
NB.  
NB. monad: clNewTeX =. ppcodelatex clTeX  
  
NB. adjust any 0 : 0 text  
'idx strs'=. (LONGCHRBEGPAT;LONGCHRENDPAT) cutpatidx y  
if. #idx do.  
  lg0strs=. long0d0latex&.> idx{strs  
  y=. ;lg0strs idx} strs  
end.  
  
NB. adjust any wrapped alert lines  
if. ALERTTOKWRAP +./@E. y do.  
  
  NB. all code lines and start/end table of wraps  
  wrgx=. wraprgidx +./@(ALERTTOKWRAP&E.)&> rlms=. <.;.2 tlf y
```

*NB. classify wrapped lines: comment, quoted string*

```
cm=. {.&> (COMMENTTOKPFX,'NB.')&E. &.> (0 {"1 wrgx){rlns
qm=. *./"1 +./@(TEXTQUOTESINGLE&E.) &> wrgx{rlns
```

*NB. comments override quotes and normals*

```
if. +./cm do.
  cx=. cm wraplix wrgx
  rlms=. ((COMMENTTOKPFX;ALERTTOKPFX)&replacetoks&.> cx{rlms) cx} rlms
  if. *./cm do. ;rlms return. end.
end.
```

*NB. quoted text - works for simple forms*

*NB. a general solution requires re-pandoc'ing*

*NB. line breaking nouns - especially complex*

*NB. boxed arrays that mix strings and other types*

```
if. +./qm=.0 (I. cm)} qm do.
  qx=. qm wraplix wrgx
  y=. ;(wrapQtlatex&.> qx{rlms) qx} rlms
end.
```

end.

```
y NB. adjusted latex
)
```

*NB. reads a file as a list of bytes*

```
read=: 1!:1&[]`<@.(32&>@.(3!:0)))
```

```
replacetoks=: 4 : 0
```

```
NB.*replacetoks v-- set all but (;1{x) pandoc tokens to (;0{x)
```

```
NB. tokens.
```

```
NB.
```

```
NB. dyad: clNewTex =. (clStringTok ; clAlertTok) replacetoks clTex
```

```
NB.
```

```
NB. ('\StringTok{' ; '\AlertTok{') replacetoks 'this is \atestTok{ bitch \NormalTok{ \99999Tok{'
```

```
NB. ('\StringTok{' ; '\AlertTok{') replacetoks 'no matches hombre'
```

```
NB. ('\StringTok{' ; '\AlertTok{') replacetoks ''
```

```
'idx strs'=. PANDOC TOKPAT patpartstr y
```

```
NB. all non (1{x) tokens to (0{x) tokens
```

```
if. 0=#idx do. y else. ;(0{x) (idx #~ (1{x) ~: idx{strs)} strs end.  
)
```

```
NB. trim right (trailing) blanks
```

```
rtrim=: ] #~ [: -. [: *./\ . ' ' " _ = ]
```

```
setifacelinks=: 4 : 0
```

```
NB.*setifacelinks v-- set hyperref links in any overview
```

```
NB. interface words section.
```

```
NB.
```

```
NB. dyad: cl =. blclIwords setifacelinks (clIfstr ; clTex)
```

```
'ifstr tex'=. y
rmrk=. '\end{Shaded}'
head=. ifstr&beforestr tex
tail=. ifstr&afterstr tex

if. +./rmrk E. tail do.
  ifbk=. formifacetex x
  tail=. rmrk&afterstr tail
  head,ifstr,(2#LF),ifbk,tail
else.
  tex
end.
)

setifacesummary=: 4 : 0

NB.*setifacesummary v-- replace markdown interface summary tag with text.
NB.
NB. dyad: cl =. clGname setifacesummary clMd

(JLINSERTIFACEMD beforestr y),(ifacemarkd x),JLINSERTIFACEMD afterstr y
)

setifacetargs=: 4 : 0

NB.*setifacetargs v-- set hyperlink targets in group latex.
NB.
```



```
NB. dyad:  cl =. blcliwords setifacetargs clTex

NB. replace troublesome _ in names
hlwords=. UBARSUB&charsub&.> x

NB. any _ chars are expanded to \_ at this stage
wnames=. '#_#\_'&changestr &.> x
targs=. (<'\NormalTok{') ,&.> wnames ,&.> <'}\AlertTok{=:}\index'

labels=. (<'}\AlertTok{=:}\phantomsection\label{' ,IFCPFX),&.> hlwords ,&.> <'}\index'
rstrs=. (<'\hypertarget{') ,&.> hlwords ,&.> (<'}{\NormalTok{') ,&.> wnames ,&.> labels

NB. delimiter character cannot be in text
assert. -.'#' e. ;targs,rstrs

chgs=. ;'#' ,&.> targs ,. rstrs
chgs changestr y
)

setjodliterate=: 3 : 0

NB.*setjodliterate v-- prepare LaTeX processing - sets out directory writes preamble.
NB.
NB. monad:  (paRc ; clDir) =. setjodliterate clWorkingDir | zl
NB.
NB.   setjodliterate 'c:\temp'          NB. windows
NB.   setjodliterate '/home/john/temp'  NB. linux
NB.
```

```
NB. NB. use the current JOD put dictionary document directory
NB. setjodliterate ''
NB.
NB. dyad: (paRc ; clDir) =. clAuthor setjodliterate clWorkingDir | zl
NB.
NB. NB. set LaTeX \author{...} text
NB. 'Bob Squarepants (\texttt{pinapple@undersea.org})' setjodliterate ''
NB. 'Batman (\texttt{dn@jl.com}), Dr. Who (\texttt{who@univ.edu})' setjodliterate ''
NB. 'First Author \ Lowly Minion' setjodliterate ''

JLDEFAULTAUTHORS setjodliterate y
:
try.

if. 3~:(4!0) <'badrc_ajod_' do. 0; '!error: jod is not loaded' return. end.
if. 0 = #DPATH__ST__JODobj do. 0; '!error: no open jod dictionaries' return. end.

NB. if the path is empty use the current put dictionary document directory !(*)=. dob
if. 0 e. $y do. y=. DOC__dob [ dob=. {:{.DPATH__ST__JODobj end.

JLAUTHOR_ajodliterate_=: x

NB. profile (*)=. IFWIN
JLDIRECTORY_ajodliterate_=: jpathsep`winpathsep@.(IFWIN) tslash2 y

NB. write main latex preamble and cleaner iff missing
preamble=. 'JODLiteratePreamble.tex'
```

```
cleaner=. '00cleantex.bat'          NB. NIMP: linux/mac scripts
if. -.fexist JLDIRECTORY,preamble do.
  (toJ JODLiteratePreamble) writeas JLDIRECTORY,preamble
end.
if. -.fexist JLDIRECTORY,cleaner do.
  (toJ JLCLEANTEX) writeas JLDIRECTORY,cleaner
end.
1;JLDIRECTORY

catchd.
  0;!'error: (setjodliterate) failure - last J error ->';13!:12 ''
end.
)

seturlsha256=: 4 : 0

NB.*seturlsha256 v-- set url and sha-256 hash in (x).
NB.
NB. If a word has an associated '_dateurlhash' set the url and
NB. hash in (x).
NB.
NB. dyad: clTex =. clTex seturlsha256 clname
NB.
NB. JLTITLETEX seturlsha256 'jodliterate'

NB. require 'jod' !(*)=. get

NB. load any hash date url noun into the JOD scratch object
```

```

if. badrc_ajod_ (;SO__JODobj) get hdu=. (alltrim y),'_hashdateurl' do. x
else.
  NB. set the hash and url
  'hash url'=. 0 2{"hdu=. hdu,'__SO__JODobj'
  pav=. 254{a. NB. use an unlikely delimiter
  tex=. (pav,'~#~ijsurl~#~',pav,url,pav,'~#~sha256~#~',pav,hash) changestr x [ (4!:55) <hdu
  NB. uncomment %\ - leave % - geared for JLTITLETEX
  tex=. '#%\#\' changestr tex
end.
)

NB. start indexes from (rmatches): srxm 's' rmatches 'start me up silly'
srxm=: {. "1@,"2

NB. appends trailing line feed character if necessary
tlf=: ] , ((10{a.)"_ = {:) }. (10{a.)"_

NB. converts character strings to J delimiter LF
toJ=: ((10{a.) I.@(e.&(13{a.))@]} ] )@:(#~ -. @((13 10{a.)&E.@,))

NB. appends trailing / iff last character is not \ or /
tslash2=: ([: - '\/' e.~ {:) }. '/' ,~ ]

NB. character list to UTF-8
utf8=: 8&u:

NB. unwrapped latex from words: uwlatexfrwords ;:'we wrap ugly'
uwlatexfrwords=: [: latexfrmarkd 0 markdfrwords ]

```

```
NB. standardizes path delimiter to windows back \ slash
winpathsep=: '\&(( '/' I.@:= ])) } )

wordlatex=: 3 : 0

NB.*wordlatex v-- LaTeX from word list.
NB.
NB. monad: clLatex =. wordlatex blclWords

NB. require 'jod' !(*) badcl_ajod_
if. badcl_ajod_ mtxt=. markdfrwords y do. mtxt return.
elseif. #mtxt do. 1 indexwraplatex <latexfrmarkd mtxt
elseif.do. ''
end.
)

wordlit=: 3 : 0

NB.*wordlit v-- make latex from word list (y).
NB.
NB. monad: (paRc ; blclTeXfiles) =. wordlit blclWords
NB.
NB. wordlit 'jodliterate'
NB.
NB. dyad: (paRc ; blclTeXfiles) =. paDw wordlit blclWords
NB.
NB. NB. do not overwrite root tex - allows for latex tweaking
```

```
NB. 0 wordlit 'jodliterate'

1 wordlit y
:
NB. require 'jod' !(*)=. badrc_ajod_ badcl_ajod_ checknames_ajod_
try.

if. 3~:(4!:0) <'badrc_ajod_' do. 0;'!error: jod is not loaded' return. end.
if. 0=#JLDIRECTORY do. 0;'!error: working directory is not set' return. end.

NB. only valid jod names
if. badrc_ajod_ wlist=. checknames_ajod_ y do. wlist return. end.

NB. use first name on word list for tex file names
texname=. ;0{wlist=. }.wlist

NB. make latex
if. badcl_ajod_ wltx=. wordlatex wlist do. wltx return. end.

NB. root .tex file
wdir=. JLDIRECTORY
jlroot=. wdir,texname, '.tex'
if. chroot=. x -: 1 do.
  root=. ('/~#~texname~#~/',texname) changestr JLWORDLITTEX
  (toJ root) writeas jlroot
end.
```

*NB. group build batch script - latex utils that compile generated files*

```
jlbuildtex=. ('/~#~group~#~/',texname) changestr JLBUILDTEX  
(toJ jlbuildtex) writeas jlbuildbat=. wdir,texname, '.bat'
```

*NB. source code .tex - return file names*

```
wltx=. ppcodelatex wltx  
(toJ wltx) writeas jlcode=. wdir,texname,JLCODEFILE  
ok_ajod_ (-.chroot) }. jlroot;jlcode;jlbuildbat
```

```
catchd.
```

```
  0; '!error: (wordlit) failure - last J error ->';13!:12 ''  
end.  
)
```

```
wrapQtlatex=: 3 : 0
```

*NB.\*wrapQtlatex v-- adjust wrapped quoted string LaTeX.*

*NB.*

*NB. monad: clNewTeX =. wrapQtlatex clTex*

*NB. require 'regex' !(\*)=. rxmatches*

*NB. assignment latex*

```
alx=. '\AlertTok{=:}' [ klx=. '\KeywordTok{=.}'
```

```
if. +./ (alx;klx) +./@E.&> < y do.
```

*NB. last token in string before quote after assignment*

```
NB. hack to handle forms like: text=. <:_1 ' you parsing me'
if. #ltp=. }.srxm PANDOCKPAT rxmatches TEXTQUOTESINGLE beforestr y do.
  hd=. ltp {. y [ ltp=. _1{ltp
  hd,(STRINGTOKPFX;ALERTTOKPFX) replacetoks ltp}.y
else.
  (alx beforestr y),alx,(STRINGTOKPFX;ALERTTOKPFX) replacetoks alx afterstr y
end.

else.
  (STRINGTOKPFX;ALERTTOKPFX) replacetoks y
end.
)

NB. expand start/end indexes in wrap table: 1 0 1 wraplix >2 5;7 8;13 27
wraplix=: [: ; (0 { "1 #) +&.> [: i.&.> [: >: [: -/"1 [: |."1 #

wraprgidx=: 3 : 0

NB.*wraprgidx v-- start/end indexes of wrapped line regions.
NB.
NB. monad: it =. wraprgidx pl

b=. firstones y
r=. 0 -.&.>~ (b <:_1 y) *&.> b <:_1 i.#y
(<:@{.&> r) ,. {:&> r
)
```



```
wrapvrblong=: 3 : 0
```

```
NB.*wrapvrblong v-- wraps verbatim text lines with length > (x).
```

```
NB.
```

```
NB. Wraps lines with length > (x) and prefixes each wrapped line
```

```
NB. with the syntactically invalid j string ')=.)=.' (WRAPPREFIX)
```

```
NB. This string is transformed by pandoc into an easily found
```

```
NB. sequence of LaTeX commands.
```

```
NB.
```

```
NB. monad: cl =. wrapvrblong clTxt
```

```
NB. dyad: cl =. iaLength wrapvrblong clTxt
```

```
WRAPLIMIT wrapvrblong y
```

```
:
```

```
NB. always trim trailing blanks
```

```
ct=. <@rtrim;._2 tlf y -. CR
```

```
NB. only wrap lines exceeding limit
```

```
if. #pos=. I. x < #&> ct do.
```

```
  wlen=. x-#WRAPLEAD
```

```
  wt=. (-wlen) (<\)&.> pos{ct
```

```
  slen=. 1&,@:<:@#&.> wt
```

```
NB. lead wrapped lines with prefix
```

```
wt=. (slen #&.> <(<''),<LF,WRAPPREFIX) ,.&.> wt
```

```
wt=. a: -.~ L: 1 ,&.> wt
```

```
NB. last wrapped line LF terminated
```

```
wt=. wt , L: 1 <LF
```

```
nwpos=. (i.#ct) -. pos
ct=. ((nwpos{ct} ,&.> LF) nwpos} ct
;;wt pos} <"0 ct
else.
  (-LF~::~:y) }. ; ct ,&.> LF
end.
)
```

```
NB. write file as list of bytes - throws unambiguous error on failure
writeas=: (1!:2 ]`<@.(32&>@.(3!:0))) ::([: 'cannot write file'&(13!:8) 1:)
```

```
NB.POST_jodliterate post processor (-.)=:
```

```
smoutput IFACE=: (0 : 0)
NB. (jodliterate) interface word(s):
NB. -----
NB. THISPANDOC      NB. full pandoc path - use (pandoc) if on shell path
NB. formifacetex    NB. formats hyperlinked and highlighted interface words
NB. grplit          NB. make latex for group (y)
NB. ifacesection    NB. interface section summary string
NB. ifc             NB. format interface comment text
NB. setjodliterate  NB. prepare LaTeX processing - sets out directory writes preamble
NB. uwlatexfrwords  NB. unwrapped latex from words: uwlatexfrwords ;:'we wrap ugly'
NB. wordlit         NB. make latex from word list (y)
)
```

```
cocurrent 'base'
coinset   'ajodliterate'

(3 : 0) ''
try.
NB. use any pandoc set in the JOD profile for this machine
if. wex_ajod_ <'PREFERREDPANDOC_ajodliterate_' do. THISPANDOC_ajodliterate_=: PREFERREDPANDOC_ajodliterate_ end.
if. +./@('pandoc'&E.) panver=. ;0{ <:_2 tlf (shell THISPANDOC_ajodliterate_,' --version') -. CR do.
    smoutput 'NOTE: adjust pandoc path if current version (' ,panver,') is not >= 2.9.1.1'
end.
catch.
    smoutput 'ERROR: pandoc not set - adjust THISPANDOC_ajodliterate_'
end.
)
```

# Index

afterstr, 25  
ALERTTOKPFX, 21  
ALERTTOKWRAP, 9  
alltrim, 25  
  
beforestr, 26  
BEGININDEX, 21  
BEGINJODHEADER, 21  
BEGINJODPOSTP, 21  
BEGINNOTJ, 21  
betweenstrs, 26  
boxopen, 26  
  
changestr, 26  
charsub, 28  
COMMENTTOKPFX, 21  
CR, 21  
ctl, 28  
cutnestidx, 28  
cutpatidx, 30  
  
dbquote, 31  
dbquoteuq, 31  
DEFAULTPANDOC, 21  
  
ENDINDEX, 21  
ENDJODHEADER, 22

ENDJODPOSTP, 22  
ENDNOTJ, 22  
  
FAKETOKENS, 22  
fboxname, 32  
ferase, 32  
fexist, 32  
firstones, 32  
formifacetex, 32  
formtexindexes, 33  
fsize, 34  
fuserows, 34  
  
gbodylatex, 35  
gheadlatex, 35  
gpostlatex, 35  
grouplatex, 36  
grplit, 37  
  
IFACE, 66  
ifacemarkd, 40  
ifacesection, 40  
ifacewords, 40  
IFACEWORDSjodliterate, 22  
IFACEWORDSPFX, 22  
ifc, 41  
IFCPFX, 22

indexgroupptex, 42  
indexwraplatex, 43  
  
JLAUTHOR, 22  
JLAUTHOR\_ajodliterate\_, 58  
JLBUILDTEX, 11  
JLCLEANTEX, 9  
JLCODEFILE, 23  
JLDEFAULTAUTHORS, 23  
JLDIRECTORY, 9  
JLDIRECTORY\_ajodliterate\_, 58  
JLGRPLITTEX, 12  
JLINSERTIFACEMD, 23  
JLOVIEWFILE, 23  
JLOVIEWSUFFIX, 23  
JLOVIEWTEX, 11  
JLTITLEFILE, 23  
JLTITLETEX, 10  
JLWORDLITTEX, 13  
JODLiteratePreamble, 14  
jodliterateVMD, 25  
jpathsep, 44  
jtokenize, 44  
  
latexfrmarkd, 44  
LATEXTMP, 23  
LF, 23

long0d0latex, 45  
LONGCHRBEGPAT, 23  
LONGCHRENDPAT, 24

markdfrghead, 45  
markdfrgpost, 46  
markdfrgroup, 47  
markdfrwords, 47  
markdj, 49  
MARKDOWNHEAD, 24  
MARKDOWNTAIL, 24  
MARKDOWNTMP, 24  
markgassign, 49  
markgnonj, 51

PANDOCTOKPAT, 24  
patpartstr, 52  
ppcodelatex, 53

read, 54  
replacetoks, 55  
ROOTWORDSjodliterate, 24  
rtrim, 55  
  
setifacelinks, 55  
setifacesummary, 56  
setifacetargs, 56  
setjodliterate, 57  
seturlsha256, 59  
srxm, 60  
STRINGTTOKPFX, 24  
  
TEXTQUOTESINGLE, 24  
THISPANDOC, 25  
THISPANDOC\_ajodliterate\_, 67  
tlf, 60  
toJ, 60  
tslash2, 60

UBARSUB, 25  
utf8, 60  
uwlutexfrwords, 60  
  
wfl, 9  
WHITESPACE, 25  
winpathsep, 61  
wordlatex, 61  
wordlit, 61  
WRAPLEAD, 9  
WRAPLIMIT, 25  
wraplix, 64  
WRAPPREFIX, 25  
WRAPPREFIXTEX, 25  
wrapQtlatex, 63  
wraprgidx, 64  
wrapvrblong, 65  
writeas, 66