


# Using jodliterate

May 25, 2020

## 0.1 Using jodliterate

The [JODSOURCE](#) addon, (a part of the [JOD](#) system), contains a handy *literate programming* tool that enables the generation of *beautiful* J source code documents.

The *Bible*, *Koran*, and *Bhagavad Gita* of Literate Programming is Donald Knuth's [masterful tome](#) of the same name.



Knuth applied Literate Programming to his T<sub>E</sub>X systems and produced what many consider [enduring masterpieces](#) of program documentation.

jodliterate is certainly [not worthy](#) of T<sub>E</sub>X level accolades but with a little work it's possible to produce fine documents. This [J kernel notebook](#) outlines how you can install and use jodliterate. [Jupyter](#) notebooks are typically executed but to accommodate J users that do not have Jupyter this notebook is also available on GitHub as a [static PDF document](#).

### Notebook Preliminaries

```
[1]: NB. show J kernel version
9!:14 ' '
```

j901/j64avx/windows/release-e/commercial/www.jsoftware.com/2020-01-29T11:15:50

```
[2]: NB. load JOD in a clear base locale
load 'general/jod' [ clear ''

NB. The distributed JOD profile automatically RESETME's.
NB. To safely use dictionaries with many J tasks they must
NB. be READONLY. To prevent opening the same put dictionary
NB. READWRITE comment out (dpset) and restart this notebook.
dpset 'RESETME'

NB. Converting Jupyter notebooks to LaTeX is
NB. simplified by ASCII box characters.
portchars ''

NB. Verb to show large boxed displays in
NB. the notebook without ugly wrapping.
sbx_ijod_=: ' ... ' , "1~ 75&{."1@":
```

**Installing jodliterate** To use jodliterate you need to:

1. Install a current version of J.
2. Install the J addons JOD, JODSOURCE, and JODDOCUMENT.
3. Build the JOD development dictionaries from JODSOURCE.
4. Install a current version of [pandoc](#).
5. Install a current version of  $\text{\TeX}$  and  $\text{\LaTeX}$ .
6. Make the jodliterate J script.
7. Run jodliterate on a JOD *group* with pandoc compatible document fragments.
8. Compile the files of the previous step to produce a PDF

When presented with long lists of program prerequisites my impulse is to *run!* Life is too short for configuration wars. Everything should be easy. Installing jodliterate requires more work than phone apps but compared to [enterprise installations](#) setting up jodliterate is trivial. We'll go through it step by step.

**Step 1: Install a current version of J** J is freely available at [jsoftware.com](#). J installation instructions can be found on the [J Wiki](#) on [this page](#).

Follow the appropriate instructions for your OS.

**Note:** JOD runs on Windows, Linux, and MacOS versions of J, hence these are the only platforms that currently support jodliterate.

**Step 2: Install the J addons JOD, JODSOURCE and JODDOCUMENT** After installing J install the J addons. J addons are installed with the J package manager [pacman](#). Pacman has three [IDE](#) flavors: a command-line flavor and two GUI flavors. The GUI flavors depend on [JQT](#) or [JHS](#). The GUI flavors of pacman are only available on some versions of J whereas the command line version is part of the base J install and is available on all platforms.

*I install all the addons. I recommend that you do the same.*

JOD depends on some J modules like `jfiles`, `regex`, and `task` that are sometimes distributed as addons. If you install all addons JOD's modules and dependents are both installed.

**Installing addons with command line pacman** Start J and do:

```
[3]: NB. install J addons with command-line pacman  
  
load 'pacman'      NB. load pacman jpkg services
```

```
[4]: 'help' jpkg ''  NB. what can you do for me?
```

Valid options are:

history, install, manifest, remove, reinstall, search,  
show, showinstalled, shownotinstalled, showupgrade,  
status, update, upgrade

[https://code.jsoftware.com/wiki/JAL/Package\\_Manager/jpkg](https://code.jsoftware.com/wiki/JAL/Package_Manager/jpkg)


```
[5]: NB. install all addons  
NB. see https://code.jsoftware.com/wiki/Pacman  
  
NB. uncomment next line if addons not installed  
NB. 'install' jpkg '*' NB.
```

```
[6]: 3 {. 'showinstalled' jpkg '' NB. first few installed addons
```


```
+-----+-----+-----+-----+  
|api/expat|1.0.11|1.0.11|libexpat      |  
+-----+-----+-----+-----+  
|api/gles |1.0.31|1.0.31|Modern OpenGL API|  
+-----+-----+-----+-----+  
|api/java |1.0.2 |1.0.2 |api: Java to J shared library|  
+-----+-----+-----+-----+
```

```
[7]: 'showupgrade' jpkg ''  NB. list addon updates
```

**Installing addons with JQT GUI pacman** I mostly use the Windows JQT version of pacman to install and maintain J addons. You can find pacman on the tools menu.



pacman shows all available addons and provides tools for installing, updating, and removing them.



The GUI version is easy to use. Press the **Select All** button and then press the **Install** button

to install all the addons. To update addons select the **Upgrades** menu and select the addons you want to update.

**Step 3: Build the JOD development dictionaries from JODSOURCE** JOD source code is distributed in the form of [JOD dictionary dumps](#). Dictionary dumps are large J scripts that serialize JOD dictionaries. Dumps contain everything stored in dictionaries. You will find source code, binary data, test scripts, documentation, build macros, and more in typical JOD dictionaries.

`jodliterate` is stored as a JOD dictionary group. A dictionary group is simply a collection of J words with optional *header* and *post-processor* scripts. JOD generates J scripts from groups. Before we can *make jodliterate* we must load the JOD development dictionaries. The JODSOURCE addon includes a J script that [loads development dictionaries](#).

Again, start J and do:

```
[8]: require 'general/jod'
```

```
[9]: NB. set a JODroot user folder
NB. if not set /jod/ is the default

NB. use paths for your OS
UserFolders_j_=: UserFolders_j_ , 'JODroot'; 'c:/temp'

NB. show added folder
UserFolders_j_ {~ (0 {"1 UserFolders_j_) i. <'JODroot'
```

```
+-----+-----+
|JODroot|c:/temp|
+-----+-----+
```

```
[10]: NB. load JOD developement dictionaries
load_dev_tmp=: 3 : 0
if. +./ (;:'joddev jod utils') e. od '' do.
  'dev dictionaries exist'
else.
  0!:(0<jpath'~addons/general/jodsource/jodsourcesetup.ijs'
end.
)

load_dev_tmp 0
```

```
dev dictionaries exist
```

```
[11]: NB. joddev, jod, utils should exist

erase 'load_dev_tmp'
(;:'joddev jod utils') e. od ''
```

```
1 1 1
```

**Step 4: Install a current version of pandoc** [pandoc](#) is easily one of the most useful markup utilities on the [intertubes](#). If you routinely deal with markup formats like markdown, XML,  $\text{\LaTeX}$ , json and you aren't using pandoc you are working too hard.

Be lazy! [Install pandoc](#).

jodliterate uses the `task` addon to *shell out* to pandoc. Versions of pandoc after 2.9.1.1 support J syntax high-lighting.

```
[12]: NB. show pandoc version from J - make sure you are running
      NB. a recent version of pandoc. There may be different
      NB. versions in many locations on various systems.
```

```
ppath=: "C:\Program Files\Pandoc\pandoc"
THISPANDOC_ajodliterate_=: ppath
shell THISPANDOC_ajodliterate_,' --version'
```

```
pandoc 2.9.1.1
Compiled with pandoc-types 1.20, texmath 0.12, skylighting 0.8.3
Default user data directory: C:\Users\john\AppData\Roaming\pandoc
Copyright (C) 2006-2019 John MacFarlane
Web: https://pandoc.org
This is free software; see the source for copying conditions.
There is no warranty, not even for merchantability or fitness
for a particular purpose.
```

```
[13]: NB. make sure your version of pandoc
      NB. supports J syntax-highlighting

      NB. appends line feed character if necessary
      tlf=:] , ((10{a.})"_ = {:) }. (10{a.})"_

      NB. J is on the supported languages list
      pcmd=: THISPANDOC_ajodliterate_,' --list-highlight-languages'
      (< ; _2 tlf (shell pcmd) -. CR) e.~ < , 'j'
```

1

**Step 5: Install a current version of LaTeX** jodliterate uses  $\text{\LaTeX}$  to compile PDF documents. When `setjodliterate` runs it sets an output directory and writes a  $\text{\LaTeX}$  preamble file `JODLiteratePreamble.tex` to it. It's a good idea to review this file to get an idea of the  $\text{\LaTeX}$  packages jodliterate uses. It's possible that some of these packages are not in your  $\text{\LaTeX}$  distribution and will have to be installed.

To ease the burden of  $\text{\LaTeX}$  package maintenance I use freely available  $\text{\TeX}$  versions that automatically install missing packages.

1. On Windows I use [MiKTeX](#)
2. On other platforms I use [TeXLive](#)

If your system automatically installs packages the first time you compile `jodliterate` output it may fetch missing packages from The Comprehensive T<sub>E</sub>X Archive Network ([CTAN](#)). If new packages are installed reprocess your files a few times to insure all the required packages are downloaded and installed.

**Step: 6 Make the `jodliterate` J script** Once the JOD development dictionaries are built (Step 3) making `jodliterate` is easy. Start J and do:

```
[14]: require 'general/jod'
```

```
NB. open dictionaries
od ;:'joddev jod utils' [ 3 od ''
```

```
++-----+-----+-----+
|1|opened (rw/ro/ro) ->|joddev|jod|utils|
++-----+-----+-----+
```

```
[15]: NB. generate jodliterate
      sbx mls 'jodliterate'
```

```
++-----+-----+-----+
|1|load script saved ->|c:/jod/joddev/script/jodliterate.ijs|
++-----+-----+-----+
...
...
...
```

`mls` creates a standard J load script. Once generated this script can be loaded with the standard J load utility. You can test this by restarting J without JOD and loading `jodliterate`.

```
[16]: NB. load generated script
      load 'jodliterate'
```

```
NB. (jodliterate) interface word(s):
NB. -----
```

```
NB. THISPANDOC      NB. full pandoc path - use (pandoc) if on shell path
NB. grplit          NB. make latex for group (y)
NB. ifacesection    NB. interface section summary string
NB. ifc             NB. format interface comment text
NB. setjodliterate  NB. prepare LaTeX processing - sets out directory writes
preamble
```

NOTE: adjust pandoc path if version (pandoc 2.9.1.1) is not  $\geq$  2.9.1.1

**Step 7: Run `jodliterate` on a JOD group with pandoc compatible document fragments**  
This sounds a lot worse than it is. There is a group in `utils` called `sunmoon` that has an interesting *pandoc compatible document fragment*.

Start J and do:

```
[17]: require 'general/jod'
```

```
od 'utils' [ 3 od ''
```

```
+--+-----+-----+
|1|opened (ro) ->|utils|
+--+-----+-----+
```

[18]: *NB. display short explanations for (sunmoon) words*  
`sbx hlpnl }. grp 'sunmoon'`

```
+-----+-----+-----+-----+-----+-----+ ...
|IFACEWORDSsunmoon|interface words (IFACEWORDSsunmoon) group ...
|NORISESET        |indicates sun never rises or sets in (sunriseset0) and ( ...
|ROOTWORDSsunmoon|root words (ROOTWORDSsunmoon) group ...
|arctan           |arc tangent ...
|calmoons         |calendar dates of new and full moons ...
|cos              |cosine radians ...
|fromjulian       |converts Julian day numbers to dates, converse (tojulian ...
|moons            |times of new and full moons for n calendar years ...
|round            |round (y) to nearest (x) (e.g. 1000 round 12345) ...
|sin              |sine radians ...
|sunriseset0      |computes sun rise and set times - see group documentatio ...
|sunriseset1      |computes sun rise and set times - see group documentatio ...
|tabit            |promotes only atoms and lists to tables ...
|tan              |tan radians ...
|today            |returns todays date ...
|yeardates        |returns all valid dates for n calendar years ...
+-----+-----+-----+-----+-----+-----+ ...
```

[19]: *NB. display part of the (sunmoon) group document header*  
*NB. this is pandoc compatible markdown - note the LaTeX*  
*NB. commands - pandoc allows markdown/LaTeX mixtures*  
`900 {. 2 9 disp 'sunmoon'`

`sunmoon` is a collection of basic astronomical algorithms  
The key verbs are `moons`, `sunriseset0` and `sunriseset1`.  
All of these verbs were derived from BASIC programs published  
in *\*Sky & Telescope\** magazine in the 1990's. The rest of  
the verbs in `sunmoon` are mostly date and trigonometric  
utilities.

```
\subsection{\texttt{sunmoon} Interface}
```

```
~~~~ { .j }
  calmoons      NB. calendar dates of new and full moons
  moons         NB. times of new and full moons for n calendar years
  sunriseset0   NB. computes sun rise and set times - see group documentation
  sunriseset1   NB. computes sun rise and set times - see group documentation
~~~~
```



```
\subsection{\textbf\texttt{sunriset0} \textsl{v--} sunrise and sunset times}
```

This verb has been adapted from a BASIC program submitted by Robin G. Stuart \*Sky & Telescope's\* shortest sunrise/set program cont

```
[20]: NB. run jodliterate on (sunmoon)
require 'jodliterate'

NB. set the output directory - when
NB. running in Jupyter use a subdirectory
NB. of your notebook directory.

ltxpath=: 'C:\Users\john\AnacondaProjects\testfolder\grplit\'
setjodliterate ltxpath
```

```
+-----+
|1|C:\Users\john\AnacondaProjects\testfolder\grplit\|
+-----+
```

```
[21]: NB. (grplit) returns a list of generated
NB. LaTeX and command files. The *.bat
NB. file compiles the generated LaTeX

.. grplit 'sunmoon'
```

```
+-----+
|1|                                     |
+-----+
|C:\Users\john\AnacondaProjects\testfolder\grplit\sunmoon.tex      |
+-----+
|C:\Users\john\AnacondaProjects\testfolder\grplit\sunmoontitle.tex|
+-----+
|C:\Users\john\AnacondaProjects\testfolder\grplit\sunmoonoview.tex|
+-----+
|C:\Users\john\AnacondaProjects\testfolder\grplit\sunmooncode.tex |
+-----+
|C:\Users\john\AnacondaProjects\testfolder\grplit\sunmoon.bat      |
+-----+
```

**Step 8: Compile the files of the previous step to produce a PDF**

```
[22]: _250 {. shell ltxpath, 'sunmoon.bat'
```

```
gular.otf><c:/program files/miktex 2.9/fonts/ope
ntype/public/lm/lmmono12-regular.otf>
Output written on sunmoon.pdf (22 pages, 107711 bytes).
Transcript written on sunmoon.log.
```

```
(base) C:\Users\john\AnacondaProjects\testfolder\grplit>endlocal
```

```
[23]: NB. uncomment to display generated PDF
      NB. shell ltxpath, 'sunmoon.pdf'
```

**Storing jodliterate pandoc compatible document fragments in JOD** Effective use of `jodliterate` requires a melange of Markdown,  $\text{\LaTeX}$ , JOD, and J skills combined with a healthy attitude about *experimentation*. You have to try things and see if they work!

However, before you can *try* `jodliterate` document fragments you have put them in JOD dictionaries.

`jodliterate` uses two types of document fragments:

1. markdown overview group documents.
2.  $\text{\LaTeX}$  overview macros.

Markdown group documents are transformed by pandoc into  $\text{\LaTeX}$  but the overview macros are not altered in any way. This enables the use of arbitrarily complex  $\text{\LaTeX}$ . The following examples show how to insert document fragments.

### Create a jodliterate Demo Dictionary

```
[24]: NB. create a demo dictionary - (didnum) insures new name
      require 'general/jod'

      NB. new dictionary in default JOD directory
      sbx newd itslit_ijod=: 'aaa'," :didnum_ajod_ ''
```

```
+--+-----+-----+-----+-----+-----+-----+-----+-----+-----+ ...
|1|dictionary created ->|aaa327403631806685638405507439206657280913|c:/user ...
+--+-----+-----+-----+-----+-----+-----+-----+-----+-----+ ...
```

```
[25]: NB. 1 if new dictionary created
      (<itslit) e. od ''
```

1

```
[26]: od itslit [ 3 od '' NB. open only new dictionary
```

```
+--+-----+-----+-----+-----+-----+-----+-----+-----+-----+
|1|opened (rw) ->|aaa327403631806685638405507439206657280913|
+--+-----+-----+-----+-----+-----+-----+-----+-----+-----+
```

```
[27]: NB. define some words
      freq=:~. ; #/.~
      movmean=: -@[ (+/ % #)\ ]
      geomean=: # %: */
```

```

bmi=: 704.5"_ * ] % [: *: [
polyprod=:+//.@(*/)

wlst=: ;:'freq movmean geomean bmi polyprod'

NB. put in dictionary
put wlst

NB. short word explanations
t=: ,: 'freq';'frequency distribution'
t=: t , 'movmean';'moving mean'
t=: t , 'geomean';'geometric mean of a list'
t=: t , 'bmi';'body mass index - (x) inches (y) lbs'
t=: t , 'polyprod';'polynomial product'

0 8 put t

```

```

++-----+
|1|5 word explanation(s) put in ->|aaa327403631806685638405507439206657280913|
++-----+

```

[28]: NB. make header and macro groups

```

grp 'litheader' ; wlst
grp 'litmacro' ; wlst

```

```

++-----+
|1|group <litmacro> put in ->|aaa327403631806685638405507439206657280913|
++-----+

```

[29]: IFACEWORDSlitheader=: wlst

```

put 'IFACEWORDSlitheader'

```

```

++-----+
|1|1 word(s) put in ->|aaa327403631806685638405507439206657280913|
++-----+

```

## Use Group Document Overview Markdown

[30]: NB. add group header markdown

```

litheader=: (0 : 0)
`litheader` is a markdown demo group.

```

This markdown text will be  
[transmogrified](https://calvinandhobbes.fandom.com)  
by `pandoc` to \LaTeX. A group interface will be  
generated from the `IFACEWORDSlitheader`  
list. Interface lists are usually, but  
not always, associated with a *\*class group\**.

```
\subsection{\texttt{litheader} Interface}
```

```
`{~{insert_interface_md_}~}`  
)
```

*NB. store markdown as a JOD group document*

```
2 9 put 'litheader';litheader
```

```
+-----+  
|1|1 group document(s) put in ->|aaa327403631806685638405507439206657280913|  
+-----+
```

[31]: *NB. run jodliterate on group*

```
ltxpath=: 'C:\Users\john\AnacondaProjects\testfolder\grplit\  
setjodliterate ltxpath  
{: grplit 'litheader'
```

```
+-----+  
|C:\Users\john\AnacondaProjects\testfolder\grplit\litheader.bat|  
+-----+
```

[32]: *NB. compile latex*

```
_250 {. shell ltxpath,'litheader.bat'
```

```
lar.otf><c:/program files/miktex 2.9/fonts/o  
pentype/public/lm/lmmono12-regular.otf>  
Output written on litheader.pdf (4 pages, 47726 bytes).  
Transcript written on litheader.log.
```

```
(base) C:\Users\john\AnacondaProjects\testfolder\grplit>endlocal
```

[33]: *NB. uncomment to show PDF*

```
NB. shell ltxpath,'litheader.pdf'
```

## Use Macro Overview LaTeX

[34]: *NB. add a LaTeX overview - this code will not*

*NB. be altered by jodliterate the suffix*

*NB. '\_oview\_tex' is required to associate*

*NB. the overview with the group 'litmacro'*

```
litmacro_oview_tex=: (0 : 0)
```

```
This \LaTeX\ code will not be  
touched by \texttt{jodliterate}.
```

```

\subsection{Business Babel}

``Truth management is enabled.''

\emph{Excerpt from an actual business document!}
Obviously composed in an irony free zone.

\subsection{Some Complicated \LaTeX}

\medskip

\[
\frac{1}{\Bigl(\sqrt{\phi \sqrt{5}}-\phi\Bigr) e^{\frac{25}{\pi}}} =
1+\frac{e^{-2\pi}}{\{1+\frac{e^{-4\pi}}{\{1+\frac{e^{-6\pi}}{\{1+\frac{e^{-8\pi}}{\{1+\ldots\}}\}}\}}\}}
\]

)

NB. store LaTeX as JOD text macro
4 put 'litmacro_oview_tex';LATEX_ajod_;litmacro_oview_tex

```

```

+-----+
|1|1 macro(s) put in ->|aaa327403631806685638405507439206657280913|
+-----+

```

```

[35]: NB. run jodliterate on group
{: grplit 'litmacro'

```

```

+-----+
|C:\Users\john\AnacondaProjects\testfolder\grplit\litmacro.bat|
+-----+

```

```

[36]: NB. compile latex
_250 {. shell ltxpath,'litmacro.bat'

```

```

e1/public/lm/lmsy6.pfb><C:/Program Files/MiKTeX 2.9/fonts/type1/public/lm/lms
y8.pfb>
Output written on litmacro.pdf (4 pages, 138976 bytes).
Transcript written on litmacro.log.

```

```

(base) C:\Users\john\AnacondaProjects\testfolder\grplit>endlocal

```

```

[37]: NB. display PDF
NB. shell ltxpath,'litmacro.pdf'

```

**Using jodliterate with larger J systems** The main jodliterate verb `grplit` works with single JOD groups. Larger systems are typically made from many groups. JOD macro and test scripts are one way to work around this limitation. The JOD development dictionaries contain several macros that illustrate this approach.

```
[38]: od ;:'joddev jod utils' [ 3 od ''

NB. list macros with substring 'latex'
4 2 dnl 'latex'
```

```
+-----+
|1|buildjodlatex|buildjodliterate|
+-----+
```

```
[39]: NB. display start of macro that
NB. applies jodliterate to JOD code
250 {. 4 disp 'buildjodlatex'
```

```
NB.*buildjodlatex s-- generates syntax highlighted JOD source LaTeX.
NB.
NB. Files are written to the put dictionary's document directory.
NB.
NB. assumes: current versions of pandoc (pandoc 2.9.1.1 or later)
NB.          check noun (THISPANDOC)
```

**Final Remarks** jodliterate is an idiosyncratic anal-retentive software utility; it's mainly for people that consider source code an art form. *Nobody likes ugly undocumented art!*

If you have any questions, suggestions, or complaints please leave a comment on this post. To include others join one of [J discussion forums](#) and post your queries there.

*May the source be with you!*