

# books Group

John D. Baker

<https://github.com/bakerjd99/jackshacks/blob/main/books.ijs>

SHA-256: 52ce64539d391b2322490c317794840a98a1fcf2c7554eba8b9aa7f34b66bdfb

November 9, 2024

## Contents

books Overview	2
books Source Code	3
=: Index	15

## books Overview

## books Source Code

```
NB.*books s-- summarize books read.
NB.
NB. verbatim:
NB.
NB. interface word(s):
NB. -----
NB.  bookctgstats  - book category statistics
NB.  booksperyear2 - books per year from standard btcl books table
NB.  manyauthors   - authors read more than once
NB.  manyreads     - books read more than once
NB.  stdbookstab   - standard books table
NB.
NB. created: 2024nov03
NB. -----
NB. 24nov05 (bookctgstats) added

coclass 'books'

NB.*end-header

NB. carriage return line feed character pair
CRLF=: 13 10{a.

NB. interface words (IFACEWORDSbooks) group
IFACEWORDSbooks=: < ; . _1 ' bookctgstats booksperyear2 manyauthors manyreads stdbookstab'
```

*NB. line feed character*

```
LF=: 10{a.
```

*NB. root words (ROOTWORDSbooks) group*

```
ROOTWORDSbooks=: <;._1 ' IFACEWORDSbooks ROOTWORDSbooks VMDbooks bookctgstats booksperyear2 dstat manyautho  
>..>rs manyreads ofreqlist portchars stdbookstab'
```

*NB. version, make count and date*

```
VMDbooks=: '0.5.0';01;'09 Nov 2024 16:14:14'
```

*NB. trims all leading and trailing white space*

```
allwhitetrim=: ] #~ [: -. [: (*./\ . +. */.\) ] e. (9 10 13 32{a.)"_
```

```
antimode=: 3 : 0
```

*NB.\*antimode v-- finds the least frequently occurring item(s) in*

*NB. a list.*

*NB.*

*NB. monad: ul =. antimode ul*

*NB.*

*NB. antimode ?.500#100*

*NB. antimode ;:'blah blah blah yada yada wisdom'*

```
if. 0 < # y =. ,y do.      NB. no antimodes for null lists
```

```
  f =. #/._~ y            NB. nub frequency
```

```
(~. y) #~ f e. <./ f  NB. lowest frequency items
else. y
end.
)

bookctgstats=: 3 : 0

NB.*bookctgstats v-- book category statistics.
NB.
NB. monad:  ct =. bookctgstats btclBtab
NB.
NB.  bookctgstats stdbookstab '~BOOKS/books.txt'

'ctg cnt'=: ofreqlist }. tolower&.> y {"1~ (tolower&.> 0{y) i. <'type'
ctg ,.' ',.':0.001 round cnt,.(100*cnt%t),.s,.t %~ s=. +/\cnt [ t=. +/\cnt
)

booksperyear2=: 3 : 0

NB.*booksperyear2 v-- books per year from standard btcl books table.
NB.
NB. monad:  it =. booksperyear2 btclBtab
NB.
NB.  btab=. stdbookstab '~BOOKS/books.txt'
NB.  d=. booksperyear2 btab
NB.  0.01 dstat 1{d
```

```
h=. tolower&.> 0{y
d=. }. y
d=. freqlist (h i. <'year') {"1 d
d=. (_1&".&> 0{d) ,: ;1{d

NB. merge in missing zero years
d=. d ,. 0 ,:~ (0{d) -.~ ({.0{d) + i. >:(>./ - <./) 0{d
(/: 0{d) {"1 d
)

charsub=: 4 : 0

NB.*charsub v-- single character pair replacements.
NB.
NB. dyad: clPairs charsub cu
NB.
NB. ' _ $ ' charsub '$123 -456 -789'

'f t'=. ((#x)$0 1)<0,&a./ .x
t {~ f i. y
)

NB. deviation about mean
dev=: -" _1 _ mean

dstat=: 3 : 0
```

```
NB.*dstat v-- descriptive statistics
NB.
NB. monad: ct =. dstat nl
NB.
NB.    dstat    ?.1000#100
NB.
NB. dyad:  ct =.  faRound dstat nl
NB.
NB.    0.1 dstat    ?.1000#100

0.0001 dstat y
:
t=. '/sample size/minimum/maximum/1st quartile/2nd quartile/3rd quartile/first mode'
t=. t , '/first antimode/mean/std devn/skewness/kurtosis'
min=. <./
max=. >./
t=. ,&' : ' ;._1 t
v=. $,min,max,q1,median,q3,({.@mode2),({.@antimode),mean,stddev,skewness,kurtosis
t,. ": x round ,. v , y
)

NB. frequency distribution of boxed list items
freqlist=: ~. ,: [: <"0 #/.~

NB. REFERENCE - standard z locale verb: jpath '~temp/'
jpath=: jpath_j_
```

*NB. kurtosis*

```
kurtosis=: # * +/@(~&4)@dev % *:@ssdev
```

```
manyauthors=: 4 : 0
```

*NB.\*manyauthors v-- authors read more than once.*

*NB.*

*NB. dyad: cl =. iaWidth manyauthors btclBtab*

*NB.*

*NB. 70 manyauthors stdbookstab '~BOOKS/books.txt'*

*NB. authors by decreasing read counts*

```
'author cnt'=. ofreq s: }. y {"1~ (tolower&.> 0{y) i. <'author'
```

*NB. read more than once*

```
author=. b#author [ cnt=. b#cnt [ b=. 2 <: cnt
```

*NB. format as wrapped author & count*

```
many=. <"1 (' _' charsub '_' ,. ": ,. cnt) ,"1 ' ; '
```

```
many=. ;(' _'&charsub&.>5 s:author) ,&.> many
```

```
' _' charsub x wrapwords '_'&rebu many
```

```
)
```

```
manyreads=: 4 : 0
```

*NB.\*manyreads v-- books read more than once.*

*NB.*



*NB. dyad: cl =. iaWidth manyreads btclBtab*

*NB.*

*NB. 70 manyreads stdbookstab '~BOOKS/books.txt'*

*NB. titles by decreasing read counts*

```
'title cnt'=. ofreq s: }. y {"1~ (tolower&.> 0{y) i. <'title'
```

*NB. read more than once*

```
title=. b#title [ cnt=. b#cnt [ b=. 2 <: cnt
```

*NB. format as wrapped author & count*

```
many=. <"1 (' _' charsub '_' ,. ": ,. cnt) ,"1 ' ; '  
many=. ;(' _'&charsub&.>5 s:title) ,&.> many  
' _' charsub x wrapwords '_'&rebu many  
)
```

*NB. mean value of a list*

```
mean=: +/ % #
```

*NB. median value of a list*

```
median=: -:@(+/@)((<. , >.)@midpt { /:~) ::_:
```

*NB. mid-point*

```
midpt=: -:@<:@#
```

```
mode2=: 3 : 0
```

```
NB.*mode2 v-- finds the most frequently occurring item(s) in a
NB. list.
NB.
NB. monad: ul =. mode2 ul
NB.
NB. mode2 ?.500#100
NB. mode2 ;:'I do what I do because I am what I am'

if. 0 < # y =. ,y do.      NB. null lists have no modes
  f =. #/.~ y              NB. nub frequency
  (~. y) #~ f e. >./ f     NB. highest frequency items
else. y
end.
)

NB. like (freq) but results in descending frequency
ofreq=: [: (([: < [: \: [: ; 1 { ]) { &.> ]) ~. ; #/.~

NB. ordered boxed list frequency distribution - see long document
ofreqlist=: [: (([: \: [: ; 1 { ]) { "1 ]) ~. ,: [: <"0 #/.~

NB. parse TAB delimited table text after removing (x) chars - see long document
parsetdwc=: [: <;._2&> (a.{~9) ,&.>~ [: <;._2 [: (] , ((10{a.)"_ = {:) }. (10{a.)"_ ) (13{a.) -.~ -.~

NB. portable box drawing characters
portchars=: [: 9!:7 '+++++++|-'_" [ ]
```

*NB. first quartile*

```
q1=: median@((median > ]) # ]) ::_:
```

*NB. third quartile*

```
q3=: median@((median < ]) # ]) ::_:
```

*NB. reads a file as a list of bytes*

```
read=: 1!:1&[<@.(32&>@ (3!:0)))
```

```
reb=: 3 : 0
```

*NB.\*reb v-- removes redundant blanks - leading, trailing multiple*

*NB.*

*NB. monad: reb cl*

*NB. dyad: ua reb ul*

```
' ' reb y
:
y=. x , y
b=. x = y
}.(b*: 1|.b)#y
)
```

*NB. removes multiple blanks (char only)*

```
rebc=: ] #~ [: -. ' ' &E.
```

*NB. generalization of (rebc) (x) argument is any atom*

```
rebu=: ] #~ [: -. (2: # []) E. ]
```

*NB. round (y) to nearest (x) (e.g. 1000 round 12345)*

```
round=: [ * [: (<.) 0.5 + %~
```

*NB. skewness*

```
skewness=: %:@# * +/@(~&3)@dev % ^&1.5@ssdev
```

*NB. sum of square deviations (2)*

```
ssdev=: +/@:*:@dev
```

```
stdbookstab=: 3 : 0
```

*NB.\*stdbookstab v-- standard books table.*

*NB.*

*NB. monad: btcl =. stdbookstab clBooksfile*

*NB.*

*NB. btab=. stdbookstab '~BOOKS/books.txt'*

*NB. btab=. stdbookstab '~JACKSHACKS/testdata/books\_sample.txt'*

```
t=. ''' -.~ utf8 read jpath y
allwhitetrim@rebc&.> ''' parsetdwc t
)
```

*NB. standard deviation (alternate spelling)*

```
stddev=: %:@:var
```

*NB. convert to lower case*

```
tolower=: 0&(3!:12)
```

*NB. transitive closure*

```
tranclose2=: # (i.~ {. ]) [: }. (, #) { ~^:a: 0:
```

*NB. character list to UTF-8*

```
utf8=: 8&u:
```

*NB. var*

```
var=: ssdev % <:@#
```

```
wrapwords=: 4 : 0
```

*NB.\*wrapwords v-- wrap words into lines of length (x).*

*NB.*

*NB. This algorithm: due to Roger Hui. Wraps words (nonblank) runs*

*NB. into lines of length (x) without breaking words. Words cannot*

*NB. be longer than (x). Transitive closure is used to compute*

*NB. where appropriate newline (LF) characters replace blanks.*

*NB.*

*NB. dyad: cl =. iaWidth wrapwords clWords*

*NB.*

*NB. 27 wrapwords 7770\$'go ahead make my day and surprise me'*

*NB. remove extra blanks and CRLF*

```
y=. reb y -. CRLF
```

```
e=. (' ' I.@:= y),#y
```

```
LF (e {~ <: tranclose2 e I. (x+2)+}:_1,e)} y
```

```
)
```

*NB.POST\_books post processor.*

```
smoutput IFACE_books=: (0 : 0)
NB. (books) interface word(s): 20241109j161414
NB. -----
NB. bookctgstats    NB. book category statistics
NB. booksperyear2  NB. books per year from standard btcl books table
NB. manyauthors    NB. authors read more than once
NB. manyreads      NB. books read more than once
NB. stdbookstab    NB. standard books table
)

cocurrent 'base'
coinsert  'books'
```

# Index

', 5

allwhitetrim, 4

antimode, 4

bookctgstats, 5

booksperyear2, 5

charsub, 6

CRLF, 3

dev, 6

dstat, 6

freqlist, 7

IFACE\_books, 14

IFACEWORDSbooks, 3

jpath, 7

kurtosis, 8

LF, 4

manyauthors, 8

manyreads, 8

mean, 9

median, 9

midpt, 9

mode2, 9

ofreq, 10

ofreqlist, 10

parsetdwc, 10

portchars, 10

q1, 11

q3, 11

read, 11

reb, 11

rebc, 11

rebu, 11

ROOTWORDSbooks, 4

round, 12

skewness, 12

ssdev, 12

stdbookstab, 12

stddev, 12

tolower, 12

tranclose2, 13

utf8, 13

var, 13

VMDbooks, 4

wrapwords, 13