

# riset\_notebook

April 12, 2023

## 1 riset Examples

This notebook demonstrates the [J riset script](#). `riset` computes the rise, transit, and set times of named [IAU Stars](#).

To run this notebook you must install a J jupyter kernel. See Martin Saurer's [GitHub repository](#) for instructions.

```
[1]: NB. J version and date
smoutput 9!:14 ''
smoutput 6!:0 ''

NB. set portable box drawing characters
portchars=:[: 9!:7 '+++++++|-'"_ [ ]
portchars 0
```

```
j9.4.2/j64avx512/windows/commercial/www.jsoftware.com/2023-04-10T01:15:50/clang-
15-0-7/SLEEF=1
2023 4 12 10 19 6.549
```

### 1.1 Installation

`riset` is distributed as a J addon. It is installed in the J `~addons/jacks` folder. It can be installed from [GitHub](#) with:

```
[2]: load 'pacman'
NB. smoutput install 'github:bakerjd99/jackshacks' NB. uncomment to install
```

The `jacks` (J-hacks) addons are self contained [JOD generated](#) J scripts. Each `ijs` script is accompanied with pdf document that describes how to use it. Some scripts, like `riset` are also packaged with a Jupyter notebook (this file) and a pdf version of the notebook. For example, the `riset` files are:

```
riset.ijs
riset.pdf
riset_notebook.ipynb
riset_notebook.pdf
```

There are other scripts in `~addons/jacks` and more will be added from time to time. To refresh the folder, reissue the install command.

In addition to these files the subfolder `~addons/jacks/testdata` contains data files. `riserset` files in `testdata` are:

```
Bright_Stars_Meridian_Almanac_23mar27.md
iau_named_stars_2022.txt
Navigation_Stars.txt
```

```
[3]: NB. addon files
dir '~addons/jacks'
```

```
testdata          <dir>      06-Apr-23 13:20:13
brandxmp.ijs       13295 28-Mar-23 22:45:21
brandxmp.pdf       125252 28-Mar-23 22:45:21
gpxutils.ijs       17079 28-Mar-23 22:45:21
gpxutils.pdf       134365 28-Mar-23 22:45:21
ipynb.ijs          4699 28-Mar-23 22:45:21
ipynb.pdf          86966 28-Mar-23 22:45:21
manifest.ijs       1329 08-Apr-23 13:00:01
riserset.ijs       38243 08-Apr-23 12:56:52
riserset.pdf       193513 08-Apr-23 12:56:52
riserset_notebook.ipynb 28125 06-Apr-23 09:41:38
riserset_notebook.pdf 69512 06-Apr-23 09:41:38
```

## 1.2 Using riserset

```
[4]: NB. load '~addons/jacks/riserset.ijs' NB. addon version
load 'riserset' NB. dev version

smoutput 'NB. vmd: ' , , '0,p<; >q<; >0,0' (8!:2) VMDriserset
```

```
NB. (riserset) interface word(s): 20230408j134518
NB. -----
NB. baby_today  NB. named Babylonian stars rising/setting today
NB. fmt_today   NB. format today verbs result
NB. iau_today   NB. named IAU stars rising/setting today
NB. loadstars   NB. loads riserset star data
NB. nav_today   NB. named navigation stars rising/setting today
NB. navdaylist  NB. sky safari 6_0 observing list of today's navigation stars
NB. riserset    NB. rise, transit, set times of stars

      fmt_today nav_today location_home 0

NB. vmd: 0.9.7; 11; 08 Apr 2023 13:45:18
```

```
[5]: NB. set a location - add your own by cloning and modifying location verbs
location_yellowstone
```

```
3 : 0
```

```
NB.*location_yellowstone v-- set parameters for Old Faithful location.
```

```
NB.
```

```
NB. monad: location_yellowstone uuIgnore
```

```
NB.
```

```
NB. location_yellowstone 0
```

```
NB. NB. uses location with current date
```

```
NB. iau_today 0
```

```
NB.
```

```
NB. dyad: bl =. fLYmfd location_yellowstone uuIgnore
```

```
NB.
```

```
NB. NB. uses location with yellowstone date
```

```
NB. (location_yellowstone 0) iau_today 0
```

```
NB.
```

```
NB. NB. arbitrary dates for location
```

```
NB. fmt_today (1712 3 15.34 location_yellowstone 0) nav_today 0
```

```
NB. fmt_today (location_yellowstone~ 1933 9 25.75) iau_today 0
```

```
2013 5 7 location_yellowstone y
```

```
:
```

```
JULIAN_riseset_=: julfrcal ymd=. x
```

```
NB. longitude, latitude with standard signs
```

```
OBSLOCATION_riseset_=: _110.82792 44.46057
```

```
LOCATIONNAME_riseset_=: 'Yellowstone - Old Faithful'
```

```
UTCOFFSET_riseset_=: 6.0 NB. MST time zone
```

```
LIMITMAG_riseset_=: 6.0 NB. stellar magnitude
```

```
LIMITHORZ_riseset_=: 10 NB. degrees above horizon
```

```
ymd;JULIAN;OBSLOCATION;UTCOFFSET;LIMITMAG;LIMITHORZ;LOCATIONNAME
```

```
)
```

```
[6]: location_yellowstone 0
'IAU locname cParms'=: iau_today 0
```

```
NB. number of rising/setting IAU stars
```

```
smoutput #IAU
```

```
NB. limit magnitude, above horizon, julian date,  $\Delta T$  in seconds, longitude, ┐
```

```
↳ latitude, year, month day.dd
```

```
smoutput locname;cParms
```

```
NB. star name, designation, transit altitude degrees, transit time 24 hours, ┐
```

```
↳ minutes
```

```
smoutput 5 {. IAU
```

243

```
+-----+-----+
-----+
|Yellowstone - Old Faithful|6 10 2460046.75 73.45591845312505 _110.82792
44.46057 2023 4 12.25 6|
+-----+-----+
-----+
+-----+-----+-----+
|Alchiba|HR 4623|20.5|0 12|
+-----+-----+-----+
|Gienah |HR 4662|28  |0 20|
+-----+-----+-----+
|Zaniah |HR 4689|44.5|0 24|
+-----+-----+-----+
|Algorab|HR 4757|29  |0 34|
+-----+-----+-----+
|Chara  |HR 4785|87  |0 37|
+-----+-----+-----+
```

Detailed rise and set information is provided by **riseset**.

```
[7]: LB=: _116.375956 43.646775  NB. Meridian
YMD=: 2023 3 27
UO=: 6 NB. MST UTC offset

NB. star name, (0=rises/sets), altitudes, times fractional day, times hours,
↪minutes
'Rs cParms'=: (YMD;UO;LB) riseset 'Algol';'Rigel';'Spica'
smoutput cParms
smoutput Rs
```

```
2460030.75 73.40741357812496 _116.375956 43.646775 2023 3 27.25 6
+-----+-----+
|Algol|0| 0.5 0.2910386461449466 6 59|
|      | |87.5 0.6908345293917257 16 35|
|      | | 0.5 0.09337060171945516 2 14|
+-----+-----+
|Rigel|0| 1 0.5527905462948185 13 16|
|      | | 38 0.7780712498266437 18 40|
|      | |0.5 0.006088476753742347 0 9|
+-----+-----+
|Spica|0| 1 0.9012706582406574 21 38 |
|      | | 35 _0.8793144933635634 2 54 |
|      | |0.5 0.3373585646884121 8 6 |
+-----+-----+
```

The stars listed by **riseset** come from IAU named stars.

```
[8]: NB. leading characters from UTF-8 CSV IAU star data file
800 {. read jpath '~addons/jacks/testdata/iau_named_stars_2022.txt'
```

```
IAU_Name,Designation,HIP,Bayer_Name,Nm,WDS_J,Vmag,RA_J2000,Dec_J2000,Origin,Source,
ID,Const,Etymology_Note
Absolutno,X0-5,X0-5,_ Lyn,_,_,12.13,116.716506,39.094572,2019 IAU100
NameExoWorlds,https://www.nameexoworlds.iau.org/2019approved-names,_,Lyn,Czech
Republic proposal;Absolutno is a fictional miraculous substance in the sci-fi
novel Továrna na absolutno (T...
Acomar,HR 897,13847, 1 Eri,A,02583-4018,2.88,44.565311,-40.304672,,, 1,Eri,
Achernar,HR 472,7588, Eri,A,-,0.45,24.428523,-57.236753,Arabic,, ,Eri,The name
was originally Arabic: ʾāḥir an-nahr ('river's end').
Achird,HR 219,3821, Cas,A,00491+5749,3.46,12.276213,57.815187,,, ,Cas,"first
applied to Cassiopeiae in the Skalnate Pleso
```

```
[9]: loadstars~ 2
smoutput 'Named stars:', "#IAU_Name
smoutput 10 {. IAU_Name
```

```
Named stars:449
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
|Absolutno|Acomar|Achernar|Achird|Acrab|Acrux|Acubens|Adhafera|Adhara|Adhil|
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
```

Additional stars/objects can be added by editing the IAU file or by doing the following.

New objects need a name, right ascension (RA), and declination (Dec) for the J2000.0 epoch.

```
[10]: NB. meeus pg. 99,100
LB=: _71.0833 42.3333 NB. Boston
YMD=: 1988 3 20
UO=: 0
NB. add objects not in IAU names - needs - name, ra, dec
AOB=. (<:;'Venus'),(<41.73129),<18.44092
AOB=. ,&.> (:;'OBJ_Name OBJ_RA_J2000 OBJ_Dec_J2000') ,. AOB
DeltaTsOverride_riseset_=: 56
'Vrs cParms'=: (YMD;UO;LB;<AOB) riseset 'Venus'
0 0$erase 'DeltaTsOverride_riseset_'
smoutput cParms
smoutput Vrs
```

```
2447240.5 56 _71.08329999999999 42.3333 1988 3 20 0
+-----+-----+-----+-----+-----+
|Venus|0| 1 0.5211284270665463 12 30|
|      | | 66 0.8169433896164773 19 36|
|      | |0.5 0.1154978057116963 2 46|
+-----+-----+-----+-----+-----+
```

### 1.3 Maintaining and modifying riseset

All **riseset** code, documentation and test scripts are stored in the JOD dictionary **futs**. To change the code or run the test cases you need to install the JOD dictionaries **futs** and **utils**.

Use J's package manager to install the JOD addons **general/jod**, **general/joddocument**. If you have installed all the addons JOD is already on your system.

After installing JOD do:

1. Download the JOD dump scripts:

<https://github.com/bakerjd99/joddumps/blob/master/utils.ijs>

<https://github.com/bakerjd99/joddumps/blob/master/futs.ijs>

and put them in a **~temp** folder.

2. Start JOD and check for the presence of **futs** and **utils**.

*NB. start JOD*

```
load 'general/jod'  
(;:'futs utils') e. od''
```

3. Only if both dictionaries are missing do:

```
newd 'utils'  NB. creates utils dictionary in '~user/joddicts/utils'  
newd 'futs'   NB. creates futs in '~user/joddicts/futs'
```

4. Load the dictionaries:

```
NB. load utils first  
od 'utils' [ 3 od ''  
0!:0 <jpath '~temp/utils.ijs'  
NB. rebuild references  
0 globs&> }. revo ''  
NB. take first binary backup  
packd 'utils'
```

```
NB. load futs with utils on path  
od ;:'futs utils' [ 3 od ''  
0!:0 <jpath '~temp/futs.ijs'  
NB. rebuild references  
0 globs&> }. revo ''  
NB. take first binary backup  
packd 'futs'
```

```
NB. close dictionaries  
3 od ''
```

The rest of this notebook *assumes* you have installed **futs** and **utils**.

It also assumes a basic knowledge of JOD. See the JOD Manual for details. The JOD Manual is distributed in the **general/joddocument** addon - see:

~addons/general/joddocument/pdfdoc/jod.pdf

jod.pdf is also available on [The JOD Page](#)

## 1.4 riseset test suite

Many riseset test cases are in futs. Groups of test cases are called suites. The contents of the riseset suite is:

```
[11]: NB. open futs and utils - assumed open until notebook end
load 'general/jod'
od ;:'futs utils' [ 3 od ''
```

```
++-----+-----+
|1|opened (rw/ro) ->|futs|utils|
++-----+-----+
```

```
[12]: NB. list test cases in (riseset) suite
smoutput ,. }. 3 grp 'riseset'
```

```
+-----+
|riseset_atan2_smoke      |
+-----+
|riseset_espenak_smoke    |
+-----+
|riseset_meeus_smoke      |
+-----+
|riseset_navstars_ecu_smoke |
+-----+
|riseset_navstars_safari_smoke|
+-----+
|riseset_riseset_smoke    |
+-----+
|riseset_tanner_smoke     |
+-----+
```

```
[13]: NB. show test case
1 disp 'riseset_riseset_smoke'
```

NB.\*riseset\_riseset\_smoke t-- (riseset) smoke tests.

NB.

NB. created: 2023mar27

NB. changes: -----

NB. 23apr01 location name added

load 'riseset'

NB. meeus pg. 99,100

```

LB=: _71.0833 42.3333 NB. Boston
YMD=: 1988 3 20
UO=: 0
NB. add objects not in IAU names - needs - name, ra, dec
AOB=. (<;:'Venus'),(<41.73129),<18.44092
AOB=. ,&.> (;:'OBJ_Name OBJ_RA_J2000 OBJ_Dec_J2000') ,. AOB
DeltaTsOverride_riseset_=: 56
'Vrs cParms'=: (YMD;UO;LB;<AOB) riseset 'Venus'
0 0$erase 'DeltaTsOverride_riseset_'

NB. values are within 10 minutes of the meeus book
NB. result - not great but good enough for demo work
Meeusmin=: +/" 1 ] 60 1 *"1 ] 12 25 , 19 41 ,: 2 55
10 > >./|Meeusmin - +/" 1 ] 60 1 *"1 ] _2 {."1 ;2 {"1 Vrs

LB=: _116.375956 43.646775 NB. Meridian
YMD=: 2023 3 27
UO=: 6 NB. MST UTC offset

'Rs cParms'=: (YMD;UO;LB) riseset 'Algol'
'Rs cParms'=: (YMD;UO;LB) riseset 'Algol';'Rigel';'Spica'

NB. Bright Stars for 2023 3 27 Meridian
NB. https://www.almanac.com/astronomy/bright-stars/zipcode/83646/2023-03-27
Bs=: ;:'Altair Deneb Fomalhaut Algol Aldebaran Rigel Capella Bellatrix'
Bs=: Bs,;:'Betelgeuse Sirius Procyon Pollux Regulus Spica Arcturus Antares Vega'

'Rs cParms'=: (YMD;UO;LB) riseset Bs

NB. transits match fairly well rise/sets differ 5 to 10 minutes
BsTransit=: 9 18,10 8,12 25,16 35,18 2,18 41,18 43,:18 51
BsTransit=: BsTransit , 19 21,20 11,21 5,21 11,23 34,2 54,3 44,5 58,:8 4

NB. transit altitude degrees
BsAlt=: 55 88 16 87 62 38 87 52
BsAlt=: BsAlt,53 29 51 74 58 35 65 19 85

TMP=: {"1 Rs
ALT=: ((<1;,0)&{&> TMP) ,. BsAlt
TRT=: ((<1;2 3)&{&> TMP) ,. BsTransit

NB. altitudes match to 1 degree
1 = >./ -/"1 ALT

NB. transit times match to 1 minute in worst case
1 = >./ | (60 #:^:_1 ] 0 1 {"1 TRT) - 60 #:^:_1 ] 2 3 {"1 TRT

'IAU NAV'=: loadstars 0

```



```

({."1 NAV)=: {."1 NAV
({."1 IAU)=: {."1 IAU
'Navrs cParms'=: (YMD;UO;LB) riseset Nav_Star_Name
'Iaurs cParms'=: (YMD;UO;LB) riseset IAU_Name

NB. default
'Meridianrs lName cParms'=: iau_today 0

NB. date of Uluru star party diner
uJD=: julfrcal uYMD=: 2022 10 19
ULURU=: 131.01941 _25.34301
uUTC=: _9.5
uLMAG=: 6.0
uLHORZ=: 5
uNAME=: 'Uluru - star party diner'
'Ulururs lName cParms'=: (uYMD;uJD;ULURU;uUTC;uLMAG;uLHORZ;uNAME) iau_today 0
'Ulururs lName cParms'=: (uYMD;uJD;ULURU;uUTC;uLMAG;uLHORZ;uNAME) nav_today 0

'Navrs lName cParms'=: (location_yellowstone~ 1933 9 25.75) iau_today 0
'Navrs lName cParms'=: (location_home~ 1956 7 18) nav_today 0
'Navrs lName cParms'=: (location_uluru~ 2043 7 2) nav_today 0

0 0$erase 'AOB Meeusmin Vrs LB YMD UO Rs Bs BsTransit BsAlt TMP ALT TRT Navrs
Iaurs cParms'
0 0$erase (;:'IAU NAV') , ({."1 NAV), {."1 IAU
0 0$erase 'uYMD uJD ULURU uUTC uLMAG uLHORZ Meridianrs Ulururs uNAME lName'

smoutput 'PASSED:: riseset_riseset_smoke'

```

[14]: *NB. run all the test cases in the suite*  
*NB. suppressing all but (smoutput) output*  
*NB. Each test will show PASSED:: if OK.*  
4 rtt 'riseset'

```

NB. (riseset) interface word(s): 20230408j134518
NB. -----
NB. baby_today  NB. named Babylonian stars rising/setting today
NB. fmt_today   NB. format today verbs result
NB. iau_today    NB. named IAU stars rising/setting today
NB. loadstars    NB. loads riseset star data
NB. nav_today    NB. named navigation stars rising/setting today
NB. navdaylist   NB. sky safari 6_0 observing list of today's navigation stars
NB. riseset      NB. rise, transit, set times of stars

      fmt_today nav_today location_home 0

PASSED:: riseset_atan2_smoke
NB. (riseset) interface word(s): 20230408j134518

```

```

NB. -----
NB. baby_today  NB. named Babylonian stars rising/setting today
NB. fmt_today   NB. format today verbs result
NB. iau_today    NB. named IAU stars rising/setting today
NB. loadstars   NB. loads riseset star data
NB. nav_today    NB. named navigation stars rising/setting today
NB. navdaylist  NB. sky safari 6_0 observing list of today's navigation stars
NB. riseset      NB. rise, transit, set times of stars

```

```
fmt_today nav_today location_home 0
```

```
PASSED:: riseset_espenak_smoke
```

```
NB. (riseset) interface word(s): 20230408j134518
```

```
NB. -----
```

```

NB. baby_today  NB. named Babylonian stars rising/setting today
NB. fmt_today   NB. format today verbs result
NB. iau_today    NB. named IAU stars rising/setting today
NB. loadstars   NB. loads riseset star data
NB. nav_today    NB. named navigation stars rising/setting today
NB. navdaylist  NB. sky safari 6_0 observing list of today's navigation stars
NB. riseset      NB. rise, transit, set times of stars

```

```
fmt_today nav_today location_home 0
```

```
PASSED:: riseset_meeus_smoke
```

```
NB. (riseset) interface word(s): 20230408j134518
```

```
NB. -----
```

```

NB. baby_today  NB. named Babylonian stars rising/setting today
NB. fmt_today   NB. format today verbs result
NB. iau_today    NB. named IAU stars rising/setting today
NB. loadstars   NB. loads riseset star data
NB. nav_today    NB. named navigation stars rising/setting today
NB. navdaylist  NB. sky safari 6_0 observing list of today's navigation stars
NB. riseset      NB. rise, transit, set times of stars

```

```
fmt_today nav_today location_home 0
```

```
ECU riseset ALL/NORTH/SOUTH HrMin freq/stats =====
```

```
raw mean: _0.2796934865900383
```

```
distribution absolute minute diffs
```

```
0 1 2 3 4 5 6 7
```

```
10 75 69 65 27 7 6 2
```

```
stats absolute minute diffs
```

```
sample size: 261
```

```
minimum: 0
```

```
maximum: 7
```

```
1st quartile: 1
```

```
2nd quartile: 2
```

```

3rd quartile:      3
first mode:        1
first antimode:    7
mean:              2.3027
std devn:          1.3489
skewness:          0.8041
kurtosis:          3.7348
PASSED:: riseset_navstars_ecu_smoke
NB. (riseset) interface word(s): 20230408j134518
NB. -----
NB. baby_today     NB. named Babylonian stars rising/setting today
NB. fmt_today      NB. format today verbs result
NB. iau_today       NB. named IAU stars rising/setting today
NB. loadstars      NB. loads riseset star data
NB. nav_today       NB. named navigation stars rising/setting today
NB. navdaylist      NB. sky safari 6_0 observing list of today's navigation stars
NB. riseset        NB. rise, transit, set times of stars

```

```

fmt_today nav_today location_home 0

```

```

SKY riseset ALL/NORTH/SOUTH HrMin freq/stats =====

```

```

raw hrmin mean: _0.02040816326530612

```

```

distribution absolute minute diffs

```

```

0 1

```

```

48 1

```

```

stats absolute minute diffs

```

```

sample size:      49

```

```

minimum:          0

```

```

maximum:          1

```

```

1st quartile:     -

```

```

2nd quartile:     0

```

```

3rd quartile:     1

```

```

first mode:       0

```

```

first antimode:   1

```

```

mean:             0.0204

```

```

std devn:         0.1429

```

```

skewness:         6.7839

```

```

kurtosis:         47.0208

```

```

SKY riseset ALL/NORTH/SOUTH Altitude freq/stats =====

```

```

raw hrmin mean: 0.01224489795918367

```

```

distribution absolute altitude diffs

```

```

0 0.1 0.2

```

```

7 24 18

```

```

stats absolute altitude diffs

```

```

sample size:      49

```

```

minimum:          0

```

```

maximum:          0.2

```

```

1st quartile:     0

```

```

2nd quartile:          0.1
3rd quartile:          0.2
first mode:            0.1
first antimode:        0
mean:                  0.1224
std devn:              0.06850000000000001
skewness:              _0.3095
kurtosis:              2.1534
PASSED:: riseset_navstars_safari_smoke
NB. (riseset) interface word(s): 20230408j134518
NB. -----
NB. baby_today  NB. named Babylonian stars rising/setting today
NB. fmt_today   NB. format today verbs result
NB. iau_today   NB. named IAU stars rising/setting today
NB. loadstars   NB. loads riseset star data
NB. nav_today   NB. named navigation stars rising/setting today
NB. navdaylist  NB. sky safari 6_0 observing list of today's navigation stars
NB. riseset     NB. rise, transit, set times of stars

```

```

    fmt_today nav_today location_home 0

```

```

PASSED:: riseset_riseset_smoke
NB. (riseset) interface word(s): 20230408j134518
NB. -----
NB. baby_today  NB. named Babylonian stars rising/setting today
NB. fmt_today   NB. format today verbs result
NB. iau_today   NB. named IAU stars rising/setting today
NB. loadstars   NB. loads riseset star data
NB. nav_today   NB. named navigation stars rising/setting today
NB. navdaylist  NB. sky safari 6_0 observing list of today's navigation stars
NB. riseset     NB. rise, transit, set times of stars

```

```

    fmt_today nav_today location_home 0

```

```

PASSED:: riseset_tanner_smoke

```

```

1

```

## 1.5 Building riseset

There are a number of test scripts in `futs` that build and distribute `riseset`. These scripts are tuned to my environment but they do illustrate how to *make* a distribution script.

```

[15]: NB. show main riseset maker
portchars 0
NB. leading characters
smoutput 500 {. 1 disp 'build_riseset'
3 od ''

```

```

NB.*build_riseset t-- build (riseset) and distribute.
NB.
NB. created: 2023mar09
NB. changes: -----

coclass tmploc_AAAbuild999_=: 'AAAbuild999' [ coerase <'AAAbuild999'
coininsert 'ijod'

scrn=: 'riseset'

>0{OPENDIC=: did 0

NB. if (imex) is first dictionary on path include it
headdic=: ('imex'-:>1{OPENDIC) #'imex '

>0{od ;: headdic,'futs utils' [ 3 od ''

>0{tmploc get ;:'gettxt getmd getbyte afterlaststr read write showpass sha
+-+-----+-----+-----+
|1|closed ->|futs|utils|
+-+-----+-----+-----+

```

1.6 All done - thanks for playing