

riset Group

John D. Baker

<https://github.com/bakerjd99/jackshacks/blob/main/risetset.ijs>

SHA-256: 7a672f8b421ceab556d43e1d60903acdb12fb713895ed2aae08f230b7d6d25d7

April 6, 2023

Contents

riset Overview	2
riset Interface	3
riset Algorithm Notes	3
riset Source Code	5
=: Index	48

riset Overview

`riset` is a collection of basic astronomical algorithms that compute the rise, transit, and set times of [IAU-named](#) stars.

`riset` is distributed as an auxillary J addon. Auxillary addons are hosted in private GitHub repositories. `riset` can be installed in the local J folder `~addons/jacks` with:

```
load 'pacman'
```

NB. files from <https://github.com/bakerjd99/jackshacks>

```
install 'github:bakerjd99/jackshacks'
```

NB. installed files

```
dir '~addons/jacks'
```

Once installed it can be loaded and run with:

```
load '~addons/jacks/riset.ijs'
```

```
location_yellowstone 0
```

NB. IAU stars rising/setting over Old Faithful

```
fmt_today iau_today 0
```

For more details about setting up, running, and “hacking” `riset` refer to the Jupyter notebook [riset_notebook.ipynb](#) or the pdf version of same [riset_notebook.pdf](#). Both of these files are installed with `riset`.

riseset Interface

`fmt_today` [17] *format today verbs result*
`iau_today` [19] *named IAU stars rising/setting today*
`loadstars` [22] *loads riseset star data*
`nav_today` [30] *named navigation stars rising/setting today*
`navdaylist` [31] *sky safari 6_0 observing list of today's navigation stars*
`riseset` [40] *rise, transit, set times of stars*

riseset Algorithm Notes

Many `riseset` algorithms are taken from Jean Meeus's book *Astronomical Algorithms*. A PDF copy of this book is available [here](https://ia802807.us.archive.org/20/items/astronomicalalgorithmsjeanmeeus1991/):

<https://ia802807.us.archive.org/20/items/astronomicalalgorithmsjeanmeeus1991/>

also here:

https://www.amazon.com/s?i=stripbooks&rh=p_27%3AJean+Meeus&s=relevancerank&text=Jean+Meeus&ref=dp_byline_sr_book_1

Nutation algorithms are from Jay Tanner's site:

<https://neoprogrammics.com/nutations/index.php>

Markdown versions of Tanner's algorithms are stored in the JOD `futs` and `utils` dictionaries — see:

1. `nutaton_in_longitude_dPsi_md`
2. `nutaton_in_obliquity_of_ecliptic_dEpsDeg_md`

in:

<https://github.com/bakerjd99/joddumps/blob/master/futs.ijs>

<https://github.com/bakerjd99/joddumps/blob/master/utils.ijs>

Delta T (ΔT) is computed using polynomial expressions by Espenak and Meeus, see:

<https://eclipse.gsfc.nasa.gov/SEhelp/deltatpoly2004.html>

A markdown version of the Delta T (ΔT) algorithm is in `futs` see:

```
1. nasa_polynomial_expressions_for_delta_t_md
```

You can display the markdown referenced about with the JOD expressions:

```
load 'general/jod'  
od ;:'futs utils'  
NB. display markdown documents  
4 disp ; }.@(4&dn1)&.> 'nutation_';'nasa_'
```

Many examples showing how to use various `riseset` words are in the JOD `futs` test suite `riseset`. You can display all the test cases with the JOD expressions:

```
3 grp 'riseset'    NB. test cases in suite  
  
3 disp 'riseset'  NB. display test suite  
  
4 rtt 'riseset'    NB. run all tests in suite
```

riset Source Code

```
NB.*riset s-- compute rise, transit and set times of IAU named stars.
NB.
NB. verbatim: interface word(s):
NB. -----
NB.  fmt_today  - format today verbs result
NB.  iau_today  - named IAU stars rising/setting today
NB.  loadstars  - loads riset star data
NB.  nav_today  - named navigation stars rising/setting today
NB.  navdaylist - sky safari 6_0 observing list of today's navigation stars
NB.  riset      - rise, transit, set times of stars
NB.
NB. created: 2023mar09
NB. changes: -----
NB. 23mar29 (iau_tonight) renamed (iau_today)
NB. 23mar29 various location setting verbs (location_uluru) added
NB. 23mar30 (nav_today) added
NB. 23apr01 (fmt_today) added
NB. 23apr06 (navdaylist) added

coclass 'riset'

(9!:11) 16 NB. high print precision
NB.*end-header

NB. Byte Order Mark: UTF-8 EF,BB,BF (hex) or 239 187 191 (dec)
BOM=: 239 187 191{a.
```

NB. carriage return character

CR=: 13{a.

NB. seconds per day

DAYSECS=: 86400

NB. interface words (IFACEWORDSriset) group

IFACEWORDSriset=: <.;_1 ' fmt_today iau_today loadstars nav_today navdaylist riset'

NB. current Julian date

JULIAN=: 2460030.5

NB. line feed character

LF=: 10{a.

NB. horizon limit in degrees

LIMITHORZ=: 20

NB. limiting magnitude

LIMITMAG=: 3.

NB. Name/description of observer location

LOCATIONNAME=: 'Meridian'

NB. approximate epoch J2000 obliquity of the ecliptic degrees, minutes, seconds

OBLIQUITYDMS2000=: 23 26 21.448000000000004

NB. observer latitude longitude, west longitudes negative

OBSLOCATION=: _116.375956000000002 43.6467749999999981

NB. root words (ROOTWORDSriseset) group

ROOTWORDSriseset=: <.;_1 ' IFACEWORDSriseset ROOTWORDSriseset VMDriseset fmt_today iau_today location_uluru
>.> location_yellowstone navdaylist'

NB. standard altitude stars - compensates for horizon atmospheric refraction

STDALTITUDE=: 0.566699999999999982

NB. UTC time zone offset in hours

UTCOFFSET=: 6

NB. version, make count and date

VMDriseset=: '0.9.6';3;'06 Apr 2023 15:23:02'

NB. retains string after first occurrence of (x)

afterstr=:] }.~ #@[+ 1&(i.~)@([E.])

NB. all zero, first, second, ... nth differences of nl: alldifs ?.10#100

alldifs=: ([>: [: i. [: - #) {.&.> [: <"1 (}. - }:)^(i.@#@[)

apparRADEC=: 4 : 0

*NB.*apparRADEC v-- apparent RA and DEC for epoch (x) from J2000.0*

```
NB. RA and DEC.
NB.
NB. This verb adjusts J2000 RA and DEC coordinates to another
NB. epoch. The method is based on Meeus (20.3) pg 126. This
NB. calculation ignores stellar proper motions and assumes that
NB. (y) RA DEC values are J2000.0. The resulting positions are
NB. accurate enough for basic rise, transit, and set
NB. calculations.
NB.
NB. dyad: ft =. flymd apparRADEC ftRADEC
NB.
NB. 2028 11 13.19 apparRADEC 41.054063 ,. 49.227750
NB.
NB. ({."1 ciau)=: {:"1 ciau
NB. 2023 4 22 apparRADEC RA_J2000 ,: Dec_J2000

'zet z th'=. zetzthT0 x NB. final epoch t
'ra dec'=. y NB. J2000 ra,dec

NB. meeus (20.4) pg. 126
A=. (cosd dec)*sind ra + zet
B=. ((cosd th)*(cosd dec)*cosd ra + zet) - (sind th)*sind dec
C=. ((sind th)*(cosd dec)*cosd ra + zet) + (cosd th)*sind dec

NB. NIMP star close celestial poles

NB. new dec,ra
```



```
ran=. z + atan2 A ,: B [ decn=. dfr arcsin C
ran ,: decn
)
```

```
NB. seconds correction apparent sidereal time - meeus pg. 84 - ( $\Delta\psi$  * cos( $\epsilon$ ))/15
apparsecs=: 15 %~ (3600 * nutation_longitude_dPsi) * [: cosd meanobliquityjd0
```

```
NB. apparent Greenwich sidereal - hms: apparsidjd0 julfrcal |: 2023 1 3,:1991 2 8.5
apparsidjd0=: ([: dmsfrdd 15 %~ [: nth0 meansidjd0) + 0 0 ,"1 [: ,. apparsecs
```

```
NB. applies the verb in string (x) to (y)
apply=: 128!:2
```

```
NB. arc cosine
arccos=: _2&o.
```

```
NB. arc sine
arcsin=: _1&o.
```

```
NB. arc tangent
arctan=: _3&o.
```

```
NB. signal with optional message
assert=: 0 0"_ $ 13!:8^:((0: e. ])^(12"_))
```

```
atan2=: 3 : 0
```

```
NB.*atan2 v-- arctangent of (Y % X) in degrees.
```

```
NB.
```

```
NB. FORTRAN (ATN2) variation of the standard (arctan) (_360.) for
NB. ratios. Based on a PASCAL function from Astronomy on the
NB. Personal Computer by Montenbruck and Pfleger ISBN
NB. 0-387-52754-0 pg. 9.
```

```
NB.
```

```
NB. Result is between _180 <: atan2 <: 180 degrees
```

```
NB.
```

```
NB. monad: fl =. atan2 flYX
```

```
NB.
```

```
NB. atan2 1 ,: 1 NB. 45 degrees
```

```
NB. atan2 1 ,: %: 3 NB. 30 degrees
```

```
NB.
```

```
NB. NB. random ratios comparing two atan2 verbs
```

```
NB. r=: ?. 2 500$50
```

```
NB. r=: r * ($r) $ (?.~ */$r) { (*/$r)$_1 1
```

```
NB. (atan2b |.r) -: atan2 r
```

```
NB.
```

```
NB. NB. surprisingly (atan2) is faster than (atan2b)
```

```
NB. NB. (j 9.41 2023) but (atan2b) consumes less memory
```

```
NB. NB. 1000 ts"1 'atan2b r',: 'atan2 |.r'
```

```
NB. vector J NB. scalar PASCAL
```

```
rad=. 0.0174532925199432955 NB. CONST RAD=0.0174532925199433;
```

```

r=. 0 #~ {: $y

b0=. */0=y          NB. IF (X=0.0) AND (Y=0.0) THEN ATN2:= 0.0
ir=. i. #r=. 0 (I. b0)} r

if. +./b1=. -.b0 do.
  t=. |(I. b1) {"1 y    NB. AX=: ABS(X); AY=: ABS(Y)
  it=. (I. b1) { ir

  b2=. (1{t) > 0{t      NB. IF (AX>AY) THEN PHI=: ARCTAN(AY/AX)/RAD
  s=. (I. b2) {"1 t
  r=. (rad %~ arctan %/s) (b2#it)} r

  s=. (I. -.b2) {"1 t    NB. ELSE PHI=: 90.0-ARCTAN(AX/AY)/RAD;
  r=. (90 - rad %~ arctan %/ |.s) (it #~ -.b2)} r
end.

x10=. I. b1 *. (1{y) < 0    NB. IF (X<0.0) THEN PHI=: 180.0-PHI;
r=. (180 - x10{r) (x10)} r
y10=. I. b1 *. (0{y) < 0    NB. IF (Y<0.0) THEN PHI=: -PHI;
r=. (-y10{r) (y10)} r

r
)

NB. retains string before first occurrence of (x)
beforestr=: ] {.~ 1&(i.~)@([ E. ])

```

NB. boxes open nouns

```
boxopen=: <^:(L. = 0:)
```

```
cold_iau_named_stars=: 3 : 0
```

*NB.*cold_iau_named_stars v-- convert IAU btcl to column dictionary.*

NB.

NB. monad: bt =. cold_iau_named_stars btcl

NB.

NB. iau=. ; {: , > {: 4 get 'iau_named_stars_2022_txt'

NB. ciau=. cold_iau_named_stars parse_iau_named_stars iau

NB.

NB. NB. define columns

NB. (0 {"1 ciau)=: 1 {"1 ciau

```
c=. 0{"1 t=. |: y
```

```
p0=. c i. ;:'Vmag RA_J2000 Dec_J2000'
```

```
d=. _999&".&> p0 { t=. }."1 t
```

```
'invalid mag, ra, dec' assert -. _999 e. d
```

```
p1=. c i. ;:'IAU_Name Designation Bayer_Name'
```

```
c ,. (<"1 ] p1 { t) , <"1 d
```

```
)
```

NB. cosine radians

```
cos=: 2&o.
```

NB. cosine degrees

```
cosd=: cos@rfd
```

NB. character table to newline delimited list

```
ctl=: }.@(@1&(",1)@(-.@(*./\."1@(&' ' @])))) # ,@((10{a.)&(",1)@]))
```

NB. decimal degrees from degrees, minutes, seconds - inverse (dmsfrdd)

```
ddfrdms=: (60"_ #. ])% 3600"
```

```
deltaT0=: 3 : 0
```

*NB.*deltaT0 v-- dynamical time ΔT in seconds.*

NB.

NB. Returns the difference in seconds between UT and TD based on

NB. polynomial expressions by Espenak and Meesus. This

NB. calculation is useful for the years -1999 to 3000: a five

NB. thousand year period.

NB.

NB. see: <https://eclipse.gsfc.nasa.gov/SEhelp/deltatpoly2004.html>

NB.

NB. also in (futs): nasa_polynomial_expressions_for_delta_t_md

NB.

NB. monad: flSecs =. deltaT0 flYd

NB.

NB. ymd=. |: (3 {. 6!:0 ' '), _1812 3 12 , _12 12 11 , 2137 12 13, 1700 1 1 ,: 35 7 6

NB. |: ymd , deltaT0 deltaTdy ymd

NB. (ry) time intervals are (l,u]

NB. before -500:

```

NB.  $\Delta T = -20 + 32 * u^2$ ; where:  $u = (y-1820)/100$ 
ry=. ,: _1999 _500
t1=. {{ _20 + 32 * U^2 [ U=. (y - 1820) % 100 ]}}

NB. between -500 and +500:
NB.  $\Delta T = 10583.6 - 1014.41 * u + 33.78311 * u^2 - 5.952053 * u^3$ 
NB.  $- 0.1798452 * u^4 + 0.022174192 * u^5 + 0.0090316521 * u^6$ ; where:  $u = y/100$ 
NB. NOTE: for the year -500 set value of 17190 to 17203.7
ry=. ry , _500 500
t2=. {{ 10583.6 - (1014.41*U) + (33.78311*U^2) - (5.952053*U^3) - (0.1798452*U^4) + (0.022174192*U^5) + 0.
>...>0090316521*U^6 [ U=. y % 100 ]}}

NB. between +500 and +1600:
NB.  $\Delta T = 1574.2 - 556.01 * u + 71.23472 * u^2 + 0.319781 * u^3$ 
NB.  $- 0.8503463 * u^4 - 0.005050998 * u^5 + 0.0083572073 * u^6$ ; where:  $u = (y-1000)/100$ 
ry=. ry , 500 1600
t3=. {{ 1574.2 - (556.01*U) + (71.23472*U^2) + (0.319781*U^3) - (0.8503463*U^4) - (0.005050998*U^5) + 0.00
>...>83572073*U^6 [ U=. (y-1000) % 100 ]}}

NB. between +1600 and +1700:
NB.  $\Delta T = 120 - 0.9808 * t - 0.01532 * t^2 + t^3 / 7129$ ; where:  $t = y - 1600$ 
ry=. ry , 1600 1700
t4=. {{ 120 - (0.9808*t) - (0.01532*t^2) + (t^3)%7129 [ t=. y - 1600 ]}}

NB. between +1700 and +1800:
NB.  $\Delta T = 8.83 + 0.1603 * t - 0.0059285 * t^2 + 0.00013336 * t^3 - t^4 / 1174000$ ; where:  $t = y - 1700$ 
ry=. ry , 1700 1800

```

```
t5=. {{ 8.83 + (0.1603*t) - (0.0059285*t^2) + (0.00013336*t^3) - (t^4)%1174000 [ t=. y - 1700 ]}}
```

NB. between +1800 and +1860:

*NB. $\Delta T = 13.72 - 0.332447 * t + 0.0068612 * t^2 + 0.0041116 * t^3 - 0.00037436 * t^4$*
 *$+ 0.0000121272 * t^5 - 0.0000001699 * t^6 + 0.000000000875 * t^7$; where: $t = y - 1800$*

```
ry=. ry , 1800 1860
```

```
t6=. {{ 13.72 - (0.332447*t) + (0.0068612*t^2) + (0.0041116*t^3) - (0.00037436*t^4) + (0.0000121272*t^5) -  
>..> (0.0000001699*t^6) + 0.000000000875*t^7 [ t=. y - 1800 ]}}
```

NB. between 1860 and 1900:

*NB. $\Delta T = 7.62 + 0.5737 * t - 0.251754 * t^2 + 0.01680668 * t^3$*
 *$- 0.0004473624 * t^4 + t^5 / 233174$; where: $t = y - 1860$*

```
ry=. ry , 1860 1900
```

```
t7=. {{ 7.62 + (0.5737*t) - (0.251754*t^2) + (0.01680668*t^3) - (0.0004473624*t^4) + (t^5)%233174 [ t=. y  
>..>- 1860 ]}}
```

NB. between 1900 and 1920:

*NB. $\Delta T = -2.79 + 1.494119 * t - 0.0598939 * t^2 + 0.0061966 * t^3 - 0.000197 * t^4$; where: $t = y - 1900$*

```
ry=. ry , 1900 1920
```

```
t8=. {{ -2.79 + (1.494119*t) - (0.0598939*t^2) + (0.0061966*t^3) - 0.000197*t^4 [ t=. y - 1900 ]}}
```

NB. between 1920 and 1941:

*NB. $\Delta T = 21.20 + 0.84493*t - 0.076100 * t^2 + 0.0020936 * t^3$; where: $t = y - 1920$*

```
ry=. ry , 1920 1941
```

```
t9=. {{ 21.20 + (0.84493*t) - (0.076100*t^2) + 0.0020936*t^3 [ t=. y - 1920 ]}}
```

NB. between 1941 and 1961:

NB. $\Delta T = 29.07 + 0.407*t - t^2/233 + t^3 / 2547$; where: $t = y - 1950$

ry=. ry , 1941 1961

t10=. {{ 29.07 + 0.407*t - ((t^2)%233) + (t^3)%2547 [t=. y - 1950]}}

NB. between 1961 and 1986:

NB. $\Delta T = 45.45 + 1.067*t - t^2/260 - t^3 / 718$; where: $t = y - 1975$

ry=. ry , 1961 1986

t11=. {{ 45.45 + (1.067*t) - ((t^2)%260) - (t^3)%718 [t=. y - 1975]}}

NB. between 1986 and 2005:

NB. $\Delta T = 63.86 + 0.3345 * t - 0.060374 * t^2 + 0.0017275 * t^3 + 0.000651814 * t^4$

NB. $+ 0.00002373599 * t^5$; where: $t = y - 2000$

ry=. ry , 1986 2005

t12=. {{ 63.86 + (0.3345*t) - (0.060374*t^2) + (0.0017275*t^3) + (0.000651814*t^4) + 0.00002373599*t^5 [t
>..>=. y - 2000]}}

NB. between 2005 and 2050:

NB. $\Delta T = 62.92 + 0.32217 * t + 0.005589 * t^2$; where: $t = y - 2000$

ry=. ry , 2005 2050

t13=. {{ 62.92 + (0.32217*t) + 0.005589*t^2 [t=. y - 2000]}}

NB. between 2050 and 2150:

NB. $\Delta T = -20 + 32 * ((y-1820)/100)^2 - 0.5628 * (2150 - y)$

ry=. ry , 2050 2150

t14=. {{ _20 + (32 * ((y-1820)%100)^2) - 0.5628 * 2150 - y]}}

NB. after 2150:

*NB. $\Delta T = -20 + 32 * u^2$; where: $u = (y-1820)/100$*

```
ry=. ry , 2150 3000
```

```
t15=. {{ _20 + 32 * U^2 [ U=. (y-1820)%100 }}
```

NB. NOTE: the $t(i)$ verbs match the intervals

```
ti=. (rb=. /:~ ~. ,ry) I. y
```

```
'year range _1999 to 3000 exceeded' assert -. (0,#rb) e. ti
```

NB. $t(i)$ gerund

```
tg=. t1`t2`t3`t4`t5`t6`t7`t8`t9`t10`t11`t12`t13`t14`t15
```

NB. apply $t(i)$ verbs to appropriate intervals

```
(;ti </. i.#y) { ;(tg {~ <: ~.ti) apply&.> ti </. y  
)
```

NB. delta ΔT decimal year: deltaTdy 2023 3 12 ,. 1959 12 11

```
deltaTdy=: (0 { ] ) + 12 %~ 0.5 ~ 1 { ]
```

NB. degrees from radian

```
dfr=: *&57.2957795130823229
```

NB. degrees, minutes, seconds from decimal degrees - inverse (ddfrdms)

```
dmsfrdd=: <. (,.) 60 60 #: 3600 * 1 | ,
```

```
fmt_today=: 3 : 0
```

```
NB.*fmt_today v-- format today verbs result.
```

```
NB.
```

```
NB. monad: cl =. fmt_today (bt ; cl ; fl)
```

```
NB.
```

```
NB.   fmt_today nav_today 0
```

```
NB.   fmt_today (location_yellowstone~ 1935 7 6) iau_today 0
```

```
'Rs lName cParms'=. y
```

```
NB. calc parameters
```

```
hdr=. <;._1' Location Mag-Lim Above-Horz Julian ΔT Longitude Latitude Year Month Day.dd UTCz'
```

```
cParms=. ctl ": <(rjust lName , ": ,. cParms) ,. ' ' ,. >hdr
```

```
NB. rise/set - sorted by transit time
```

```
Rs=. >&.> <"1 |: Rs
```

```
Rs=. (('5.1'&(8!:2)@,. ) &.> 2 { Rs) (2)} Rs
```

```
Rs=. ('3.0'&(8!:2)&.> 3 { Rs) (3)} Rs
```

```
Rs=. ctl ": Rs ,:~ <;._1' Name Designation Tr-Alt-Deg Tr-24-HrMin'
```

```
cParms,LF,Rs
```

```
)
```

```
NB. fractional centuries from epoch J2000 Meeus pg. 83: gT0jd julfrcal 1957 10 4.81
```

```
gT0jd=: 36525 %~ 2451545. -- ]
```

```
NB. fractional centuries from epoch J2000 Meeus pg. 83: gT0ymd 1957 10 4.81
```

```
gT0ymd=: 36525 %~ 2451545. -- julfrcal
```

```
NB. hours, minutes from decimal seconds: hmfrds dsfrhms 20 27 43.23
hmfrds=: [: 24 60&#: 60 %~ ]

iau_today=: 3 : 0

NB.*iau_today v-- named IAU stars rising/setting today.
NB.
NB. monad: (bt ; clLoc ; flParms) =. iau_today uuIgnore
NB.
NB.    iau_today 0
NB.
NB. dyad: (bt ; clLoc ; flParms) =. bLYmd_LB_UO_LMAG_LHORZ_LOC iau_today uuIgnore
NB.
NB.    'Riseset Location cParms'=. (location_yellowstone~ 1935 7 6) iau_today 0

jd=. julfrcal ymd=. 3 {. 6!:0 ''
(ymd;jd;OBSLOCATION;UTCOFFSET;LIMITMAG;LIMITHORZ;LOCATIONNAME) iau_today y
:
NB. date, julian, location, UTC timezone, magnitude, horizon, location
'YMD JD LB UO LMAG LHORZ LOCNAME'=. x

NB. star data
'IAU NAV'=. loadstars 0
({."1 NAV)=. {:"1 NAV [ ({."1 IAU)=. {:"1 IAU

NB. brighter magnitude limit !(*)=. Vmag IAU_Name Designation
'Rs lName cParms'=. x today_calc (LMAG > Vmag) # IAU_Name
```

```
NB. include Designation names
Rs=. 1 0 2 3 {"1 Rs ,.~ (IAU_Name i. 0 {"1 Rs){Designation
Rs;lName;cParms
)

intr3p=: 4 : 0

NB.*intr3p v-- interpolate three values - meeus pg 25.
NB.
NB. dyad: fln intr3p fl
NB.
NB. NB. meeus pg. 24
NB. yi=. 0.884226 0.877366 0.870531
NB. 0.05 intr3p yi

NB. y = y2 + (n/2)(a + b nc)
NB. a b c are differences

'only 3 values' assert 3=#y

d=. 1 2{alldifs y
'a b'=. >0{d [ c=. ,/ >1{d
(1{y) + (x%2) * a + b + x*c
)

julfrcal=: 3 : 0
```

```
NB.*julfrcal v-- Julian dates from calendar dates.
NB.
NB. Astronomical Julian date. Similiar to (tojulian) but handles
NB. the fact that Julian days start at noon rather than midnight
NB. for calendar days.
NB.
NB. monad: fl =. julfrcal ilYYYYMMDD / ftYYYYMMDD
NB.
NB. julfrcal 2001 9 11
NB. julfrcal 1776 1941 1867 , 7 12 7 ,: 4 7 1
NB.
NB. NB. Meeus (Astronomical Algorithms) test cases (pg. 61)
NB. NB. NOTE: the fractional day representation of time
NB. 2436116.31 = julfrcal 1957 10 4.81 NB. 7.a Sputnik 1
NB. 1842713.0 = julfrcal 333 1 27.5 NB. 7.b
NB.
NB. NB. zero date is roughly the age of the oldest bristlecone pines (coincidence?)
NB. julfrcal -4711 10 29.5

NB. vector J
'y m d'=. y
g=. 1582 <: y
f=. (d - d1) - 0.5 [ d1=. <. d
j=. - <. 7 * 4 %~ <.y + 12 %~ m+9

s=. * m-9 [ a=. | m-9
j3=. <. y + s * <. a%7

NB. scalar BASIC
NB. INPUT "Y,M,D ";Y,M,D
NB. G=1: IF Y<1582 THEN G=0
NB. D1=INT(D): F=D-D1-0.5
NB. J=-INT(7*(INT((M+9)/12)+Y)/4)
NB. IF G=0 THEN 805
NB. S=SGN(M-9): A=ABS(M-9)
NB. J3=INT(Y+S*INT(A/7))
```

```

j3=. - <. 3r4 * >: <. j3 % 100      NB. J3=-INT((INT(J3/100)+1)*3/4)
j=. j + (<.275 * m%9) + d1 + g*j3    NB. 805 J=J+INT(275*M/9)+D1+G*J3
j=. j + 1721027 + (2*g) + 367*y      NB. J=J+1721027+2*G+367*Y
b=. f >: 0                          NB. IF F>=0 THEN 825
f=. f + b [ j=. j - b                NB. F=F+1: J=J-1
f + j
)

```

NB. left justify table

```
ljust=: ' '&$: :([] |."_1~ i."1&0@([] e. [])
```

```
loadstars=: 3 : 0
```

```

NB.*loadstars v-- loads riseset star data.
NB.
NB. monad: bLIAU_Nav =. loadstars uuIgnore
NB.
NB. loadstars 0
NB.
NB. dyad: bLIAU_Nav=. pa loadstars uuIgnore
NB.
NB. 0 loadstars 0 NB. files
NB. 1 loadstars 0 NB. JOD
NB.
NB. loadstars~ 0 NB. idiom files
NB. loadstars~ 1 NB. idiom JOD
NB.

```

NB. 2 loadstars 0 NB. files - define columns

```
0 loadstars y
:
'invalid option' assert x e. 0 1 2

if. x e. 0 2 do.
  NB. load star data from addon directory !(*)=. jpath
  paddon=. jpath '~addons/jacks/testdata/'
  ciau=. read paddon, 'iau_named_stars_2022.txt'
  cnavs=. read paddon, 'Navigation_Stars.txt'
elseif. x-:1 do.
  NB. load star data from JOD (futs) !(*)=. get od require
  rc=. od ;:'futs utils' [ 3 od '' [ require 'general/jod'
  ciau=. ; {: , > {: MACRO_ajod_ get 'iau_named_stars_2022_txt'
  cnavs=. ; {: , > {: MACRO_ajod_ get 'Navigation_Stars_txt'
end.

ciau=. cold_iau_named_stars parse_iau_named_stars ciau
cnavs=. parsetd cnavs -. CR
cnavs=. (0 { cnavs) ,. <"1 |: }. cnavs
'star column overlap' assert 0 = #(0 {"1 cnavs) ([ -. -. ) 0 {"1 ciau

NB. define columns - override mixed assignments (<:)=:
if. x-:2 do.
  (0 {"1 ciau)=: 1 {"1 ciau
  (0 {"1 cnavs)=: 1 {"1 cnavs
```

```
(<ciau),(<cnavs),<(0 {"1 ciau),0 {"1 cnavs
else.
  (<ciau),<cnavs
end.
)
```

```
location_home=: 3 : 0
```

```
NB.*location_home v-- set parameters for "home" location.
```

```
NB.
```

```
NB. monad: bl =. location_home uuIgnore
```

```
NB.
```

```
NB. location_home 0
```

```
NB. NB. uses location with current date
```

```
NB. fmt_today iau_today 0
```

```
NB.
```

```
NB. dyad: bl =. flymfd location_home uuIgnore
```

```
NB.
```

```
NB. NB. uses location with home date
```

```
NB. (location_home 0) iau_today 0
```

```
NB. (location_home 0) nav_today 0
```

```
NB.
```

```
NB. NB. arbitrary dates for location
```

```
NB. fmt_today (1712 3 15.34 location_home 0) nav_today 0
```

```
NB. fmt_today (location_home~ 1933 9 25.75) iau_today 0
```

```
NB. test date https://www.almanac.com/astronomy/bright-stars/zipcode/83646/2023-03-27
```

```
2023 3 27 location_home y
```



```
:
JULIAN_risese_=: julfrcal ymd=. x

NB. longitude, latitude with standard signs
OBSLOCATION_risese_=: _116.375956 43.646775
LOCATIONNAME_risese_=: 'Home - Meridian'

UTCOffset_risese_=: 6.0    NB. MST time zone
LIMITMAG_risese_=: 3.0    NB. stellar magnitude
LIMITHORZ_risese_=: 20    NB. degrees above horizon

ymd;JULIAN;OBSLOCATION;UTCOffset;LIMITMAG;LIMITHORZ;LOCATIONNAME
)

location_uluru=: 3 : 0

NB.*location_uluru v-- set parameters for Uluru location.
NB.
NB. monad: location_uluru uuIgnore
NB.
NB. location_uluru 0
NB. NB. uses location with current date
NB. iau_today 0
NB.
NB. dyad: bl =. flymfd location_uluru uuIgnore
NB.
NB. NB. uses location with uluru date
NB. (location_uluru 0) iau_today 0
```

```
NB.
NB.  NB. arbitrary dates for location
NB.  fmt_today (1712 3 15.34 location_uluru 0) nav_today 0
NB.  fmt_today (location_uluru~ 1933 9 25.75) iau_today 0

2022 10 19 location_uluru y
:
JULIAN_risese_=: julfrcal ymd=. x

NB. longitude, latitude with standard signs
OBSLOCATION_risese_=: 131.01941 _25.34301
LOCATIONNAME_risese_=: 'Uluru - star party diner'

UTCOffset_risese_=: _9.5  NB. time zone
LIMITMAG_risese_=: 6.0    NB. stellar magnitude
LIMITHORZ_risese_=: 5     NB. degrees above horizon

ymd;JULIAN;OBSLOCATION;UTCOffset;LIMITMAG;LIMITHORZ;LOCATIONNAME
)

location_yellowstone=: 3 : 0

NB.*location_yellowstone v-- set parameters for Old Faithful location.
NB.
NB. monad: location_yellowstone uuIgnore
NB.
NB.  location_yellowstone 0
NB.  NB. uses location with current date
```

```
NB.    iau_today 0
NB.
NB. dyad:  bl =. flYmfd location_yellowstone uuIgnore
NB.
NB.    NB. uses location with yellowstone date
NB.    (location_yellowstone 0) iau_today 0
NB.
NB.    NB. arbitrary dates for location
NB.    fmt_today (1712 3 15.34 location_yellowstone 0) nav_today 0
NB.    fmt_today (location_yellowstone~ 1933 9 25.75) iau_today 0

2013 5 7 location_yellowstone y
:
JULIAN_riseseT_=: julfrcal ymd=. x

NB. longitude, latitude with standard signs
OBSLOCATION_riseseT_=: _110.82792 44.46057
LOCATIONNAME_riseseT_=: 'Yellowstone - Old Faithful'

UTCOffset_riseseT_=: 6.0    NB. MST time zone
LIMITMAG_riseseT_=:  6.0    NB. stellar magnitude
LIMITHORZ_riseseT_=: 10     NB. degrees above horizon

ymd;JULIAN;OBSLOCATION;UTCOffset;LIMITMAG;LIMITHORZ;LOCATIONNAME
)

meanobliquityT0=: 3 : 0
```

*NB.*meanobliquityT0 v-- mean obliquity of the ecliptic IAU in degrees.*

NB.

NB. monad: fl =. meanobliquityT0 flT

NB. units are decimal arc seconds

*ea=. +/3600 60 1 * OBLIQUITYDMS2000*

NB. meeus (21.2) pg. 135

*3600 %~ ea - (46.8150*y) - (0.00059*y^2) + 0.001813*y^3
)*

meanobliquityT1=: 3 : 0

*NB.*meanobliquityT1 v-- mean obliquity of the ecliptic Laskar in*

NB. degrees.

NB.

NB. Mean obliquity using Laskar's polynomial. This expression is

NB. more accurate than (meanobliquityT0): see Meeus (21.2) pg.

NB. 135.

NB.

NB. monad: fl =. meanobliquityT1 flT

NB. units are decimal arc seconds

*ea=. +/3600 60 1 * OBLIQUITYDMS2000*

NB. time units 10000 Julian years

U=. y % 100

```
e0=. (39.05*U^6) + (7.12*U^7) + (27.87*U^8) + (5.79*U^9) + 2.45*U^10
3600 %~ ea - (4680.93*U) - (1.55*U^2) + (1999.25*U^3) - (51.38*U^4) - (249.67*U^5) - e0
)
```

```
meanobliquityjd0=: 3 : 0
```

```
NB.*meanobliquityjd0 v-- mean obliquity ecliptic for Julian date (y) degrees.
```

```
NB.
```

```
NB. monad: fl =. meanobliquityjd0 flJD
```

```
NB.
```

```
NB. NB. meeus pg. 136
```

```
NB. e0=. ,dmsfrdd meanobliquityjd0 2446895.5
```

```
NB.
```

```
NB. NB. matches to 3 decimals
```

```
NB. 23 26 27.407 -: 0.001 round e0
```

```
NB.
```

```
NB. dyad: fl =. pa meanobliquityjd0 flJD
```

```
NB.
```

```
NB. NB. Laskar algorithm
```

```
NB. el=. ,dmsfrdd 1 meanobliquityjd0 2446895.5
```

```
0 meanobliquityjd0 y
```

```
:
```

```
meanobliquityT0`meanobliquityT1@.(x) gT0jd y
```

```
)
```

```
meansid0=: 4 : 0
```

*NB.*meansid0 v-- mean sidereal time at Greenwich for T (x) JD (y).*

NB.

NB. dyad: flDegs =. flT meansid flJD

NB. meeus (11.4) pg 84

*280.46061837 + (360.98564736629 * y - 2451545.0) + (0.000387933 * x^2) - 38710000 %~ x^3*
)

meansidjd0=: 3 : 0

*NB.*meansidjd0 v-- mean sidereal time at Greenwich for julian day (y) in degrees.*

NB.

NB. monad: fl =. meansidjd0 flJD

NB.

NB. NB. julian day for April 10, 1987 19h:24m:00s UT

NB. JD=. julfrcal 1987 4,10 + fdfrhms 19 21 0

NB. meansidjd0 JD

(gT0jd y) meansid0 y
)

nav_today=: 3 : 0

*NB.*nav_today v-- named navigation stars rising/setting today.*

NB.

NB. monad: (bt ; clLoc ; flParms) =. nav_today uuIgnore

NB.

```
NB.   nav_today 0
NB.
NB. dyad:  (bt ; clLoc ; flParms) =. blymd_LB_UO_LMAG_LHORZ_LOC nav_today uuIgnore
NB.
NB.   'Riseset Location cParms'=. (location_yellowstone~ 1935 7 6) nav_today 0

jd=. julfrcal ymd=. 3 {. 6!:0 ''
(ymd;jd;OBSLOCATION;UTCOFFSET;LIMITMAG;LIMITHORZ;LOCATIONNAME) nav_today y
:
NB. star data
'IAU NAV'=. loadstars 0
({."1 NAV)=. {: "1 NAV [ ({."1 IAU)=. {: "1 IAU

NB. !(*)=. Nav_Star_Name IAU_Name Designation
'Rs lName cParms'=. x today_calc Nav_Star_Name

NB. include Designation names
Rs=. 1 0 2 3 {"1 Rs ,.~ (IAU_Name i. 0 {"1 Rs){Designation
Rs;lName;cParms
)

navdaylist=: 3 : 0

NB.*navdaylist v-- sky safari 6_0 observing list of today's navigation stars.
NB.
NB. The files created by this verb can be loaded into the Sky
NB. Safari iOS and Mac apps.
NB.
```

```
NB. monad:  cl =. navdaylist uuIgnore
NB.
NB.   navhome=. navdaylist 0
NB.   navhome write jpath '~JODIMEX/Navigation_Stars_Home.skylist'

NB. j profile !(*)=. jpath
skl=. read jpath '~addons/jacks/testdata/Navigation_Stars.skylist'
'st loc cParms'=. nav_today 0 [ location_home 0

NB. skylist header
cst=. 'SortedBy=Default Order'
hdr=. cst ((,&LF)@[ ,~ beforestr) skl

NB. cut skylist objects
sob=. ([ <;.1~ 'SkyObject=BeginObject' E. ]) cst afterstr skl

NB. retain objects that match star and hdr names
b=. +./ (0 {"1 st) +./@E.&>"0 1 sob
sob=. sob #~ b *. +./ (1 {"1 st) +./@E.&>"0 1 sob

NB. reset sort order
sob=. ];._2 tlf ;sob
ix=. I. +./"1 (,: 'DefaultIndex=') E. sob
ns=. '='&beforestr"1 ix{sob
ns=. ns ,. '=' ,. ljust ": ,. i. #ns
hdr,ctl >(<"1 ns) (ix)} <"1 sob
)
```


NB. normalize negative degree sidereal time: nnth0 -1677831.2621266
*nnth0=:] + 360 * [: | [: (<.) 360 %~]*

NB. normalize positive degree sidereal time: npth0 1677831.2621266
*npth0=:] - 360 * [: (<.) 360 %~]*

NB. normalize degree sidereal time: nth0 _35555 77777
nth0=: npth0`nnth0@.(0&>:@[])

nututation_longitude_dPsi=: 3 : 0

*NB.*nututation_longitude_dPsi v-- nututation in ecliptical longitude in degrees (1980 iau theory).*

NB.

NB. NOTE: the pseudo-code is vector ready and easily converted to J.

NB.

NB. verbatim: algorithm from Jay Tanner <https://neoprogrammics.com/nutations/>

NB.

NB. see: nututation_in_longitude_dPsi_md

NB.

NB. monad: flDeg =. nututation_longitude_dPsi flJD

NB.

NB. ymd=. |: 2023 3 12 , 1959 12 11 , 2135 12 13, 1700 1 1 ,: 1935 7 6

NB. JD=. julfrcal ymd NB. no delT adj.

NB. 2460015.5 = 0{JD

NB. nututation_longitude_dPsi JD

NB.

NB. NB. see (futs) test: (risetset_tanner_smoke) for examples

```

T=. (y - 2451545) % 36525  NB.  T  = (JD - 2451545) / 36525
T2=. T*T                  NB.  T2 = T*T
T3=. T*T2                 NB.  T3 = T*T2

NB. DegToRad = 3.1415926535897932 / 180
DegToRad=. 3.1415926535897932 % 180

NB. w1 = 297.85036 + 445267.11148*T - 0.0019142*T2 + (T3 / 189474)
w1=. 297.85036 + (445267.11148*T) - (0.0019142*T2) + (T3 % 189474)
w1=. DegToRad*(w1)        NB.  w1 = DegToRad*(w1)

NB. w2 = 357.52772 + 35999.05034*T - 0.0001603*T2 - (T3 / 300000)
w2=. 357.52772 + (35999.05034*T) - (0.0001603*T2) - (T3 % 300000)
w2=. DegToRad*(w2)        NB.  w2 = DegToRad*(w2)

NB. w3 = 134.96298 + 477198.867398*T + 0.0086972*T2 + (T3 / 56250)
w3=. 134.96298 + (477198.867398*T) + (0.0086972*T2) + (T3 % 56250)
w3=. DegToRad*(w3)        NB.  w3 = DegToRad*(w3)

NB. w4 = 93.27191 + 483202.017538*T - 0.0036825*T2 + (T3 / 327270)
w4=. 93.27191 + (483202.017538*T) - (0.0036825*T2) + (T3 % 327270)
w4=. DegToRad*(w4)        NB.  w4 = DegToRad*(w4)

NB. w5 = 125.04452 - 1934.136261*T + 0.0020708*T2 + (T3 / 450000)
w5=. 125.04452 - (1934.136261*T) + (0.0020708*T2) + (T3 % 450000)
w5=. DegToRad*(w5)        NB.  w5 = DegToRad*(w5)

```

```

w=. (sin w5)*((_174.2*T) - 171996)      NB. w = sin(w5)*(-174.2*T - 171996)
w=. w + (sin 2 * w4 + w5 - w1)*((-1.6*T) - 13187)  NB. w = w + sin(2*(w4 + w5 - w1))*(-1.6*T - 13187)
w=. w + (sin 2 * w4 + w5)*(_2274 - 0.2*T)          NB. w = w + sin(2*(w4 + w5))*(-2274 - 0.2*T)
w=. w + (sin 2 * w5)*((0.2*T) + 2062)              NB. w = w + sin(2 * w5)*(0.2*T + 2062)
w=. w + (sin w2)*(1426 - 3.4*T)                   NB. w = w + sin(w2)*(1426 - 3.4*T)
w=. w + (sin w3)*((0.1*T) + 712)                  NB. w = w + sin(w3)*(0.1*T + 712)

NB. w = w + sin(2*(w4 + w5 - w1) + w2)*(1.2*T - 517)
w=. w + (sin (2 * w4 + w5 - w1) + w2)*((1.2*T) - 517)

w=. w + (sin (2*w4) + w5)*((-0.4*T) - 386)        NB. w = w + sin(2 * w4 + w5)*(-0.4*T - 386)

NB. w = w + sin(2*(w4 + w5 - w1) - w2)*(217 - 0.5*T)
w=. w + (sin (2 * w4 + w5 - w1) - w2)*(217 - 0.5*T)

w=. w + (sin (2*w4 - w1) + w5)*(129 + 0.1*T)      NB. w = w + sin(2*(w4 - w1) + w5)*(129 + 0.1*T)
w=. w + (sin w3 + w5)*((0.1*T) + 63)              NB. w = w + sin(w3 + w5)*(0.1*T + 63)
w=. w + (sin w5 - w3)*((-0.1*T) - 58)             NB. w = w + sin(w5 - w3)*(-0.1*T - 58)
w=. w + (sin 2*w2)*(17 - 0.1*T)                   NB. w = w + sin(2*w2)*(17 - 0.1*T)
w=. w + (sin 2 * w2 + w4 + w5 - w1)*((0.1*T) - 16) NB. w = w + sin(2*(w2 + w4 + w5 - w1))*((0.1*T) - 16)
w=. w - 301*(sin (2 * w4 + w5) + w3)               NB. w = w - 301*sin(2*(w4 + w5) + w3)
w=. w - 158*(sin w3 - 2*w1)                       NB. w = w - 158*sin(w3 - 2*w1)
w=. w + 123*(sin (2 * w4 + w5) - w3)               NB. w = w + 123*sin(2*(w4 + w5) - w3)
w=. w + 63*(sin 2*w1)                             NB. w = w + 63*sin(2*w1)
w=. w - 59*(sin (2 * w1 + w4 + w5) - w3)           NB. w = w - 59*sin(2*(w1 + w4 + w5) - w3)
w=. w - 51*(sin (2*w4) + w3 + w5)                 NB. w = w - 51*sin(2 * w4 + w3 + w5)

```

```

w=. w + 48*sin(2 * w3 - w1)
w=. w + 46*(sin (2 * w4 - w3) + w5)
w=. w - 38*(sin 2 * w1 + w4 + w5)
w=. w - 31*(sin 2 * w3 + w4 + w5)
w=. w + 29*(sin 2*w3)
w=. w + 29*(sin (2 * w4 + w5 - w1) + w3)
w=. w + 26*(sin 2*w4)
w=. w - 22*(sin 2* w4 - w1)
w=. w + 21*(sin (2*w4) + w5 - w3)
w=. w + 16*(sin (2*w1) - w3 + w5)
w=. w - 15*(sin w2 + w5)
w=. w - 13*(sin w3 + w5 - 2*w1)
w=. w - 12*(sin w5 - w2)
w=. w + 11*(sin 2 * w3 - w4)
w=. w - 10*(sin (2 * w4 + w1) + w5 - w3)
w=. w - 8*(sin (2 * w4 + w1 + w5) + w3)
w=. w + 7*(sin (2 * w4 + w5) + w2)
w=. w - 7*(sin w3 - (2*w1) + w2)
w=. w - 7*(sin (2 * w4 + w5) - w2)
w=. w - 7*(sin (2*w1) + (2*w4) + w5)
w=. w + 6*(sin (2*w1) + w3)
w=. w + 6*(sin 2 * w3 + w4 + w5 - w1)
w=. w + 6*(sin (2 * w4 - w1) + w3 + w5)
w=. w - 6*(sin (2 * w1 - w3) + w5)
w=. w - 6*(sin (2*w1) + w5)
w=. w + 5*(sin w3 - w2)
w=. w - 5*(sin (2* w4 - w1) + w5 - w2)

```

```

NB. w = w + 48*sin(2*(w3 - w1))
NB. w = w + 46*sin(2*(w4 - w3) + w5)
NB. w = w - 38*sin(2*(w1 + w4 + w5))
NB. w = w - 31*sin(2*(w3 + w4 + w5))
NB. w = w + 29*sin(2*w3)
NB. w = w + 29*sin(2*(w4 + w5 - w1) + w3)
NB. w = w + 26*sin(2*w4)
NB. w = w - 22*sin(2*(w4 - w1))
NB. w = w + 21*sin(2*w4 + w5 - w3)
NB. w = w + 16*sin(2*w1 - w3 + w5)
NB. w = w - 15*sin(w2 + w5)
NB. w = w - 13*sin(w3 + w5 - 2*w1)
NB. w = w - 12*sin(w5 - w2)
NB. w = w + 11*sin(2*(w3 - w4))
NB. w = w - 10*sin(2*(w4 + w1) + w5 - w3)
NB. w = w - 8*sin(2*(w4 + w1 + w5) + w3)
NB. w = w + 7*sin(2*(w4 + w5) + w2)
NB. w = w - 7*sin(w3 - 2*w1 + w2)
NB. w = w - 7*sin(2*(w4 + w5) - w2)
NB. w = w - 7*sin(2*w1 + 2*w4 + w5)
NB. w = w + 6*sin(2*w1 + w3)
NB. w = w + 6*sin(2*(w3 + w4 + w5 - w1))
NB. w = w + 6*sin(2*(w4 - w1) + w3 + w5)
NB. w = w - 6*sin(2*(w1 - w3) + w5)
NB. w = w - 6*sin(2*w1 + w5)
NB. w = w + 5*sin(w3 - w2)
NB. w = w - 5*sin(2*(w4 - w1) + w5 - w2)

```

```

w=. w - 5*(sin w5 - 2*w1)
w=. w - 5*(sin (2 * w3 + w4) + w5)
w=. w + 4*(sin (2 * w3 - w1) + w5)
w=. w + 4*(sin (2 * w4 - w1) + w2 + w5)
w=. w + 4*(sin w3 - 2*w4)
w=. w - 4*(sin w3 - w1)
w=. w - 4*(sin w2 - 2*w1)
w=. w - 4*(sin w1)
w=. w + 3*(sin (2*w4) + w3)
w=. w - 3*(sin 2 * w4 + w5 - w3)
w=. w - 3*(sin w3 - w1 - w2)
w=. w - 3*(sin w2 + w3)
w=. w - 3*(sin (2 * w4 + w5) + w3 - w2)
w=. w - 3*(sin (2 * w1 + w4 + w5) - w2 - w3)
w=. w - 3*(sin (2 * w4 + w5) + 3*w3)
w=. w - 3*(sin (2 * w1 + w4 + w5) - w2)

NB. w = w - 5*sin(w5 - 2*w1)
NB. w = w - 5*sin(2*(w3 + w4) + w5)
NB. w = w + 4*sin(2*(w3 - w1) + w5)
NB. w = w + 4*sin(2*(w4 - w1) + w2 + w5)
NB. w = w + 4*sin(w3 - 2*w4)
NB. w = w - 4*sin(w3 - w1)
NB. w = w - 4*sin(w2 - 2*w1)
NB. w = w - 4*sin(w1)
NB. w = w + 3*sin(2*w4 + w3)
NB. w = w - 3*sin(2*(w4 + w5 - w3))
NB. w = w - 3*sin(w3 - w1 - w2)
NB. w = w - 3*sin(w2 + w3)
NB. w = w - 3*sin(2*(w4 + w5) + w3 - w2)
NB. w = w - 3*sin(2*(w1 + w4 + w5) - w2 - w3)
NB. w = w - 3*sin(2*(w4 + w5) + 3*w3)
NB. w = w - 3*sin(2*(w1 + w4 + w5) - w2)

dPsiDeg=. w % 36000000.0 NB. dPsiDeg = w / 36000000.0
)

parse_iau_named_stars=: 3 : 0

NB.*parse_iau_named_stars v-- IAU named star list to btcl header
NB. table.
NB.
NB. Original star name data was downloaded from:
NB.
NB. https://www.iau.org/public/themes/naming\_stars/

```

```
NB.
NB. and slightly adjusted in Excel. The data stored in (futs) is
NB. a Unicode UTF-8 CSV export.
NB.
NB. monad: btcl =. parse_iau_named_stars clTxt
NB.
NB. NB. get stars from (futs)
NB. NB. od ;:'futs utils'
NB. iau=. ;{: , >{: 4 get 'iau_named_stars_2022_txt'
NB. parse_iau_named_stars iau

NB. remove any byte order mark
t=. parsecsv y }.~ (BOM -: (#BOM){.y){0,#BOM

NB. extract relevant columns
c=. ;:'IAU_Name Designation Bayer_Name Vmag RA_J2000 Dec_J2000'
t=. t {"1~ (0 { t) i. c

NB. scrub objects with questionable magnitude
t #~ _ ~: _999&".&> (c i. <'Vmag') {"1 t
)

parscsv=: 3 : 0

NB.*parscsv v-- parses comma delimited files. (x) is the field
NB. delimiter. Lines are delimited with either CRLF or LF
NB.
NB. monad: btcl =. parsecsv cl
```

```
NB. dyad:  btcl =. ca parsecsv cl
NB.
NB.      ', ' parsecsv read 'c:\comma\delimited\text.csv'
```

```
', ' parsecsv y
:
'separator cannot be the " character' assert -. x -: ''
```

```
NB. CRLF delimited *.csv text to char table
y=. x ,. ] ;. _2 y -. CR
```

```
NB. bit mask of unquoted " field delimiters
b=. -. }. ~:/\ ''' e.~ ' ' , , y
b=. ($y) $ b *. , x = y
```

```
NB. use masks to cut lines
b <;. _1"1 y
)
```

```
NB. parse TAB delimited table text - see long document
parsetd=: [: <;. _2&> (a.{~9) ,&.>~ [: <;. _2 [: (] , ((10{a.})"_ = {(:) }. (10{a.})"_ (13{a.}) -.~ ]
```

```
NB. reads a file as a list of bytes
read=: 1!:1&([`<@.(32&>@ (3!:0)))
```

```
NB. radians from degrees
rfd=: *&0.0174532925199432955
```

```
riset=: 4 : 0
```

```
NB.*riset v-- rise, transit, set times of IAU named stars.
```

```
NB.
```

```
NB. dyad: (btRs ; flParms) =. bLYMD_UO_LB_AOBJ riset blclStarNames
```

```
NB.
```

```
NB. LB=. _116.375956 43.646775 NB. Meridian
```

```
NB. YMD=. 2023 3 27
```

```
NB. UO=. 6
```

```
NB. (YMD;UO;LB) riset 'Algol'
```

```
NB. (YMD;UO;LB) riset 'Algol';'Rigel';'Spica'
```

```
NB.
```

```
NB. NB. add objects not IAU names - need name, ra, dec
```

```
NB. AOB=. (<;:'Venus'),(<41.73129),<18.44092
```

```
NB. AOB=. ,&.> (;:'OBJ_Name OBJ_RA_J2000 OBJ_Dec_J2000') ,. AOB
```

```
NB. (YMD;UO;LB;<AOB) riset 'Venus'
```

```
NB. local time, UT offset (0=Greenwich), Latitude Longitude
```

```
'ymfd uo LB AOB'=. 4 {. x
```

```
NB. convert LB to meeu convention
```

```
LB=. _1 1 * LB
```

```
NB. local time to UT
```

```
UT=. ymfd + 0 0,uo%24
```

```
NB. look up RA, Dec
```



```
'IAU Navigation'=. loadstars 0
NB. IAU stars !(*)=. IAU_Name RA_J2000 Dec_J2000
({."1 IAU)=. {:"1 IAU
Stars=. boxopen y

if. #AOB do.
  NB. insert additional objects
  ({."1 AOB)=. {:"1 AOB
  NB. !(*)=. OBJ_Dec_J2000 OBJ_Name OBJ_RA_J2000
  IAU_Name=. OBJ_Name , IAU_Name
  RA_J2000=. OBJ_RA_J2000 , RA_J2000
  Dec_J2000=. OBJ_Dec_J2000 , Dec_J2000
end.

if. 0 e. b=. Stars e. IAU_Name do.
  smoutput 'not in IAU named stars -> '; Stars #~ -.b
else.
  ix=. IAU_Name i. Stars
  RA=. <ix{RA_J2000 [ Dec=. <ix{Dec_J2000
  riseset_calc UT;uo;LB;(<Stars),RA,Dec
end.
)

riseset_calc=: 3 : 0

NB.*riseset_calc v-- rise, transit, set times of stars.
NB.
NB. Main rise/set calculations. Argument (y) set in (riseset).
```

```
NB.
NB. monad: (btRs ; flParms) =. riseset_calc bLYMD_UO_LB_OBJ_RA_Dec

'ymd uo LB obj ra dec'=. ,&.> y

NB. (L) longitude, west positive
NB. (B) latitude, north positive
'L B'=. LB

obj=. obj ,"0 1 a:,a: NB. result table

NB. dynamical time  $\Delta T$  in fractional days NOTE:  $\Delta T$  is not
NB. going to change a lot over the interpolation period !(*)=. nc
if. 0=nc<'DeltaTsOverride_riseset_' do. dTs=. DeltaTsOverride_riseset_
else.
  dTs=. ,/deltaT0 deltaTdy ymd
end.
dTfd=. dTs%DAYSECS

NB. apparent sidereal time Greenwich at 0h in degrees
th0=. ,/ddfrdms 15 * apparsidjd0 JD=. julfrcal ymd

NB. TD times  $\Delta T + UT = TD$ 
TD=. (2 {. ymd),"1 0 (_1 0 1 + {:ymd) + dTfd

NB. apparent ra,dec for _1 0 1 days around rise/set
rdi=. |: TD apparRADEC"1 _ ra ,: dec
```

```
h0=. STDALTITUDE
```

```
NB. approximate times (14.1) meeus pg. 98
```

```
cosH0=. ((sind h0) - (sind B)*sind (<a;1;1){rdi} % (cosd B)*cosd (<a;1;1){rdi
```

```
NB. 1 indicates above or below horizon
```

```
bhrz=. 1 < |cosH0
```

```
obj=. (<"0 bhrz) (<a;1){obj
```

```
obj=. (<'above or below horizon') (<(I. bhrz);2){obj
```

```
ix=. I. -.bhrz NB. objects that rise and set
```

```
NB. m(i) are fractional day times (1/) puts mi in [0,1]
```

```
H0=. dfr arccos ix{cosH0
```

```
m0=. 1|360 %~ ((<ix;0;1){rdi} + L - th0
```

```
m1=. 1|m0 - H0 % 360
```

```
m2=. 1|m0 + H0 % 360
```

```
NB. rise, transit, setting
```

```
m=. m1 ,. m0 ,. m2
```

```
NB. sidereal time at Greenwich - meeus pg. 99
```

```
th=. nth0 th0 + 360.985647*m
```

```
NB. adjusted ra,dec
```

```
rda=. nu intr3p"1 ix{rdi [ nu=. dTfd + m
```

```
NB. local hour angles
```

```
rax=. <a;;0 [ decx=. <a;;1  
H=. (th - L) - rax{rda
```

NB. body's altitude (12.6) meeus pg. 89

```
sih=. ((sind B)*sind decx{rda) + (cosd B)*(cosd decx{rda)*cosd H
```

NB. degree altitudes positive

```
h=. |dfr arcsin sih
```

NB. corrections for transits (trx), rise/sets (rsx)

```
dltm=. ($m)$0  
trx=. <a;;1 [ rsx=. <a;;0 2  
dltm=. (-(trx{H}%360) trx} dltm  
drs=. rsx { (h - h0) % 360 * (cosd decx{rda)*(cosd B)*sind H  
dltm=. drs rsx} dltm  
m=. m + dltm
```

NB. calc parameters Julian date, ΔT, Longitude, Latitude, ymfd, timez

```
cParms=. JD,dTs,(-L),B,ymd,uo
```

NB. objects, above/below, altitudes, fractional day UT, UT hours/minutes

```
cParms ;~ (<"2 (,."1 ] 0.5 round h) ,"1 (,."1 m) ,"1 ] 1 round hmfrds DAYSECS*m) (<ix;2)} obj  
)
```

NB. right justify table

```
rjust=: ' '&$: :([ |."_1~ +/"1@(-.@(<./\"1@([ = ])))
```

NB. round (y) to nearest (x) (e.g. 1000 round 12345)

```
round=: [ * [: (<.) 0.5 + %~

NB. sine radians
sin=: 1&o.

NB. sin degrees
sind=: sin@rfd

NB. session manager output
smoutput=: 0 0 $ 1!:2&2

NB. appends trailing line feed character if necessary
tlf=: ] , ((10{a.)"_ = {:) }. (10{a.)"_

today_calc=: 4 : 0

NB.*today_calc v-- named (y) stars rising/setting today.
NB.
NB. dyad: (bt ; flParms) =. bLYmd_LB_UO_LMAG_LHORZ iau_today uuIgnore
NB.
NB. stars=. 'Algol';'Rigel';'Spica'
NB. 'Riseset cParms'=. (location_uluru 0) today_calc stars

NB. date, julian, location, UTC timezone, magnitude, horizon
'YMD JD LB UO LMAG LHORZ LOCNAME'=. x
```

```
'Rsiau cParms'=. (YMD;UO;LB) riseset y
```

```
NB. retain rising setting - circumpolar NIMP
```

```
Rsiau=. Rsiau #~ -. ; 1 {"1 Rsiau
```

```
NB. name ,. transit altitude, hour minutes
```

```
ahm=. 1&{&.> 2 {"1 Rsiau
```

```
Rsiau=. (0 {"1 Rsiau) ,. (0 {&.> ahm) ,. (<2 3){&.> ahm
```

```
NB. retain above local horizon
```

```
Rsiau=. Rsiau #~ LHORZ < 0&{&> 1 {"1 Rsiau
```

```
NB. sort by transit time
```

```
(LOCNAME;LMAG,LHORZ,cParms) ;~ Rsiau {~ /: >2 {"1 Rsiau
```

```
)
```

```
zetzthT0=: 3 : 0
```

```
NB.*zetzthT0 v-- epoch adjustment terms for J2000 RA DEC in degrees.
```

```
NB.
```

```
NB. monad: fT =. zetzthT0 ftYYYYMMDD
```

```
NB.
```

```
NB. zetzthT0 2028 11 13.19
```

```
NB.
```

```
NB. zetzthT0 2023 4 23 , 1988 3 20 ,: 1987 4,10 + fdfrhms 19 21 0
```

```
t=. gT0ymd y
```

```
't2 t3'=. t (^"1 0) 2 3 NB. t^2 and t^3
```

NB. meeus (20.3) pg. 126

```
zet=. (2306.2181*t) + (0.30188*t2) + 0.017988*t3
```

```
z=. (2306.2181*t) + (1.09468*t2) + 0.018203*t3
```

```
th=. (2004.3109*t) + (0.42665*t2) + 0.041833*t3
```

NB. insure degree result rank matches (y) rank

```
3600 %~ zet , z (,`,: )@.(2=#$y) th
```

```
)
```

NB.POST_riseset post processor.

```
smoutput IFACE=: (0 : 0)
```

```
NB. (riseset) interface word(s): 20230406j152302
```

```
NB. -----
```

```
NB. fmt_today NB. format today verbs result
```

```
NB. iau_today NB. named IAU stars rising/setting today
```

```
NB. loadstars NB. loads riseset star data
```

```
NB. nav_today NB. named navigation stars rising/setting today
```

```
NB. navdaylist NB. sky safari 6_0 observing list of today's navigation stars
```

```
NB. riseset NB. rise, transit, set times of stars
```

```
)
```

NB. smoutput 'NB. vmd: ' , , '0,p<; >q<; >0,0' (8!:2) VMDriseset

```
cocurrent 'base'
```

```
coinsert 'riseset'
```

Index

(...)=:, 23

afterstr, 7

alldifs, 7

apparRADEC, 7

apparsecs, 9

apparsidjd0, 9

apply, 9

arccos, 9

arcsin, 9

arctan, 9

assert, 9

atan2, 10

beforestr, 11

BOM, 5

boxopen, 12

cold_iau_named_stars, 12

cos, 12

cosd, 12

CR, 6

ctl, 13

DAYSECS, 6

ddfrdms, 13

deltaT0, 13

deltaTdy, 17

dfr, 17

dmsfrdd, 17

fmt_today, 17

gT0jd, 18

gT0ymd, 18

hmfrds, 19

iau_today, 19

IFACE, 47

IFACEWORDSriserset, 6

intr3p, 20

julfrcal, 20

JULIAN, 6

JULIAN_riserset_, 25–27

LF, 6

LIMITHORZ, 6

LIMITHORZ_riserset_, 25–27

LIMITMAG, 6

LIMITMAG_riserset_, 25–27

ljust, 22

loadstars, 22

location_home, 24

location_uluru, 25

location_yellowstone, 26

LOCATIONNAME, 6

LOCATIONNAME_riserset_, 25–27

meanobliquityjd0, 29

meanobliquityT0, 27

meanobliquityT1, 28

meansid0, 29

meansidjd0, 30

nav_today, 30

navdaylist, 31

nnth0, 33

npth0, 33

nth0, 33

nutration_longitude_dPsi, 33

OBLIQUITYDMS2000, 6

OBSLOCATION, 7

OBSLOCATION_riserset_, 25–27

parse_iau_named_stars, 37

parsecsv, 38

parsetd, 39

read, 39

rfd, 39

risetset, 40
risetset_calc, 41
rjust, 44
ROOTWORDSrisetset, 7
round, 45
sin, 45

sind, 45
smoutput, 45
STDALTITUDE, 7

tlf, 45
today_calc, 45

UTCOffset, 7
UTCOffset_risetset_, 25–27

VMDrisetset, 7

zetzthT0, 46