

jodliterate Group

John D. Baker

October 4, 2020

Contents

jodliterate Overview	2
jodliterate Interface	2
jodliterate and JOD	2
Running jodliterate	3
jodliterate Source Code	6
=: Index	57

jodliterate Overview

jodliterate is a J utility script that generates [literate](#) documents directly from JOD dictionary groups.

See the following for details:

1. [Using jodliterate notebook](#).
2. [Using jodliterate PDF](#).

jodliterate Interface

<code>THISPANDOC</code>	<i>full pandoc path - use (pandoc) if on shell path</i>
<code>formifacetex</code>	<i>formats hyperlinked and highlighted interface words</i>
<code>grplit</code>	<i>make latex for group (y)</i>
<code>ifacesection</code>	<i>interface section summary string</i>
<code>ifc</code>	<i>format interface comment text</i>
<code>setjodliterate</code>	<i>prepare LaTeX processing - sets out directory writes preamble</i>
<code>wordlit</code>	<i>make latex from word list (y)</i>

jodliterate and JOD

jodliterate makes some assumptions about the J code and document text it processes. It assumes:

1. All source code is stored in JOD dictionaries.
2. jodliterate document fragments are either:

- Markdown group headers: `2 9 disp 'groupname'`
- \LaTeX suffixed macros: `4 disp 'groupname','_oview_tex'`

Running jodliterate

jodliterate runs on Windows, Linux and Mac versions of J.¹

To use jodliterate you must:

1. Install JOD. [JOD](#) is a J addon. It is usually installed with [pacman](#).
2. Install JODSOURCE. [JODSOURCE](#) is also a J addon. Install it with [pacman](#). It contains the JOD dictionaries required to build JOD. JODSOURCE also contains jodliterate.
3. Install a current version of [pandoc](#). pandoc version 2.9.1.1 and beyond supports J syntax highlighting. Prior versions required modification. The following blog posts provide more information:
 - (a) [More J Pandoc Syntax HighLighting](#)
 - (b) [Pandoc based J Syntax Highlighting](#)
 - (c) [Semi-Literate JOD](#).
4. Build jodliterate. jodliterate is a J group. JOD makes J scripts from groups. To make jodliterate do:

```
require 'general/jod'
od ;:'joddev jod utils' [ 3 od ''
mls 'jodliterate'
```

¹jodliterate will run on J 8.01 and beyond.

5. Open the JOD dictionaries containing the group you want to document.

```
od ;:'joddev jod utils' [ 3 od ''
```

6. Load *jodliterate*. After making *jodliterate* it can be loaded like any J script.

```
load 'jodliterate'
```

7. Set a working directory. *jodliterate* generates \LaTeX files. All such files are written to the directory specified by *setjodliterate*.

```
setjodliterate '' NB. current JOD put dictionary document directory
```

```
setjodliterate 'c:\temp' NB. windows
```

```
setjodliterate '/home/john/temp' NB. linux
```

8. Run *grplit* on the group you want to document. *grplit* generates \LaTeX files in the working directory. The root \LaTeX file is given the group name.

```
grplit 'jodliterate' NB. makes jodliterate.tex
```

9. Use \LaTeX to compile the files generated by *grplit*.

A batch *bat* script is written to the *setjodliterate* directory that shows the sequence of \LaTeX compilation commands.

Files may be processed with *pdflatex*, *xelatex* or *lualatex*. Your choice will be dictated by the presence of Unicode characters. For more details see the preamble file *JODLiteratePreamble.tex* in the working directory.

There are some \LaTeX settings you may want to adjust.

1. Edit `JODLiteratePreamble.tex` to change the number of index columns. The default is four but this may result in long names running together. To decrease or increase index columns change:

```
\begin{multicols}{4}[\section*{\indexname}]
```

2. `jodliterate` wraps long source code lines. Wrapping is controlled by `WRAPLIMIT`. The default is 110 characters. Change this value if you change font or page size. Wrapped lines are preceded with the string `WRAPLEAD` with default `>...>`.

jodliterate Source Code

*NB.*jodliterate s-- generates literate source code documents directly from JOD groups.*
NB.
NB. verbatim: see the following blog posts and github files
NB.
NB. <https://analyzethedatanotthedrivel.org/2012/10/01/semi-literate-jod/>
NB. <https://analyzethedatanotthedrivel.org/2020/02/19/more-j-pandoc-syntax-highlighting/>
NB. <https://github.com/bakerjd99/jacks/blob/master/jodliterate/UsingJodliterate.pdf>
NB. <https://github.com/bakerjd99/jacks/blob/master/jodliterate/Using%20jodliterate.ipynb>
NB.
NB. interface word(s):
NB. -----
NB. THISPANDOC - full pandoc path - use (pandoc) if on shell path
NB. formifacetex - formats hyperlinked and highlighted interface words
NB. grplit - make latex for group (y)
NB. ifacesection - interface section summary string
NB. ifc - format interface comment text
NB. setjodliterate - prepare LaTeX processing - sets out directory writes preamble
NB. wordlit - make latex from word list (y)
NB.
NB. author: John D. Baker
NB. created: 2012oct01
NB. -----
NB. 12oct03 (x) grplit argument added to suppress root tex overwrites
NB. 12oct04 group IFACEWORDSgroupname hyperlinked
NB. 12oct05 replaced ;: parsing with (wfl) - handles bad j code

NB. 12oct08 added error handling - replaced (write) with (writeas)

NB. 12oct11 adjusted LaTeX preamble - changing monofonts

NB. 12oct12 added (sbtokens) - useful for analyzing code text

NB. 12oct17 added (wrapvrb) - long source lines now wrapped

NB. 13dec29 added to (jacks) GitHub repository

NB. 20may07 adjusted word formation (wfl) for J 9.01

NB. 20may08 updated for current (pandoc) versions

NB. 20jun07 added (formifacete) to interface words

```
coclass 'ajodliterate'
coinsert 'ijod'
```

*NB.*dependents*

NB. declared global here to avoid confusing LaTeX names with J names

NB. ()=: JLTITLETEX JLOVIEWTEX JLBUILDTTEX JLGRPLITTEX JLWORDLITTEX JODLiteratePreamble*

NB. Roger Hui's word formation state machine - similiar to ;: but

NB. parses text with LFs, retains whitespace and handles open quotes.

NB.

NB. verbatim: note difference

NB.

NB. wfl'+/ i. 23 5, ''OPEN QUOTE'

NB. ;:'+/ i. 23 5, ''OPEN QUOTE'

NB. hide script locals !()=. mfl sfl*

mfl=. 256\$0 NB. X other

mfl=. 1 (9,a.i.' ') }mfl NB. S whitespace (space and horizontal tab)

```

mfl=. 2  (,(a.i.'Aa')+/i.26) }mfl  NB. A A-Z a-z excluding N B
mfl=. 3  (a.i.'N')           }mfl  NB. N the letter N
mfl=. 4  (a.i.'B')           }mfl  NB. B the letter B
mfl=. 5  (a.i.'0123456789_') }mfl  NB. 9 digits and _
mfl=. 6  (a.i.'.')           }mfl  NB. D .
mfl=. 7  (a.i.':')           }mfl  NB. C :
mfl=. 8  (a.i.'\"')          }mfl  NB. Q quote
mfl=. 9  (13)                }mfl  NB. CR
mfl=. 10 (10)                }mfl  NB. LF

sfl=. _2]\"1 }.\".;._2 (0 : 0)
' X      S      A      N      B      9      D      C      Q      CR      LF ' ]0
1 1  12 1  2 1  3 1  2 1  6 1  1 1  1 1  7 1  10 1  1 1  NB. 0  initial
1 2  12 2  2 2  3 2  2 2  6 2  1 0  1 0  7 2  10 2  1 2  NB. 1  other
1 2  12 2  2 0  2 0  2 0  2 0  1 0  1 0  7 2  10 2  1 2  NB. 2  alp/num
1 2  12 2  2 0  2 0  4 0  2 0  1 0  1 0  7 2  10 2  1 2  NB. 3  N
1 2  12 2  2 0  2 0  2 0  2 0  5 0  1 0  7 2  10 2  1 2  NB. 4  NB
9 0   9 0  9 0  9 0  9 0  9 0  1 0  1 0  9 0  10 2  1 2  NB. 5  NB.
1 4  13 0  6 0  6 0  6 0  6 0  6 0  1 0  7 4  10 2  1 2  NB. 6  num
7 0   7 0  7 0  7 0  7 0  7 0  7 0  7 0  8 0  10 2  1 2  NB. 7  '
1 2  11 2  2 2  3 2  2 2  6 2  1 2  1 2  7 0  10 2  1 2  NB. 8  ''
9 0   9 0  9 0  9 0  9 0  9 0  9 0  9 0  9 0  10 2  1 2  NB. 9  comment
1 2  11 2  2 2  4 2  2 2  6 2  1 2  1 2  7 2  10 2  11 0 NB. 10 CR
1 2  11 2  2 2  4 2  2 2  6 2  1 2  1 2  7 2  10 2  1 2  NB. 11 CRLF
1 2  12 0  2 2  3 2  2 2  6 0  1 2  1 2  7 2  10 2  1 2  NB. 12 space
1 2  13 0  2 2  3 2  2 2  6 0  1 2  1 2  7 2  10 2  1 2  NB. 13 space after num
)

```


NB. word formation for lines

wfl=: (0;sfl;mfl) & ;:

JLDIRECTORY=: ''

*NB.*enddependents*

NB.<<~~~~ { .latex }

NB. group title and author - standard \maketitle

JLTITLETEX=: 0 : 0

% latex author and title

\author{~#~author~#~}

\title{\texttt{~#~group~#~} Group}

)

NB. group overview header

JLOVIEWTEX=: 0 : 0

% this jodliterate overview

\section{\texttt{~#~group~#~} Overview}

)

NB. latex group build script

JLBUILDTEX=: 0 : 0

```
rem sequence of latex commands that generate PDF
rem assumes latex exes are on the working path
setlocal
cd /d %~dp0
lualatex ~#~group~#~
makeindex ~#~group~#~
lualatex ~#~group~#~
lualatex ~#~group~#~
endlocal
)
```

NB. group root tex - columns may need adjusting
JLGRPLITTEX=: 0 : 0

```
% Main jodliterate (grplit) latex file. (grplit) generates "group"
% named versions of this file for each JOD group it processes.
```

```
\input{JODLiteratePreamble.tex}
```

```
\input{~#~group~#~title.tex}
```

```
\maketitle
```

```
\tableofcontents
```

```
\newpage
```

```
% commands for adjusting distance
```

```
% between columns and inserting a rule
```

```
%\setlength{\columnsep}{3em}
%\setlength{\columnseprule}{0.5pt}
%\twocolumn
\input{~#~group~#~oview.tex}

\newpage
%\onecolumn
\input{~#~group~#~code.tex}

\newpage
\phantomsection
\addcontentsline{toc}{section}{\texttt{=:} Index}
\printindex

\end{document}
)

NB. word lit root tex
JLWORDLITTEX=: 0 : 0

% Main jodliterate (wordlit) latex file.

\input{JODLiteratePreamble.tex}

\newpage

% commands for adjusting distance
```

```
% between columns and inserting a rule
%\setlength{\columnsep}{3em}
%\setlength{\columnseprule}{0.5pt}
%\twocolumn

%\onecolumn
\input{~~~texname~~~code.tex}

\newpage
\phantomsection
\addcontentsline{toc}{section}{\texttt{=:} Index}
\printindex

\end{document}
)

NB. main jodliterate LaTeX preamble
JODLiteratePreamble=: 0 : 0

% jodliterate latex preamble.
%
% This file is a highly customized version of the preamble
% material generated by pandoc's -s option when producing
% .tex output. pandoc highlighting is overridden and
% the standard index is redefined.
```

```
\documentclass[12pt]{article}

\usepackage[landscape]{geometry}
\usepackage[headings]{fullpage}
\usepackage{lmodern}
\usepackage{amssymb,amsmath}
\usepackage{ifxetex,ifluatex}

% provides \textsubscript
\usepackage{fixltx2e}

% use microtype if available
\IfFileExists{microtype.sty}{\usepackage{microtype}}{}
\ifnum 0\ifxetex 1\fi\ifluatex 1\fi=0 % if pdftex
  \usepackage[utf8]{inputenc}
\else % if luatex or xelatex
  \usepackage{fontspec}
  \ifxetex
    \usepackage{xltxtra,xunicode}
  \fi
  \defaultfontfeatures{Mapping=tex-text,Scale=MatchLowercase}
  % replace EUROUC with unicode euro character
  % if you need this character - the presence of
  % this single character in the preamble forces use of xelatex, lualated
  %\newcommand{\euro}{EUROUC}
  % can set other monospace fonts if they're available
  % I rather like Source Code Pro see:
```

```
% http://blogs.adobe.com/typblography/2012/09/source-code-pro.html
%\setmonofont{FreeMono}
%\setmonofont{Source Code Pro}
\fi

% Redefine labelwidth for lists; otherwise, the enumerate package will cause
% markers to extend beyond the left margin.
\makeatletter\AtBeginDocument{%
  \renewcommand{\@listi}
    {\setlength{\labelwidth}{4em}}
}\makeatother
\usepackage{enumerate}

% tightlist command for list spacing
\providecommand{\tightlist}{%
  \setlength{\itemsep}{0pt}\setlength{\parskip}{0pt}}

% build document index
\usepackage{makeidx}

% colors
\usepackage{color}
\definecolor{shadecolor}{RGB}{248,248,248}
% j control structures
\definecolor{keywcolor}{rgb}{0.13,0.29,0.53}
% j explicit arguments x y m n u v
\definecolor{datacolor}{rgb}{0.13,0.29,0.53}
```

```
% j numbers - all types see j.xml
\definecolor{decvcolor}{rgb}{0.00,0.00,0.81}
\definecolor{basencolor}{rgb}{0.00,0.00,0.81}
\definecolor{floatcolor}{rgb}{0.00,0.00,0.81}
% j local assignments
\definecolor{charcolor}{rgb}{0.31,0.60,0.02}
\definecolor{stringcolor}{rgb}{0.31,0.60,0.02}
\definecolor{commentcolor}{rgb}{0.56,0.35,0.01}
% primitive adverbs and conjunctions
\definecolor{othercolor}{rgb}{0.56,0.35,0.01}
\definecolor{othercolor}{RGB}{0,0,255}
% global assignments
\definecolor{alertcolor}{rgb}{0.94,0.16,0.16}
% primitive J verbs and noun names
\definecolor{funccolor}{rgb}{0.00,0.00,0.00}

\usepackage{fancyvrb}
\DefineShortVerb[commandchars=\\\{\}\{\|\}
\DefineVerbatimEnvironment{Highlighting}{Verbatim}{commandchars=\\\{\}\}
% Add ',fontsize=\small' for more characters per line

% pandoc generated syntax coloring commands - names
% are fixed in generated code but definitions may
% be set to any valid text formatting command
\usepackage{framed}
\newenvironment{Shaded}{}{}
\newcommand{\KeywordTok}[1]{\textcolor{keywcolor}{\textbf{#1}}}
```

```
% works better with Source Code Pro
%\newcommand{\KeywordTok}[1]{\textcolor{keywcolor}{#1}}
%\newcommand{\DataTypeTok}[1]{\textcolor{datacolor}{#1}}
%\newcommand{\DecValTok}[1]{\textcolor{decvcolor}{#1}}
%\newcommand{\DecValTok}[1]{#1}
%\newcommand{\BaseNTok}[1]{\textcolor{basencolor}{#1}}
%\newcommand{\FloatTok}[1]{\textcolor{floatcolor}{#1}}
%\newcommand{\CharTok}[1]{\textcolor{charcolor}{\textbf{#1}}}
%\newcommand{\StringTok}[1]{\textcolor{stringcolor}{#1}}
%\newcommand{\CommentTok}[1]{\textcolor{commentcolor}{\textit{#1}}}
%\newcommand{\OtherTok}[1]{\textcolor{othercolor}{#1}}
%\newcommand{\AlertTok}[1]{\textcolor{alertcolor}{\textbf{#1}}}
%\newcommand{\FunctionTok}[1]{\textcolor{funccolor}{#1}}
%\newcommand{\FunctionTok}[1]{#1}
%\newcommand{\RegionMarkerTok}[1]{#1}
%\newcommand{\ErrorTok}[1]{\textbf{#1}}
%\newcommand{\NormalTok}[1]{#1}

% JOD oriented auxiliary commands for post processing pandoc generated latex
\newenvironment{JODGroupHeader}{}{}
\newenvironment{JODPostProcessor}{}{}

\usepackage{fancyhdr}
\pagestyle{fancy}

% date each page
\rfoot{\emph{\today}}
```



```
\ifxetex
  \usepackage[setpagesize=false, % page size defined by xetex
             unicode=false,      % unicode breaks when used with xetex
             xetex]{hyperref}
\else
  \usepackage[unicode=true]{hyperref}
\fi

\hypersetup{breaklinks=true,
            bookmarks=true,
            pdfauthor={},
            pdftitle={},
            colorlinks=true,
            urlcolor=blue,
            linkcolor=magenta,
            pdfborder={0 0 0}}

\setlength{\parindent}{0pt}
\setlength{\parskip}{6pt plus 2pt minus 1pt}
\setlength{\emergencystretch}{3em} % prevent overfull lines
\setcounter{secnumdepth}{0}

% reset latex index to use four columns - default is two
% which results in lots of wasted page space in landscape
% NOTE: adjust if index names run together
% from: http://www.latex-community.org/viewtopic.php?f=4&t=1735
\usepackage{multicol}
```

```
\makeatletter
\renewenvironment{theindex}
  {\if@twocolumn
    \@restonecolfalse
  \else
    \@restonecoltrue
  \fi
  \setlength{\columnseprule}{0pt}
  \setlength{\columnsep}{35pt}
  \begin{multicols}{4}[\section*{\indexname}]
  \markboth{\MakeUppercase\indexname}%
    {\MakeUppercase\indexname}%
  \thispagestyle{plain}
  \setlength{\parindent}{0pt}
  \setlength{\parskip}{0pt plus 0.3pt}
  \relax
  \let\item\@idxitem}%
  {\end{multicols}\if@restonecol\onecolumn\else\clearpage\fi}
\makeatother

\makeindex

\begin{document}

)
NB.>>~~~~
```

*NB.*end-header*

NB. string marking start of LaTeX indexed word - see FAKETOKENS

BEGININDEX=: '\KeywordTok{=:.:}'

NB. marks start of JOD group header in pandoc latex

BEGINJODHEADER=: '\begin{JODGroupHeader}'

NB. marks start of JOD group postprocessor in pandoc latex

BEGINJODPOSTP=: '\begin{JODPostProcessor}'

NB. marks the start of J script text that is not J

BEGINNOTJ=: 'NB.<<~~~'

NB. carriage return character

CR=: 13{a.

NB. default pandoc install location

DEFAULTPANDOC=: '"C:\Program Files\Pandoc\pandoc"'

NB. string marking end of LaTeX indexed word - see FAKETOKENS

ENDINDEX=: '\KeywordTok{=..=..}'

NB. marks end of JOD group header in pandoc latex

ENDJODHEADER=: '\end{JODGroupHeader}'

NB. marks end of JOD group postprocessor in pandoc latex

ENDJODPOSTP=: '\end{JODPostProcessor}'

NB. marks the end of J script text that is not J

ENDNOTJ=: 'NB.>>~~~'

NB. 2 and 3 j (wfl) tokens - the trailing blank of (;1{FAKETOKENS}) matters!

FAKETOKENS=: <;._1 ' |=::=:: |=..=.. '

NB. interface word list name prefix

IFACEWORDSPFX=: 'IFACEWORDS'

NB. interface words for (jodliterate) group

IFACEWORDSjodliterate=: <;._1 ' THISPANDOC formifacetex grplit ifacesection ifc setjodliterate wordlit'

NB. interface words \pageref \label prefix

IFCPFX=: 'ifc:'

NB. jodliterate author - inserted in latex \author{}

JLAUTHOR=: 'John D. Baker'

NB. suffix of jodliterate code file

JLCODEFILE=: 'code.tex'

NB. markdown text string that marks where generated group interface inserted

JLINSERTIFACEMD=: '~{~{insert_interface_md_}~}'

NB. suffix of jodliterate overview file

JLOVIEWFILE=: 'oview.tex'

NB. name suffix of markdown overview text

JLOVIEWSUFFIX=: '_oview_tex'

NB. suffix of jodliterate title file

JLTITLEFILE=: 'title.tex'

NB. temporary latex file

LATEXTMP=: 'jltemp.tex'

NB. line feed character

LF=: 10{a.

NB. marks start of J code for pandoc -- requires pandoc with j syntax coloring

MARKDOWNHEAD=: '~~~~ { .j }'

NB. marks end J code for pandoc

MARKDOWNTAIL=: '~~~~'

NB. temporary markdown file

MARKDOWNTMP=: 'jltemp.markdown'

NB. root words for (jodliterate) group

ROOTWORDSjodliterate=: <;._1 ' DEFAULTPANDOC IFACEWORDSjodliterate ROOTWORDSjodliterate grplit sbtokens set
>.>jodliterate wordlit'

NB. full pandoc path - use (pandoc) if on shell path

THISPANDOC=: "C:\Program Files\Pandoc\pandoc"

NB. interface word _ character replacement

UBARSUB=: ' _: '

NB. white space characters

WHITESPACE=: 10 13 9 32{a.

NB. wrapped line prefix

WRAPLEAD=: '>..>'

NB. maximum number of code listing characters - adjust for given LaTeX pagesize

WRAPLIMIT=: 110

NB. invalid j string starting wrapped line - exclude '=' - trailing blank matters

WRAPPREFIX=: ')=.)=. '

NB. pandoc LaTeX fragment from (WRAPPREFIX) - these strings must correspond

WRAPPREFIXTEX=: '\RegionMarkerTok{}}\KeywordTok{=.}\RegionMarkerTok{}}\KeywordTok{=.}'

NB. retains string after first occurrence of (x)

afterstr=:] }~ #@[+ 1&(i~)@([E.])

NB. trims all leading and trailing blanks

alltrim=:] #~ [: -. [: (*. /\ . +. *./ \) ' '&=

NB. retains string before first occurrence of (x)

```
beforestr=: ] {.~ 1&(i.~)@([ E. ])
```

```
betweenstrs=: 4 : 0
```

*NB.*betweenstrs v-- select sublists between nonnested delimiters*

NB. discarding delimiters.

NB.

NB. dyad: blcl =. (clStart;clEnd) betweenstrs cl

NB. blnl =. (nlStart;nlEnd) betweenstrs nl

NB.

NB. ('start';'end') betweenstrs 'start yada yada end boo hoo start ahh end'

NB.

NB. NB. also applies to numeric delimiters

NB. (1 1;2 2) betweenstrs 1 1 66 666 2 2 7 87 1 1 0 2 2

```
's e'=. x
```

```
llst=. ((-#s) (|.!.0) s E. y) +. e E. y
```

```
mask=. ~:/\ llst
```

```
(mask#llst) <|.1 mask#y
```

```
)
```

NB. boxes open nouns

```
boxopen=: <^:(L. = 0:)
```

```
changestr=: 4 : 0
```

```

NB.*changestr v-- replaces substrings - see long documentation.
NB.
NB. dyad:  clReps changestr cl
NB.
NB.  NB. first character delimits replacements
NB.  '/change/becomes/me/ehh' changestr 'blah blah ...'

pairs=. 2 {."(1) _2 [\ <; _1 x      NB. change table
cnt=. _1 [ lim=. # pairs
while. lim > cnt=.>:cnt do.        NB. process each change pair
  't c'=. cnt { pairs              NB. /target/change
  if. +./b=. t E. y do.            NB. next if no target
    r=. I. b                       NB. target starts
    'l q'=. #&> cnt { pairs         NB. lengths
    p=. r + 0,+/\(<:# r)$ d=. q - 1 NB. change starts
    s=. * d                        NB. reduce < and > to =
    if. s = _1 do.
      b=. 1 #~ # b
      b=. ((1 * # r)$ 1 0 #~ q,l-q) (,r +/ i. l)} b
      y=. b # y
      if. q = 0 do. continue. end. NB. next for deletions
    elseif. s = 1 do.
      y=. y #~ >: d r} b           NB. first target char replicated
    end.
    y=. (c $~ q *# r) (,p +/i. q)} y NB. insert replacements
  end.
end. y                             NB. altered string

```



```
)

charsub=: 4 : 0

NB.*charsub v-- single character pair replacements.
NB.
NB. dyad: clPairs charsub cu
NB.
NB.   '-_$ ' charsub '$123 -456 -789'

'f t'=. ((#x)$0 1)<@,&a./x
t {~ f i. y
)

NB. character table to newline delimited list
ctl=: }.@(@1&(",1)@(-.@(*./\"1@(&' '0]))) # ,@((10{a.)&(",1)@])

cutnestidx=: 4 : 0

NB.*cutnestidx v-- cut list into nested runs and other.
NB.
NB. Nested runs are delimited by begin and end tags. This verb is
NB. oriented toward XML parsing where typical begin end tags are
NB. <ul> </ul> and tags with attributes like: <hoo boy="2">
NB. </hoo>
NB.
NB. This verb can process numeric lists but care must be taken to
```

```

NB. insure the pad item (1{.0$y) does not match begin and end
NB. values.
NB.
NB. dyad: (ilIdx ;< blcl) =. (clStart;clEnd) cutnestidx cl
NB.      (ilIdx ;< blnl) =. (nlStart;nlEnd) cutnestidx nl
NB.
NB. xml=. 'yada <ol><li>one</li><ol><li>sub one</li></ol></ol> boo'
NB. ('<ol';'</ol>') cutnestidx xml
NB.
NB. 88 99 cutnestidx (i.5),88,(10?10),99 88 5 5 5 5 5 99

if. #y do.
  's e'=. ,&.> x      NB. start end lists
  ut=. 1{.0$y         NB. padding
  assert. -.s -: e     NB. they must differ
  assert. -. (s -:ut) +. e -:ut
  sp=. s E. ut=.y,ut   NB. start mask

  NB. quit if no delimiters
  if. -.1 e. sp do. (i.0);<<y return. end.

  ep=. e E. ut        NB. end mask
  assert. (+/sp) = +/ep NB. basic balance
  dp=. sp + - ep      NB. start end marks
  assert. 0 *./ . <: +/\ dp NB. nested balance
  ep=. I. _1=dp [ sp=. I. 1=dp NB. start end indexes
  ut=. +/\dp -. 0     NB. scanned marks

```

```

dp=. /:~ sp,ep          NB. all indexes
sp=. (firstones 1<:ut)#dp  NB. starts of nested
ep=. (#e)+(0=ut)#dp      NB. starts of other
dp=. /:~ ~.0,sp,ep       NB. cut starts
ut=. }: 1 dp} (>:#y)#0   NB. cut mask
(dp i. sp);<ut <;.1 y    NB. nest indexes cut list
else.
  (i.0);<<y              NB. empty arg result
end.
)

NB. double quotes - doubles internal " quotes like (quote)
dbquote=: '""&,@(&'""')@(#~ >:@(=&'""'))

NB. quote unquoted strings containing blanks: dbquoteuq 'c:\blanks in\paths bitch'
dbquoteuq=: ]`dbquote@.([[: -. '""'&-:@({: , {.)} *. ' ' e. ])

decomm=: 3 : 0

NB.*decomm v-- removes comments from j words. The (x) argument
NB. specifies whether all blank lines are removed or retained.
NB.
NB. monad: decomm ctWord
NB.
NB. decomm jcr 'decomm' NB. decomment self
NB.
NB. dyad: pa decomm ctWord

```

```
NB.  
NB. 1 decomm jcr 'decomm' NB. remove blanks (default)  
NB. 0 decomm jcr 'decomm' NB. retain all blank lines
```

```
1 decomm y  
:  
NB. mask of unquoted comment starts  
c=. ($y)$'NB.' E. ,y  
c=. +./\"1 c > ~:/\"1 y e. ''''
```

```
NB. ,, work around for j8.05 bug - remove when fixed  
NB. y=. ,,y
```

```
NB. blank out comments  
y=. ' ' (I. ,c)} ,y  
y=. y $~ $c
```

```
NB. remove blank lines - default  
if. x do. y #~ y +./ . ~: ' ' end.  
)
```

```
NB. boxes UTF8 names  
fboxname=: ([: < 8 u: >) ::]
```

```
NB. erase files - cl / blcl of path file names  
ferase=: 1!:55 ::(_1:)@(fboxname&>)@boxopen
```

NB. 1 if file exists 0 otherwise

```
fexist=: 1:@(1!:(4) ::0:@(fboxname&>))@boxopen
```

NB. 0's all but first 1 in runs of 1's - like (firstone) but differs for nulls

```
firstones=: > (0: , }:)
```

```
formifacetex=: 3 : 0
```

*NB.*formifacetex v-- formats hyperlinked and highlighted interface words.*

NB.

NB. monad: cl =. formifacetex blclIwords

NB.

NB. NB. inteface latex

NB. formifacetex IFACEWORDSjodliterate

NB. require 'jod' !()=. get*

```
head=. '\begin{Shaded}',LF,'\begin{Highlighting}[]',LF
```

```
tail=. '\end{Highlighting}',LF,'\end{Shaded}',LF
```

```
ctok=. '\CommentTok{'
```

```
ntok=. '\NormalTok{'
```

```
href=. '\hyperlink{'
```

NB. using [] brackets for page references

```
pgrefhd=. '[\pageref{',IFCPFX
```

```
pgreftl=. '}] '
```

NB. fetch current short descriptions !()=. WORD_ajod_ EXPLAIN_ajod_*

NB. form latex index commands

```
indexes=. (<'\AlertTok{=:}\index{'} ,&.> inames ,&.> (<'\texttt{'} ,&.> inames ,&.> <'}}')
```

NB. replace indirect and multiple assignments with fixed proxies

```
indexes=. ((#pma) # <'\AlertTok{=:}\index{00multiple@\texttt{'...'='=:}}') pma} indexes
```

```
indexes=. ((#pia) # <'\AlertTok{=:}\index{01indirect@\texttt{(...)=:}}') pia} indexes
```

NB. adjust j locative chars _ they give latex indexing grief

NB. later versions of pandoc handle this case

NB. if. #pos=. I. '_ 'e.&> indexes do.

```
NB. indexes=. ('#_#_ 'echange&> pos{indexes) pos} indexes
```

NB. end.

```
indexes
```

```
)
```

NB. size of file in bytes

```
fsize=: 1!:4 ::(_1:)@fboxname&>@boxopen
```

NB. opens and catenates boxed lists on the last axis

```
fuserows=: >@((>@[ , "1 >@)) /)
```

```
gbodylatex=: 3 : 0
```

*NB.*gbodylatex v-- group body latex.*

NB.

```
NB. monad: clTex =. gbodylatex clGroupname

if. #mtxt=. markdfrgroup y do. latexfrmarkd mtxt else. '' end.
)

gheadlatex=: 3 : 0

NB.*gheadlatex v-- group header latex.
NB.
NB. monad: clTex =. gheadlatex clGroupname

if. #mtxt=. markdfrghead y do.
    BEGINJODHEADER,LF,(tlf latexfrmarkd mtxt),ENDJODHEADER,2#LF
else.
    ''
end.
)

gpostlatex=: 3 : 0

NB.*gpostlatex v-- group post processor latex.
NB.
NB. monad: clTex =. gpostlatex clGroupname

if. #mtxt=. markdfrgpost y do.
    BEGINJODPOSTP,LF,(tlf latexfrmarkd mtxt),ENDJODPOSTP
else.
```



```
''
end.
)

grouplatex=: 3 : 0

NB.*grouplatex v-- group latex with pandoc syntax highlighting.
NB.
NB. monad: clTex =. grouplatex clGroupname
NB.
NB.    NB. requires open JOD dictionary with a 'jod' group
NB.    gtex=. grouplatex 'jod'
NB.
NB. dyad: clTex =. paIndex grouplatex clGroupname
NB.
NB.    0 grouplatex 'jod' NB. do not replace marks with index

1 grouplatex y
:
NB. require 'jod' !(*)=. badrc_ajod_ grp jderr_ajod_
if. badrc_ajod_ gnames=. grp y do. gnames return. end.

ltx=. x indexwraplatex (gheadlatex ; gbodylatex ; gpostlatex) y
'\section{\texttt{'',(alltrim y),' } Source Code}',LF,LF,ltx
)

grplit=: 3 : 0
```

```
NB.*grplit v-- make latex for group (y).
NB.
NB. monad: (paRc ; blclTeXfiles) =. grplit clGroupname
NB.
NB.   grplit 'jodliterate' NB. document self
NB.
NB. dyad: (paRc ; blclTeXfiles) =. paOw grplit glGroupname
NB.
NB.   NB. do not overwrite root tex - allows for latex tweaking
NB.   0 grplit 'jodliterate'

1 grplit y
:
NB. require 'jod' !(*)=. badrc_ajod_ get grp jderr_ajod_ ok_ajod_
try.

if. 3~:(4!:0) <'badrc_ajod_' do. 0;'!error: jod is not loaded' return. end.
if. 0=#JLDIRECTORY do. 0;'!error: working directory is not set' return. end.

NB. group must exist
if. badrc_ajod_ glist=. GROUP_ajod_ grp group=. y -. ' ' do. glist return. end.

NB. default overview
ohd=. ('/~#~group~#~/',alltrim y) changestr JLOVIEWTEX [ gdoc=. ''
iwords=. ifacewords group

NB. overview documents are either markdown/latex group headers or stored LaTeX macros
```

```
if. badrc_ajod_ gdoc=. MACRO_ajod_ get group,JLOVIEWSUFFIX do.
  NB. no stored LaTeX generate LaTeX from group document markdown/latex
  if. badrc_ajod_ gdoc=. (GROUP_ajod_,DOCUMENT_ajod_) get group do. gdoc return. end.
  if. #gdoc=. ;{:,>1{gdoc do.
    NB. insert interface md based on IFACEWORDSgroup
    if. +./JLINSERTIFACEMD E. gdoc do.
      gdoc=. group setifacesummary gdoc
    end.
    gdoc=. latexfrmarkd gdoc
    ifstr=. ifacesection group
    if. (+./ifstr E. gdoc) *. (<IFACEWORDSPFX,group) e. glist do.
      gdoc=. iwords setifacelinks ifstr;gdoc
    end.
  end.
else.
  NB. stored macro LaTeX - no adjustments
  gdoc=. ;{:,>1{gdoc
end.

NB. root .tex file - gets group name
wdir=. JLDIRECTORY
jlroot=. wdir,group,'.tex'
if. chroot=. x -: 1 do.
  root=. ('/~#~group~#~/','group) changestr JLGRPLITTEX
  (toJ root) writeas jlroot
end.
```

```
NB. author title .tex file
agstrs=. '/~#~author~#~/',(alltrim JLAUTHOR),'/~#~group~#~/',alltrim y
(toJ agstrs changestr JLTITLETEX) writeas jltitle=. wdir,group,JLTITLEFILE

NB. group overview .tex file
ohd=. ohd,LF,gdoc
(toJ ohd) writeas jloverview=. wdir,group,JLOVIEWFILE

NB. group build batch script - latex utils that compile generated files
jlbuildtex=. ('/~#~group~#~/',alltrim y) changestr JLBUILDTEX
(toJ jlbuildtex) writeas jlbuildbat=. wdir,group,'.bat'

NB. group source code .tex - return file names
gltx=. grouplatex group
gltx=. iwords setifacetargs gltx
(toJ gltx) writeas jlcode=. wdir,group,JLCODEFILE
ok_ajod_ (-.chroot) }. jlroot;jltitle;jloverview;jlcode;jlbuildbat

catchd.
  0;!'!error: (grplit) failure - last J error ->';13!:12 ''
end.
)

ifacemarkd=: 3 : 0

NB.*ifacemarkd v-- generate word interface markdown section.
NB.
NB. monad: clMd =. ifacemarkd clGroupName
```

```
NB.
NB.   ifacemarkd 'jodliterate'

LF,'~~~{ .j }',LF,(2 ifc y),LF,'~~~',LF
)

ifacesection=: 3 : 0

NB.*ifacesection v-- interface section summary string.
NB.
NB. This verb produces the interface section summary string. For
NB. (jodliterate) to include an updated hyperlinked interface
NB. summary it must find this string in generated latex. Edit
NB. this verb if you change the section layout.
NB.
NB. monad: cl =. ifacesection clGroupname

'\subsection{\texttt{' ,y,'} Interface}'
)

ifacewords=: 3 : 0

NB.*ifacewords v-- return interface word list.
NB.
NB. Assume the interface is out of date fetch current definition
NB. from dictionary. We need the value not the storage
NB. representation so define it in the JOD scratch object.
```

```
NB.
NB. monad:  blcl =. ifacewords clGroupname

NB. require 'jod' !(*)=. get
iname=. (IFACEWORDSPFX,y) -. ' '
(;SO__JODobj) get iname
iname=. iname, '__SO__JODobj'
words=. ". iname
words [ (4!:55) <iname
)

ifc=: 3 : 0

NB.*ifc v-- format interface comment text.
NB.
NB. Looks up interface words of a group and formats text for
NB. insertion into group headers and postprocessors.
NB.
NB. monad:  ifc clGroupName
NB. dyad:   iaOption ifc clGroupName

1 ifc y
:
NB. require 'jod' !(*)=. badrc_ajod_ get jderr_ajod_ badcl_ajod_ badil_ajod_
if. badcl_ajod_ y do. jderr_ajod_ 'invalid group name' return.
else.
  iface=. 'IFACEWORDS',alltrim y
end.
```

```
x=. {. ,x [ msg=. 'invalid ifc options'
if. badil_ajod_ x do. jderr_ajod_ msg return. end.
if. -.x e. i.3 do. jderr_ajod_ msg return. end.

NB. set comment style (header, postprocessor)
cpx=. ; x { (<'NB. ';' - '),(<'NB. ';' NB. '),<'';' NB. '

NB. define interface list in jod scratch locale
NB. !(*)=. SO__JODobj erase__SO__JODobj locsfx_ajod_ nl__SO__JODobj
if. badrc_ajod_ rc=. (;SO__JODobj) get iface do. rc return.
elseif. ilist=. ".iface , ;locsfx_ajod_ ;SO__JODobj
      erase__SO__JODobj nl__SO__JODobj i. 4
      badrc_ajod_ rc=. 0 8 get /:~ ~.ilist do. rc return.
elseif. 0=#txt=. >1{rc do. jderr_ajod_ 'no interface words' return.
elseif.do.
  ctl fuserows >&.> <"1 |: ((#txt)#,:cpx) ,&.> txt
end.
)

indexgrouptex=: 3 : 0

NB.*indexgrouptex v-- insert index commands in pandoc highlight group latex.
NB.
NB. dyad: cl =. clGroupName indexgrouptex clTex

'pos ltx'=. (BEGININDEX;ENDINDEX) cutnestidx y
```

```
if. #pos do. ; (formtexindexes pos{ltx} pos} ltx else. y end.
)

indexwraplatex=: 4 : 0

NB. *indexwraplatex v-- insert index commands and handle spurious blanks.
NB.
NB. dyad:  clLatex =. paIndex indexwraplatex clLatex

ltx=. ]`indexgrouptex@.(1 -: x) ; tlf&.> y -. a:

NB. wrap prefix final LaTeX
wpfx=. '\AlertTok{' , WRAPLEAD , '}'

NB. convert wrap marks to LaTeX fragments - handle trailing blank first
ltx=. ('#', WRAPPREFIXTEX, ' ', '#', wpfx) changestr ltx
ltx=. ('#', WRAPPREFIXTEX, '#', wpfx) changestr ltx

NB. remove spurious normal token blanks
sprb=. wpfx, '\NormalTok{'
('#', sprb, ' #', sprb) changestr ltx
)

NB. standarizes J path delimiter to unix/linux forward slash
jpathsep=: '/'&(('\ ' I.@:= ]))

jtokenize=: 3 : 0
```



```
NB.*jtokenize v-- tokenizes j text with (wfl).
NB.
NB. Similar to (;:&.>)@(<.<.2) but preserves whitespace and is
NB. able to parse invalid j text containing open quotes. When an
NB. open quote is encountered it is treated like an unterminated
NB. string.
NB.
NB. monad: blblcl =. jtokenize clJtext
NB.
NB. jtokenize 5!:5 <'jtokenize'

ct=. wfl y,LF
(ct -:&> <,LF) <.<.2 ct
)

latexfrmarkd=: 3 : 0

NB.*latexfrmarkd v-- latex from markdown using pandoc.
NB.
NB. monad: clTex =. latexfrmarkd clMarkdown

NB. require 'task' !(*)=. shell
if. #y do.
  ferase mrktmp=. JLDIRECTORY,MARKDOWNTMP
  ferase ltxtmp=. JLDIRECTORY,LATEXTMP
  (toJ y) writeas mrktmp
  NB. highlighting style is overridden in latex preamble
  shell THISPANDOC,' --highlight-style=tango ',(dbquoteuq mrktmp),' -o ',dbquoteuq ltxtmp
```

```
    assert. 0 < fsize ltxtmp
    tex=. read ltxtmp
    tex [ ferase ltxtmp [ ferase mrktmp
else.
    y
end.
)
```

```
markdfrghead=: 3 : 0
```

```
NB.*markdfrghead v-- markdown text from group header.
```

```
NB.
```

```
NB. monad: cl =. markdfrghead clGroupname
```

```
NB.
```

```
NB. mtxt=. markdfrghead 'jod'
```

```
NB. (toHOST mtxt) write 'c:/temp/jodhdr.markdown'
```

```
NB. require 'jod' !(*)=. badrc_ajod_ get HEADEND_ajodmake_ GROUP_ajod_
```

```
if. badrc_ajod_ hdr=. GROUP_ajod_ get y do. hdr return. end.
```

```
if. 0=#hdr=. ;1{,>1{hdr do. '' return. end.
```

```
hdr=. hdr,LF,HEADEND_ajodmake_
```

```
NB. handle any non j code regions
```

```
'idx chd'=. (BEGINNOTJ;ENDNOTJ) cutnestidx hdr
```

```
if. #idx do.
```

```
    psj=. idx -.~ i.#chd
```

```
    chd=. (markgnonj&.> idx{chd) idx} chd
```

```
    chd=. (markgassign&.> psj{chd) psj} chd
    hdr=. ;chd
else.
    hdr=. markgassign hdr
end.

if. #hdr do. markdj hdr else. '' end.
)

markdfrgpost=: 3 : 0

NB.*markdfrgpost v-- markdown from group post processor.
NB.
NB. monad: clMarkdown =. markdfrgpost clGroupname

NB. require 'jod' !(*)=. get MACRO_ajod_
'rc post'=. 2 {. MACRO_ajod_ get 'POST_',y -.' '
if. rc do. markdj markgassign ; {: , post else. '' end.
)

markdfrgroup=: 3 : 0

NB.*markdfrgroup v-- markdown text from group.
NB.
NB. monad: cl =. markdfrgrp clGroupname
NB.
NB. mtxt=. markdfrgroup 'jod'
```

NB. (toHOST txt) write 'c:/temp/jcode.markdown'

```
NB. require 'jod' !(*)=. badrc_ajod_ get gdeps grp
if. badrc_ajod_ gnl=. grp y do. gnl return. end.
if. badrc_ajod_ gdp=. gdeps y do. gdp return. end.
if. #gnl=. (gnl -. gdp) -. a: do. markdfrwords gnl else. '' end.
)
```

markdfrwords=: 3 : 0

*NB.*markdfrwords v-- markdown text from word list.*

NB.

NB. This verb takes a blcl of JOD word names and returns a UTF-8

NB. encoded cl of word source code in markdown format. Markdown

NB. is a simple but versatile text markup format that is almost

NB. ideal for documenting program source code, see:

NB.

NB. <http://daringfireball.net/projects/markdown/>

NB.

NB. monad: clMarkdown =. markdfrwords blclWords

NB.

NB. markdfrwords ;:'go ahead mark us up'

NB.

NB. NB. markdown text from JOD group words

NB. txt=. markdfrwords }. grp 'jod'

NB. require 'jod' !()=. WORD_ajod_ NVTABLE_ajod_ badrc_ajod_ get wttxt__MK__JODobj*

if. badrc_ajod_ src=. (WORD_ajod_,NVTABLE_ajod_) get y do. src return. end.

NB. commented source code (name,source) table.

```
if. badrc_ajod_src=. 0 0 1 wtttext__MK__JODobj >1{src do. src
else.
  src=. markgassign&.> {"1 >1{src
  NB. similar to (markdj) but faster here
  utf8 ; (<LF,MARKDOWNHEAD,LF) ,&.> src ,&.> <LF,MARKDOWNTAIL,LF
end.
)
```

```
markdj=: 3 : 0
```

*NB.*markdj v-- mark j code for markdown.*

NB.

NB. monad: clM =. markdj clJ

```
utf8 (LF,MARKDOWNHEAD,LF),(tlf y),MARKDOWNTAIL,LF
)
```

```
markgassign=: 3 : 0
```

*NB.*markgassign v-- mark j code for latex indexing.*

NB.

*NB. This verb tokenizes j code and replaces all global
NB. assignments with syntactically incorrect j strings that will
NB. be transformed by pandoc into easily located latex strings
NB. that will then be converted by a post pandoc processor into*

```
NB. valid latex index commands. This works because regex based
NB. pandoc coloring does not "understand" j's parsing rules.
NB.
NB. monad: cl =. markgassign clJcode
NB.
NB. jcode=. 'markgassign=: ' , 5!:5 <'markgassign'
NB. markgassign jcode
```

```
if. 0=#jcode=. y -. CR do. y return. end.
jcode=. WRAPLIMIT wrapvrblong jcode
jtokens=. jtokenize jcode
```

```
NB. only interested in global assignment lines
if. #gix=. I. ; (<'=:') e. L: 1 jtokens do.
  jgl=. gix{jtokens
  jshp=. $jat=. >jgl
  jix=. I. jat = <'=: ' [ jat=. ,jat
  NB. extract global assignments
  NB. ignoring interleaving blanks
  jat2=. (jat -.&.> ' ') -. a:
  anames=. (<:I.(<'=:') -:&> jat2){jat2
  NB. (0{FAKETOKENS) and (1{FAKETOKENS) are invalid in j
  faketoks=. (0{FAKETOKENS) ,&.> anames ,&.> 1{FAKETOKENS
  jat=. <"1 jshp $ faketoks jix} jat
  jat=. (#&> jgl) {.&.> jat
  NB. adjust last LF
  (-LF={:y) }. ;;jat gix} jtokens
```

```
else.  
  y  
end.  
)
```

```
markgnonj=: 3 : 0
```

```
NB.*markgnonj v-- mark non j code region global assignments.
```

```
NB.
```

```
NB. Non J code is often inserted in J scripts as character nouns
```

```
NB. using explicit multi-line '0 : 0' definitions. This verb
```

```
NB. marks the assigned noun name. Only '=: 0 : 0' will be found
```

```
NB. and marked.
```

```
NB.
```

```
NB. verbatim:
```

```
NB.
```

```
NB. IamFound =: 0 : 0
```

```
NB. .... non j code ...
```

```
NB. )
```

```
NB.
```

```
NB. monad: cl =. markgnonj clNonj
```

```
ct=. <|.2 tlf y
```

```
mrk=. '=:0:0'
```

```
pos=. I. mrk&=:&> (-#mrk)&{.&.> ct -.&.> <WHITESPACE
```

```
ct=. ;(LF ,&.>~ markgassign&.> pos{ct) pos} ct
```

```
(-LF={:y) }. ct
```

```
)
```

NB. reads a file as a list of bytes

```
read=: 1!:1&[]`<@.(32&>@ (3!:0)))
```

NB. trim right (trailing) blanks

```
rtrim=: ] #~ [: -. [: *./\ . ' ' " _ = ]
```

NB. blcl of nonempty noncomment J cl tokens

```
sbtokens=: a: -.~ (<13 10 9{a.) -.&.>~ [: alltrim&.> [: wfl [: ctl [: decomm [: ];_1 (10{a.) , (13{a.) -.~ ]
```

```
setifacelinks=: 4 : 0
```

*NB.*setifacelinks v-- set hyperref links in any overview*

NB. interface words section.

NB.

NB. dyad: cl =. blclIwords setifacelinks (clIfstr ; clTex)

```
'ifstr tex'=. y
```

```
rmrk=. '\end{Shaded}'
```

```
head=. ifstr&beforestr tex
```

```
tail=. ifstr&afterstr tex
```

```
if. +./rmrk E. tail do.
```

```
    ifbk=. formifacetex x
```

```
    tail=. rmrk&afterstr tail
```

```
    head,ifstr,(2#LF),ifbk,tail
```

```
else.
```

```
    tex
```



```
end.
)

setifacesummary=: 4 : 0

NB.*setifacesummary v-- replace markdown interface summary tag with text.
NB.
NB. dyad: cl =. clGname setifacesummary clMd

(JLINSERTIFACEMD beforestr y),(ifacemarkd x),JLINSERTIFACEMD afterstr y
)

setifacetargs=: 4 : 0

NB.*setifacetargs v-- set hyperlink targets in group latex.
NB.
NB. dyad: cl =. blcliwords setifacetargs clTex

NB. replace troublesome _ in names
hlwords=. UBARSUB&charsub&.> x

NB. any _ chars are expanded to \_ at this stage
wnames=. '#_#\_'&changestr &.> x
targs=. (<'\NormalTok{') ,&.> wnames ,&.> <'}\AlertTok{=:}\index'

labels=. (<'}\AlertTok{=:}\phantomsection\label{' ,IFCPFX),&.> hlwords ,&.> <'}\index'
rstrs=. (<'\hypertarget{') ,&.> hlwords ,&.> (<'}{\NormalTok{') ,&.> wnames ,&.> labels
```

```
NB. delimiter character cannot be in text
assert. -. '#' e. ;targs,rstrs

chgs=. ; '#' ,&.> targs ,. rstrs
chgs changestr y
)

setjodliterate=: 3 : 0

NB.*setjodliterate v-- prepare LaTeX processing - sets out directory writes preamble.
NB.
NB. monad: (paRc ; clDir) =. setjodliterate clWorkingDir | zl
NB.
NB.   setjodliterate 'c:\temp'           NB. windows
NB.   setjodliterate '/home/john/temp'   NB. linux
NB.
NB.   NB. use the current JOD put dictionary document directory
NB.   setjodliterate ''

try.

if. 3~:(4!:0) <'badrc_ajod_' do. 0; '!error: jod is not loaded' return. end.
if. 0 = #DPATH__ST__JODobj   do. 0; '!error: no open jod dictionaries' return. end.

NB. if the path is empty use the current put dictionary document directory !(*)=. dob
if. 0 e. $y do. y=. DOC__dob [ dob=: {:{.DPATH__ST__JODobj end.
```

```
NB. profile (*)=. IFWIN
JLDIRECTORY_ajodliterate_=: jpathsep`winpathsep@.(IFWIN) tslash2 y

NB. write main latex preamble once per directory
preamble=. 'JODLiteratePreamble.tex'
if. -.fexist JLDIRECTORY,preamble do.
  (toJ JODLiteratePreamble) writeas JLDIRECTORY,preamble
end.
1;JLDIRECTORY

catchd.
  0;'!error: (setjodliterate) failure - last J error ->';13!:12 ''
end.
)

NB. appends trailing line feed character if necessary
tlf=: ] , ((10{a.})"_ = {:) }. (10{a.})"_

NB. converts character strings to J delimiter LF
toJ=: ((10{a.}) I.@(e.&(13{a.}))@] } )@:(#~ -.@((13 10{a.})&E.@,))

NB. appends trailing / iff last character is not \ or /
tslash2=: ([: - '\/' e.~ {:) }. '/' ,~ ]

NB. character list to UTF-8
utf8=: 8&u:
```

```
NB. standardizes path delimiter to windows back \ slash
winpathsep=: '\&(('/' I.@:= ]))

wordlatex=: 3 : 0

NB.*wordlatex v-- LaTeX from word list.
NB.
NB. monad: clLatex =. wordlatex blclWords

NB. require 'jod' !(*) badcl_ajod_
if. badcl_ajod_ mtxt=. markdfrwords y do. mtxt return.
elseif. #mtxt do. 1 indexwraplatex <latexfrmarkd mtxt
elseif.do. ''
end.
)

wordlit=: 3 : 0

NB.*wordlit v-- make latex from word list (y).
NB.
NB. monad: (paRc ; blclTeXfiles) =. wordlit blclWords
NB.
NB. wordlit 'jodliterate'
NB.
NB. dyad: (paRc ; blclTeXfiles) =. paDw wordlit blclWords
NB.
NB. NB. do not overwrite root tex - allows for latex tweaking
```

```
NB. 0 wordlit 'jodliterate'

1 wordlit y
:
NB. require 'jod' !(*)=. badrc_ajod_ badcl_ajod_ checknames_ajod_
try.

if. 3~:(4!:0) <'badrc_ajod_' do. 0; '!error: jod is not loaded' return. end.
if. 0=#JLDIRECTORY do. 0; '!error: working directory is not set' return. end.

NB. only valid jod names
if. badrc_ajod_ wlist=. checknames_ajod_ y do. wlist return. end.

NB. use first name on word list for tex file names
texname=. ;0{wlist=. }.wlist

NB. make latex
if. badcl_ajod_ wltx=. wordlatex wlist do. wltx return. end.

NB. root .tex file
wdir=. JLDIRECTORY
jlroot=. wdir,texname, '.tex'
if. chroot=. x -: 1 do.
  root=. ('/~#~texname~#~/',texname) changestr JLWORDLITTEX
  (toJ root) writeas jlroot
end.
```

```
NB. group build batch script - latex utils that compile generated files
jlbuiltex=. ('/~#~group~#~/',texname) changestr JLBUILDTEX
(toJ jlbuiltex) writeas jlbuiltbat=. wdir,texname,'.bat'
```

```
NB. source code .tex - return file names
NB. gltx=. iwords setifacetargs gltx
(toJ wltx) writeas jlcode=. wdir,texname,JLCODEFILE
ok_ajod_ (-.chroot) }. jlroot;jlcode;jlbuiltbat
```

```
catchd.
  0;!'!error: (wordlit) failure - last J error ->';13!:12 ''
end.
)
```

```
wrapvrblong=: 3 : 0
```

```
NB.*wrapvrblong v-- wraps verbatim text lines with length > (x).
NB.
NB. Wraps lines with length > (x) and prefixes each wrapped line
NB. with the syntactically invalid j string ')=.)=.' (WRAPPREFIX)
NB. This string is transformed by pandoc into an easily found
NB. sequence of LaTeX commands.
NB.
NB. monad: cl =. wrapvrblong clTxt
NB. dyad: cl =. iaLength wrapvrblong clTxt
```

```
WRAPLIMIT wrapvrblong y
:
```

NB. always trim trailing blanks

```
ct=. <@rtrim;._2 tlf y -. CR
```

NB. only wrap lines exceeding limit

```
if. #pos=. I. x < #&> ct do.
```

```
  wlen=. x-#WRAPLEAD
```

```
  wt=. (-wlen) (<\)&.> pos{ct
```

```
  slen=. 1&,@:<:@#&.> wt
```

NB. lead wrapped lines with prefix

```
  wt=. (slen #&.> <(<''),<LF,WRAPPREFIX) ,.&.> wt
```

```
  wt=. a: -.~ L: 1 ,&.> wt
```

NB. last wrapped line LF terminated

```
  wt=. wt , L: 1 <LF
```

```
  nwpos=. (i.#ct) -. pos
```

```
  ct=. ((nwpos{ct) ,&.> LF) nwpos} ct
```

```
  ;;wt pos} <"0 ct
```

```
else.
```

```
  (-LF~:{:y) }. ; ct ,&.> LF
```

```
end.
```

```
)
```

NB. write file as list of bytes - throws unambiguous error on failure

```
writeas=: (1!:2 ]`<@.(32&>@.(3!:0))) ::([: 'cannot write file'&(13!:8) 1:)
```

NB.POST_jodliterate post processor (-.)=:

```
smoutput IFACE=: (0 : 0)
```

```
NB. (jodliterate) interface word(s):
NB. -----
NB. THISPANDOC      NB. full pandoc path - use (pandoc) if on shell path
NB. formifacetex    NB. formats hyperlinked and highlighted interface words
NB. grplit          NB. make latex for group (y)
NB. ifacesection    NB. interface section summary string
NB. ifc             NB. format interface comment text
NB. setjodliterate  NB. prepare LaTeX processing - sets out directory writes preamble
NB. wordlit         NB. make latex from word list (y)
)

cocurrent 'base'
coinsert 'ajodliterate'

(3 : 0) ''
if. +./@('pandoc'&E.) panver=. ;0{ <;._2 tlf (shell THISPANDOC,' --version') -. CR do.
  smoutput 'NOTE: adjust pandoc path if version ('panver,') is not >= 2.9.1.1'
else.
  smoutput 'ERROR: pandoc not set - adjust THISPANDOC'
  smoutput 'THISPANDOC_ajodliterate_=: 'pandoc' NB. when pandoc on path'
end.
)
```


Index

afterstr, 22
alltrim, 22

beforestr, 23
BEGININDEX, 19
BEGINJODHEADER, 19
BEGINJODPOSTP, 19
BEGINNOTJ, 19
betweenstrs, 23
boxopen, 23

changestr, 23
charsub, 25
CR, 19
ctl, 25
cutnestidx, 25

dbquote, 27
dbquoteuq, 27
decomm, 27
DEFAULTPANDOC, 19
dob, 50

ENDINDEX, 19
ENDJODHEADER, 19
ENDJODPOSTP, 20
ENDNOTJ, 20

FAKETOKENS, 20
fboxname, 28
ferase, 28
fexist, 29
firstones, 29
formifacetex, 29
formtexindexes, 30
fsize, 31
fuserows, 31

gbodylatex, 31
gheadlatex, 32
gpostlatex, 32
grouplatex, 33
grplit, 33

IFACE, 55
ifacemarkd, 36
ifacesection, 37
ifacewords, 37
IFACEWORDSjodliterate,
20
IFACEWORDSPFX, 20
ifc, 38
IFCPFX, 20
indexgrouptex, 39
indexwraplatex, 40

JLAUTHOR, 20
JLBUILDTEX, 9
JLCODEFILE, 20
JLDIRECTORY, 9
JLDIRECTORY_ajodliterate_,
51
JLGRPLITTEX, 10
JLINSERTIFACEMD, 20
JLOVIEWFILE, 21
JLOVIEWSUFFIX, 21
JLOVIEWTEX, 9
JLTITLEFILE, 21
JLTITLETEX, 9
JLWORDLITTEX, 11
JODLiteratePreamble, 12
jpathsep, 40
jtokenize, 40

latexfrmarkd, 41
LATEXTMP, 21
LF, 21

markdfrghead, 42
markdfrgpost, 43
markdfrgroup, 43
markdfrwords, 44
markdj, 45

MARKDOWNHEAD, 21
MARKDOWNTAIL, 21
MARKDOWNTMP, 21
markgassign, 45
markgnonj, 47

read, 48
ROOTWORDSjodliterate,
21
rtrim, 48

sbtokens, 48
setifacelinks, 48
setifacesummary, 49
setifacetargs, 49
setjodliterate, 50

THISPANDOC, 22
tlf, 51
toJ, 51
tslash2, 51

UBARSUB, 22
utf8, 51

wfl, 9
WHITESPACE, 22
winpathsep, 52

wordlatex, 52
wordlit, 52

WRAPLEAD, 22
WRAPLIMIT, 22

WRAPPREFIX, 22
WRAPPREFIXTEX, 22

wrapvrblong, 54
writeas, 55