Sandbox for WSM v8.5.0

Vocus Web Services

Commercial and in confidence

Vocus Group Limited | ABN 96 084 115 499 | vocus.com.au
Level 10, 452 Flinders Street, Melbourne
Victoria 3000, AUSTRALIA

Copyright Notice

This document is provided by Vocus Group Limited on the basis that you will treat it as confidential. No part of this documentation may be reproduced or copied in any form by any means without the written permission of Vocus Group Limited. Unless otherwise expressly agreed in writing, the information contained in this document is subject to change without notice and Vocus Group Limited assumes no responsibility for any alteration to, or any error or other deficiency, in this document.

Copyright © 2009 - 2025 Vocus Group Limited. All rights reserved.

1 Table of Contents

1 Table of Contents 1
2 Overview 2
2.1 Accessing the Sandbox 2
2.2 Simulating a Successful Operation 2
2.3 Simulating a Failed Operation 2
3 WSM Gateway Sandbox 3
3.1 Authentication Test Case 3
3.1.1 Login to WSM Sandbox 3
3.1.2 Executing an Operation without Login 3
3.2 System Protection Test Case 3
3.2.1 Flood Attack 3
3.3 XML Validation Test Case 4
3.3.1 Badlly Formatted XML 4
3.3.2 XML Not Following WSM Format 5
3.3.3 Requesting Invalid ProductID 5
4 ProductID TCAS Sandbox 7
4.1 TCAS::Get 7
4.1.1 Scope RESPONSE 7
4.1.2 Scope REQUEST 7
4.1.3 Scope STEPS 8
4.2 Unsupported Operations 9
4.2.1 TCAS::Create 9
5 Other ProductID Sandbox 10
5.1 ProductID DIR::Create 10
5.2 Generating DIR Errors 11
5.2.1 Generating DIR-4220 Error Code 11
5.2.2 Generating Any Other Error Code 11
5.3 ProductID ADSL::Create 12
5.4 ADSL::Get scope SERVICE 13
5.5 ProductID OPER::Get Scope USAGE-DAILY 13

2 Overview

The **WSM Sandbox** is made available to aid in the development of the client application. The sandbox WSM interface is identical to the production system, but returns **canned** responses.

In the production environment requests undergo multiple stages of processing including authentication, verification, validation and then the actual processing by backend infrastructure. In contrast the sandbox will execute a SOAP request only up to the validation stage and then returns predefined responses. All asynchronous transaction results will be delivered via canned call-back.

Access to the testing environment is only available during the client's development and testing stage.

This documentation contains a subset of the test cases supported by WSM Sandbox. Client is encouraged to try their own combination of XML strings and compose their own test cases suitable for the project.

Only ProductID ADSL, OPER, and TCAS is included in this documentation, but all ProductID in WSM have sandbox built in and follow the same simulation rule below.

2.1 Accessing the Sandbox

The sandbox domain name / IP address is not advertised via Vocus public DNS. To access the sandbox the client needs to configure the client **operating system host file** with the following IP address:

Hostname	IP Address
wsm.webservice.m2.com.au	203.23.116.113

The sandbox system is protected by firewall, self signed HTTPS and requires a valid authentication certificate. The client must request access to the sandbox from Vocus prior to accessing this system.

2.2 Simulating a Successful Operation

To simulate a successful operation, send any **valid** request to the WSM. There is no concept of persistence in the sandbox, thus no transaction data will be stored and all responses are predefined, including the TransactionID and *returned* ServiceID.

There is an exception for operation TCAS::Get scope RESPONSE - to simulate the different Transaction States, the client can send SUCCESS, QUEUED, PROCESSNG, or WITHDRAWN as the request TransactionID.

2.3 Simulating a Failed Operation

To initiate any other error codes, the client can send the ProductID error code as the ServiceID or TransactionID of the SOAP request for **any** available WSM operation. These error codes must belong to the ProductID under testing.

For error code 4220 "validation error", the client can send a request with **invalid** Params to the WSM. To simulate error code 4222 send an **invalid** ProductID to WSM.

Authentication, verification and flood protection errors can be initiated by sending an invalid certificate or flooding the server with requests. Asynchronous transaction results will be delivered via SOAP call-back.

3 WSM Gateway Sandbox

3.1 Authentication Test Case

3.1.1 Login to WSM Sandbox

HTTP RAW Request

```
GET https://wsm.webservice.m2.com.au:9443/login/ HTTP/1.1
Connection: close
Accept-Encoding: gzip,deflate
Host: wsm.webservice.m2.com.au:9443
```

HTTP RAW Response – Successful login

```
HTTP/1.1 202 Accepted
X-Powered-By: nginx
Set-Cookie: JSESSIONID=5A15674C8F36D8F6C03C2DB1813ED74A; Path=/login; Secure
Content-Type: text/html;charset=UTF-8
Content-Length: 7
Date: Fri, 29 Oct 2010 03:32:13 GMT
Connection: close
```

3.1.2 Executing an Operation without Login

SOAP Request

```
Any request without login.
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <env:Fault>
         <faultcode>env:Server</faultcode>
         <faultstring>Login required</faultstring>
         <detail>
            <FaultResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
               <TransactionID>SANDBOX</TransactionID>
               <ErrorCode>WSM-4005</ErrorCode>
            </FaultResponse>
         </detail>
      </env:Fault>
   </env:Body>
</env:Envelope>
```

3.2 System Protection Test Case

3.2.1 Flood Attack

Repeatedly send any SOAP request to generate more than 100 requests in a 10 second interval. After the flood protection is initiated, client is restricted from making further requests for a short period. For example:

SOAP Request x 100

```
Any valid SOAP request.
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <env:Fault>
         <faultcode>env:Server</faultcode>
         <faultstring>Certificate request rate limit exceeded</faultstring>
         <detail>
            <FaultResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
               <TransactionID>SANDBOX</TransactionID>
               <ErrorCode>WSM-4080</ErrorCode>
            </FaultResponse>
         </detail>
      </env:Fault>
   </env:Body>
</env:Envelope>
```

3.3 XML Validation Test Case

3.3.1 Badlly Formatted XML

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
   <soapenv:Body>
      <whol:CreateRequest>
</whol:PlanID>
         </whol:Parameters>
      </whol:CreateRequest>
   </soapenv:Body>
</soapenv:Envelope>
```

No WSM ErrorCode is returned because the request did not reach the WSM layer.

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <env:Fault>
         <faultcode>env:Client</faultcode>
         <faultstring>org.xml.sax.SAXParseException: The element type
"whol:CreateRequest" must be terminated by the matching end-tag
"&lt;/whol:CreateRequest>".</faultstring>
      </env:Fault>
   </env:Body>
</env:Envelope>
```

3.3.2 XML Not Following WSM Format

For example, the ServiceID Param is missing from the following XML.

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
   <soapenv:Body>
      <whol:CreateRequest>
         <whol:AccessKey>1234567890123456</whol:AccessKey>
         <whol:ProductID>ADSL</whol:ProductID>
         <whol:PlanID>ANY-PLAN-ID</whol:PlanID>
         <whol:Parameters>
            <stan:Param id="Username">anton.kattan@staff.your-dsl.net</stan:Param>
            <stan:Param id="Password">abcdef</stan:Param>
            <stan:Param id="CarrierID">0399999999</stan:Param>
            <stan:Param id="OrderType">NEW</stan:Param>
            <stan:Param id="AnniversaryDay">1</stan:Param>
            <stan:Param id="IPAssignment">STATIC</stan:Param>
            <stan:Param id="LocationReference">VIC</stan:Param>
         </whol:Parameters>
      </whol:CreateRequest>
   </soapenv:Body>
</soapenv:Envelope>
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <env:Fault>
         <faultcode>env:Server</faultcode>
         <faultstring>Invalid Parameter: ServiceID</faultstring>
         <detail>
            <FaultResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
               <TransactionID>SANDBOX</TransactionID>
               <ErrorCode>ADSL-4220</ErrorCode>
            </FaultResponse>
         </detail>
      </env:Fault>
   </env:Body>
</env:Envelope>
```

3.3.3 Requesting Invalid ProductID

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
   <soapenv:Body>
      <whol:CreateRequest>
         <whol:AccessKey>1234567890123456</whol:AccessKey>
         <whol:ProductID>SUSHI</whol:ProductID>
         <whol:PlanID>FLX-MONTHLY-1GB</whol:PlanID>
         <whol:Parameters>
            <stan:Param id="ServiceID">2222</stan:Param>
```

```
            <stan:Param id="MSN">0412111222</stan:Param>
            <stan:Param id="SIMNumber">124567890</stan:Param>
            <stan:Param id="Realm">12</stan:Param>
            <stan:Param id="TimeZone">AEST</stan:Param>
            <stan:Param id="AccountID">1234</stan:Param>
            <stan:Param id="DirectoryID">12</stan:Param>
         </whol:Parameters>
      </whol:CreateRequest>
   </soapenv:Body>
</soapenv:Envelope>
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <env:Fault>
         <faultcode>env:Server</faultcode>
         <faultstring>Invalid ProductID: SUSHI</faultstring>
         <detail>
            <FaultResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
               <TransactionID>SANDBOX</TransactionID>
               <ErrorCode>WSM-4221</ErrorCode>
            </FaultResponse>
         </detail>
      </env:Fault>
   </env:Body>
</env:Envelope>
```

4 ProductID TCAS Sandbox

4.1 TCAS::Get

4.1.1 Scope RESPONSE

There is an exception to the normal Sandbox restriction on persistence for TCAS::Get scope RESPONSE. In order to simulate the different TransactionStates the client can send SUCCESS, QUEUED, PROCESSING, or WITHDRAWN as the request TransactionID.

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
   <soapenv:Body>
      <whol:GetRequest>
         <whol:AccessKey>1234567890123456</whol:AccessKey>
         <whol:ProductID>TCAS</whol:ProductID>
         <whol:PlanID>TRANSACTION-ID</whol:PlanID>
         <whol:Scope>RESPONSE</whol:Scope>
         <whol:Parameters>
            <stan:Param id="TransactionID">SUCCESS</stan:Param>
         </whol:Parameters>
      </whol:GetRequest>
   </soapenv:Body>
</soapenv:Envelope>
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <GetResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
         <TransactionID>SANDBOX</TransactionID>
         <ResponseType>SYNC</ResponseType>
         <Parameters>
            <ns2:Param id="TransactionState">SUCCESS</ns2:Param>
            <ns2:Param id="ServiceID">SANDBOX-ADSL</ns2:Param>
            <ns2:Param id="Username">akattan@m2.your-dsl.net.au</ns2:Param>
            <ns2:Param id="Password">password</ns2:Param>
            <ns2:Param id="CarrierID">0399998888</ns2:Param>
            <ns2:Param id="ServiceStatus">ACTIVE</ns2:Param>
            <ns2:Param id="ShapeStatus">FALSE</ns2:Param>
            <ns2:Param id="PlanID">SANDBOX-PlanID</ns2:Param>
            <ns2:Param id="AnniversaryDay">1</ns2:Param>
            <ns2:Param id="IPAddress">203.132.224.176</ns2:Param>
            <ns2:Param id="RoutedSubnet">255.255.255.127/28</ns2:Param>
            <ns2:Param id="IPAssignment">STATIC</ns2:Param>
            <ns2:Param id="LocationReference">3000</ns2:Param>
            <ns2:Param id="DirectoryID">SANDBOX-DIR</ns2:Param>
         </Parameters>
      </GetResponse>
   </env:Body>
</env:Envelope>
```

4.1.2 Scope REQUEST

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
   <soapenv:Body>
      <whol:GetRequest>
         <whol:AccessKey>1234567890123456</whol:AccessKey>
         <whol:ProductID>TCAS</whol:ProductID>
         <whol:PlanID>TRANSACTION-ID</whol:PlanID>
         <whol:Scope>REQUEST</whol:Scope>
         <whol:Parameters>
            <stan:Param id="TransactionID">QUEUED</stan:Param>
         </whol:Parameters>
      </whol:GetRequest>
   </soapenv:Body>
</soapenv:Envelope>
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <GetResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
         <TransactionID>SANDBOX</TransactionID>
         <ResponseType>SYNC</ResponseType>
         <Parameters>
            <ns2:Param id="Operation">GET</ns2:Param>
            <ns2:Param id="AccessKey">BBGF</ns2:Param>
            <ns2:Param id="ProductID">ADSL</ns2:Param>
            <ns2:Param id="PlanID">STANDARD-160GB</ns2:Param>
            <ns2:Param id="Scope">SERVICE</ns2:Param>
            <ns2:Param id="ServiceID">SANDBOX</ns2:Param>
         </Parameters>
      </GetResponse>
   </env:Body>
</env:Envelope>
```

4.1.3 Scope STEPS

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
   <soapenv:Body>
      <whol:GetRequest>
         <whol:AccessKey>1234567890123456</whol:AccessKey>
         <whol:ProductID>TCAS</whol:ProductID>
         <whol:PlanID>TRANSACTION-ID</whol:PlanID>
         <whol:Scope>STEPS</whol:Scope>
         <whol:Parameters>
            <stan:Param id="TransactionID">PROCESSING</stan:Param>
         </whol:Parameters>
      </whol:GetRequest>
   </soapenv:Body>
</soapenv:Envelope>
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
```

```
      <GetResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
         <TransactionID>SANDBOX</TransactionID>
         <ResponseType>SYNC</ResponseType>
         <Parameters>
             <ns2:Param id="SUCCESS">Client session accepted</ns2:Param>
             <ns2:Param id="SUCCESS">Validate XML</ns2:Param>
             <ns2:Param id="SUCCESS">Retrieve PlanID Details</ns2:Param>
             <ns2:Param id="SUCCESS"> Examine ServiceID</ns2:Param>
             <ns2:Param id="SUCCESS">Examine ADSL Order Type</ns2:Param>
             <ns2:Param id="FAILED">Service Qualification</ns2:Param>
             <ns2:Param id="PROCESSING">M2 Infrastructure Provisioning</ns2:Param>
         </Parameters>
      </GetResponse>
   </env:Body>
</env:Envelope>
```

4.2 Unsupported Operations

4.2.1 TCAS::Create

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
   <soapenv:Body>
      <whol:CreateRequest>
         <whol:AccessKey>1234567890123456</whol:AccessKey>
         <whol:ProductID>TCAS</whol:ProductID>
         <whol:PlanID>TRANSACTION-ID</whol:PlanID>
         <whol:Parameters>
            <stan:Param id="TransactionID">ABCDEF</stan:Param>
         </whol:Parameters>
      </whol:CreateRequest>
   </soapenv:Body>
</soapenv:Envelope>
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <env:Fault>
         <faultcode>env:Server</faultcode>
         <faultstring>Not implemented</faultstring>
         <detail>
            <FaultResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
               <TransactionID>SANDBOX</TransactionID>
               <ErrorCode>TCAS-5050</ErrorCode>
            </FaultResponse>
         </detail>
      </env:Fault>
   </env:Body>
</env:Envelope>
```

5 Other ProductID Sandbox

All WSM ProductID will have a sandbox instance. This section show some examples of other ProductID sandboxes.

5.1 ProductID DIR::Create

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
   <soapenv:Body>
      <whol:CreateRequest>
         <whol:AccessKey>1234567890123456</whol:AccessKey>
         <whol:ProductID>DIR</whol:ProductID>
         <whol:PlanID>STANDARD</whol:PlanID>
         <whol:Parameters>

            <stan:Param id="FirstName">Anton</stan:Param>
            <stan:Param id="LastName">Kattan</stan:Param>
            <stan:Param id="DOB">20091211</stan:Param>

            <stan:Param id="Main.Street1stNumber">12</stan:Param>
            <stan:Param id="Main.StreetName">Nowhere</stan:Param>
            <stan:Param id="Main.StreetType">RD</stan:Param>
            <stan:Param id="Main.Suburb">SYDNEY</stan:Param>
            <stan:Param id="Main.State">NSW</stan:Param>
            <stan:Param id="Main.PostCode">2000</stan:Param>
            <stan:Param id="Main.Country">61</stan:Param>

            <stan:Param id="Directory.Street1stNumber">12</stan:Param>
            <stan:Param id="Directory.StreetName">Nowheres</stan:Param>
            <stan:Param id="Directory.StreetType">RD</stan:Param>
            <stan:Param id="Directory.Suburb">SYDNEY</stan:Param>
            <stan:Param id="Directory.State">NSW</stan:Param>
            <stan:Param id="Directory.PostCode">2000</stan:Param>
            <stan:Param id="Directory.Country">61</stan:Param>

            <stan:Param id="Billing.Street1stNumber">12</stan:Param>
            <stan:Param id="Billing.StreetName">Nowheres</stan:Param>
            <stan:Param id="Billing.StreetType">RD</stan:Param>
            <stan:Param id="Billing.Suburb">SYDNEY</stan:Param>
            <stan:Param id="Billing.State">NSW</stan:Param>
            <stan:Param id="Billing.PostCode">2000</stan:Param>
            <stan:Param id="Billing.Country">61</stan:Param>

            <stan:Param id="Normal.ContactFirstName">Anton</stan:Param>
            <stan:Param id="Normal.ContactLastName">Kattan</stan:Param>
            <stan:Param id="Normal.Phone">0399998888</stan:Param>

            <stan:Param id="Emergency.ContactFirstName">Anton</stan:Param>
            <stan:Param id="Emergency.ContactLastName">Kattan</stan:Param>
            <stan:Param id="Emergency.Phone">0399998888</stan:Param>
         </whol:Parameters>
      </whol:CreateRequest>
   </soapenv:Body>
</soapenv:Envelope>
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <CreateResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
```

```
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
         <TransactionID>SANDBOX</TransactionID>
         <ResponseType>SYNC</ResponseType>
         <Parameters>
            <ns2:Param id="DirectoryID">SandboxDirectoryID</ns2:Param>
         </Parameters>
      </CreateResponse>
   </env:Body>
</env:Envelope>
```

5.2 Generating DIR Errors

To initiate the return of any error code (beside TCAS-4220, see below), the client can send the TCAS error code as the TransactionID of the SOAP request.

5.2.1 Generating DIR-4220 Error Code

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
   <soapenv:Body>
      <whol:GetRequest>
         <whol:AccessKey>1234567890123456</whol:AccessKey>
         <whol:ProductID>DIR</whol:ProductID>
         <whol:PlanID>STANDARD</whol:PlanID>
         <whol:Parameters>
            <stan:Param id="Non_Existing_Param">DIR-4220</stan:Param>
         </whol:Parameters>
      </whol:GetRequest>
   </soapenv:Body>
</soapenv:Envelope>
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <env:Fault>
         <faultcode>env:Server</faultcode>
         <faultstring>Invalid parameters: Non_Existing_Param</faultstring>
         <detail>
            <FaultResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
               <TransactionID>SANDBOX</TransactionID>
               <ErrorCode>DIR-4220</ErrorCode>
            </FaultResponse>
         </detail>
      </env:Fault>
   </env:Body>
</env:Envelope>
```

5.2.2 Generating Any Other Error Code

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
```

```
   <soapenv:Body>
      <whol:GetRequest>
         <whol:AccessKey>1234567890123456</whol:AccessKey>
         <whol:ProductID>DIR</whol:ProductID>
         <whol:Parameters>
            <stan:Param id="DirectoryID">DIR-5030</stan:Param>
         </whol:Parameters>
      </whol:GetRequest>
   </soapenv:Body>
</soapenv:Envelope>
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <env:Fault>
         <faultcode>env:Server</faultcode>
         <faultstring>Syndicated Service Error</faultstring>
         <detail>
            <FaultResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
               <TransactionID>SANDBOX</TransactionID>
               <ErrorCode>DIR-5030</ErrorCode>
            </FaultResponse>
         </detail>
      </env:Fault>
   </env:Body>
</env:Envelope>
```

5.3 ProductID ADSL::Create

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
   <soapenv:Body>
      <whol:CreateRequest>
         <whol:AccessKey>1234567890123456</whol:AccessKey>
         <whol:ProductID>ADSL</whol:ProductID>
         <whol:PlanID>ANY-PLAN-ID</whol:PlanID>
         <whol:Parameters>
            <stan:Param id="ServiceID">TEST-123</stan:Param>
            <stan:Param id="Username">anton.kattan@staff.your-dsl.net</stan:Param>
            <stan:Param id="Password">abcdef</stan:Param>
            <stan:Param id="CarrierID">0399999999</stan:Param>
            <stan:Param id="OrderType">NEW</stan:Param>
            <stan:Param id="AnniversaryDay">1</stan:Param>
            <stan:Param id="IPAssignment">STATIC</stan:Param>
            <stan:Param id="LocationReference">VIC</stan:Param>
         </whol:Parameters>
      </whol:CreateRequest>
   </soapenv:Body>
</soapenv:Envelope>
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <CreateResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
```

```
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
         <TransactionID>SANDBOX</TransactionID>
         <ResponseType>ASYNC</ResponseType>
      </CreateResponse>
   </env:Body>
</env:Envelope>
```

5.4 ADSL::Get scope SERVICE

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
   <soapenv:Body>
      <whol:GetRequest>
         <whol:AccessKey>1234567890123456</whol:AccessKey>
         <whol:ProductID>ADSL</whol:ProductID>
         <whol:Scope>SERVICE</whol:Scope>
         <whol:Parameters>
            <stan:Param id="ServiceID">SANDBOX</stan:Param>
         </whol:Parameters>
      </whol:GetRequest>
   </soapenv:Body>
</soapenv:Envelope>
```

SOAP Response

```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <GetResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
         <TransactionID>SANDBOX</TransactionID>
         <ResponseType>SYNC</ResponseType>
         <Parameters>
            <ns2:Param id="ServiceID">SANDBOX-ADSL</ns2:Param>
            <ns2:Param id="Username">akattan@m2.your-dsl.net.au</ns2:Param>
            <ns2:Param id="Password">password</ns2:Param>
            <ns2:Param id="CarrierID">0399998888</ns2:Param>
            <ns2:Param id="ServiceStatus">ACTIVE</ns2:Param>
            <ns2:Param id="ShapeStatus">FALSE</ns2:Param>
            <ns2:Param id="PlanID">SANDBOX-PlanID</ns2:Param>
            <ns2:Param id="AnniversaryDay">1</ns2:Param>
            <ns2:Param id="IPAddress">203.132.224.176</ns2:Param>
            <ns2:Param id="RoutedSubnet">255.255.255.127/28</ns2:Param>
            <ns2:Param id="IPAssignment">STATIC</ns2:Param>
            <ns2:Param id="LocationReference">3000</ns2:Param>
            <ns2:Param id="DirectoryID">SANDBOX-DIR</ns2:Param>
         </Parameters>
      </GetResponse>
   </env:Body>
</env:Envelope>
```

5.5 ProductID OPER::Get Scope USAGE-DAILY

SOAP Request

```
<soapenv:Envelope xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:whol="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:stan="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
   <soapenv:Header/>
   <soapenv:Body>
```

```
      <whol:GetRequest>
         <whol:AccessKey>1234567890123456</whol:AccessKey>
         <whol:ProductID>OPER</whol:ProductID>
         <whol:Scope>USAGE-DAILY</whol:Scope>
         <whol:Parameters>
            <stan:Param id="ProductID">ADSL</stan:Param>
            <stan:Param id="ServiceID">SANDBOX</stan:Param>
            <stan:Param id="Year">2010</stan:Param>
            <stan:Param id="Month">12</stan:Param>
         </whol:Parameters>
      </whol:GetRequest>
   </soapenv:Body>
</soapenv:Envelope>
```


SOAP Response


```
<env:Envelope xmlns:env="http://schemas.xmlsoap.org/soap/envelope/">
   <env:Header/>
   <env:Body>
      <GetResponse
xmlns="https://wsm.webservice.m2.com.au/schemas/WholesaleServiceManagement.xsd"
xmlns:ns2="https://wsm.webservice.m2.com.au/schemas/StandardDataTypes.xsd">
         <TransactionID>SANDBOX</TransactionID>
         <ResponseType>SYNC</ResponseType>
         <Parameters>
            <ns2:Param
id="DailyUsageRecord"><![CDATA[<DailyUsageRecord><ServiceID>SANDBOX</ServiceID><Recor
dDate>20101001</RecordDate><OffPeakExternalDownload>1087438252</OffPeakExternalDownlo
ad><OffPeakExternalUpload>87438153</OffPeakExternalUpload><PeakExternalDownload>28122
187</PeakExternalDownload><PeakExternalUpload>8122187</PeakExternalUpload></DailyUsag
eRecord>]]></ns2:Param>
            <ns2:Param
id="DailyUsageRecord"><![CDATA[<DailyUsageRecord><ServiceID>SANDBOX</ServiceID><Recor
dDate>20101002</RecordDate><OffPeakExternalDownload>2017438312</OffPeakExternalDownlo
ad><OffPeakExternalUpload>37138121</OffPeakExternalUpload><PeakExternalDownload>58113
181</PeakExternalDownload><PeakExternalUpload>923181</PeakExternalUpload></DailyUsage
Record>]]></ns2:Param>
            <ns2:Param
id="DailyUsageRecord"><![CDATA[<DailyUsageRecord><ServiceID>SANDBOX</ServiceID><Recor
dDate>20101003</RecordDate><OffPeakExternalDownload>87438253</OffPeakExternalDownload
><OffPeakExternalUpload>7438153</OffPeakExternalUpload><PeakExternalDownload>5123181<
/PeakExternalDownload><PeakExternalUpload>132187</PeakExternalUpload></DailyUsageReco
rd>]]></ns2:Param>
         </Parameters>
      </GetResponse>
   </env:Body>
</env:Envelope>
```