

TTIC 31230 Fundamentals of Deep Learning

Problems for Graphical Models.

Problem 1. Pseudolikelihood of a one dimensional spin glass. We let \hat{x} be an assignment of a value to every node where the nodes are numbered from 1 to N_{nodes} and for every node i we have $\hat{x}[i] \in \{0, 1\}$. We define the score of \hat{x} by

$$f(\hat{x}) = \sum_{i=1}^{N-1} \mathbf{1}[\hat{x}[i] = \hat{x}[i+1]]$$

The probability distribution over assignments is defined by a softmax. We let $\hat{x}[i := v]$ be the assignment identical to \hat{x} except that node i is assigned the value v . The expression $\hat{x}[i] = v$ is either true or false depending on whether i is assigned value v in \hat{x} . So these are quite different.

$$P_f(\hat{x}) = \text{softmax}_{\hat{x}} f(\hat{x})$$

Pseudolikelihood is defined in terms of the softmax probability P_f as follows.

$$\tilde{P}_f(\hat{x}) = \prod_i P_f(\hat{x}[i] \mid \hat{x} \setminus i)$$

What is the pseudolikelihood of the all ones assignment under the definition of f given above?

Solution: In a graphical model $P_f(\hat{x}[i] \mid \hat{x}/i)$ is determined by the neighbors of i and we can consider only how a value is scored against its neighbors. For \hat{x} equal to all ones we have

$$f(\hat{x}) = N - 1$$

$$f(\hat{x}[i := 0]) = \begin{cases} N - 3 & \text{for } 1 < i < N \\ N - 2 & \text{for } i = 1 \text{ or } i = N \end{cases}$$

For $1 < i < N$ we get

$$\begin{aligned} Q_f(\hat{x}[i = 1] \mid \hat{x}/i) &= \frac{e^{N-1}}{e^{N-1} + e^{N-3}} \\ &= \frac{1}{1 + e^{-2}} \end{aligned}$$

and for $i = 1$ or $i = N$ we get

$$Q_f(\hat{x}[i = 1] \mid \hat{x}/i) = \frac{1}{1 + e^{-1}}$$

This gives

$$\tilde{Q}(\hat{x}) = (1 + e^{-1})^{-2} (1 + e^{-2})^{-(N-2)}$$

Problem 2. Pseudolikelihood for images. Consider a semantic segmentation $\hat{y}[i]$ on pixels i with $\hat{y}[i]$ a semantic class label in $\{C_1, \dots, C_K\}$. We also assume a scoring function s_Φ on semantic segmentations defining

$$P_\Phi(\hat{y}) = \underset{\hat{y}}{\text{softmax}} \ s_\Phi(\hat{y})$$

Pseudolikelihood is defined by

$$\tilde{P}_\Phi(\hat{y}) = \prod_i P_\Phi(\hat{y}[i] \mid \hat{y} \setminus i)$$

where $\hat{y} \setminus i$ assigns a class to every pixel other than i , and $\hat{y}[i := c]$ is the semantic segmentation identical to \hat{y} except that pixel i is labeled with semantic class c . In a typical graphical model for images we have

$$P_\Phi(\hat{y}[i] \mid \hat{y} \setminus i) = P_\Phi(\hat{y}[i] \mid \hat{y}[N(i)])$$

where $\hat{y}[N(i)]$ is \hat{y} restricted to those pixels which are neighbors of pixel i .

(a) show

$$\frac{P_\Phi(\hat{y})}{\sum_c P_\Phi(\hat{y}[i := c])} = \underset{c}{\text{softmax}} \ s_\Phi(\hat{y}[i := c]) \quad \text{evaluated at } c = y[i]$$

Solution:

$$\begin{aligned} \frac{P_\Phi(\hat{y})}{\sum_c P_\Phi(\hat{y}[i := c])} &= \frac{\frac{1}{Z} e^{s_\Phi(\hat{y})}}{\sum_c \frac{1}{Z} e^{s_\Phi(\hat{y}[i := c])}} \\ &= \frac{e^{s_\Phi(\hat{y})}}{\sum_c e^{s_\Phi(\hat{y}[i := c])}} \\ &= \underset{c}{\text{softmax}} \ s_\Phi(\hat{y}[i := c]) \quad \text{evaluated at } c = y[i] \end{aligned}$$

(b) How many scores need to be computed in the worst case for computing $P_\Phi(\hat{y})$. Given the result of part (a), how many for computing $\tilde{P}_\Phi(\hat{y})$?

Solution: K^N for P_Φ and KN for \tilde{P}_Φ .

(c) Consider a distribution on semantic segmentations where for each pixel the class assigned to that pixel is uniquely determined by the classes of its neighbors. Can this distribution be defined by a softmax over scores? Explain your answer.

Solution: No. Since $e^s > 0$ for any finite s , all semantic segmentations must have nonzero probability.

(d) If P_Φ is a distribution defined in some other way such that the class of each pixel is completely determined by the other pixels, given a simple expression for $\tilde{P}_\Phi(\hat{y})$ in the case where \hat{y} has nonzero probability under P_Φ .

Solution: We have $P_\Phi(\hat{y}|\hat{y}\setminus i) = 1$ which implies $\tilde{P}(\hat{y}) = 1$.