

ARMATUURI SPETSIFIKATSIOON																		MARKUS	
ARMATUURI KUUV				D	L	dL	KAAL	PAINUTUSMÕÕDUD [mm]											
TÜÜP	POS	ARV	KLASS	[mm]	[mm]	[mm]	[kg]	a	b	c	d	e	u	v	x	TD			
D	1	12	B500B	12	540		5.8	170	300	120							48		
D	2	36	B500B	12	590		19.0	170	350	120							48		
E	3	50	B500B	12	915		40.6	400	115	400			44	136	289	48			
D	4	30	B500B	12	2865		76.4	110	2700	110							60		
U	5	170	B500B	6	725		27.4	80	150	170							24		
G	6	30	B500B	12	2445		65.2	135	165	1860	165	135	34	34	104	60			
A	7	9	B500B	12	2075		16.6	2075											
A	8	2	B500B	12	7620		13.5	7620											
A	9	4	B500B	12	9650		34.3	9650											
B	10	50	B500B	12	970		43.2	500	500				90			48			
A	11	2	B500B	12	7595		13.5	7595											
A	12	2	B500B	12	7560		13.4	7560											
A	13	6	B500B	12	6730		35.9	6730											
A	15	8	B500B	12	11645		82.8	11645											
A	16	6	B500B	12	3135		16.7	3135											
A	17	10	B500B	12	2730		24.2	2730											
A	18	4	B500B	12	2720		9.7	2720											
A	19	6	B500B	12	6785		36.2	6785											
A	20	2	B500B	12	7600		13.5	7600											
B	21	50	B500B	12	1205		53.5	160	1070				90			48			
D	24	12	B500B	12	640		6.9	170	400	120						48			
A	25	100	B500B	12	400		35.5	400											
B	64	40	B500B	12	1105		39.3	500	635				90			48			
D	66	20	B500B	12	390		7.0	170	150	120						48			
U	72	15	B500B	6	925		3.1	80	170	250						24			
U	81	3	B500B	6	1325		0.9	80	170	450						24			
U	82	12	B500B	6	1225		3.3	80	170	400						24			
A	83	10	B500B	12	635		5.6	635											
KOKKU:																742.9	kg		

1.korruse vahelae armeering
1:50

