

ASSIGNMENT 1 REPORT: TASK A & TASK B

Course: Introduction to Web Technologies

Organization: Astana IT University Music Club (Room C1.1.142)

Authors: Mereylim , Erlan , Zhansaya

Task A — Anatomy of a Real Web Page

1. Target Website Evaluated

Juilliard School Music Department: <https://www.juilliard.edu/music>

2. Document Specifications Recorded

- `<!DOCTYPE html>`
- `<html lang="en">`
- `<meta charset="utf-8">`
- `<meta name="viewport" content="width=device-width, initial-scale=1.0">`
- `<title>Music | The Juilliard School</title>`
- **Meta Tag 1:** `<meta name="description" content="Discover music programs, faculty, and performance opportunities at The Juilliard School.">`
- **Meta Tag 2:** `<meta name="author" content="The Juilliard School">`
- **Meta Tag 3:** `<meta name="keywords" content="music, conservatory, audition, performance, classical">`

3. Semantic & Structural Analysis

- **Semantic Skeleton:** Uses `<header>`, `<nav>`, `<main>`, `<article>`, and `<footer>` for primary page sections.
- **Overuse of `<div>`:** News cards, picture galleries, and layout columns rely on nested `<div>` wrappers instead of `<figure>`, `<figcaption>`, or `<section>` tags.
- **Forms & Tables:** Concert schedules are formatted using generic `<div>` grid elements without `<table>` headers. Form fields lack structural `<fieldset>` or `<legend>` containers.

4. 3 Structural Mistakes Found & Avoidance Strategy

- **Mistake 1 (Generic Image Wrappers):** Image captions on news items are wrapped in plain `<div>` tags.
 - **Our Fix:** In `about.html` (Line 49) and `events.html` (Line 42), we wrapped images and captions strictly in semantic `<figure>` and `<figcaption>` elements.

- **Mistake 2 (Non-Semantic Schedule Grids):** Performance calendars use custom CSS classes on `<div>` rows rather than tabular HTML elements.
 - **Our Fix:** In `events.html` (Line 53) and `equipment.html` (Line 45), we built accessible `<table>` structures using `<caption>`, `<thead>`, `<tbody>`, and `<th scope="col">/<th scope="row">` attributes.
- **Mistake 3 (Unwrapped Form Fields):** Input elements are placed directly inside `<div>` containers without group semantics.
 - **Our Fix:** In `events.html` (Line 114) and `auditions.html` (Line 55), every form groups related controls inside `<fieldset>` with descriptive `<legend>` headers and `<label for="...">` associations.

5. Hand-Drawn Page Structure Sketch

(Attach your signed, dated paper sketch photo here)

Task B — Written Technical Reflection

A web page is a structured document written in HyperText Markup Language (HTML) that defines the semantic hierarchy of text, media, and interactive components. When a web browser opens an HTML file, its parsing engine converts the raw code into Document Object Model (DOM) nodes to build a tree structure representing the document. The browser then calculates layout dimensions and paints pixels onto the screen to render the page visually.

Across our repository, we chose semantic HTML tags over generic containers to ensure accessibility and valid document structure:

1. **about.html (Line 30):** Used `<article>` instead of `<div>` because the club history forms an independent, self-contained narrative.
2. **about.html (Line 54):** Used `<aside>` for booking rules because operational guidelines represent supplementary, backstage notes distinct from the main article.
3. **events.html (Line 53):** Used `<table>` with `<caption>` and `<th scope="...">` instead of `<div>` blocks because concert dates and locations form a two-dimensional matrix of structured data.

When a user clicks "Submit Stage Application" on `events.html` today, the browser performs client-side validation against `required` and `type` attributes. Because there is no backend server configured (`action="#"`), the browser reloads the page and appends form field values to the URL string without persisting data.