Learning Hyperplane Branching for Integer Optimization

Nicholas Jones Bala Krishnamoorthy

Washington State University

Integer Optimization

* $\min \{ \bar{c}^T \bar{x} \mid A\bar{x} \leq \bar{b}, \bar{x} \in \mathbb{Z}^n \}$

Integer Optimization

* $\min \{ \bar{c}^T \bar{x} \mid A\bar{x} \leq \bar{b}, \underline{\bar{x} \in \mathbb{Z}^n} \}$
  → makes it hard!
* NP-hard

Integer Optimization

* $\min \{ \bar{c}^T \bar{x} \mid A\bar{x} \leq \bar{b}, \underline{\bar{x} \in \mathbb{Z}^n} \}$
  → makes it hard!
* NP-hard
* use branch-and-bound, cutting planes
  - solve linear relaxation ($\bar{x} \in \mathbb{R}^n$)
  - e.g., $x_i = 3.45$ < $x_i \leq 3$ / $x_i \geq 4$

Integer Optimization

* $\min \{ \bar{c}^T \bar{x} \mid A\bar{x} \leq \bar{b}, \underline{\bar{x} \in \mathbb{Z}^n} \}$
  → makes it hard!
* NP-hard
* use branch-and-bound, cutting planes
  - solve linear relaxation ($\bar{x} \in \mathbb{R}^n$)
  - e.g., $x_i = 3.45$ < $x_i \leq 3$ / $x_i \geq 4$
* which x_i to branch on? → hard to decide!

Integer Optimization

* $\min \{ \bar{c}^T \bar{x} \mid A\bar{x} \leq \bar{b}, \underline{\bar{x} \in \mathbb{Z}^n} \}$
  → makes it hard!
* NP-hard
* use branch-and-bound, cutting planes
  - solve linear relaxation ($\bar{x} \in \mathbb{R}^n$)
  - e.g., $x_i = 3.45$ → $x_i \leq 3$ or $x_i \geq 4$
* which x_i to branch on? → hard to decide!

✓ Dilkina et al., (2016,2017) : learning to branch

HYPERPLANE BRANCHING


* e.g., $1.28 \leq \vec{p}^T \vec{x} \leq 4.56 \Rightarrow \vec{p}^T \vec{x} = k, \; k = 2, 3, 4$

HYPERPLANE BRANCHING

* e.g., $1.28 \leq \bar{p}^T \bar{x} \leq 4.56 \Rightarrow \bar{p}^T \bar{x} = k, \; k = 2, 3, 4$
* Lenstra (1982): IP in poly time in fixed dim.
  Kannan & Lovász (1988): "flatness" results

HYPERPLANE BRANCHING

* e.g., $1.28 \le \bar{p}^T\bar{x} \le 4.56 \Rightarrow \bar{p}^T\bar{x} = k,\ k = 2,3,4$
* Lenstra (1982): IP in poly time in fixed dim.
  Kannan & Lovász (1988): "flatness" results
* K. & Pataki (2009): decomposable knapsack problem (DKP)




$$(P)\left\{\beta' \le \bar{a}^T\bar{x} \le \beta \atop 0 \le \bar{x} \le \bar{u}\right\},\quad P \cap \mathbb{Z}^n = \emptyset$$

$$\bar{a} = \bar{p}M + \bar{r} \quad (M: \text{large})$$

HYPERPLANE BRANCHING

* e.g., $1.28 \le \bar{p}^T\bar{x} \le 4.56 \Rightarrow \bar{p}^T\bar{x} = k,\ k = 2,3,4$
* Lenstra (1982): IP in poly time in fixed dim.
  Kannan & Lovász (1988): "flatness" results
* K. & Pataki (2009): decomposable knapsack problem (DKP)



$$(P)\ \{\beta' \le \bar{a}^T\bar{x} \le \beta,\ 0 \le \bar{x} \le \bar{u}\},\quad P \cap \mathbb{Z}^n = \emptyset$$

$$\bar{a} = \bar{p}M + \bar{r}\ \ (M: \text{large})$$

✓ branching on $\bar{p}^T\bar{x}$ kills the problem!

LEARNING HYPERPLANES?

? Can we learn to predict $\bar{p}$ from $\bar{\alpha}, \beta, \beta$?
– DKP learner?

LEARNING HYPERPLANES?

? Can we learn to predict $\bar{p}$ from $\bar{a}, \beta, \beta$?
- DKP learner?

? Generalize to non-DKPs?
- cascade knapsack problems?

$$\bar{a} = \bar{p}_1 M_1 + \bar{p}_2 M_2 + \cdots + \bar{p}_k M_k + \bar{r}$$

LEARNING HYPERPLANES?

? Can we learn to predict $\bar{p}$ from $\bar{a}, \beta, \beta$?
- DKP learner?

? Generalize to non-DKPs?
- cascade knapsack problems?

$$\bar{a} = \bar{p}_1 M_1 + \bar{p}_2 M_2 + \cdots + \bar{p}_k M_k + \bar{r}$$

? DKP learner on general IPs ($A\bar{x} \leq \bar{b}$)?

RESULTS

✓ DKP learner: recovers $\bar{b}$ from $\bar{a}, \beta', \beta$

RESULTS

- ✓ DKP learner: recovers $\bar{F}$ from $\bar{\alpha}, \beta', \beta$
- ✓ Min. certificate rank: min r s.t. some $F_1, \ldots, F_r$ together certify integer infeasibility
  - every F_i admits a DKP representation

RESULTS

- ✓ DKP learner: recovers $\bar{p}$ from $\bar{a}, \beta', \beta$
- ✓ Min. certificate rank: min r s.t. some $F_1, \ldots, F_r$ together certify integer infeasibility
  - every F_i admits a DKP representation
- ✓ CKP with $\bar{a} = \bar{p}_1 M_1 + \cdots + \bar{p}_k M_k + \bar{r}$
  - study DKP learner recovering $F_1, \ldots, F_k$

RESULTS


- ✓ DKP learner: recovers $\bar{p}$ from $\bar{a}, \beta', \beta$
- ✓ Min. certificate rank: min r s.t. some $\bar{F}_1, \ldots, \bar{F}_r$ together certify integer infeasibility
  - every $\bar{F}_i$ admits a DKP representation
- ✓ CKP with $\bar{a} = \bar{p}_1 M_1 + \cdots + \bar{p}_k M_k + \bar{r}$
  - study DKP learner recovering $\bar{F}_1, \ldots, \bar{F}_k$
- ✓ Generalize to $A\bar{x} \leq \bar{b}$
  - helps when DKP directions present
  - fails in general instances

DKP LEARNER

* NN for $(\bar{\alpha}, \bar{\beta}', \beta)$ $\xrightarrow{\text{predict}}$ $\bar{P}$ s.t. $\bar{\alpha} = \bar{P}M + \bar{r}$

DKP LEARNER

* NN for $(\bar{a}, \beta', \beta)$ predict $\bar{p}$ s.t. $\bar{a} = \bar{p}M + \bar{r}$




$n \rightarrow$


training set = 10^6 instances

DKP LEARNER

* NN for $(\bar{a}, \bar{\beta}', \beta)$ predict $\bar{p}$ s.t. $\bar{a} = \bar{p}M + \bar{r}$



$n \rightarrow$



training set = 10^6 instances

$n = 80$

DKP CERTIFICATES

Lemma Let $S \subset \mathbb{R}^n$ and $\bar{p} \in \mathbb{Z}^n \setminus \{\bar{0}\}$ s.t. $\bar{p}^T \bar{x} \notin \mathbb{Z}$ for some $\bar{x} \in S$. Then $\exists\ \bar{p}, M, \bar{r}, \beta', \beta$ s.t. DKP w/ $\bar{a} = \bar{p}M + \bar{r}$ has $S \cap \{\beta' \leq \bar{a}\bar{x} \leq \beta\} \neq \emptyset$.

DKP CERTIFICATES

Lemma Let $S \subset \mathbb{R}^n$ and $\bar{p} \in \mathbb{Z}^n \setminus \{\bar{0}\}$ s.t. $\bar{p}^T \bar{x} \notin \mathbb{Z}$ for some $\bar{x} \in S$. Then $\exists\ \bar{p}, M, \bar{r}, \beta', \beta$ s.t. DKP w/ $\bar{a} = \bar{p}M + \bar{r}$ has $S \cap \{\beta' \le \bar{a}\bar{x} \le \beta\} \neq \emptyset$.

✓ DKP-representable

DKP CERTIFICATES

Lemma Let $S \subset \mathbb{R}^n$ and $\bar{p} \in \mathbb{Z}^n \setminus \{\bar{0}\}$ s.t. $\bar{p}^T \bar{x} \notin \mathbb{Z}$ for some $\bar{x} \in S$. Then $\exists\ \bar{p}, M, \bar{r}, \beta', \beta$ s.t. DKP w/ $\bar{a} = \bar{p}M + \bar{r}$ has $S \cap \{\beta' \leq \bar{a}\bar{x} \leq \beta\} \neq \emptyset$.

✓ DKP-representable

Theorem Let $\mathcal{F} \subset \mathbb{R}^n$ be bounded, $\mathcal{F} \neq \emptyset$ but $\mathcal{F} \cap \mathbb{Z}^n = \emptyset$. Let $P = [\bar{p}_1^T \cdots \bar{p}_r^T]$ s.t. $P(\mathcal{F}) \cap \mathbb{Z}^r = \emptyset$ and r is minimal. Then each $\bar{p}_i$ is DKP-representable

Cascade Knapsacks

* Generalizes DKPs

Cascade Knapsacks

* Generalizes DKPs
* $\{\beta' \le \bar{a}^T \bar{x} \le \beta\} \cap \mathbb{Z}^n = \phi$ with
  $\bar{a} = \bar{p}_1 M_1 + \bar{p}_2 M_2 + \cdots + \bar{p}_k M_k + \bar{r}$

Cascade Knapsacks


* Generalizes DKPs
* $\{\beta' \le \bar{a}^T \bar{x} \le \beta\} \cap \mathbb{Z}^n = \emptyset$ with
  $\bar{a} = \bar{p}_1 M_1 + \bar{p}_2 M_2 + \cdots + \bar{p}_k M_k + \bar{r}$
  - $\bar{p}_i^T \bar{x} = k_i$ for one $k_i \in \mathbb{Z}$ for $i = 1, \ldots, k-1$
  - then $\bar{p}_k^T \bar{x}$ proves infeasibility

Cascade Knapsacks


* Generalizes DKPs
* $\{\beta' \le \bar{a}^T \bar{x} \le \beta\} \cap \mathbb{Z}^n = \emptyset$ with
  $\bar{a} = \bar{p}_1 M_1 + \bar{p}_2 M_2 + \cdots + \bar{p}_k M_k + \bar{r}$
  - $\bar{p}_i^T \bar{x} = k_i$ for one $k_i \in \mathbb{Z}$ for $i = 1, \ldots, k-1$
  - then $\bar{p}_k^T \bar{x}$ proves infeasibility

? Can DKP learner predict $\bar{p}_1, \ldots, \bar{p}_{k-1}$ and $\bar{p}_k$?

CKPs with DKP Learner





CKPs with DKP Learner



* Can predict $\bar{p}_2$ well when exact $\bar{p}_1$ given

CKPs WITH DKP LEARNER





* Can predict $\bar{p}_2$ well when exact $\bar{p}_1$ given

* struggles to predict $\bar{p}_2$ when predicted $\bar{p}_1$ is branched on

Marketshare Problems

* $\{\bar{x} \mid A\bar{x} = \bar{b}, 0 \leq \bar{x} \leq \bar{1}\} \cap \mathbb{Z}^n = \phi$, A: m rows

MARKETSHARE PROBLEMS


* $\{\bar{x} \mid A\bar{x} = \bar{b}, 0 \le \bar{x} \le \bar{1}\} \cap \mathbb{Z}^n = \phi$, A: m rows
  - "hide" a DKP direction in $A\bar{x} = \bar{b}$

MARKETSHARE PROBLEMS

* $\{\bar{x} \mid A\bar{x} = \bar{b}, 0 \le \bar{x} \le \bar{1}\} \cap \mathbb{Z}^n = \phi$, A: m rows
  - "hide" a DKP direction in $A\bar{x} = \bar{b}$
  - integer combinations of rows of $A\bar{x} = \bar{b}$ as inputs to DKP learner, branch on $\bar{p}^T\bar{x}$

MARKETSHARE PROBLEMS


* $\{\bar{x} \mid A\bar{x} = \bar{b}, 0 \le \bar{x} \le \bar{1}\} \cap \mathbb{Z}^n = \phi$, A: m rows
  - "hide" a DKP direction in $A\bar{x} = \bar{b}$
  - integer combinations of rows of $A\bar{x} = \bar{b}$ as inputs to DKP learner, branch on $\bar{p}^T\bar{x}$




n=40

Marketshare Problems

* $\{\bar{x} \mid A\bar{x} = \bar{b}, 0 \le \bar{x} \le \bar{1}\} \cap \mathbb{Z}^n = \phi$, A: m rows
  - "hide" a DKP direction in $A\bar{x} = \bar{b}$
  - integer combinations of rows of $A\bar{x} = \bar{b}$ as inputs to DKP learner, branch on $\bar{p}^T\bar{x}$



n=40



v/s Gurobi

Points to Note

- ✗ DKP learner fails on general marketshare probs

Points to Note

- ✗ DKP learner fails on general marketshare probs
- ? "better" DKP learner?

Points to Note

- ✗ DKP learner fails on general marketshare probs
- ? "better" DKP learner?
- ? CKP or marketshare learner?

Points to Note

- ✗ DKP learner fails on general marketshare probs
- ? "better" DKP learner?
- ? CKP or marketshare learner?
- ? Methods to discover representable directions?

Points to Note

- ✗ DKP learner fails on general marketshare probs
- ? "better" DKP learner?
- ? CKP or marketshare learner?
- ? Methods to discover representable directions?

Thank You!