

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 1\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 14

#### Section 1 : MCQ

1. What is the value of the following expression?

`float(22//3+3/3)`

**Answer**

8.0

**Status : Correct**

**Marks : 1/1**

2. Which is the correct operator for power(xy)?

**Answer**

`x**y`

**Status : Correct**

**Marks : 1/1**

3. Which of the following represents the bitwise XOR operator?

**Answer**

`^`

**Status : Correct**

**Marks : 1/1**

4. What will be the output of the following code?

```
x = int(34.56 - 2 * 2)
print(x)
```

**Answer**

30

**Status : Correct**

**Marks : 1/1**

5. What is the output of the following program?

```
print((1, 2) + (3, 4))
```

**Answer**

(1, 2, 3, 4)

**Status : Correct**

**Marks : 1/1**

6. Which of the following expressions results in an error?

**Answer**

```
int('10.8')&nbsp;
```

**Status : Correct**

**Marks : 1/1**

7. Which of the following operators has its associativity from right to left?

**Answer**

`**`

**Status :** Correct

**Marks :** 1/1

8. What is the output of the below expression?

```
print(3*1**3)
```

**Answer**

3

**Status :** Correct

**Marks :** 1/1

9. What is the value of x in the following program?

```
x = int(43.55+2/2)
print(x)
```

**Answer**

44

**Status :** Correct

**Marks :** 1/1

10. Which of the following is an example of the type casting?

**Answer**

All of the above

**Status :** Correct

**Marks :** 1/1

11. What will be the output for the below code?

```
x=15
y=12
print(x&y)
```

**Answer**

12

**Status :** Correct

**Marks :** 1/1

12. Which of the following can convert the string to a float number?

**Answer**

`float(str)`

**Status :** Correct

**Marks :** 1/1

13. What will the following code output?

```
z = 3 + 4j
print(abs(z))
```

**Answer**

5.0

**Status :** Correct

**Marks :** 1/1

14. What is the output of the following number conversion?

```
z = complex(1.25)
print(z)
```

**Answer**

(1.25+0j)

**Status :** Correct

**Marks :** 1/1

15. The value of the expressions  $4/(3*(2-1))$  and  $4/3*(2-1)$  is the same. True or False?

**Answer**

False

**Status :** Wrong

**Marks :** 0/1

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 1\_COD

Attempt : 1  
Total Mark : 5  
Marks Obtained : 5

### Section 1 : Coding

#### 1. Problem Statement

A company has hired two employees, Alice and Bob. The company wants to swap the salaries of both employees. Alice's salary is an integer value and Bob's salary is a floating-point value.

Write a program to swap their salaries and print the new salary of each employee.

#### ***Input Format***

The first line of input consists of an integer N, representing Alice's salary.

The second line consists of a float value F, representing Bob's salary.

#### ***Output Format***

The first line of output displays "Initial salaries:"

The second line displays "Alice's salary = N", where N is Alice's salary.

The third line of output displays "Bob's salary = F", where F is Bob's salary.

After a new line space, the following line displays "New salaries after swapping:"

The next line displays "Alice's salary = X", where X is the swapped salary.

The last line displays "Bob's salary = Y", where Y is the swapped salary.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 10000

15400.55

Output: Initial salaries:

Alice's salary = 10000

Bob's salary = 15400.55

New salaries after swapping:

Alice's salary = 15400.55

Bob's salary = 10000

### **Answer**

```
n=int(input())
f=float(input())
print("Initial salaries:")
print("Alice's salary =",n)
print("Bob's salary =",f,"\n")

temp=n
n=f
f=temp
print("New salaries after swapping:")
print("Alice's salary =",n)
print("Bob's salary =",f)
```

**Status :** Correct

**Marks :** 1/1

## 2. Problem Statement

Bob, the owner of a popular bakery, wants to create a special offer code for his customers. To generate the code, he plans to combine the day of the month with the number of items left in stock.

Help Bob to encode these two values into a unique offer code.

Note: Use the bitwise operator to calculate the offer code.

### Example

Input:

15

9

Output:

Offer code: 6

Explanation:

Given the day of the month 15th day (binary 1111) and there are 9 items left (binary 1001), the offer code is calculated as 0110 which is 6.

### ***Input Format***

The first line of input consists of an integer D, representing the day of the month.

The second line consists of an integer S, representing the number of items left in stock.

### ***Output Format***

The output displays "Offer code: " followed by an integer representing the encoded offer code.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 15

9

Output: Offer code: 6

### **Answer**

```
d=int(input())
s=int(input())
m=d^s
print("Offer code:",m)
```

**Status :** Correct

**Marks :** 1/1

## **3. Problem Statement**

In a family, two children receive allowances based on the gardening tasks they complete. The older child receives an allowance rate of Rs.5 for each task, with a base allowance of Rs.50. The younger child receives an allowance rate of Rs.3 for each task, with a base allowance of Rs.30.

Your task is to calculate and display the allowances for the older and younger children based on the number of gardening tasks they complete, along with the total allowance for both children combined.

### **Input Format**

The first line of input consists of an integer  $n$ , representing the number of chores completed by the older child.

The second line consists of an integer  $m$ , representing the number of chores completed by the youngest child.

### **Output Format**

The first line of output displays "Older child allowance: Rs." followed by an integer representing the allowance calculated for the older sibling.

The second line displays "Younger child allowance: Rs." followed by an integer



representing the allowance calculated for the youngest sibling.

The third line displays "Total allowance: Rs." followed by an integer representing the sum of both siblings' allowances.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 10

5

Output: Older child allowance: Rs.100

Younger child allowance: Rs.45

Total allowance: Rs.145

### **Answer**

```
n=int(input())
m=int(input())
oc=5
yc=3
y=(oc*n)+50
m=(yc*m)+30
print("Older child allowance: Rs.",y)
print("Younger child allowance:","Rs.",m)
print("Total allowance:","Rs.",y+m)
```

**Status :** Correct

**Marks :** 1/1

## **4. Problem Statement**

A science experiment produces a decimal value as the result. However, the scientist needs to convert this value into an integer so that it can be used in further calculations.

Write a Python program that takes a floating-point number as input and converts it into an integer.

### **Input Format**

The input consists of a floating point number, F.

**Output Format**

The output prints "The integer value of F is: {result}", followed by the integer number equivalent to the floating point number.

Refer to the sample output for the formatting specifications.

**Sample Test Case**

Input: 10.36

Output: The integer value of 10.36 is: 10

**Answer**

```
f=float(input())  
n=int(f)  
print("The integer value of ",f, "is:",n)
```

**Status :** Correct

**Marks :** 1/1

## 5. Problem Statement

Quentin, a mathematics enthusiast, is exploring the properties of numbers. He believes that for any set of four consecutive integers, calculating the average of their fourth powers and then subtracting the product of the first and last numbers yields a constant value.

To validate his hypothesis, check if the result is indeed constant and display.

Example:

Input:

5

Output:

Constant value: 2064.5

Explanation:

Find the Average:

Average:  $(625 + 1296 + 2401 + 4096)/4 = 2104.5$

Now, we calculate the product of a and (a + 3):

Product =  $5 \times (5 + 3) = 5 \times 8 = 40$

Final result:  $2104.5 - 40 = 2064.5$

### ***Input Format***

The input consists of an integer a, representing the first of four consecutive integers.

### ***Output Format***

The output displays "Constant value: " followed by the computed result based on Quentin's formula.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

Output: Constant value: 2064.5

### ***Answer***

```
n=int(input())
a1=n**4
a2=(n+1)**4
a3=(n+2)**4
a4=(n+3)**4
average=(a1+a2+a3+a4)/4
product=n*(n+3)
m=average-product
print("Constant value:",m)
```

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 1\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

### Section 1 : Coding

#### 1. Problem Statement

Mandy is working on a mathematical research project involving complex numbers. For her calculations, she often needs to swap the real and imaginary parts of two complex numbers.

Mandy needs a Python program that takes two complex numbers as input and swaps their real and imaginary values.

#### ***Input Format***

The first line of input consists of a complex number in the format  $a+bj$ , representing the first complex number.

The second line consists of a complex number in the format  $a+bj$ , representing the second complex number.

### **Output Format**

The first line of output displays "New first complex number: " followed by the swapped complex number.

The second line of output displays "New second complex number: " followed by the swapped complex number.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 10+8j  
7-9j

Output: New first complex number: (8+10j)  
New second complex number: (-9+7j)

### **Answer**

```
m=complex(input())
n=complex(input())
newm=complex(m.imag,m.real)
newn=complex(n.imag,n.real)
print("New first complex number:",newm)
print("new second complex number:",newn)
```

**Status :** Correct

**Marks :** 10/10

## **2. Problem Statement**

John is developing a financial application to help users manage their investment portfolios. As part of the application, he needs to write a program that receives the portfolio's main value and the values of two specific investments as inputs. The program should then display these values in reverse order for clear visualization.

Help John achieve this functionality by writing the required program.

### **Input Format**

The first line of input consists of a float, representing the first investment value.

The second line of input consists of a float, representing the second investment value.

The third line of input consists of an integer, representing the portfolio ID.

### **Output Format**

The first line of output prints "The values in the reverse order:".

The second line prints the integer, representing the portfolio ID.

The third line prints the second float, representing the second investment value.

The fourth line prints the first float, representing the first investment value.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 35.29

9374.11

48

Output: The values in the reverse order:

48

9374.11

35.29

### **Answer**

```
first=float(input())
second=float(input())
portid=int(input())
print("The values in the reverse order:")
print(portid)
print(second)
print(first)
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Emily is organizing a taco party and needs to determine the total number of tacos required and the total cost. Each attendee at the party will consume 2 tacos. To ensure there are enough tacos:

If there are 10 or more attendees, Emily will need to provide an additional 5 tacos. If there are fewer than 10 attendees, Emily must ensure a minimum of 20 tacos are provided.

The cost of each taco is \$25. Write a program that calculates both the total number of tacos required and the total cost based on the number of attendees.

#### ***Input Format***

The input consists of an integer  $n$ , representing the number of attendees.

#### ***Output Format***

The first line prints "Number of tacos needed: " followed by an integer representing the number of tacos needed for  $n$  attendees.

The second line prints "Total cost: " followed by an integer representing the total cost.

Refer to the sample output for the formatting specifications.

#### ***Sample Test Case***

Input: 10

Output: Number of tacos needed: 25

Total cost: 625

#### ***Answer***

```
n=int(input())
tacos=n*2
if n>=10:
    tacos+=5
else:
    tacos=max(tacos,20)
```

```
costper=25
total=tacos*costper
print("Number of tacos needed:",tacos)
print("Total cost:",total)
```

**Status :** Correct

**Marks : 10/10**

#### 4. Problem Statement

Olivia is creating a wellness dashboard for her new fitness app, FitTrack. She needs a program that can capture and display key details about a user's workout. The program should read the user's full name, the total steps they ran, the energy they expended in kilojoules, and the duration of their workout in hours. After collecting this information, the program will generate a detailed summary of the user's fitness activity.

Your task is to guide Olivia through the program.

##### ***Input Format***

The first line of input consists of a string, representing the user's name.

The second line consists of an integer, representing the total steps taken.

The third line consists of a float value, representing the calories burned.

The fourth line consists of a float value, representing the workout duration in hours.

##### ***Output Format***

The first line of output prints "User Name: " followed by the user's name.

The second line prints "Total Steps: " followed by the total steps.

The third line prints "Calories Burned: " followed by the calories burned, rounded off to one decimal place.

The fourth line prints "Workout Duration: X hours" where X is the workout duration, rounded off to one decimal place.



Refer to the sample output for formatting specifications.

**Sample Test Case**

Input: Alex

10000

350.5

1.5

Output: User Name: Alex

Total Steps: 10000

Calories Burned: 350.5

Workout Duration: 1.5 hours

**Answer**

```
user_name=input().strip()
total_steps=int(input().strip())
calories_burned=float(input().strip())
workout_duration=float(input().strip())
print(f"User Name: {user_name}")
print(f"Total Steps: {total_steps}")
print(f"Calories Burned: {calories_burned:.1f}")
print(f"Workout Duration: {workout_duration:.1f} hours")
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 1\_PAH

Attempt : 1  
Total Mark : 6  
Marks Obtained : 5.35

### Section 1 : Coding

#### 1. Problem Statement

Ella, an avid TV show enthusiast, is planning a binge-watching marathon for a new series. She has a specific routine: after watching a set number of episodes, she takes a short break.

She is provided with the following information:

Each episode of the series has a fixed duration of 45 minutes. After a certain number of episodes, there is a break of 15 minutes.

Ella wants to know the total time she will need to watch the entire series, including the breaks. Your task is to help Ella by calculating the total viewing time.

#### **Input Format**

The first line of input consists of an integer E, representing the total number of episodes in the series.

The second line consists of an integer B, representing the number of episodes watched before taking a break.

### **Output Format**

The output prints an integer representing the total viewing time required to watch the entire series, including the breaks.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

2

Output: 255 minutes

### **Answer**

```
E = int(input())
B = int(input())
c = (E*45) + (int(E/B)*15)
print(c,"minutes")
```

**Status :** Partially correct

**Marks :** 0.35/1

## **2. Problem Statement**

Shawn, a passionate baker, is planning to bake cookies for a large party. His original recipe makes 15 cookies, with the following ingredient quantities: 2.5 cups of flour, 1 cup of sugar, and 0.5 cups of butter.

Write a program to calculate the amounts of flour, sugar, and butter needed for a different number of cookies. Provide the ingredient quantities for a specified number of cookies, maintaining the original proportions of the recipe.

### **Input Format**

The input consists of an integer  $n$ , representing the number of cookies.

### **Output Format**

The first line prints "Flour: X cups" where X represents the amount of flour required for  $n$  cookies, as a double value rounded to two decimal places.

The second line prints "Sugar: Y cups" where Y represents the amount of Sugar required for  $n$ , as a double value rounded to two decimal places.

The third line prints "Butter: Z cups" where Z represents the amount of flour required for  $n$ , as a double value rounded to two decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 15

Output: Flour: 2.50 cups

Sugar: 1.00 cups

Butter: 0.50 cups

### **Answer**

```
n=int(input())
flour=(2.5/15)
m="%.2f"%(n*flour)
print("Flour:",m,"cups")
sugar=(1/15)
t="%.2f"%(n*sugar)
print("Sugar:",t,"cups")
butter=(0.5/15)
s="%.2f"%(n*butter)
print("Butter:",s,"cups")
```

**Status :** Correct

**Marks :** 1/1

## **3. Problem Statement**

Mandy is debating with her friend Rachel about an interesting

mathematical claim. Rachel asserts that for any positive integer  $n$ , the ratio of the sum of  $n$  and its triple to the integer itself is always 4. Mandy, intrigued by this statement, decides to validate it using logical operators and basic arithmetic.

She wants to confirm if the statement holds true for any positive integer  $n$ .

### ***Input Format***

The input consists of a positive integer  $n$ , representing the integer to be tested.

### ***Output Format***

The first line of output displays "Sum:" followed by an integer representing the calculated sum.

The second line displays "Rachel's statement is: " followed by a Boolean value indicating whether Rachel's statement is correct.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 12

Output: Sum: 48

Rachel's statement is: True

### ***Answer***

```
n=int(input())
m=(n*3)+n
print("Sum:",m)
if m%4==0:
    print("Rachel's statement is: True")
```

**Status :** Correct

**Marks :** 1/1

## **4. Problem Statement**

A smart home system tracks the temperature and humidity of each room. Create a program that takes the room name (string), temperature (float), and humidity (float).

Display the room's climate details.

### ***Input Format***

The first line of input consists of a string, representing the room name.

The second line consists of a float value, representing the temperature.

The third line consists of a float value, representing the humidity.

### ***Output Format***

The first line of output prints "Room: " followed by the room name (string).

The second line prints "Temperature: " followed by the temperature (float) formatted to two decimal places.

The third line prints "Humidity: " followed by the humidity (float) formatted to two decimal places and a percentage sign (%).

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: Living Room

23.45

45.78

Output: Room: Living Room

Temperature: 23.45

Humidity: 45.78%

### ***Answer***

```
a=input()
```

```
b=input()
```

```
c=input()
```

```
d="Room: %s\nTemperature: %s\nHumidity: %s" % (a,b,c)
```

```
print(d+"%")
```

Status : Correct

Marks : 1/1

## 5. Problem Statement

Liam works at a car dealership and is responsible for recording the details of cars that arrive at the showroom. To make his job easier, he wants a program that can take the car's make, model, and price, and display the information in a formatted summary.

Assist him in the program.

### **Input Format**

The first line of input contains a string, representing the car make.

The second line contains a string, representing the car model.

The third line contains a float value, representing the car price.

### **Output Format**

The first line of output prints "Car Make: ", followed by the car make.

The second line prints "Car Model: ", followed by the car model.

The third line prints "Price: ", followed by the car price, formatted to two decimal places.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: Toyota

Camry

23450.75

Output: Car Make: Toyota

Car Model: Camry

Price: Rs.23450.75

### **Answer**

```
a=input()
b=input()
c=input()
print("Car Make: %s\nCar Model: %s\nPrice: Rs.%s" %(a,b,c))
```

**Status :** Correct

**Marks :** 1/1

## 6. Problem Statement

Oliver is planning a movie night with his friends and wants to download a high-definition movie. He knows the file size of the movie in megabytes (MB) and his internet speed in megabits per second (Mbps). To ensure the movie is ready in time, Oliver needs to calculate the download time.

Your task is to write a program that calculates the download time and displays it in hours, minutes, and seconds.

Example

Input:

MB = 800

mbps = 40

Output:

Download Time: 0 hours, 2 minutes, and 40 seconds

Explanation:

Convert the file size to bits ( $800 \text{ MB} \times 8 \text{ bits/byte} = 6400 \text{ megabits}$ ) and divide it by the download speed ( $6400 \text{ Mbps} / 40 \text{ Mbps} = 160 \text{ seconds}$ ). Now, convert the download time in seconds to hours, minutes, and seconds: 160 seconds is equal to 2 minutes and 40 seconds. So, the download time is 0 hours, 2 minutes and 40 seconds.

**Input Format**

The first line of input consists of an integer N, representing the file size in megabytes (MB).



The second line consists of an integer S, representing the network speed in megabits per second(mbps).

### **Output Format**

The output prints "Download Time: X hours, Y minutes, and Z seconds", where X, Y, and Z are integers representing the hours, minutes, and seconds respectively.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 180

3

Output: Download Time: 0 hours, 8 minutes, and 0 seconds

### **Answer**

```
a=int(input())
b=int(input())
s=(a*8)/b
m=int(s/60)
h=int(m/60)
m=m%60
s=s%60
print("Download Time: %d hours, %d minutes, and %d seconds" % (h,m,s))
```

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 2\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 8

#### Section 1 : MCQ

1. What will be the output for the following code snippet?

```
i = 0  
for i in range(10):  
    break  
print(i)
```

**Answer**

9

**Status : Wrong**

**Marks : 0/1**

2. What is the output of the following?

```
for i in range(10):
```

```
if i == 5:
    break
else:
    print(i, end=' ')
else:
    print("Here")
```

**Answer**

0 1 2 3 4 5 Here

**Status : Wrong**

**Marks : 0/1**

3. What will be the output of the following Python code?

```
i = 1
while True:
    if i % 2 == 0:
        i += 1
        continue
    if i > 10:
        break
    print(i, end = " ")
    i += 2
```

**Answer**

1 3 5 7 9

**Status : Correct**

**Marks : 1/1**

4. What will be the output of the following Python code?

```
i = 5
while True:
    if i%0011 == 0:
        break
    print(i, end = " ")
    i += 1
```

**Answer**

5 6 7 8

**Status :** Correct

**Marks :** 1/1

5. What is the output of the following?

```
i=0
while(1):
    i++
    print i
    if(i==4):
        break
```

**Answer**

1 2 3 4

**Status :** Wrong

**Marks :** 0/1

6. What is the output of the following?

```
True = False
while True:
    print(True)
    break
```

**Answer**

error

**Status :** Correct

**Marks :** 1/1

7. Which keyword is used to immediately terminate a loop?

**Answer**

break

**Status :** Correct

**Marks :** 1/1

8. What will be the output of the following Python code?

```
i = 0
while i < 5:
    print(i)
    i += 1
    if i == 3:
        break
else:
    print(0)
```

**Answer**

012

**Status :** Correct

**Marks :** 1/1

9. What is the output of the following code?

```
for i in range(5):
    if i == 5:
        break
    else:
        print(i)
else:
    print("Here")
```

**Answer**

0 1 2 3 4

**Status :** Wrong

**Marks :** 0/1

10. When does the else statement written after the loop execute?

**Answer**

When loop condition becomes false

**Status :** Correct

**Marks :** 1/1

11. What will the following code output?

```
x = 0
while x < 5:
    if x == 3:
        break
    x += 1
else:
    print("Completed")
print(x)
```

**Answer**

3

**Status :** Correct

**Marks :** 1/1

12. What will be the output of the following Python code?

```
i = 1
while True:
    if i%3 == 0:
        break
    print(i)
    i += 1
```

**Answer**

1 2 3

**Status :** Wrong

**Marks :** 0/1

13. What is the output of the following code?

```
i = 5
while True:
    if i%009 == 0:
        break
    print(i)
    i += 1
```

**Answer**

5 6 7 8

**Status : Wrong**

**Marks : 0/1**

14. What will be the output of the following Python code?

```
i = 1
while False:
    if i%2 == 0:
        break
    print(i)
    i += 2
```

**Answer**

The code runs successfully but does not print anything

**Status : Correct**

**Marks : 1/1**

15. What will be the output of the following Python code?

```
i = 1
while True:
    if i%3 == 0:
        break
    print(i)
    i += 1
```

**Answer**

None of the mentioned options

**Status : Wrong**

**Marks : 0/1**

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 2\_COD\_Updated

Attempt : 1  
Total Mark : 50  
Marks Obtained : 50

#### Section 1 : Coding

##### 1. Problem Statement

You work as an instructor at a math enrichment program, and your goal is to develop a program that showcases the concept of using control statements to manipulate loops. Your task is to create a program that takes an integer 'n' as input and prints the squares of even numbers from 1 to 'n', while skipping odd numbers.

##### ***Input Format***

The input consists of a single integer, which represents the upper limit of the range.

##### ***Output Format***

The output displays the square of even numbers from 1 to 'n' separated by lines.



Refer to the sample output for the formatting specifications.

**Sample Test Case**

Input: 10

Output: 4

16

36

64

100

**Answer**

```
n=int(input())
for i in range(1,n+1):
    if i%2==0:
        print(i**2)
```

**Status :** Correct

**Marks : 10/10**

## 2. Problem Statement

As a junior developer working on a text analysis project, your task is to create a program that displays the consonants in a sentence provided by the user, separated by spaces.

You need to implement a program that takes a sentence as input and prints the consonants while skipping vowels and non-alphabetic characters using only control statements.

**Input Format**

The input consists of a string representing the sentence.

**Output Format**

The output displays space-separated consonants present in the sentence.

Refer to the sample output for the formatting specifications.

**Sample Test Case**

Input: Hello World!

Output: H I I W r l d

**Answer**

```
a=str(input())
for i in a:
    if i.isalpha():
        if i not in "AEIOUaeiou":
            print(i,end=" ")
```

**Status :** Correct

**Marks : 10/10**

### 3. Problem Statement

John, a software developer, is analyzing a sequence of numbers within a given range to calculate their digit sum. However, to simplify his task, he excludes all numbers that are palindromes (numbers that read the same backward as forward).

Help John find the total sum of the digits of non-palindromic numbers in the range [start, end] (both inclusive).

Example:

Input:

10

20

Output:

55

Explanation:

Range [10, 20]: Non-palindromic numbers are 10, 12, 13, 14, 15, 16, 17, 18,

19 and 20.

Digit sums:  $1+0 + 1+2 + 1+3 + 1+4 + 1+5 + 1+6 + 1+7 + 1+8 + 1+9 + 2+0 = 55$ .

Output: 55

### ***Input Format***

The first line of input consists of an integer, representing the starting number of the range.

The second line of input consists of an integer, representing the ending number of the range.

### ***Output Format***

The output prints a single integer, representing the total sum of the digits of all non-palindromic numbers in the range.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 10

20

Output: 55

### ***Answer***

```
n=int(input())
m=int(input())
st=0
for i in range(n,m+1):
    strn=str(i)
    if strn==strn[::-1]:
        continue
    for j in strn:
        st+=int(j)
print(st)
```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Ethan, a curious mathematician, is fascinated by perfect numbers. A perfect number is a number that equals the sum of its proper divisors (excluding itself). Ethan wants to identify all perfect numbers within a given range.

Help him write a program to list these numbers.

##### ***Input Format***

The first line of input consists of an integer start, representing the starting number of the range.

The second line consists of an integer end, representing the ending number of the range.

##### ***Output Format***

The output prints all perfect numbers in the range, separated by a space.

Refer to the sample output for formatting specifications.

##### ***Sample Test Case***

Input: 1

100

Output: 6 28

##### ***Answer***

```
n=int(input())
m=int(input())
for i in range(n,m):
    s=0
    for j in range(1,i):
        if i%j==0:
            s+=j
    if s==i:
        print(i,end=" ")
```

**Status :** Correct

**Marks :** 10/10

## 5. Problem Statement

Emma, a mathematics enthusiast, is exploring a range of numbers and wants to count how many of them are not Fibonacci numbers.

Help Emma determine the count of non-Fibonacci numbers within the given range [start, end] using the continue statement.

### *Input Format*

The first line of input consists of an integer, representing the starting number of the range.

The second line consists of an integer, representing the ending number of the range.

### *Output Format*

The output prints a single integer, representing the count of numbers in the range that are not Fibonacci numbers.

Refer to the sample output for formatting specifications.

### *Sample Test Case*

Input: 1

10

Output: 5

### *Answer*

```
def isfibo(n):  
    a,b=0,1  
    while b<n:  
        a,b=b,a+b  
    return b==n  
a=int(input())  
b=int(input())  
nf=0
```

```
for i in range(a,b+1):  
    if isfibo(i):  
        continue  
    nf+=1  
print(nf)
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 2\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 40

### Section 1 : Coding

#### 1. Problem Statement

Alex is practicing programming and is curious about prime and non-prime digits. He wants to write a program that calculates the sum of the non-prime digits in a given integer using loops.

Help Alex to complete his task.

Example:

Input:

845

output:

12

Explanation:

Digits: 8 (non-prime), 4 (non-prime), 5 (prime)

The sum of Non-Prime Digits:  $8 + 4 = 12$

Output: 12

### ***Input Format***

The input consists of a single integer X.

### ***Output Format***

The output prints an integer representing the sum of non-prime digits in X.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 845

Output: 12

### ***Answer***

```
n=input()
np={0,1,4,6,8,9}
t=0
for i in n:
    if int(i) in np:
        t+=int(i)
print(t)
```

**Status :** Correct

**Marks :** 10/10

## **2. Problem Statement**

Gabriel is working on a wildlife research project where he needs to compute various metrics for different animals based on their characteristics. Each animal type requires a different calculation: a deer's



distance traveled, a bear's weight based on footprint size, or a bird's altitude based on its flying pattern.

Conditions:

For Deer (Mode 'D' or 'd'): Distance = speed of sound \* time taken, where the speed of sound in air is 343 meters per second. For Bear (Mode 'B' or 'b'): Weight = footprint size \* average weight, where the average weight per square inch for a bear is 5.0 pounds. For Bird (Mode 'F' or 'f'): Altitude = flying pattern \* distance covered (in meters).

Write a program to help Gabriel analyze the characteristics of animals based on the given inputs.

### ***Input Format***

The first line of input consists of a character, representing the type of animal 'D/d' for deer, 'B/b' for bear, and 'F/f' for bird.

If the choice is 'D' or 'd':

The second line of input consists of a floating-point value T, representing the time taken from the deer's location to the observer.

If the choice is 'B' or 'b':

The second line of input consists of a floating-point value S, representing the size of the bear's footprint in square inches.

If the choice is 'F' or 'f':

1. The second line of input consists of a floating-point value P, representing the bird's flying pattern.
2. The third line consists of a floating-point value D, representing the distance covered by the bird in meters.

### ***Output Format***

The output prints one of the following:

If the choice is 'D' or 'd':

The output prints "Distance: X m" where X is a floating point value rounded off to

two decimal places, representing the calculated distance traveled by the sound wave in meters.

If the choice is 'B' or 'b':

The output prints "Weight: Y lb" where Y is a floating point value rounded off to two decimal places, representing the estimated weight of the bear in pounds.

If the choice is 'F' or 'f':

The output prints "Altitude: Z m" where Z is a floating point value rounded off to two decimal places, representing the calculated altitude of the bird's flight in meters.

If the given choice is invalid, print "Invalid".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: d

2.5

Output: Distance: 857.50 m

### **Answer**

```
a=input().strip()
if a in ("D","d"):
    t=float(input())
    n=343*t
    r=format(n,.2f)
    print("Distance:",r,"m")
elif a in ("B","b"):
    s=float(input())
    w=s*5.0
    p=format(w,.2f)
    print("Weight:",p,"lb")
elif a in ("F","f"):
    p=float(input())
    d=float(input())
    z=p*d
```

```
f=format(z,.2f")
print("Altitude:",f,"m")
else:
    print("Invalid")
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Rohith is a data analyst who needs to categorize countries based on their population growth rates. Each country is assigned a unique code. Rohith will receive a code and corresponding data based on the code. If the data falls within specific thresholds, he needs to classify the country's priority level.

Your task is to write a program that reads a country code and its associated data, and then determines if the priority is "High" or "Low."

Thresholds: France: Priority is "High" if the percentage < 50, else "Low". Japan: Priority is "High" if life expectancy > 80, else "Low". Brazil: Priority is "High" if the urban population > 80, else "Low".

#### **Input Format**

The first line of input consists of an integer, representing the country code (1 for France, 2 for Japan, 3 for Brazil).

If the country code is 1,

- The second line consists of a floating-point value N, representing the percentage of the English-speaking population.

If the country code is 2,

- The second line consists of a floating-point value A, representing the average life expectancy in years.

If the country code is 3,

- The second line consists of a floating-point value P, representing the

percentage of the urban population.

### **Output Format**

The first line of output displays "Priority: High" or "Priority: Low" based on the input data.

If the country code is invalid, print "Invalid".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1

30.0

Output: Priority: High

### **Answer**

```
a=int(input())
if a==1:
    m=float(input())
    if m<50:
        print("Priority: High")
    else:
        print("Priority: Low")
elif a==2:
    n=float(input())
    if n>80:
        print("Priority: High")
    else:
        print("Priority: Low")
elif a==3:
    p=float(input())
    if p>80:
        print("Priority: High")
    else:
        print("Priority: Low")
else:
    print("Invalid")
```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Students are allowed to work on our computer center machines only after entering the correct secret code. If the code is correct, the message "Logged In" is displayed. They are not allowed to log in to the machine until they enter the correct secret code.

Write a program to allow the student to work only if he/she enters the correct secret code.

Note: Here, secret code means the last three digits should be divisible by the first digit of the number.

#### ***Input Format***

The input consists of an integer n, which represents the secret code.

#### ***Output Format***

The output displays either "Logged In" or "Incorrect code" based on the given condition.

Refer to the sample output for the formatting specifications.

#### ***Sample Test Case***

Input: 2345

Output: Incorrect code

#### ***Answer***

```
n=int(input())
ns=str(n)
fd=int(ns[0])
ltd=int(ns[-3:])
if len(ns) >= 3:
    ltd=int(ns[-3:])
else:
```

```
ltd=int(ns)
if fd!=0 and ltd%fd==0:
    print("Logged In")
else:
    print("Incorrect code")
```


**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 2\_PAH\_Updated

Attempt : 1  
Total Mark : 60  
Marks Obtained : 50

#### Section 1 : Coding

##### 1. Problem Statement

Aarav is fascinated by the concept of summing numbers separately based on their properties. He plans to write a program that calculates the sum of even numbers and odd numbers separately from 1 to a given positive integer.

Aarav wants to input an integer value to represent the upper limit of the range. Help Aarav by developing a program that computes and displays the sum of even and odd numbers separately.

##### ***Input Format***

The input consists of a single integer N, where N is the upper limit of the range.

##### ***Output Format***

The output consists of two lines:

- The first line displays the sum of even numbers from 1 to N.
- The second line displays the sum of odd numbers from 1 to N.

Refer to the sample output for the exact format.

### **Sample Test Case**

Input: 10

Output: Sum of even numbers from 1 to 10 is 30

Sum of odd numbers from 1 to 10 is 25

### **Answer**

```
n=int(input())
sum1=0
sum2=0
for i in range(1,n+1):
    if i%2==0:
        sum1+=i
    else:
        sum2+=i
print("Sum of even numbers from 1 to",n,"is",sum1)
print("Sum of odd numbers from 1 to",n,"is",sum2)
```

**Status :** Correct

**Marks :** 10/10

## **2. Problem Statement**

As a software engineer, your goal is to develop a program that facilitates the identification of leap years in a specified range. Your task is to create a program that takes two integer inputs, representing the start and end years of the range and then prints all the leap years within that range.

### **Input Format**

The first line of the input consists of an integer, which represents the start year.

The second line consists of an integer, which represents the end year.



### **Output Format**

The output displays the leap years within the given range, separated by lines.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 2000

2053

Output: 2000

2004

2008

2012

2016

2020

2024

2028

2032

2036

2040

2044

2048

2052

### **Answer**

```
n=int(input())
```

```
m=int(input())
```

```
for i in range(n,m+1):
```

```
    if (i%4==0)and (i%100!=0)or (i%400==0):
```

```
        print(i)
```

**Status :** Correct

**Marks :** 10/10

### **3. Problem Statement**

Kamali recently received her electricity bill and wants to calculate the amount she needs to pay based on her usage. The electricity company charges different rates based on the number of units consumed.

For the first 100 units, there is no charge. For units consumed beyond 100 and up to 200, there is a charge of Rs. 5 per unit. For units consumed beyond 200, there is a charge of Rs. 10 per unit.

Write a program to help Kamali calculate the amount she needs to pay for her electricity bill based on the units consumed.

### ***Input Format***

The input consists of an integer, representing the number of units.

### ***Output Format***

The output prints the total amount of the electricity bill, an integer indicating the amount Kamali needs to pay in the format "Rs. amount".

Refer to the sample output for the exact format.

### ***Sample Test Case***

Input: 350

Output: Rs. 2000

### ***Answer***

```
n=int(input())
b=0
if n>200:
    b+=(n-200)*10
    n=200
if n>100:
    b+=(n-100)*5
print("Rs.",b)
```

**Status :** Correct

**Marks : 10/10**

## **4. Problem Statement**

Imagine being entrusted with the responsibility of creating a program that simulates a math workshop for students. Your task is to develop an

interactive program that not only calculates but also showcases the charm of factorial values. Your program should efficiently compute and present the sum of digits for factorial values of only odd numbers within a designated range. This approach will ingeniously keep even factorials at bay, allowing students to delve into the intriguing world of mathematics with enthusiasm and clarity.

### ***Input Format***

The input consists of a single integer, n.

### ***Output Format***

The output displays the factorial and sum of digits of the factorial of odd numbers within the given range.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 6

Output: 1! = 1, sum of digits = 1

3! = 6, sum of digits = 6

5! = 120, sum of digits = 3

### ***Answer***

```
n=int(input())
for i in range(1,n+1,2):
    fact=1
    for i in range(1,n+1):
        fact*=i
    s=sum(int(d)for d in str(fact))
    print(f"{fact},sum of digits={s}")
```

**Status : Wrong**

**Marks : 0/10**

## **5. Problem Statement**

Rajesh wants to design a program that simulates a real-time scenario

based on a mathematical concept known as the Collatz Conjecture. This concept involves the repeated application of rules to a given starting number until the number becomes 1. The rules are as follows:

If the number is even, divide it by 2. If the number is odd, multiply it by 3 and add 1.

Your task is to write a program that takes a positive integer as input, applies the Collatz Conjecture rules to it, counts the number of steps taken to reach 1, and provides an output accordingly. If the process exceeds 100 steps, the program should print a message indicating so and use break to exit.

#### ***Input Format***

The input consists of a single integer, n.

#### ***Output Format***

The output displays the total number of steps taken to reach 1 if it's under 100.

If it's more than 100, it displays "Exceeded 100 steps. Exiting...".

Refer to sample output for the formatting specifications.

#### ***Sample Test Case***

Input: 6

Output: Steps taken to reach 1: 8

#### ***Answer***

```
n=int(input())
s=0
while n!=1 and s<100:
    if n%2==0:
        n//=2
    else:
        n=3*n+1
    s+=1
if n==1:
    print("Steps taken to reach 1:",s)
```

```
else:  
    print("Exceeded 100 steps. Exiting...")
```

**Status :** Correct

**Marks :** 10/10

## 6. Problem Statement

Sophia, a primary school teacher, wants to calculate the sum of numbers within a given range, excluding those that are multiples of 3.

Write a program to help Sophia compute the sum of all numbers between start and end (inclusive) that are not divisible by 3 using the continue statement.

### **Input Format**

The first line of input consists of an integer, representing the starting number of the range.

The second line of input consists of an integer, representing the ending number of the range.

### **Output Format**

The output prints a single integer, representing the sum of numbers in the range that are not multiples of 3.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 1  
10

Output: 37

### **Answer**

```
m=int(input())  
n=int(input())  
sum=0
```

```
for i in range(m,n+1):  
    if i%3!=0:  
        sum+=i  
print(sum)
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 3\_MCQ

Attempt : 1  
Total Mark : 25  
Marks Obtained : 22

#### Section 1 : MCQ

1. What is the output of the following Python code?

```
string1 = "Hello"  
string2 = "World"  
result = string1 + string2  
print(result)
```

**Answer**

HelloWorld

**Status : Correct**

**Marks : 1/1**

2. What is the result of the slicing operation `lst[-5:-2]` on the list `lst = [1, 2, 3, 4, 5, 6]`?

**Answer**

[3, 4, 5]

Status : Wrong

Marks : 0/1

3. What is the output of the following Python code?

```
txt = "My Classroom"  
print(txt.find("o"))  
print(txt.index("o"))
```

Answer

99

Status : Correct

Marks : 1/1

4. If you have a list lst = [1, 2, 3, 4, 5, 6], what does the slicing operation lst[-3:] return?

Answer

The last three elements of the list

Status : Correct

Marks : 1/1

5. What is the output of the following code?

```
my_list = [3, 6, 1, 2, 5, 4]  
print(sorted(my_list) == my_list.sort())
```

Answer

True

Status : Wrong

Marks : 0/1

6. What will be the output of the following program?

```
numbers = [1, 2, 3, 4, 5]  
numbers.append(6, 7)  
print(numbers)
```



**Answer**

Compile Time Error

**Status :** Correct

**Marks :** 1/1

7. What is the output of the following Python code?

```
name = "John"
age = 25
message = "My name is %s and I am %d years old." % (name, age)
print(message)
```

**Answer**

My name is John and I am 25 years old.

**Status :** Correct

**Marks :** 1/1

8. What will be the output of the following code?

```
my_list = [1, 2, 2, 3]
print(my_list.count(2))
```

**Answer**

2

**Status :** Correct

**Marks :** 1/1

9. Suppose list1 is [2, 33, 222, 14, 25], What is list1[-1]?

**Answer**

25

**Status :** Correct

**Marks :** 1/1

10. Which of the following is a valid way to use the '%' operator to concatenate strings in Python?

**Answer**

`"%s %s" % (string1, string2)`

**Status :** Correct

**Marks :** 1/1

11. What does the `append()` method do in Python?

**Answer**

Adds a new element to the end of the list

**Status :** Correct

**Marks :** 1/1

12. Suppose `list1` is `[4, 2, 2, 4, 5, 2, 1, 0]`, Which of the following is the correct syntax for slicing operation?

**Answer**

all of the mentioned options

**Status :** Correct

**Marks :** 1/1

13. Which method in Python is used to create an empty list?

**Answer**

`list()`

**Status :** Correct

**Marks :** 1/1

14. What is the output of the following code?

```
my_list = [1, 2, 3]
my_list *= 2
print(len(my_list))
```

**Answer**

6

**Status :** Correct

**Marks :** 1/1

15. What is the output of the following Python code?

```
word = "Python"  
result = word[::-1]  
print(result)
```

**Answer**

nohtyp

**Status : Wrong**

**Marks : 0/1**

16. What is the output of the following Python code?

```
text = "Python"  
result = text.center(10, "*")  
print(result)
```

**Answer**

\*\*Python\*\*

**Status : Correct**

**Marks : 1/1**

17. What does the following code output?

```
lst = [10, 20, 30, 40, 50]  
print(lst[-4:-1])
```

**Answer**

[20, 30, 40]

**Status : Correct**

**Marks : 1/1**

18. What is the output of the following Python code?

```
text = " Python "  
answer = text.strip()  
print(answer)
```

**Answer**

Python

**Status :** Correct

**Marks :** 1/1

19. Which method is used to add multiple items to the end of a list?

**Answer**

extend()

**Status :** Correct

**Marks :** 1/1

20. What does negative indexing in Python lists allow you to do?

**Answer**

Access elements in the list from the end

**Status :** Correct

**Marks :** 1/1

21. What will be the output of the following code?

```
numbers = [1, 2, 3, 4, 5]
numbers.remove(6)
print(numbers)
```

**Answer**

ValueError: list.remove(x): x not in list

**Status :** Correct

**Marks :** 1/1

22. What is the output of the following Python code?

```
word = "programming"
answer = word.index("gram")
print(answer)
```

**Answer**

3

**Status :** Correct

**Marks :** 1/1

23. What is the output of the following Python code?

```
a = "Hello"  
b = "World"  
c = a + " " + b  
print(c)
```

**Answer**

Hello World

**Status :** Correct

**Marks :** 1/1

24. Suppose list1 is [2, 33, 222, 14, 25], What is list1[: -1]?

**Answer**

[2, 33, 222, 14]

**Status :** Correct

**Marks :** 1/1

25. What is the output of the following Python code?

```
b = "Projects!"  
print(b[2:5])
```

**Answer**

oje

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 3\_COD

Attempt : 1  
Total Mark : 50  
Marks Obtained : 50

### Section 1 : Coding

#### 1. Problem Statement

Given a list of positive and negative numbers, arrange them such that all negative integers appear before all the positive integers in the array. The order of appearance should be maintained.

Example

Input:

[12, 11, -13, -5, 6, -7, 5, -3, -6]

Output:

List = [-13, -5, -7, -3, -6, 12, 11, 6, 5]

Explanation:

The output is the arranged list where all the negative integers appear before the positive integers while maintaining the original order of appearance.

### ***Input Format***

The input consists of a single line containing a list of integers enclosed in square brackets separated by commas.

### ***Output Format***

The output displays "List = " followed by an arranged list of integers as required, separated by commas and enclosed in square brackets.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: [12, 11, -13, -5, 6, -7, 5, -3, -6]

Output: List = [-13, -5, -7, -3, -6, 12, 11, 6, 5]

### ***Answer***

```
import ast
a=input()
m=ast.literal_eval(a)
p=[]
n=[]
for j in m:
    if j<0:
        n.append(j)
    else:
        p.append(j)
print("List=",n+p)
```

**Status :** Correct

**Marks :** 10/10

## **2. Problem Statement**

You have a string containing a phone number in the format "(XXX) XXX-XXXX". You need to extract the area code from the phone number and

create a new string that contains only the area code.

Write a Python program for the same.

**Note**

(XXX) - Area code

XXX-XXXX - Phone number

***Input Format***

The input consists of a string, representing the phone number in the format "(XXX) XXX-XXXX".

***Output Format***

The output displays "Area code: " followed by a string representing the area code for the given phone number.

Refer to the sample output for the formatting specifications.

***Sample Test Case***

Input: (123) 456-7890

Output: Area code: 123

***Answer***

```
# You are using Python
pn=input()
ac=pn[1:4]
print("Area code:",ac)
```

**Status :** Correct

**Marks : 10/10**

### 3. Problem Statement

Dhruv wants to write a program to slice a given string based on user-defined start and end positions.



The program should check whether the provided positions are valid and then return the sliced portion of the string if the positions are within the string's length.

### ***Input Format***

The first line consists of the input string as a string.

The second line consists of the start position (0-based index) as an integer.

The third line consists of the end position (0-based index) as an integer.

### ***Output Format***

The output displays the following format:

If the start and end positions are valid, print the sliced string.

If the start and end positions are invalid, print "Invalid start and end positions".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: pythonprogramming

0

5

Output: python

### ***Answer***

```
s=input()
start=int(input())
end=int(input())
l=len(s)
if 0<=start<l and 0<=end<l and start<=end:
    ss=s[start:end+1]
    print(ss)
else:
    print("Invalid start and end positions")
```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Alex is working on a Python program to manage a list of elements. He needs to append multiple elements to the list and then remove an element from the list at a specified index.

Your task is to create a program that helps Alex manage the list. The program should allow Alex to input a list of elements, append them to the existing list, and then remove an element at a specified index.

##### ***Input Format***

The first line contains an integer  $n$ , representing the number of elements to be appended to the list.

The next  $n$  lines contain integers, representing the elements to be appended to the list.

The third line of input consists of an integer  $M$ , representing the index of the element to be popped from the list.

##### ***Output Format***

The first line of output displays the original list.

The second line of output displays the list after popping the element of the index  $M$ .

The third line of output displays the popped element.

Refer to the sample output for the formatting specifications.

##### ***Sample Test Case***

Input: 5

64

98

-1

5

26

3

Output: List after appending elements: [64, 98, -1, 5, 26]

List after popping last element: [64, 98, -1, 26]

Popped element: 5

**Answer**

```
n=int(input())
t=[]
for i in range(n):
    val=int(input())
    t.append(val)
print("List after appending elements:",t)
m=int(input())
p=t.pop(m)
print("List after popping last element:",t)
print("Popped element:",p)
```

**Status :** Correct

**Marks :** 10/10

## 5. Problem Statement

Ram is working on a program to manipulate strings. He wants to create a program that takes two strings as input, reverses the second string, and then concatenates it with the first string.

Ram needs your help to design a program.

**Input Format**

The input consists of two strings in separate lines.

**Output Format**

The output displays a single line containing the concatenated string of the first string and the reversed second string.

Refer to the sample output for the formatting specifications.

**Sample Test Case**

Input: hello  
word

Output: hellodrow

**Answer**

```
a=input()
b=input()
c=b[::-1]
s=a+c
print(s)
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 3\_CY

Attempt : 1  
Total Mark : 30  
Marks Obtained : 30

### Section 1 : Coding

#### 1. Problem Statement

Gina is working on a data analysis task where she needs to extract sublists from a given list of integers and find the median of each sublist. For each median found, she also needs to determine its negative index in the original list.

Help Gina by writing a program that performs these tasks.

Note: The median is the middle value in the sorted list of numbers, or the first value of the two middle values if the list has an even number of elements.

Example

Input

10

1 2 3 4 5 7 8 9 10 11

3

1 5

2 6

3 10

Output

3 : -8

4 : -7

7 : -5

Explanation

For the first range (1 to 5), the sublist is [1, 2, 3, 4, 5]. The median is 3, and its negative index in the original list is -8.

For the second range (2 to 6), the sublist is [2, 3, 4, 5, 7]. The median is 4, and its negative index in the original list is -7.

For the third range (3 to 10), the sublist is [3, 4, 5, 7, 8, 9, 10, 11]. The median is 7, and its negative index in the original list is -5.

**Input Format**

The first line of input consists of an integer N, representing the number of elements in the list.

The second line consists of N space-separated integers representing the elements of the list.

The third line consists of an integer R, representing the number of ranges.

The next R lines each consist of two integers separated by space representing the start and end indices (1-based) of the ranges.

**Output Format**

The output consists of n lines, displaying "X : Y" where X is the median of the

sublist and Y is the negative index in the original list.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 10

1 2 3 4 5 7 8 9 10 11

3

1 5

2 6

3 10

Output: 3 : -8

4 : -7

7 : -5

### **Answer**

# You are using Python

```
n=int(input())
```

```
a=list(map(int,input().split()))
```

```
for i in range(int(input())):
```

```
    l,r=map(int,input().split())
```

```
    s=sorted(a[l-1:r])
```

```
    m=s[(len(s)-1)//2]
```

```
    print(f"{m}:{a.index(m)-len(a)}")
```

**Status : Correct**

**Marks : 10/10**

## **2. Problem Statement**

You have two strings str1 and str2, both of equal length.

Write a Python program to concatenate the two strings such that the first character of str1 is followed by the first character of str2, the second character of str1 is followed by the second character of str2, and so on.

For example, if str1 is "abc" and str2 is "def", the output should be "adbecf".

### ***Input Format***

The input consists of two strings in each line.

### ***Output Format***

The output displays the concatenated string in the mentioned format.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: abc  
def

Output: adbecf

### ***Answer***

```
# You are using Python
str1=input().strip()
str2=input().strip()
result=""
for i in range(len(str1)):
    result+=str1[i]+str2[i]
print(result)
```

**Status :** Correct

**Marks :** 10/10

## **3. Problem Statement**

A company is creating email accounts for its new employees. They want to use a naming convention for email addresses that consists of the first letter of the employee's first name, followed by their last name, followed by @company.com.

The company also has a separate email domain for administrative employees.

Write a program that prompts the user for their first name, last name, role, and company and then generates their email address using the



appropriate naming convention based on their role. This is demonstrated in the below examples.

Note:

The generated email address should consist of the first letter of the first name, the last name in lowercase, and a suffix based on the role and company, all in lowercase.

### ***Input Format***

The first line of input consists of the first name of an employee as a string.

The second line consists of the last name of an employee as a string.

The third line consists of the role of the employee as a string.

The last line consists of the company name as a string.

### ***Output Format***

The output consists of a single line containing the generated email address for the employee, following the specified naming convention.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: John

Smith

admin

iamNeo

Output: jsmith@admin.iamneo.com

### ***Answer***

```
# You are using Python
```

```
fn=input().strip()
```

```
ln=input().strip()
```

```
r=input().strip()
```

```
c=input().strip()
```

```
fi=fn[0].lower()
```

```
ln=ln.lower()
r=r.lower()
c=c.lower()
if r=="admin":
    domain=f"admin.{c}.com"
else:
    domain=f"{c}.com"
email=f"{fi}{ln}@{domain}"
print(email)
```

**Status :** Correct

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 3\_PAH

Attempt : 1  
Total Mark : 60  
Marks Obtained : 50

### Section 1 : Coding

#### 1. Problem Statement

You are tasked with writing a program that takes  $n$  integers as input from the user and stores them in a list. After this, you need to transform the list according to the following rules:

The element at index 0 should be replaced with 0. For elements at even indices (excluding index 0), replace the element with its cube. For elements at odd indices, replace the element with its square.

Additionally, you should sort the list in ascending order before applying these transformations.

#### *Input Format*

The first line of input represents the size of the list,  $N$ .

The elements of the list are represented by the next N lines.

### **Output Format**

The first line of output displays "Original List: " followed by the original list.

The second line displays "Replaced List: " followed by the replacement list as per the given condition.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 5

5  
1  
2  
3  
4

Output: Original List: [1, 2, 3, 4, 5]

Replaced List: [0, 4, 27, 16, 125]

### **Answer**

```
n=int(input())
l=[]
for i in range(n):
    l.append(int(input()))
m=sorted(l)
p=[]
for j in range(n):
    if j==0:
        p.append(0)
    elif j%2==0:
        p.append(m[j]**3)
    else:
        p.append(m[j]**2)
print("Original List:",m)
print("Replaced List:",p)
```

**Status : Correct**

**Marks : 10/10**

## 2. Problem Statement

Neha is learning string operations in Python and wants to practice using built-in functions. She is given a string A, and her task is to:

Find the length of the string using a built-in function. Copy the content of A into another string B using built-in functionality.

Help Neha implement a program that efficiently performs these operations.

### ***Input Format***

The input consists of a single line containing the string A (without spaces).

### ***Output Format***

The first line of output prints the length of the given string.

The second line prints the copied string without an extra newline at the end.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: technology-23

Output: Length of the string: 13

Copied string: technology-23

### ***Answer***

```
# You are using Python
st1=input()
print("Length of the string:",len(st1))
st2=st1
print(f"Copied string: {st2}")
```

**Status :** Correct

**Marks :** 10/10

## 3. Problem Statement

Gowri was doing her homework. She needed to write a paragraph about

modern history. During that time, she noticed that some words were repeated repeatedly. She started counting the number of times a particular word was repeated.

Your task is to help Gowri to write a program to get a string from the user. Count the number of times a word is repeated in the string.

Note: Case-sensitive

### ***Input Format***

The first line of input consists of a string, str1.

The second line consists of a single word that needs to be counted, str2.

### ***Output Format***

The output displays the number of times the given word is in the string.

If the second string str2 is not present in the first string str1, it prints 0.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: I felt happy because I saw the others were happy and because I knew I  
should feel happy  
happy

Output: 3

### ***Answer***

```
import string# You are using Python
str1=input()
str2=input()
for p in string.punctuation:
    str1=str1.replace(p," ")
w=str1.split()
c=0
for i in w:
    if i==str2:
```

```
c+=1  
print(c)
```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Imagine you are developing a text analysis tool for a cybersecurity company. Your task is to analyze input strings to categorize and count the characters into four categories: uppercase letters, lowercase letters, digits, and special characters. The company needs this tool to process log files and identify potential security threats.

##### **Input Format**

The input consists of the log entry provided as a single string.

##### **Output Format**

The output consists of four lines:

The first line contains an integer representing the count of uppercase letters in the format "Uppercase letters: {uppercase count}".

The second line contains an integer representing the count of lowercase letters in the format "Lowercase letters: {lowercase count}".

The third line contains an integer representing the count of digits in the format "Digits: {digits count}".

The fourth line contains an integer representing the count of special characters in the format "Special characters: {special characters count}".

Refer to the sample output for the formatting specifications.

##### **Sample Test Case**

Input: Hello123

Output: Uppercase letters: 1

Lowercase letters: 4

Digits: 3  
Special characters: 0

**Answer**

```
# You are using Python
st=input()
upc=0
lc=0
dc=0
sc=0
for char in st:
    if char.isupper():
        upc+=1
    elif char.islower():
        lc+=1
    elif char.isdigit():
        dc+=1
    else:
        sc+=1
print(f"Uppercase letters: {upc}")
print(f"Lowercase letters: {lc}")
print(f"Digits: {dc}")
print(f"Special characters: {sc}")
```

**Status :** Correct

**Marks : 10/10**

**5. Problem Statement**

Accept an unsorted list of length  $n$  with both positive and negative integers, including 0. The task is to find the smallest positive number missing from the array. Assume the  $n$  value is always greater than zero.

**Input Format**

The first line consists of  $n$ , which means the number of elements in the array.

The second line consists of the values in the list as space-separated integers.

**Output Format**

The output displays the smallest positive number, which is missing from the array.



Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 6  
-5 2 0 -1 -10 2

Output: 1

### **Answer**

```
n=int(input())
lst=list(map(int,input().split()))
pre=[False]*(n+2)
for i in range(n):
    if 1<=lst[i]<=n:
        pre[lst[i]]=True
for i in range(1,n+2):
    if not pre[i]:
        print(i)
        break
```

**Status :** Correct

**Marks :** 10/10

## 6. Problem Statement

Kyara is analyzing a series of measurements taken over time. She needs to identify all the "peaks" in this list of integers.

A peak is defined as an element that is greater than its immediate neighbors. Boundary elements are considered peaks if they are greater than their single neighbor.

Your task is to find and list all such peaks using list comprehension.

### **Example**

Input

1 3 2 4 1 5 7 6 10 2 8

Output

Peaks: [3, 4, 7, 10, 8]

Explanation

3 is a peak because it's greater than 1 and 2.

4 is a peak because it's greater than 2 and 1.

7 is a peak because it's greater than 5 and 6.

10 is a peak because it's greater than 6 and 2.

8 is a peak because it is an boundary element and it is greater than 2.

**Input Format**

The input consists of several integers separated by spaces, representing the measurements.

**Output Format**

The output displays "Peaks: " followed by a list of integers, representing the peak elements in the list.

Refer to the sample output for the formatting specifications.

**Sample Test Case**

Input: 1 3 2 4 1 5 7 6 10 2 8

Output: Peaks: [3, 4, 7, 10, 8]

**Answer**

```
arr=list(map(int,input().split()))
n=len(arr)
```

```
pks=[
    arr[i] for i in range(len(arr))
    if (i==0 and arr[i]>arr[i+1]) or (i==n-1 and arr[i]>arr[i-1])
    (0<i<n-1 and arr[i]>arr[i-1] and arr[i]>arr[i+1])
```

```
]
print("Peaks:",pks)
```

**Status : Wrong**

**Marks : 0/10**

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 4\_MCQ

Attempt : 1  
Total Mark : 15  
Marks Obtained : 12

#### Section 1 : MCQ

1. How is a lambda function different from a regular named function in Python?

**Answer**

A lambda function can only take one argument, while a regular function can take multiple arguments

**Status : Wrong**

**Marks : 0/1**

2. What will be the output of the following Python code?

```
def func(a, b=5, c=10):  
    print('a is', a, 'and b is', b, 'and c is', c)  
  
func(3, 7)
```

```
func(25, c = 24)
func(c = 50, a = 100)
```

**Answer**

a is 3 and b is 7 and c is 10 a is 25 and b is 5 and c is 24 a is 100 and b is 5 and c is 50

**Status : Correct**

**Marks : 1/1**

3. What will be the output of the following Python code?

```
def C2F(c):
    return c * 9/5 + 32
print(C2F(100))
print(C2F(0))
```

**Answer**

None of the mentioned options

**Status : Wrong**

**Marks : 0/1**

4. What keyword is used to define a lambda function in Python?

**Answer**

lambda

**Status : Correct**

**Marks : 1/1**

5. What is the output of the following code snippet?

```
def square(x):
    return x ** 2
```

```
result = square(4)
print(result)
```

**Answer**

16

**Status :** Correct

**Marks :** 1/1

6. What is the output of the following code snippet?

```
def add(a, b=2):  
    return a - b
```

```
result = add(3)  
print(result)
```

**Answer**

1

**Status :** Correct

**Marks :** 1/1

7. What will be the output of the following Python code?

```
multiply = lambda x, y: x * y  
print(multiply(2, 'Hello'))
```

**Answer**

HelloHello

**Status :** Correct

**Marks :** 1/1

8. What is the output of the code shown below?

```
def f1(x):  
    x += 1  
    print(x)
```

```
global_variable = 15  
f1(global_variable)  
print("hello")
```

**Answer**

16hello

**Status :** Correct

**Marks :** 1/1

9. What will be the output of the following code?

```
number = 7
result = abs(number) + pow(number, 2)
print(result)
```

**Answer**

56

**Status :** Correct

**Marks :** 1/1

10. What is the main advantage of using lambda functions in Python?

**Answer**

They can be called directly from the command line without defining them

**Status :** Wrong

**Marks :** 0/1

11. What will be the output of the following Python code?

```
def cube(x):
    return x * x * x
x = cube(3)
print(x)
```

**Answer**

27

**Status :** Correct

**Marks :** 1/1

12. What will be the output of the following Python code?

```
def is_even(number):
    if number % 2 == 0:
        return True
```

```
result = is_even(6)
print(result)
```

**Answer**

True

**Status :** Correct

**Marks :** 1/1

13. What will be the output of the following code?

```
num = -5  
result = abs(num)  
print(result)
```

**Answer**

5

**Status :** Correct

**Marks :** 1/1

14. What will be the output of the following code?

```
value = 42  
result = abs(value) + len(str(value))  
print(result)
```

**Answer**

44

**Status :** Correct

**Marks :** 1/1

15. What will be the output of the following Python code?

```
def absolute_value(x):  
    if x < 0:  
        return -x  
    return x
```

```
result = absolute_value(-9)  
print(result, absolute_value(5))
```

**Answer**



9 5

Status : Correct

Marks : 1/1

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 4\_COD\_Updated

Attempt : 1  
Total Mark : 50  
Marks Obtained : 50

#### Section 1 : Coding

##### 1. Problem Statement

Imagine you are building a messaging application, and you want to know the length of the messages sent by the users. You need to create a program that calculates the length of a message using the built-in function `len()`.

##### ***Input Format***

The input consists of a string representing the message.

##### ***Output Format***

The output prints an integer representing the length of the entered message.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: hello!!

Output: 7

### **Answer**

```
n=input()
b=len(n)
print(b)
```

**Status :** Correct

**Marks : 10/10**

## **2. Problem Statement**

Sneha is building a more advanced exponential calculator. She wants to implement a program that does the following:

Calculates the result of raising a given base to a specific exponent using Python's built-in `pow()` function. Displays all intermediate powers from  $\text{base}^1$  to  $\text{base}^{\text{exponent}}$  as a list. Calculates and displays the sum of these intermediate powers.

Help her build this program to automate her calculations.

### **Input Format**

The input consists of line-separated two integer values representing base and exponent.

### **Output Format**

The first line of the output prints the calculated result of raising the base to the exponent.

The second line prints a list of all powers from  $\text{base}^1$  to  $\text{base}^{\text{exponent}}$ .

The third line prints the sum of all these powers.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 2

3

Output: 8

[2, 4, 8]

14

### **Answer**

```
n=int(input())
m=int(input())
p=pow(n,m)
l=[]
for i in range(1,m+1):
    l.append(pow(n,i))
print(p)
print(l)
print(sum(l))
```

**Status :** Correct

**Marks : 10/10**

### **3. Problem Statement**

Implement a program that needs to identify Armstrong numbers.

Armstrong numbers are special numbers that are equal to the sum of their digits, each raised to the power of the number of digits in the number.

Write a function `is_armstrong_number(number)` that checks if a given number is an Armstrong number or not.

Function Signature: `armstrong_number(number)`

#### **Input Format**

The first line of the input consists of a single integer, `n`, representing the number to be checked.

#### **Output Format**

The output should consist of a single line that displays a message indicating whether the input number is an Armstrong number or not.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 153

Output: 153 is an Armstrong number.

### **Answer**

```
# You are using Python
def armstrong_number(n):
    sum=0
    temp=n
    f=len(str(n))
    while(temp>0):
        b=temp%10
        sum=sum+pow(b,f)
        temp//=10

    if n==sum:
        print(n,"is an Armstrong number.")
    else:
        print(n,"is not an Armstrong number.")
a=int(input())
armstrong_number(a)
```

**Status : Correct**

**Marks : 10/10**

## **4. Problem Statement**

Imagine you are developing a text analysis tool for a cybersecurity company. Your task is to create a function that analyzes input strings to categorize and count the characters into four categories: uppercase letters, lowercase letters, digits, and special characters. The company needs this tool to process log files and identify potential security threats.

Function Signature: analyze\_string(input\_string)

### ***Input Format***

The input consists of a single string (without space), which may include uppercase letters, lowercase letters, digits, and special characters.

### ***Output Format***

The first line contains an integer representing the count of uppercase letters in the format "Uppercase letters: [count]".

The second line contains an integer representing the count of lowercase letters in the format "Lowercase letters: [count]".

The third line contains an integer representing the count of digits in the format "Digits: [count]".

The fourth line contains an integer representing the count of special characters in the format "Special characters: [count]".

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: Hello123

Output: Uppercase letters: 1

Lowercase letters: 4

Digits: 3

Special characters: 0

### ***Answer***

```
def analyze_string(input_string):
```

```
    uppercase_count=0
```

```
    lowercase_count=0
```

```
    digit_count=0
```

```
    special_count=0
```

```
    for i in input_string:
```

```
        if i.isupper():
```

```
            uppercase_count+=1
```

```

        elif i.islower():
            lowercase_count+=1
        elif i.isdigit():
            digit_count+=1
        else:
            special_count+=1
    return(uppercase_count,lowercase_count,digit_count,special_count)

input_string = input()
uppercase_count, lowercase_count, digit_count, special_count =
analyze_string(input_string)

print("Uppercase letters:", uppercase_count)
print("Lowercase letters:", lowercase_count)
print("Digits:", digit_count)
print("Special characters:", special_count)

```

**Status :** Correct

**Marks :** 10/10

## 5. Problem Statement

Sara is developing a text-processing tool that checks if a given string starts with a specific character or substring. She needs to implement a function that accepts a string and a character (or substring), and returns True if the string starts with the provided character/substring, or False otherwise.

Write a program that uses a lambda function to help Sara perform this check.

### **Input Format**

The first line contains a string `str` representing the main string to be checked.

The second line contains a string `n`, which is the character or substring to check if the main string starts with it.

### **Output Format**

The first line of output prints "True" if the string starts with the given character/substring, otherwise prints "False".

Refer to the sample for the formatting specifications.

**Sample Test Case**

Input: Examly  
e

Output: False

**Answer**

# You are using Python

```
n=input()
```

```
m=input()
```

```
c=lambda a,b:a.startswith(m)
```

```
d=c(n,m)
```

```
print(d)
```

**Status :** Correct

**Marks : 10/10**



# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 4\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 37

### Section 1 : Coding

#### 1. Problem Statement

Create a program for a mathematics competition where participants need to find the smallest positive divisor of a given integer  $n$ . Your program should efficiently determine this divisor using the `min()` function and display the result.

#### ***Input Format***

The input consists of a single positive integer  $n$ , representing the number for which the smallest positive divisor needs to be found.

#### ***Output Format***

The output prints the smallest positive divisor of the input integer in the format: "The smallest positive divisor of  $[n]$  is: [smallest divisor]".

Refer to the sample output for the exact format.

### **Sample Test Case**

Input: 24

Output: The smallest positive divisor of 24 is: 2

### **Answer**

```
# You are using Python
n=int(input())
d=[i for i in range(2,n+1)if n%i==0]
s=min(d)
print(f"The smallest positive divisor of {n} is:{s}")
```

**Status :** Correct

**Marks : 10/10**

## **2. Problem Statement**

You are tasked with designing a shipping cost calculator program that calculates the shipping cost for packages based on their weight and destination. The program utilizes different shipping rates for domestic, international, and remote destinations. The rates for each destination type are provided as global constants.

Constant Values:

DOMESTIC\_RATE = 5.0

INTERNATIONAL\_RATE = 10.0

REMOTE\_RATE = 15.0

Function Signature: calculate\_shipping(weight, destination)

Formula: shipping cost = weight \* destination rate

### **Input Format**

The first line of the input consists of a float representing the weight of the package.

The second line consists of a string representing the destinations(Domestic or International or Remote).

### ***Output Format***

The program outputs any one of the following:

1. If the input is valid and the destination is recognized, the output should consist of a single line stating the calculated shipping cost for the given weight and destination in the format: "Shipping cost to [destination] for a [weight] kg package: \$[calculated cost]" with two decimal places.
2. If the input weight is not a positive float, print "Invalid weight. Weight must be greater than 0."
3. If the input destination is not one of the valid options, print "Invalid destination."

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 5.5

Domestic

Output: Shipping cost to Domestic for a 5.5 kg package: \$27.50

### ***Answer***

#

# You are using Python

```
def calculate_shipping(weight,destination):
```

```
    rates={"Domestic":5.0,"International":10.0,"Remote":15.0}
```

```
    if weight<=0:
```

```
        print("Invalid weight.Weight must be greater than 0.")
```

```
        return None
```

```
    if destination=="Domestic":
```

```
        return weight*5.0
```

```
    elif destination=="International":
```

```
        return weight*10.0
```

```
    elif destination=="Remote":
```

```
        return weight*15.0
```

```
    else:
```

```
print("Invalid destination.")
return None
weight=float(input())
destination=input()
shipping_cost=calculate_shipping(weight,destination)

if shipping_cost is not None:
    print(f"Shipping cost to {destination} for a {weight} kg package:
    ${shipping_cost:.2f}")
```

**Status :** Correct

**Marks : 10/10**

### 3. Problem Statement

Develop a text analysis tool that needs to count the occurrences of a specific substring within a given text string.

Write a function `count_substrings(text, substring)` that takes two inputs: the text string and the substring to be counted. The function should count how many times the substring appears in the text string and return the count.

Function Signature: `count_substrings(text, substring)`

#### ***Input Format***

The first line of the input consists of a string representing the text.

The second line consists of a string representing the substring.

#### ***Output Format***

The output should display a single line of output containing the count of occurrences of the substring in the text string.

Refer to the sample output for the formatting specifications.

#### ***Sample Test Case***

Input: programming is fun and programming is cool

programming

Output: The substring 'programming' appears 2 times in the text.

**Answer**

```
def count_substrings(text,substring):
    c=0
    for i in text.split():
        if i==substring:
            c+=1
    print(f"The substring '{substring}' appears {c} times in the text.")
t=input()
m=input()
count_substrings(t,m)
```

**Status :** Partially correct

**Marks :** 7/10

#### 4. Problem Statement

Amrita is developing a password strength checker for her website. She wants the checker to consider the length and the diversity of characters used in the password. A strong password should be long and include a mix of character types: uppercase, lowercase, digits, and special symbols.

She also wants the feedback to be user-friendly, so she wants to include the actual password in the output. Help Amrita finish this password checker using Python's built-in string methods.

Character Types Considered:

Lowercase letters (a-z) Uppercase letters (A-Z) Digits (0-9) Special characters (from string.punctuation, e.g. @, !, #, \$)

**Input Format**

The input consists of a single string representing the user's password.

**Output Format**

The program prints the strength of the password in this format:

If the password length < 6 characters or fewer than 2 of the 4 character types,

the output prints "<password> is Weak"

If password length  $\geq 6$  and at least 2 different character types, the output prints "<password> is Moderate"

If Password length  $\geq 10$  and all 4 character types present, the output prints "<password> is Strong"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: password123

Output: password123 is Moderate

### **Answer**

```
import string
p=input()
l=len(p)
t=0
if any(c.islower() for c in p):
    t+=1
if any(c.isupper() for c in p):
    t+=1
if any(c.isdigit() for c in p):
    t+=1
if any(c in string.punctuation for c in p):
    t+=1
if l<6 or t<2:
    result="Weak"
elif l>=10 and t==4:
    result="Strong"
else:
    result="Moderate"
print(f"{p} is {result}")
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 4\_PAH\_Updated

Attempt : 1  
Total Mark : 60  
Marks Obtained : 60

#### Section 1 : Coding

##### 1. Problem Statement

Ella is designing a messaging application that needs to handle long text messages efficiently. To optimize storage and transmission, she plans to implement a text compression feature that replaces consecutive repeated characters with the character followed by its count, while leaving non-repeated characters unchanged.

Help Ella create a recursive function to achieve this compression without altering the original message's meaning.

Function Specification: `def compress_string(*args)`

##### ***Input Format***

The input consists of a single line containing the string to be compressed.

### Output Format

The output consists of a single line containing the compressed string.

Refer to the sample output for the formatting specifications.

### Sample Test Case

Input: aaaBBBccc

Output: a3B3c3

### Answer

```
# You are using Python
def compress_strings(*args):
    s=args[0]
    def compress(i,result):
        if i>=len(s):
            return result
        c=1
        while i+c<len(s)and s[i]==s[i+c]:
            c+=1
        result+=s[i]+(str(c)if c>1 else "")
        return compress(i+c,result)
    print(compress(0,""))
a=input()
compress_strings(a)
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Sophia is developing a feature for her online banking application that calculates the total sum of digits in customers' account numbers. This sum is used to generate unique verification codes for secure transactions. She needs a program that takes an account number as input and outputs the sum of its digits.

Help Sophia to complete her task.



Function Specification: def sum\_digits(num)

**Input Format**

The input consists of an integer, representing the customer's account number.

**Output Format**

The output prints an integer representing the sum of the digits of the account number.

Refer to the sample output for formatting specifications.

**Sample Test Case**

Input: 123245

Output: 17

**Answer**

```
num = int(input())
# You are using Python
def sum_digits(num):
    sum=0
    n=num
    while n>0:
        a=n%10
        sum+=a
        n//=10
    return sum

sum = sum_digits(num)
print(sum)
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Ravi is working on analyzing a set of integers to determine how many of them are divisible by 3 and how many are divisible by 5. He decides to use

lambda functions to filter and count the numbers based on their divisibility.

Write a program that takes a list of integers, calculates how many numbers are divisible by 3, and how many are divisible by 5, and then prints the results.

Additionally, the program should calculate the total sum of all numbers divisible by 3 and divisible by 5 separately.

### ***Input Format***

The first line contains an integer  $n$ , representing the number of integers in the list.

The second line contains  $n$  space-separated integers.

### ***Output Format***

The first line should print the count of numbers divisible by 3.

The second line should print the count of numbers divisible by 5.

The third line should print the sum of numbers divisible by 3.

The fourth line should print the sum of numbers divisible by 5.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 6  
3 5 6 10 15 20  
Output: 3  
4  
24  
50

### ***Answer***

```
# You are using Python
n=int(input())
```

```
num=list(map(int,input().split()))
div_3=list(filter(lambda x:x%3==0,num))
div_5=list(filter(lambda x:x%5==0,num))
print(len(div_3))
print(len(div_5))
print(sum(div_3))
print(sum(div_5))
```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Create a Python program to monitor temperatures in a greenhouse using two sensors. Calculate and display the absolute temperature difference between the two sensor readings to ensure proper temperature control.

Note: Use the abs() built-in function.

##### ***Input Format***

The first line consists of a floating-point number, representing the temperature reading from Sensor 1.

The second line consists of a floating-point number, representing the temperature reading from Sensor 2.

##### ***Output Format***

The output displays the absolute temperature difference between Sensor 1 and Sensor 2, rounded to two decimal places.

Refer to the sample output for the exact format.

##### ***Sample Test Case***

Input: 33.2

26.7

Output: Temperature difference: 6.50 °C

##### ***Answer***

```
# You are using Python
a=float(input())
b=float(input())
d=abs(a-b)
print(F"Temperature difference: {d:.2f} °C")
```

**Status :** Correct

**Marks :** 10/10

## 5. Problem Statement

Hussain wants to create a program to calculate a person's BMI (Body Mass Index) based on their weight in kilograms and height in meters. The BMI is a measure of a person's body fat relative to their height.

Your program should take user input for weight and height, calculate the BMI, and display the result.

Function Signature: `calculate_bmi(weight, height)`

Formula:  $BMI = \text{Weight} / (\text{Height})^2$

### ***Input Format***

The first line of input consists of a positive floating-point number, the person's weight in kilograms.

The second line of input consists of a positive floating-point number, the person's height in meters.

### ***Output Format***

The output displays "Your BMI is: [BM]" followed by a float value representing the calculated BMI, rounded off two decimal points.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 70.0

1.75

Output: Your BMI is: 22.86

**Answer**

```
weight = float(input())
height = float(input())

# You are using Python
def calculate_bmi(weight,height):
    bmi=weight/((height)**2)
    print("Your BMI is: ",round(bmi,2))

calculate_bmi(weight, height)
```

**Status :** Correct

**Marks : 10/10**

## 6. Problem Statement

Alice works at a digital marketing company, where she analyzes large datasets. One day, she's tasked with processing customer ID numbers, which are long numeric sequences.

To simplify her task, Alice needs to calculate the digital root of each ID. The digital root is obtained by repeatedly summing the digits of a number until a single digit remains.

Help Alice write a program that reads a customer ID number, calculates its digital root, and prints the result using a loop-based approach.

For example, the sum of the digits of 98675 is  $9 + 8 + 6 + 7 + 5 = 35$ , then  $3 + 5 = 8$ , which is the digital root.

Function prototype: `def digital_root(num)`

**Input Format**

The input consists of an integer num.

**Output Format**

The output prints an integer representing the sum of digits for a given number until a single digit is obtained.

Refer to the sample output for the formatting specifications.

**Sample Test Case**

Input: 451110

Output: 3

**Answer**

```
num = int(input())
def digital_root(num):
    n=num
    sum=0
    while n>0:
        r=n%10
        sum+=r
        n//=10
    m=0
    while sum>0:
        c=sum%10
        m+=c
        sum//=10
    return m
print(digital_root(num))
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 5\_MCQ

Attempt : 1  
Total Mark : 20  
Marks Obtained : 14

#### Section 1 : MCQ

1. Fill in the code in order to get the following output.

Output:

Tuple: (1, 3, 4)

Max value: 4

t=(1,)

```
_____  
print("Tuple:" ,t)  
print("Max value:",_____)
```

**Answer**

1) t=t+(3,4)2) max(t)

**Status : Correct**

**Marks : 1/1**

2. Which of the following is a Python tuple?

**Answer**

(1, 2, 3)

**Status :** Correct

**Marks :** 1/1

3. What will be the output of the following code?

```
a=(1,2,3,4)
print(sum(a,3))
```

**Answer**

The method sum() doesn't exist for tuples

**Status :** Wrong

**Marks :** 0/1

4. If 'a' is a dictionary with some key-value pairs, what does a.popitem() do?

**Answer**

Removes the key-value pair for the key given as an argument

**Status :** Wrong

**Marks :** 0/1

5. What is the output of the following code?

```
a={1:"A",2:"B",3:"C"}
b=a.copy()
b[2]="D"
print(a)
```

**Answer**

{1: 'A', 2: 'D', 3: 'C'}

**Status :** Wrong

**Marks :** 0/1

6. What is the result of print(type({})) is set)?



**Answer**

False

**Status :** Correct

**Marks :** 1/1

7. What will be the output for the following code?

```
t1 = (1, 2, 4, 3)
t2 = (1, 2, 3, 4)
print(t1 < t2)
```

**Answer**

Error

**Status :** Wrong

**Marks :** 0/1

8. What will be the output of the following program?

```
set1 = {1, 2, 3}
set2 = set1.copy()
set2.add(4)
print(set1)
```

**Answer**

{1, 2, 3}

**Status :** Correct

**Marks :** 1/1

9. Suppose t = (1, 2, 4, 3), which of the following is incorrect?

**Answer**

t[3] = 45

**Status :** Correct

**Marks :** 1/1

10. What is the output of the following?

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}
print(set1.issubset(set2))
print(set2.issuperset(set1))
```

**Answer**

TrueFalse

**Status :** Wrong

**Marks :** 0/1

11. Which of the following statements is used to create an empty tuple?

**Answer**

( )

**Status :** Correct

**Marks :** 1/1

12. What is the output of the following code?

```
a=(1,2,(4,5))
b=(1,2,(3,4))
print(a<b)
```

**Answer**

False

**Status :** Correct

**Marks :** 1/1

13. Which of the following isn't true about dictionary keys?

**Answer**

Keys must be immutable

**Status :** Wrong

**Marks :** 0/1

14. Predict the output of the following Python program

```
init_tuple_a = 1, 2, 8
```

```
init_tuple_b = (1, 2, 7)
set1=set(init_tuple_b)
set2=set(init_tuple_a)
print (set1 | set2)
print (init_tuple_a | init_tuple_b)
```

**Answer**

{1, 2, 7, 8}TypeError: unsupported operand type

**Status :** Correct

**Marks :** 1/1

15. What will be the output for the following code?

```
a=(1,2,3)
b=('A','B','C')
c=zip(a,b)
```

```
print(c)
print(tuple(c))
```

**Answer**

((1, 'A'), (2, 'B'), (3, 'C'))

**Status :** Correct

**Marks :** 1/1

16. Which of the statements about dictionary values is false?

**Answer**

Values of a dictionary must be unique

**Status :** Correct

**Marks :** 1/1

17. What will be the output?

```
a={'B':5,'A':9,'C':7}
print(sorted(a))
```

**Answer**

['A', 'B', 'C'].

**Status :** Correct

**Marks :** 1/1

18. Set  $s1 = \{1, 2, 4, 3\}$  and  $s2 = \{1, 5, 4, 6\}$ , find  $s1 \& s2$ ,  $s1 - s2$ ,  $s1 \mid s2$  and  $s1 \wedge s2$ .

**Answer**

$s1 \& s2 = \{1, 4\}$   $s1 - s2 = \{2, 3\}$   $s1 \wedge s2 = \{2, 3, 5, 6\}$   $s1 \mid s2 = \{1, 2, 3, 4, 5, 6\}$

**Status :** Correct

**Marks :** 1/1

19. What is the output of the following code?

```
a={"a":1,"b":2,"c":3}
b=dict(zip(a.values(),a.keys()))
print(b)
```

**Answer**

{1: 'a', 2: 'b', 3: 'c'}

**Status :** Correct

**Marks :** 1/1

20. What is the output of the below Python code?

```
list1 = [1, 2, 3]
list2 = [5, 6, 7]
list3 = [10, 11, 12]
set1 = set(list2)
set2 = set(list1)
set1.update(set2)
set1.update(list3)
print(set1)
```

**Answer**

{1, 2, 3, 5, 6, 7, 10, 11, 12}

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 5\_COD

Attempt : 1  
Total Mark : 50  
Marks Obtained : 50

### Section 1 : Coding

#### 1. Problem Statement

James is managing a list of inventory items in a warehouse. Each item is recorded as a tuple, where the first element is the item ID and the second element is a list of quantities available for that item. James needs to filter out all quantities that are above a certain threshold to find items that have a stock level above this limit.

Help James by writing a program to process these tuples, filter the quantities from all the available items, and display the results.

Note:

Use the filter() function to filter out the quantities greater than the specified threshold for each item's stock list.

### ***Input Format***

The first line of input consists of an integer N, representing the number of tuples.

The next N lines each contain a tuple in the format (ID, [quantity1, quantity2, ...]), where ID is an integer and the list contains integers.

The final line consists of an integer threshold, representing the quantity threshold.

### ***Output Format***

The output should be a single line displaying the filtered quantities, space-separated. Each quantity is strictly greater than the given threshold.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 2

(1, [1, 2])

(2, [3, 4])

2

Output: 3 4

### ***Answer***

# You are using Python

```
n=int(input())
```

```
items=[]
```

```
for i in range(n):
```

```
    l=input()
```

```
    item=eval(l)
```

```
    items.append(item)
```

```
threshold=int(input())
```

```
result=[]
```

```
for m,n in items:
```

```
    filtered=list(filter(lambda x:x>threshold,n))
```

```
    result.extend(filtered)
```

```
print(*result)
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Liam is analyzing a list of product IDs from a recent sales report. He needs to determine how frequently each product ID appears and calculate the following metrics:

Frequency of each product ID: A dictionary where the key is the product ID and the value is the number of times it appears. Total number of unique product IDs. Average frequency of product IDs: The average count of all product IDs.

Write a program to read the product IDs, compute these metrics, and output the results.

### Example

Input:

```
6 //number of product ID
101
102
101
103
101
102 //product IDs
```

Output:

```
{101: 3, 102: 2, 103: 1}
```

Total Unique IDs: 3

Average Frequency: 2.00

Explanation:

Input 6 indicates that you will enter 6 product IDs.

A dictionary is created to track the frequency of each product ID.

Input 101: Added with a frequency of 1.

Input 102: Added with a frequency of 1.

Input 101: Frequency of 101 increased to 2.

Input 103: Added with a frequency of 1.

Input 101: Frequency of 101 increased to 3.

Input 102: Frequency of 102 increased to 2.

The dictionary now contains 3 unique IDs: 101, 102, and 103.

Total Unique is 3.

The average frequency is 2.00.

### ***Input Format***

The first line of input consists of an integer  $n$ , representing the number of product IDs.

The next  $n$  lines each contain a single integer, each representing a product ID.

### ***Output Format***

The first line of output displays the frequency dictionary, which maps each product ID to its count.

The second line displays the total number of unique product IDs, preceded by "Total Unique IDs: ".

The third line displays the average frequency of the product IDs. This is calculated by dividing the total number of occurrences of all product IDs by the total number of unique product IDs, rounded to two decimal places. It is preceded by "Average Frequency: ".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 6  
101



102  
101  
103  
101  
102

Output: {101: 3, 102: 2, 103: 1}

Total Unique IDs: 3

Average Frequency: 2.00

### **Answer**

```
n=int(input())
f={}
for i in range(n):
    p=int(input())
    if p in f:
        f[p]+=1
    else:
        f[p]=1
t=len(f)
tc=sum(f.values())
af=tc/t
print(f)
print("Total Unique IDs:",t)
print(f"Average Frequency:{af:.2f}")
```

**Status : Correct**

**Marks : 10/10**

### **3. Problem Statement**

Professor Adams needs to analyze student participation in three recent academic workshops. She has three sets of student IDs: the first set contains students who registered for the workshops, the second set contains students who actually attended, and the third set contains students who dropped out.

Professor Adams needs to determine which students who registered also attended, and then identify which of these students did not drop out.

Help Professor Adams identify the students who registered, attended, and did not drop out of the workshops.

### ***Input Format***

The first line of input consists of integers, representing the student IDs who registered for the workshops.

The second line consists of integers, representing the student IDs who attended the workshops.

The third line consists of integers, representing the student IDs who dropped out of the workshops.

### ***Output Format***

The first line of output displays the intersection of the first two sets, which shows the IDs of students who registered and attended.

The second line displays the result after removing student IDs that are in the third set (dropped out), showing the IDs of students who both attended and did not drop out.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 1 2 3

2 3 4

3 4 5

Output: {2, 3}

{2}

### ***Answer***

```
# You are using Python
r=set(map(int,input().split()))
a=set(map(int,input().split()))
do=set(map(int,input().split()))
ra=r&a
m=ra-do
print(ra)
print(m)
```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Gowshik is working on a task that involves taking two lists of integers as input, finding the element-wise sum of the corresponding elements, and then creating a tuple containing the sum values.

Write a program to help Gowshik with this task.

Example:

Given list:

[1, 2, 3, 4]

[3, 5, 2, 1]

An element-wise sum of the said tuples: (4, 7, 5, 5)

##### ***Input Format***

The first line of input consists of a single integer  $n$ , representing the length of the input lists.

The second line of input consists of  $n$  integers separated by commas, representing the elements of the first list.

The third line of input consists of  $n$  integers separated by commas, representing the elements of the second list.

##### ***Output Format***

The output is a single line containing a tuple of integers separated by commas, representing the element-wise sum of the corresponding elements from the two input lists.

Refer to the sample output for the formatting specifications.

##### ***Sample Test Case***

Input: 4  
1, 2, 3, 4

3, 5, 2, 1

Output: (4, 7, 5, 5)

**Answer**

```
# You are using Python
a=int(input())
n=list(map(int,input().split(",")))
n1=list(map(int,input().split(",")))
d=[]
for i in range(a):
    d.append(n[i]+n1[i])
print(tuple(d))
```

**Status :** Correct

**Marks : 10/10**

## 5. Problem Statement

Ella is analyzing the sales data for a new online shopping platform. She has a record of customer transactions where each customer's data includes their ID and a list of amounts spent on different items. Ella needs to determine the total amount spent by each customer and identify the highest single expenditure for each customer.

Your task is to write a program that computes these details and displays them in a dictionary.

### **Input Format**

The first line of input consists of an integer  $n$ , representing the number of customers.

Each of the next  $n$  lines contains a numerical customer ID followed by integers representing the amounts spent on different items.

### **Output Format**

The output displays a dictionary where the keys are customer IDs and the values are lists containing two integers: the total expenditure and the maximum single expenditure.

Refer to the sample output for formatting specifications.

**Sample Test Case**

Input: 2

101 100 150 200

102 50 75 100

Output: {101: [450, 200], 102: [225, 100]}

**Answer**

# You are using Python

```
n=int(input())
```

```
f={}
```

```
for i in range(n):
```

```
    m=list(map(int,input().split()))
```

```
    f[m[0]]=sum(m[1:]),max(m[1:])
```

```
print(f)
```

**Status : Correct**

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 5\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 39

### Section 1 : Coding

#### 1. Problem Statement

Alex is working with grayscale pixel intensities from an old photo that has been scanned in a single row. To detect edges in the image, Alex needs to calculate the differences between each pair of consecutive pixel intensities.

Your task is to write a program that performs this calculation and returns the result as a tuple of differences.

#### ***Input Format***

The first line of input contains an integer  $n$ , representing the number of pixel intensities.

The second line contains  $n$  space-separated integers representing the pixel intensities.

### **Output Format**

The output displays a tuple containing the absolute differences between consecutive pixel intensities.

Refer to the sample output for format specifications.

### **Sample Test Case**

Input: 5

200 100 20 80 10

Output: (100, 80, 60, 70)

### **Answer**

```
n=int(input())
p=list(map(int,input().split()))
d=tuple(abs(p[i]-p[i+1]) for i in range(n-1))
print(d)
```

**Status :** Correct

**Marks : 10/10**

## **2. Problem Statement**

Alex is tasked with managing the membership lists of several exclusive clubs. Each club has its own list of members, and Alex needs to determine the unique members who are part of exactly one club when considering all clubs together.

Your goal is to help Alex by writing a program that calculates the symmetric difference of membership lists from multiple clubs and then finds the total number of unique members.

### **Input Format**

The first line of input consists of an integer  $k$ , representing the number of clubs.

The next  $k$  lines each contain a space-separated list of integers, where each integer represents a member's ID.

### **Output Format**

The first line of output displays the symmetric difference of the membership lists as a set.

The second line displays the sum of the elements in this symmetric difference.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 3

1 2 3

2 3 4

5 6 7

Output: {1, 4, 5, 6, 7}

23

### **Answer**

```
n=int(input())
```

```
c=[]
```

```
for i in range(n):
```

```
    m=set(map(int,input().split()))
```

```
    c.append(m)
```

```
from functools import reduce
```

```
um=reduce(lambda x,y:x.symmetric_difference(y),c)
```

```
print(um)
```

```
print(sum(um))
```

**Status :** Partially correct

**Marks :** 9/10

### **3. Problem Statement**

Riley is analyzing DNA sequences and needs to determine which bases match at the same positions in two given DNA sequences. Each DNA sequence is represented as a tuple of integers, where each integer corresponds to a DNA base.

Your task is to write a program that compares these two sequences and



identifies the bases that match at the same positions and print it.

### ***Input Format***

The first line of input consists of an integer n, representing the size of the first tuple.

The second line contains n space-separated integers, representing the elements of the first DNA sequence tuple.

The third line of input consists of an integer m, representing the size of the second tuple.

The fourth line contains m space-separated integers, representing the elements of the second DNA sequence tuple.

### ***Output Format***

The output is a space-separated integer of the matching bases at the same positions in both sequences.

Refer to the sample output for format specifications.

### ***Sample Test Case***

Input: 4

5 1 8 4

4

4 1 8 2

Output: 1 8

### ***Answer***

```
n=int(input())
s=list(map(int,input().split()))
m=int(input())
l=list(map(int,input().split()))
r=[]
for i in range(min(n,m)):
    if s[i]==l[i]:
        r.append(s[i])
print(*r)
```

Status : Correct

Marks : 10/10

#### 4. Problem Statement

Samantha is working on a text analysis tool that compares two words to find common and unique letters. She wants a program that reads two words, w1, and w2, and performs the following operations:

Print the letters common to both words, in alphabetical order. Print the letters that are unique to each word, in alphabetical order. Determine if the set of letters in the first word is a superset of the letters in the second word. Check if there are no common letters between the two words and print the result as a Boolean value.

Ensure the program ignores case differences and leading/trailing spaces in the input words.

Your task is to help Samantha in implementing the same.

#### ***Input Format***

The first line of input consists of a string representing the first word, w1.

The second line consists of a string representing the second word, w2.

#### ***Output Format***

The first line of output should display the sorted letters common to both words, printed as a list.

The second line should display the sorted letters that are unique to each word, printed as a list.

The third line should display a Boolean value indicating if the set of letters in w1 is a superset of the set of letters in w2.

The fourth line should display a Boolean value indicating if there are no common letters between w1 and w2.

Refer to the sample output for the formatting specifications.

**Sample Test Case**

Input: program

Peace

Output: ['a', 'p']

['c', 'e', 'g', 'm', 'o', 'r']

False

False

**Answer**

# You are using Python

```
s1=input().strip().lower()
```

```
s2=input().strip().lower()
```

```
l=set(s1)
```

```
m=set(s2)
```

```
c=sorted(l&m)
```

```
print(c)
```

```
u=sorted(l^m)
```

```
print(u)
```

```
print(l>=m)
```

```
print(l.isdisjoint(m))
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 5\_PAH

Attempt : 1  
Total Mark : 60  
Marks Obtained : 46

### Section 1 : Coding

#### 1. Problem Statement

Rishi is working on a program to manipulate a set of integers. The program should allow users to perform the following operations:

Find the maximum value in the set. Find the minimum value in the set. Remove a specific number from the set.

The program should handle these operations based on user input. If the user inputs an invalid operation choice, the program should indicate that the choice is invalid.

#### ***Input Format***

The first line contains space-separated integers that will form the initial set. Each integer x is separated by a space.

The second line contains an integer `ch`, representing the user's choice:

- 1 to find the maximum value
- 2 to find the minimum value
- 3 to remove a specific number from the set

If `ch` is 3, the third line contains an integer `n1`, which is the number to be removed from the set.

### ***Output Format***

The first line of output prints the original set in descending order.

For choice 1: Print the maximum value from the set.

For choice 2: Print the minimum value from the set.

For choice 3: Print the set after removing the specified number, in descending order.

For invalid choices: Print "Invalid choice".

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 1 2 3 4 5

1

Output: {5, 4, 3, 2, 1}

5

### ***Answer***

```
# You are using Python
n=list(map(int,input().split()))
c=int(input())
n1=sorted(n,reverse=True)
print("{"+",".join(map(str,n))+"}")
if c==1:
    print(max(n))
elif c==2:
    print(min(n))
```

```
elif c==3:
    r=int(input())
    if r in n:
        n.remove(r)
        n1=sorted(n,reverse=True)
        print("{"+",".join(map(str,n))+"}")
    else:
        print("Invalid choice")
```

**Status : Wrong**

**Marks : 0/10**

## 2. Problem Statement

Tom wants to create a dictionary that lists the first n prime numbers, where each key represents the position of the prime number, and the value is the prime number itself.

Help Tom generate this dictionary based on the input she provides.

### ***Input Format***

The input consists of an integer n, representing the number of prime numbers Tom wants to generate.

### ***Output Format***

The output displays the generated dictionary where each key is an integer from 1 to n, and the corresponding value is the prime number.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 4

Output: {1: 2, 2: 3, 3: 5, 4: 7}

### ***Answer***

```
def isp(num):
```

```

    if n<2:
        return False
    for i in range(2,int(num**0.5)+1):
        if num%i==0:
            return False
    return True
n=int(input())
p={}
c=0
num=2
while c<n:
    if isp(num):
        c+=1
        p[c]=num
        num+=1
print(p)

```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Mia is organizing a list of integers into a series of pairs for his new project. She wants to create pairs of consecutive integers from the list. The last integer should be paired with None to complete the series. The pairing happens as follows: ((Element 1, Element 2), (Element 2, Element 3)..... (Element n, None)).

Your task is to help Henry by writing a Python program that reads a list of integers, forms these pairs, and displays the result in tuple format.

#### **Input Format**

The first line of input consists of an integer n, representing the number of elements in the tuple.

The second line of input contains n space-separated integers, representing the elements of the tuple.

#### **Output Format**

The output displays a tuple containing pairs of consecutive integers from the input. The last integer in the tuple is paired with 'None'.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 3

5 10 15

Output: ((5, 10), (10, 15), (15, None))

### **Answer**

```
# You are using Python
n=int(input())
e=list(map(int,input().split()))
p=[]
for i in range(n-1):
    p.append((e[i],e[i+1]))
p.append((e[-1],None))
print(tuple(p))
```

**Status :** Correct

**Marks :** 10/10

## **4. Problem Statement**

Sophia is organizing a list of event IDs representing consecutive days of an event. She needs to group these IDs into consecutive sequences. For example, if the IDs 3, 4, and 5 appear consecutively, they should be grouped.

Write a program that helps Sophia by reading the total number of event IDs and the IDs themselves, then display each group of consecutive IDs in tuple format.

### **Input Format**

The first line of input consists of an integer  $n$ , representing the number of event IDs.

The next  $n$  lines contain integers representing the event IDs, where each integer



corresponds to an event ID.

### **Output Format**

The output should display each group of consecutive event IDs in a tuple format. Each group should be printed on a new line, and single event IDs should be displayed as a single-element tuple.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 3

1  
2  
3

Output: (1, 2, 3)

### **Answer**

```
n=int(input())
ids=[int(input()) for i in range(n)]
ids.sort()
g=[ids[0]]
for i in range(1,n):
    if ids[i]==ids[i-1]+1:
        g.append(ids[i])
    else:
        print(tuple(g)if len(g)>1 else(g[0],))
        g=[ids[i]]
print(tuple(g)if len(g)>1 else(g[0],))
```

**Status :** Partially correct

**Marks :** 6/10

## **5. Problem Statement**

Jordan is creating a program to process a list of integers. The program should take a list of integers as input, remove any duplicate integers while preserving their original order, concatenate the remaining unique integers into a single string, and then print the result.

Help Jordan in implementing the same.

**Input Format**

The input consists of space-separated integers representing the elements of the set.

**Output Format**

The output prints a single integer formed by concatenating the unique integers from the input in the order they appeared.

Refer to the sample output for the formatting specifications.

**Sample Test Case**

Input: 11 11 33 50

Output: 113350

**Answer**

```
# You are using Python
m=input().split()
n=set()
s=""
for i in m:
    if i not in n:
        n.add(i)
        s+=i
print(s)
```

**Status :** Correct

**Marks : 10/10**

## 6. Problem Statement

Maya wants to create a dictionary that maps each integer from 1 to a given number  $n$  to its square. She will use this dictionary to quickly reference the square of any number up to  $n$ .

Help Maya generate this dictionary based on the input she provides.

### ***Input Format***

The input consists of an integer n, representing the highest number for which Maya wants to calculate the square.

### ***Output Format***

The output displays the generated dictionary where each key is an integer from 1 to n, and the corresponding value is its square.

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 5

Output: {1: 1, 2: 4, 3: 9, 4: 16, 5: 25}

### ***Answer***

```
# You are using Python
n=int(input())
s={i:i*i for i in range(1,n+1)}
print(s)
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 6\_MCQ

Attempt : 1  
Total Mark : 20  
Marks Obtained : 16

#### Section 1 : MCQ

1. What happens if an exception is not caught in the except clause?

**Answer**

The program will display a traceback error and stop execution

**Status : Correct**

**Marks : 1/1**

2. How do you create a user-defined exception in Python?

**Answer**

By using the raise keyword

**Status : Wrong**

**Marks : 0/1**

3. What will be the output of the following Python code?

```
# Predefined lines to simulate the file content
lines = [
    "This is 1st line",
    "This is 2nd line",
    "This is 3rd line",
    "This is 4th line",
    "This is 5th line"
]

print("Name of the file: foo.txt")

# Print the first 5 lines from the predefined list
for index in range(5):
    line = lines[index]
    print("Line No %d - %s" % (index + 1, line.strip()))
```

**Answer**

Compile Time Error

**Status : Wrong**

**Marks : 0/1**

4. Match the following:

- a) f.seek(5,1) i) Move file pointer five characters behind from the current position
- b) f.seek(-5,1) ii) Move file pointer to the end of a file
- c) f.seek(0,2) iii) Move file pointer five characters ahead from the current position
- d) f.seek(0) iv) Move file pointer to the beginning of a file

**Answer**

a-iii, b-i, c-ii, d-iv

**Status : Correct**

**Marks : 1/1**

5. How do you rename a file?

**Answer**

`os.rename(existing_name, new_name)`

**Status : Correct**

**Marks : 1/1**

6. What is the purpose of the except clause in Python?

**Answer**

To handle exceptions during code execution

**Status : Correct**

**Marks : 1/1**

7. Which of the following is true about

`fp.seek(10,1)`

**Answer**

Move file pointer ten characters ahead from the current position

**Status : Correct**

**Marks : 1/1**

8. Which clause is used to clean up resources, such as closing files in Python?

**Answer**

`finally`

**Status : Correct**

**Marks : 1/1**

9. What is the correct way to raise an exception in Python?

**Answer**

`raise Exception()`

**Status : Correct**

**Marks : 1/1**

10. What will be the output of the following Python code?

```
f = None
for i in range (5):
    with open("data.txt", "w") as f:
        if i > 2:
            break
print(f.closed)
```

**Answer**

True

**Status :** Correct

**Marks :** 1/1

11. What is the output of the following code?

```
try:
    x = "hello" + 5
except TypeError:
    print("Type Error occurred")
finally:
    print("This will always execute")
```

**Answer**

Type Error occurredThis will always execute

**Status :** Correct

**Marks :** 1/1

12. What is the output of the following code?

```
try:
    x = 1 / 0
except ZeroDivisionError:
    print("Caught division by zero error")
finally:
    print("Executed")
```

**Answer**

Caught division by zero errorExecuted

**Status :** Correct

**Marks :** 1/1

13. What is the difference between r+ and w+ modes?

**Answer**

in r+ the pointer is initially placed at the beginning of the file and the pointer is at the end for w+

**Status :** Correct

**Marks :** 1/1

14. What is the output of the following code?

```
class MyError(Exception):  
    pass
```

```
try:  
    raise MyError("Something went wrong")  
except MyError as e:  
    print(e)
```

**Answer**

Something went wrong

**Status :** Correct

**Marks :** 1/1

15. Which of the following is true about the finally block in Python?

**Answer**

The finally block is always executed, regardless of whether an exception occurs or not

**Status :** Correct

**Marks :** 1/1

16. Fill in the blanks in the following code of writing data in binary files.



```

import _____ (1)
rec=[]
while True:
    rn=int(input("Enter"))
    nm=input("Enter")
    temp=[rn, nm]
    rec.append(temp)
    ch=input("Enter choice (y/N)")
    if ch.upper=="N":
        break
f.open("stud.dat",_____)(2)
_____.dump(rec,f)(3)
_____.close()(4)

```

**Answer**

(pickle,wb,pickle,f)

**Status : Correct**

**Marks : 1/1**

17. Fill in the code in order to get the following output:

Output:

Name of the file: ex.txt

```

fo = open(_____(1), "wb")
print("Name of the file: ",_____(2))

```

**Answer**

1) "ex.txt" 2) fo.name()

**Status : Wrong**

**Marks : 0/1**

18. Fill the code to in order to read file from the current position.

Assuming exp.txt file has following 3 lines, consider current file position is beginning of 2nd line

Meri,25

John,21

Raj,20

Ouptput:

['John,21\n','Raj,20\n']

```
f = open("exp.txt", "w+")  
_____(1)  
print _____(2)
```

**Answer**

1) f.seek(0, 1) 2) f.readlines()

**Status : Correct**

**Marks : 1/1**

19. What is the default value of reference\_point in the following code?

```
file_object.seek(offset [,reference_point])
```

**Answer**

0

**Status : Correct**

**Marks : 1/1**

20. What happens if no arguments are passed to the seek function?

**Answer**

error

**Status : Wrong**

**Marks : 0/1**

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 6\_COD

Attempt : 1  
Total Mark : 50  
Marks Obtained : 47.5

### Section 1 : Coding

#### 1. Problem Statement

A retail store requires a program to calculate the total cost of purchasing a product based on its price and quantity. The program performs validation to ensure valid inputs and handles specific error conditions using exceptions:

Price Validation: If the price is zero or less, raise a ValueError with the message: "Invalid Price". Quantity Validation: If the quantity is zero or less, raise a ValueError with the message: "Invalid Quantity". Cost Threshold: If the total cost exceeds 1000, raise RuntimeError with the message: "Excessive Cost".

#### ***Input Format***

The first line of input consists of a double value, representing the price of a product.

The second line consists of an integer, representing the quantity of the product.

### **Output Format**

If the calculation is successful, print the total cost rounded to one decimal place.

If the price is zero or less prints "Invalid Price".

If the quantity is zero or less prints "Invalid Quantity".

If the total cost exceeds 1000, prints "Excessive Cost".

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 20.0

5

Output: 100.0

### **Answer**

# You are using Python

try:

p=float(input())

q=int(input())

if p<=0:

raise ValueError("Invalid Price")

if q<=0:

raise ValueError("Invalid Quantity")

t=p\*q

if t>1000:

raise RuntimeError("Excessive Cost")

print(f"{t:.1f}")

except ValueError as ve:

print(ve)

except RuntimeError as re:

print(re)

**Status : Correct**

**Marks : 10/10**

## 2. Problem Statement

Tara is a content manager who needs to perform case conversions for various pieces of text and save the results in a structured manner.

She requires a program to take a user's input string, save it in a file, and then retrieve and display the string in both upper-case and lower-case versions. Help her achieve this task efficiently.

File Name: text\_file.txt

### ***Input Format***

The input consists of a single line containing a string provided by the user.

### ***Output Format***

The first line displays the original string read from the file in the format: "Original String: {original\_string}".

The second line displays the upper-case version of the original string in the format: "Upper-Case String: {upper\_case\_string}".

The third line displays the lower-case version of the original string in the format: "Lower-Case String: {lower\_case\_string}".

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: #SpecialSymBoLs1234

Output: Original String: #SpecialSymBoLs1234

Upper-Case String: #SPECIALSYMBOLS1234

Lower-Case String: #specialsymbols1234

### ***Answer***

```
# You are using Python
f=open("text_file.txt","w")
a=input()
f.write(a)
```

```
f.close()
f=open("text_file.txt","r")
b=f.read()
print("Original String:",b)
print("Upper-case String:",b.upper())
print("Lower-case String:",b.lower())
f.close()
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

In a voting system, a person must be at least 18 years old to be eligible to vote. If a user enters an age below 18, the system should raise a user-defined exception indicating that they are not eligible to vote.

#### ***Input Format***

The input contains a positive integer representing age.

#### ***Output Format***

If the age is less than 18, the output displays "Not eligible to vote".

Otherwise, the output displays "Eligible to vote".

Refer to the sample output for formatting specifications.

#### ***Sample Test Case***

Input: 18

Output: Eligible to vote

#### ***Answer***

# You are using Python

try:

    age=int(input())

    if age<18:

        raise Exception("Not eligible to vote")

    print("Eligible to vote")

except Exception as e:  
print(e)

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

Sophie enjoys playing with words and wants to count the number of words in a sentence. She inputs a sentence, saves it to a file, and then reads it from the file to count the words.

Write a program to determine the number of words in the input sentence.

File Name: sentence\_file.txt

##### **Input Format**

The input consists of a single line of text containing words separated by spaces.

##### **Output Format**

The output displays the count of words in the sentence.

Refer to the sample output for the formatting specifications.

##### **Sample Test Case**

Input: Four Words In This Sentence

Output: 5

##### **Answer**

```
# You are using Python
f=open("sentence_file.txt","w")
a=input()
f.write(a)
f.close()
f=open("sentence_file.txt","r")
b=f.read()
c=b.split()
```

```
print(len(c))
```

**Status :** Correct

**Marks :** 10/10

## 5. Problem Statement

Write a program that calculates the average of a list of integers. The program prompts the user to enter the length of the list (n) and each element of the list. It performs error handling to ensure that the length of the list is a non-negative integer and that each input element is a numeric value.

### **Input Format**

The first line of the input is an integer n, representing the length of the list as a positive integer.

The second line of the input consists of an element of the list as an integer, separated by a new line.

### **Output Format**

If the length of the list is not a positive integer or zero, the output displays "Error: The length of the list must be a non-negative integer."

If a non-numeric value is entered for the length of the list, the output displays "Error: You must enter a numeric value."

If a non-numeric value is entered for a list element, the output displays "Error: You must enter a numeric value."

If the inputs are valid, the program calculates and prints the average of the provided list of integers with two decimal places: "The average is: [average]".

Refer to the sample output for the formatting specifications.



### Sample Test Case

Input: -2

1  
2

Output: Error: The length of the list must be a non-negative integer.

### Answer

try:

```
n=input()
```

```
if not n.isdigit():
```

```
    raise ValueError("Error:You must enter a numeric value.")
```

```
n=int(n)
```

```
if n<=0:
```

```
    print("Error:The length of the list must be a non-negative integer.")
```

```
else:
```

```
    t=0
```

```
    for i in range(n):
```

```
        v=input()
```

```
        if not v.lstrip("-").isdigit():
```

```
            raise ValueError("Error:You must enter a numeric value.")
```

```
        t+=int(v)
```

```
    avg=t/n
```

```
    print(f"The average is:{avg:.2f}")
```

```
except ValueError as e:
```

```
    print(e)
```

Status : Partially correct

Marks : 7.5/10

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 6\_CY

Attempt : 1  
Total Mark : 40  
Marks Obtained : 36

### Section 1 : Coding

#### 1. Problem Statement

Implement a program that checks whether a set of three input values can form the sides of a valid triangle. The program defines a function `is_valid_triangle` that takes three side lengths as arguments and raises a `ValueError` if any side length is not a positive value. It then checks whether the sum of any two sides is greater than the third side to determine the validity of the triangle.

#### ***Input Format***

The first line of input consists of an integer A, representing side1.

The second line of input consists of an integer B, representing side2.

The third line of input consists of an integer C, representing side3.

### **Output Format**

The output prints either "It's a valid triangle" if the input side lengths form a valid triangle,

or "It's not a valid triangle" if they do not.

If there is a ValueError, it should print "ValueError: <error\_message>".

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 3

4

5

Output: It's a valid triangle

### **Answer**

# You are using Python

```
def is_valid_triangle(a,b,c):
```

```
    if a<=0 or b<=0 or c<=0:
```

```
        raise ValueError("Side lengths must be positive")
```

```
    if(a+b>c) and (a+c>b) and(b+c>a):
```

```
        return True
```

```
    else:
```

```
        return False
```

```
try:
```

```
    s1=int(input())
```

```
    s2=int(input())
```

```
    s3=int(input())
```

```
    if is_valid_triangle(s1,s2,s3):
```

```
        print("It's a valid triangle")
```

```
    else:
```

```
        print("it's not a valid triangle")
```

```
except ValueError as e:
```

```
    print("ValueError:",e)
```

**Status : Correct**

**Marks : 10/10**

## 2. Problem Statement

Write a program to obtain the start time and end time for the stage event show. If the user enters a different format other than specified, an exception occurs and the program is interrupted. To avoid that, handle the exception and prompt the user to enter the right format as specified.

Start time and end time should be in the format 'YYYY-MM-DD HH:MM:SS'. If the input is in the above format, print the start time and end time. If the input does not follow the above format, print "Event time is not in the format "

### ***Input Format***

The first line of input consists of the start time of the event.

The second line of the input consists of the end time of the event.

### ***Output Format***

If the input is in the given format, print the start time and end time.

If the input does not follow the given format, print "Event time is not in the format".

Refer to the sample output for formatting specifications.

### ***Sample Test Case***

Input: 2022-01-12 06:10:00

2022-02-12 10:10:12

Output: 2022-01-12 06:10:00

2022-02-12 10:10:12

### ***Answer***

```
# You are using Python
from datetime import datetime
try:
    s=input()
    e=input()
    format="%Y-%m-%d" "%H:%M:%S"
```

```
datetime.strptime(s,format)
datetime.strptime(e,format)
print(s)
print(e)
except:
    print("Event time is not in the format")
```

**Status :** Partially correct

**Marks :** 6/10

### 3. Problem Statement

Bob, a data analyst, requires a program to automate the process of analyzing character frequency in a given text. This program should allow the user to input a string, calculate the frequency of each character within the text, save these character frequencies to a file named "char\_frequency.txt," and display the results.

#### ***Input Format***

The input consists of the string.

#### ***Output Format***

The first line prints "Character Frequencies:".

The following lines print the character frequency in the format: "X: Y" where X is the character and Y is the count.

Refer to the sample output for the formatting specifications.

#### ***Sample Test Case***

Input: aaabbbccc

Output: Character Frequencies:

a: 3

b: 3

c: 3

**Answer**

```

# You are using Python
t=input()
f={}
for i in t:
    f[i]=f.get(i,0)+1
with open("char_frequency.txt","w") as file:
    file.write("Character Frequencies:\n")
    for i,count in f.items():
        file.write(f"{i}:{count}\n")
print("Character Frequencies:")
for i,count in f.items():
    print(f"{i}:{count}")

```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

A shopkeeper is recording the daily sales of an item for N days, where the price of the item remains the same for all days. Write a program to calculate the total sales for each day and save them in a file named sales.txt that can store the data for a maximum of 30 days. Then, read the file and display the total earnings for each day.

Note: Total Earnings for each day = Number of Items sold in that day × Price of the item.

##### **Input Format**

The first line of input consists of an integer N, representing the number of days.

The second line of input consists of N space-separated integers representing the number of items sold each day.

The third line of input consists of an integer M, representing the price of the item that is common for all N days.

##### **Output Format**

If the number of days entered exceeds 30 ( $N > 30$ ), the output prints "Exceeding limit!" and terminates.

Otherwise, the code reads the contents of the file and displays the total earnings

for each day on separate lines.

Contents of the file: The total earnings for N days, with each day's earnings appearing on a separate line.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 4

5 10 5 0

20

Output: 100

200

100

0

### **Answer**

# You are using Python

```
n=int(input())
```

```
if n>30:
```

```
    print("Exceeding limit!")
```

```
else:
```

```
    items=input().split()
```

```
    m=int(input())
```

```
    with open("sales.txt","w") as file:
```

```
        for i in range(n):
```

```
            t=int(items[i])*m
```

```
            file.write(str(t)+"\n")
```

```
    with open("sales.txt","r") as file:
```

```
        for i in file:
```

```
            print(i.strip())
```

**Status : Correct**

**Marks : 10/10**

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 6\_PAH

Attempt : 1  
Total Mark : 30  
Marks Obtained : 26

### Section 1 : Coding

#### 1. Problem Statement

Peter manages a student database and needs a program to add students. For each student, Alex inputs their ID and name. The program checks for duplicate IDs and ensures the database isn't full.

If a duplicate or a full database is detected, an appropriate error message is displayed. Otherwise, the student is added, and a confirmation message is shown. The database has a maximum capacity of 30 students, and each student must have a unique ID.

#### ***Input Format***

The first line contains an integer  $n$ , representing the number of students to be added to the school database.



The next n lines each contain two space-separated values, representing the student's ID (integer) and the student's name (string).

### **Output Format**

The output will depend on the actions performed in the code.

If a student is added to the database, the output will display: "Student with ID [ID number] added to the database."

If there is an exception due to a duplicate student ID, the output will display: "Exception caught. Error: Student ID already exists."

If there is an exception due to the database being full, the output will display: "Exception caught. Error: Student database is full."

Refer to the sample outputs for the formatting specifications.

### **Sample Test Case**

Input: 3  
16 Sam  
87 Sabari  
43 Dani

Output: Student with ID 16 added to the database.  
Student with ID 87 added to the database.  
Student with ID 43 added to the database.

### **Answer**

```
# You are using Python
MAX_CAPACITY=30
database={}
n=int(input())
for i in range(n):
    try:
        if len(database)>=MAX_CAPACITY:
            raise Exception("Student database is full.")
        l=input().strip()
```

```
s,name=l.split()
s=int(s)
if s in database:
    raise Exception("Student ID already exists.")
database[s]=name
print(f"Student with ID {s} added to the database.")
except Exception as e:
    print(f"Exception caught. Error: {e}")
```

**Status :** Partially correct

**Marks :** 6/10

## 2. Problem Statement

John is a data analyst who often works with text files. He needs a program that can analyze the contents of a text file and count the number of times a specific character appears in the file.

John wants a simple program that allows him to specify a file and a character to count within that file.

### ***Input Format***

The first line of input consists of the file's name to be analyzed.

The second line of the input consists of the string they want to write within the file.

The third line of the input consists of a character to count within the file.

### ***Output Format***

If the character is found, the output displays "The character 'X' appears {Y} times in the file." where X is the character and Y is the count,

If the character does not appear in the file, the output displays "Character not found."

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: test.txt

This is a test file to check the character count.

e

Output: The character 'e' appears 5 times in the file.

### **Answer**

# You are using Python

```
f=input().strip()
```

```
t=input()
```

```
c=input()
```

```
with open(f,"w") as m:
```

```
    m.write(t)
```

```
with open(f,"r") as m:
```

```
    n=m.read()
```

```
count=n.lower().count(c.lower())
```

```
if count>0:
```

```
    print(f"The character '{c}' appears {count} times in the file.")
```

```
else:
```

```
    print("Character not found in the file.")
```

**Status :** Correct

**Marks :** 10/10

### **3. Problem Statement**

Reeta is playing with numbers. Reeta wants to have a file containing a list of numbers, and she needs to find the average of those numbers. Write a program to read the numbers from the file, calculate the average, and display it.

File Name: user\_input.txt

### **Input Format**

The input file will contain a single line of space-separated numbers (as a string).

These numbers may be integers or decimals.

### **Output Format**

If all inputs are valid numbers, the output should print: "Average of the numbers is: X.XX" (where X.XX is the computed average rounded to two decimal places)

If the input contains invalid data, print: "Invalid data in the input."

Refer to the sample output for format specifications.

### **Sample Test Case**

Input: 1 2 3 4 5

Output: Average of the numbers is: 3.00

### **Answer**

```
try:
    l=input().strip()
    n=l.split()
    v=[]
    for i in n:
        try:
            v.append(float(i))
        except ValueError:
            print("Invalid data in the input.")
            exit()
    a=sum(v)/len(v)
    print(f"Average of the numbers is:{a:.2f}")
except:
    pass
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 7\_MCQ

Attempt : 1  
Total Mark : 20  
Marks Obtained : 20

#### Section 1 : MCQ

1. In NumPy, how do you access the first element of a one-dimensional array arr?

**Answer**

arr[0]

**Status : Correct**

**Marks : 1/1**

2. Minimum number of argument we require to pass in pandas series ?

**Answer**

1

**Status : Correct**

**Marks : 1/1**

3. What is the primary data structure used in NumPy for numerical computations?

**Answer**

Array

**Status :** Correct

**Marks :** 1/1

4. In the DataFrame created in the code, what is the index for the row containing the data for 'Jack'?

```
import pandas as pd

data = {'Name': ['Tom', 'Jack', 'nick', 'juli'],
        'marks': [99, 98, 95, 90]}

df = pd.DataFrame(data, index=['rank1',
                               'rank2',
                               'rank3',
                               'rank4'])
print(df)
```

**Answer**

rank2

**Status :** Correct

**Marks :** 1/1

5. What is the output of the following NumPy code?

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
r = arr[2:4]
print(r)
```

**Answer**

[3 4]

**Status :** Correct

**Marks :** 1/1

6. Which NumPy function is used to find the indices of the maximum and minimum values in an array?

**Answer**

argmax() and argmin()

**Status : Correct**

**Marks : 1/1**

7. Which NumPy function is used to create an identity matrix?

**Answer**

numpy.identity()

**Status : Correct**

**Marks : 1/1**

8. What is the primary purpose of Pandas DataFrame?

**Answer**

To store data in tabular form for analysis and manipulation

**Status : Correct**

**Marks : 1/1**

9. Which function is used to create a Pandas DataFrame?

**Answer**

pd.DataFrame()

**Status : Correct**

**Marks : 1/1**

10. What will be the output of the following code snippet?

```
import numpy as np
arr = np.array([1, 2, 3])
result = np.concatenate((arr, arr))
print(result)
```

**Answer**

[1 2 3 1 2 3]

**Status :** Correct

**Marks :** 1/1

11. What is the purpose of the following NumPy code snippet?

```
import numpy as np
arr = np.zeros((3, 4))
print(arr)
```

**Answer**

Displays a 3x4 matrix filled with zeros

**Status :** Correct

**Marks :** 1/1

12. The important data structure of pandas is/are \_\_\_\_.

**Answer**

Both Series and Data Frame

**Status :** Correct

**Marks :** 1/1

13. Which NumPy function is used to calculate the standard deviation of an array?

**Answer**

numpy.std()

**Status :** Correct

**Marks :** 1/1

14. What is the output of the following NumPy code snippet?

```
import numpy as np
arr = np.array([1, 2, 3, 4, 5])
r = arr[arr > 2]
print(r)
```

**Answer**



[3 4 5]

**Status :** Correct

**Marks :** 1/1

15. What is the result of the following NumPy operation?

```
import numpy as np
arr = np.array([1, 2, 3])
r = arr + 5
print(r)
```

**Answer**

[6 7 8]

**Status :** Correct

**Marks :** 1/1

16. What will be the output of the following code?

```
import pandas as pnd
pnd.Series([1,2], index= ['a','b','c'])
```

**Answer**

Value Error

**Status :** Correct

**Marks :** 1/1

17. What does the np.arange(10) function in NumPy do?

**Answer**

Creates an array with values from 1 to 9

**Status :** Correct

**Marks :** 1/1

18. What does NumPy stand for?

**Answer**

Numerical Python

**Status :** Correct

**Marks :** 1/1

19. What is the output of the following code?

```
import numpy as np
a = np.arange(10)
print(a[2:5])
```

**Answer**

[2, 3, 4]

**Status :** Correct

**Marks :** 1/1

20. Which of the following is a valid way to import NumPy in Python?

**Answer**

```
import numpy as np
```

**Status :** Correct

**Marks :** 1/1

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 7\_COD

Attempt : 1  
Total Mark : 50  
Marks Obtained : 50

### Section 1 : Coding

#### 1. Problem Statement

Sita is analyzing her company's daily sales data to find all sales values that are multiples of 5 and exceed 100. She wants to filter these specific sales values from the list.

Help her to implement the task using the numpy package.

Formula:

To filter sales values:

Select all values  $s$  from sales such that  $(s \% 5 == 0)$  and  $(s > 100)$

#### ***Input Format***

The first line of input consists of an integer value,  $n$ , representing the number of

sales entries.

The second line of input consists of n floating-point values, sales, separated by spaces, representing daily sales figures.

### **Output Format**

The output prints: filtered\_sales

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 5

50.0 100.0 105.0 150.0 99.0

Output: [105. 150.]

### **Answer**

```
# You are using Python
import numpy as np
n=int(input())
sales=np.array(list(map(float,input().split()))))
f=sales[(sales%5==0)&(sales>100)]
print(f)
```

**Status :** Correct

**Marks :** 10/10

## **2. Problem Statement**

Sita works as a sales analyst and needs to analyze monthly sales data for different cities. She receives lists of cities, months, and corresponding sales values and wants to create a pandas DataFrame using a MultiIndex of cities and months.

Help her to implement this task and calculate total sales for each city.

### **Input Format**

The first line of input consists of an integer value, n, representing the number of records.

The second line of input consists of n space-separated city names.

The third line of input consists of n space-separated month names.

The fourth line of input consists of n space-separated float values representing sales for each city-month combination.

### ***Output Format***

The first line of output prints: "Monthly Sales Data with MultiIndex:"

The next lines print the DataFrame with MultiIndex (City, Month) and their corresponding sales values.

The following line prints: "\nTotal Sales Per City:"

The final lines print the total sales per city, computed by grouping the sales data on city names.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 4

NYC NYC LA LA

Jan Feb Jan Feb

100 200 300 400

Output: Monthly Sales Data with MultiIndex:

Sales

City Month

NYC Jan 100.0

Feb 200.0

LA Jan 300.0

Feb 400.0

Total Sales Per City:

Sales

City

LA 700.0

NYC 300.0

### **Answer**

```
# You are using Python
import pandas as pd
n=int(input())
c=input().split()
m=input().split()
s=list(map(float,input().split()))
df=pd.DataFrame({"City":c,"Month":m,"Sales":s})
df.set_index(["City","Month"],inplace=True)
print("Monthly Sales Data with MultiIndex:")
print(df)
print("\nTotal Sales Per City:")
print(df.groupby("City").sum())
```

**Status : Correct**

**Marks : 10/10**

### **3. Problem Statement**

Rekha works in hospital data management and receives patient records with missing or incomplete data. She needs to clean the records by performing the following tasks:

Calculate the mean of the available Age values. Replace any missing (NaN) values in the Age column with this mean age. Remove any rows where the Diagnosis value is missing (NaN). Reset the DataFrame index after removing these rows.

Implement this data cleaning task using the pandas package.

#### **Input Format**

The first line of input contains an integer  $n$  representing the number of patient records.

The second line contains the CSV header — comma-separated column names (e.g., "Name, Age, Diagnosis, Gender").

The next  $n$  lines each contain one patient record in comma-separated format.

#### **Output Format**

The first line of output is the text:

Cleaned Hospital Records:

The next lines print the cleaned pandas DataFrame (as produced by `print(cleaned_df)`).

This will include the updated values of the Age column (with missing ages filled by the mean age), and any rows with missing Diagnosis removed.

The DataFrame will be displayed using the default pandas `print()` representation.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 5

PatientID,Name,Age,Diagnosis

1,John Doe,45,Flu

2,Jane Smith,,Cold

3,Bob Lee,50,

4,Alice Green,38,Fever

5,Tom Brown,,Infection

Output: Cleaned Hospital Records:

	PatientID	Name	Age	Diagnosis
0	1	John Doe	45.000000	Flu
1	2	Jane Smith	44.333333	Cold
2	4	Alice Green	38.000000	Fever
3	5	Tom Brown	44.333333	Infection

### **Answer**

# You are using Python

```
import pandas as pd
```

```
import numpy as np
```

```
n=int(input())
```

```
cols=input().split(",")
```

```
rows=[input().split(",")for i in range(n)]
```

```
df=pd.DataFrame(rows,columns=cols)
```

```
df["Age"]=pd.to_numeric(df["Age"],errors="coerce")
```

```
df["Age"].fillna(df["Age"].mean(),inplace=True)
```

```
df["Diagnosis"].replace("np.nan,inplace=True)
df.dropna(subset=["Diagnosis"],inplace=True)
df.reset_index(drop=True,inplace=True)
print("Cleaned Hospital Records:")
print(df)
```

**Status :** Correct

**Marks :** 10/10

#### 4. Problem Statement

A company tracks the monthly sales data of various products. You are given a table where each row represents a product and each column represents its monthly sales in sequential months.

Your task is to compute the cumulative monthly sales for each product using numpy, where the cumulative sales for a month is the total sales from month 1 up to that month.

##### ***Input Format***

The first line of input consists of two integer values, products and months, separated by a space.

Each of the next products lines consists of months integer values representing the monthly sales data of a product.

##### ***Output Format***

The first line of output prints: "Cumulative Monthly Sales:"

The second line of output prints: the 2D numpy array cumulative\_array that contains the cumulative sales data for each product.

Refer to the sample output for the formatting specifications.

##### ***Sample Test Case***

Input: 2 4  
10 20 30 40  
5 15 25 35



Output: Cumulative Monthly Sales:

```
[[ 10 30 60 100]
 [ 5 20 45 80]]
```

**Answer**

```
# You are using Python
import numpy as np
n,m=map(int,input().split())
data=[list(map(int,input().split()))for i in range(n)]
s=np.array(data)
c=np.cumsum(s,axis=1)
print("Cumulative Monthly Sales:")
print(c)
```

**Status :** Correct

**Marks :** 10/10

## 5. Problem Statement

Alex is a data scientist analyzing the relationship between two financial indicators over time. He has collected two time series datasets representing daily values of these indicators over several months. Alex wants to understand how these two indicators correlate at different time lags to identify possible leading or lagging behaviors.

Your task is to help Alex compute the cross-correlation of these two time series using numpy, so he can analyze the similarity between the two signals at various time shifts.

### **Input Format**

The first line of input consists of space-separated float values representing the first time series, array1.

The second line of input consists of space-separated float values representing the second time series, array2.

### **Output Format**

The first line of output prints: "Cross-correlation of the two time series:"

The second line of output prints: the 1D numpy array cross\_corr representing the cross-correlation of array1 and array2 across different lags.

Refer to the sample output for the formatting specifications.

**Sample Test Case**

Input: 1.0 2.0 3.0  
4.0 5.0 6.0

Output: Cross-correlation of the two time series:  
[ 6. 17. 32. 23. 12.]

**Answer**

```
# You are using Python
import numpy as np
n1=np.array(list(map(float,input().split()))))
n2=np.array(list(map(float,input().split()))))
cc=np.correlate(n1,n2,mode="full")
print("Cross-correlation of the two time series:")
print(cc)
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 7\_CY

Attempt : 1  
Total Mark : 50  
Marks Obtained : 50

### Section 1 : Coding

#### 1. Problem Statement

Rekha works as an e-commerce data analyst. She receives transaction data containing purchase dates and needs to extract the month and day from these dates using the pandas package.

Help her implement this task by performing the following steps:

Convert the Purchase Date column to datetime format, treating invalid date entries as NaT (missing).

Create two new columns:

Purchase Month, containing the month (as an integer) extracted from the Purchase Date.

Purchase Day, containing the day (as an integer) extracted from the

Purchase Date. Keep the rest of the data as is.

### ***Input Format***

The first line of input contains an integer  $n$ , representing the number of records.

The second line contains the CSV header — comma-separated column names.

The next  $n$  lines each contain a transaction record in comma-separated format.

### ***Output Format***

The first line of output is the text:

Transformed E-commerce Transaction Data:

The next lines print the pandas DataFrame with:

The original columns (including Purchase Date, which is now in datetime format or NaT if invalid).

Two additional columns: Purchase Month and Purchase Day.

The output uses the default pandas DataFrame string representation as produced by `print(transformed_df)`.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 3

Customer,Purchase Date

Alice,2023-05-15

Bob,2023-06-20

Charlie,2023-07-01

Output: Transformed E-commerce Transaction Data:

	Customer	Purchase Date	Purchase Month	Purchase Day
0	Alice	2023-05-15	5	15
1	Bob	2023-06-20	6	20
2	Charlie	2023-07-01	7	1

### Answer

```
# You are using Python
import pandas as pd
n=int(input())
columns=input().split(",")
data=[input().split(",")for i in range(n)]
df=pd.DataFrame(data,columns=columns)
df["Purchase Date"]=pd.to_datetime(df["Purchase Date"],errors="coerce")
df["Purchase Month"]=df["Purchase Date"].dt.month
df["Purchase Day"]=df["Purchase Date"].dt.day
print("Transformed E-commerce Transaction Data:")
print(df)
```

**Status :** Correct

**Marks : 10/10**

## 2. Problem Statement

Rekha is a meteorologist analyzing rainfall data collected over 5 years, with monthly rainfall recorded for each year. She wants to find the total rainfall each year and also identify the month with the maximum rainfall for every year.

Help her to implement the task using the numpy package.

Formula:

Yearly total rainfall = sum of all 12 months' rainfall for each year

Month with max rainfall = index of the maximum rainfall value within the 12 months for each year (0-based index)

### Input Format

The input consists of 5 lines.

Each line contains 12 floating-point values separated by spaces, representing the rainfall data (in mm) for each month of that year.

### Output Format

The first line of output prints: yearly\_totals

The second line of output prints: max\_rainfall\_months

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 1.0 2.0 3.0 4.0 5.0 6.0 7.0 8.0 9.0 10.0 11.0 12.0  
2.0 3.0 4.0 5.0 6.0 7.0 8.0 9.0 10.0 11.0 12.0 13.0  
3.0 4.0 5.0 6.0 7.0 8.0 9.0 10.0 11.0 12.0 13.0 14.0  
4.0 5.0 6.0 7.0 8.0 9.0 10.0 11.0 12.0 13.0 14.0 15.0  
5.0 6.0 7.0 8.0 9.0 10.0 11.0 12.0 13.0 14.0 15.0 16.0  
Output: [ 78. 90. 102. 114. 126.]  
[11 11 11 11 11]

### **Answer**

```
# You are using Python
import numpy as np
d=[list(map(float,input().split()))for i in range(5)]
arr=np.array(d)
yt=np.sum(arr,axis=1)
mr=np.argmax(arr,axis=1)
print(yt)
print(mr)
```

**Status :** Correct

**Marks : 10/10**

### **3. Problem Statement**

You are working as a data analyst for a small retail store that wants to track the stock levels of its products. Each product has a unique Name (such as "Toothpaste", "Shampoo", "Soap") and an associated Quantity in stock. Management wants to identify which products have zero stock so they can be restocked.

Write a Python program using the pandas library to help with this task. The program should:

Read the number of products, n. Read n lines, each containing the Name of

the product and its Quantity, separated by a space. Convert this data into a pandas DataFrame. Identify and display the Name and Quantity of products with zero stock. If no products have zero stock, display: No products with zero stock.

### ***Input Format***

The first line contains an integer  $n$ , the number of products.

The next  $n$  lines each contain:

<Product\_ID> <Quantity>

where <Product\_ID> is a single word (e.g., "Shampoo") and <Quantity> is a non-negative integer (e.g., 5).

### ***Output Format***

The first line of output prints:

Products with Zero Stock:

If there are any products with zero stock, the following lines print the pandas DataFrame showing those products with two columns: Product\_ID and Quantity.

The column headers Product\_ID and Quantity are printed in the second line.

Each subsequent line shows the product's name and quantity, aligned under the respective headers, with no index column.

The output formatting (spacing and alignment) follows the default pandas `to_string(index=False)` style.

If no products have zero stock, print:

No products with zero stock.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 3

P101 10

P102 0

P103 5

Output: Products with Zero Stock:

Product_ID	Quantity
------------	----------

P102	0
------	---

### **Answer**

# You are using Python

```
import pandas as pd
```

```
n=int(input())
```

```
r=[]
```

```
c=[]
```

```
for i in range(n):
```

```
    l,m=input().split()
```

```
    r.append(l)
```

```
    c.append(int(m))
```

```
df=pd.DataFrame({"Product_ID":r,"Quantity":c})
```

```
z=df[df["Quantity"]==0]
```

```
print("Products with Zero Stock:")
```

```
if z.empty:
```

```
    print("No products with zero stock.")
```

```
else:
```

```
    print(z.to_string(index=False))
```

**Status : Correct**

**Marks : 10/10**

## **4. Problem Statement**



Arjun is monitoring hourly temperature data recorded continuously for multiple days. He needs to calculate the average temperature for each day based on 24 hourly readings.

Help him to implement the task using the numpy package.

Formula:

Reshape the temperature readings into rows where each row has 24 readings (one day).

Average temperature per day = mean of 24 hourly readings in each row.

### ***Input Format***

The first line of input consists of an integer value, n, representing the total number of temperature readings.

The second line of input consists of n floating-point values separated by spaces, representing hourly temperature readings.

### ***Output Format***

The output prints: avg\_per\_day

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 30

30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0  
30.0 30.0 30.0 30.0 30.0 30.0 30.0 30.0

Output: [30.]

### ***Answer***

```
# You are using Python
import numpy as np
n=int(input())
m=list(map(float,input().split()))
arr=np.array(m).reshape(-1,24)
a=np.mean(arr,axis=1)
```

print(a)

**Status :** Correct

**Marks :** 10/10

## 5. Problem Statement

Arjun is developing a system to monitor environmental sensors installed in different rooms of a smart building. Each sensor records multiple temperature readings throughout the day. To compare sensor data fairly despite differing scales, Arjun needs to normalize each sensor's readings so that they have a mean of zero and standard deviation of one.

Help him implement this normalization using numpy.

Normalization Formula:

### ***Input Format***

The first line of input consists of two integers: sensors (number of sensors) and samples (number of readings per sensor).

The next sensors lines each contain samples space-separated floats representing the sensor readings.

### ***Output Format***

The first line of output prints: "Normalized Sensor Data."

The next lines print the normalized readings as a numpy array, where each row corresponds to a sensor's normalized values.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 3 3  
1.0 2.0 3.0  
4.0 5.0 6.0

7.0 8.0 9.0

Output: Normalized Sensor Data:

```
[[ -1.22474487  0.      1.22474487]
 [ -1.22474487  0.      1.22474487]
 [ -1.22474487  0.      1.22474487]]
```

**Answer**

```
# You are using Python
import numpy as np
n,m=map(int,input().split())
l=[list(map(float,input().split()))for i in range(n)]
r=np.array(l)
a=r.mean(axis=1,keepdims=True)
t=r.std(axis=1,keepdims=True)
s=(r-a)/t
print("Normalized Sensor Data:")
print(s)
```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Balaambiga C.A  
Email: 240701068@rajalakshmi.edu.in  
Roll no: 240701068  
Phone: 7397651248  
Branch: REC  
Department: I CSE FA  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23221\_Python Programming

### REC\_Python\_Week 7\_PAH

Attempt : 1  
Total Mark : 50  
Marks Obtained : 40

### Section 1 : Coding

#### 1. Problem Statement

A software development company wants to classify its employees based on their years of service at the company. They want to categorize employees into three experience levels: Junior (less than 3 years), Mid (3 to 6 years, inclusive), and Senior (more than 6 years).

Experience Level Classification:

Junior: Years at Company < 3

Mid:  $3 \leq$  Years at Company < 6

Senior: Years at Company > 5

You need to create a Python program using the pandas library that reads employee data, processes it into a DataFrame, and adds a new column

"Experience Level" to display the appropriate classification for each employee.

### ***Input Format***

First line: an integer  $n$  representing the number of employees.

Next  $n$  lines: each line has a string `Name` and a floating-point number `Years at Company` (space-separated).

### ***Output Format***

First line: "Employee Data with Experience Level:"

The employee data table printed with no index column, and with columns: `Name`, `Years at Company`, `Experience Level`.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 5

Alice 2

Bob 4

Charlie 7

Diana 3

Evan 6

Output: Employee Data with Experience Level:

Name	Years at Company	Experience Level
Alice	2.0	Junior
Bob	4.0	Mid
Charlie	7.0	Senior
Diana	3.0	Mid
Evan	6.0	Senior

### ***Answer***

# You are using Python

```
import pandas as pd
```

```
n=int(input())
```

```
data=[input().split()for i in range(n)]
```

```
df=pd.DataFrame(data,columns=["Name","Years at Company"])
```

```
df["Years at Company"]=df["Years at Company"].astype(float)
def classify(y):
    if y<3:
        return "Junior"
    elif y<6:
        return "Mid"
    else:
        return "Senior"
df["Experience Level"]=df["Years at Company"].apply(classify)
print("Employee Data with Experience Level:")
print(df.to_string(index=False))
```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Arjun is a data scientist working on an image processing task. He needs to normalize the pixel values of a grayscale image matrix to scale between 0 and 1. The input image data is provided as a matrix of integers.

Help him to implement the task using the numpy package.

Formula:

To normalize each pixel value in the image matrix:

$$\text{normalized\_pixel} = (\text{pixel} - \text{min\_pixel}) / (\text{max\_pixel} - \text{min\_pixel})$$

where min\_pixel and max\_pixel are the minimum and maximum pixel values in the image matrix, respectively. If all pixel values are the same, the normalized image matrix should be filled with zeros.

### ***Input Format***

The first line of input consists of an integer value, rows, representing the number of rows in the image matrix.

The second line of input consists of an integer value, cols, representing the number of columns in the image matrix.

The next rows lines each consist of cols integer values separated by a space, representing the pixel values of the image matrix.

### Output Format

The output prints: normalized\_image

Refer to the sample output for the formatting specifications.

### Sample Test Case

Input: 2

3

1 2 3

4 5 6

Output:  $\begin{bmatrix} 0. & 0.2 & 0.4 \\ 0.6 & 0.8 & 1. \end{bmatrix}$

### Answer

# You are using Python

```
import numpy as np
```

```
r=int(input())
```

```
c=int(input())
```

```
m=[]
```

```
for i in range(r):
```

```
    m.append(list(map(int,input().split())))
```

```
im=np.array(m,dtype=float)
```

```
minpixel=np.min(im)
```

```
maxpixel=np.max(im)
```

```
if minpixel==maxpixel:
```

```
    ni=np.zeros((r,c))
```

```
else:
```

```
    ni=(im-minpixel)/(maxpixel-minpixel)
```

```
print(ni)
```

**Status :** Correct

**Marks :** 10/10

### 3. Problem Statement

Arjun manages a busy customer service center and wants to analyze the distribution of customer wait times to improve service efficiency. He decides to group the wait times into intervals of 5 minutes each and count

how many customers fall into each interval bucket.

Help him implement this bucketing and counting task using NumPy.

**Bucketing Logic:**

Divide the wait times into intervals (buckets) of size 5 minutes, e.g.:

[0-5), [5-10), [10-15), ...

Use NumPy's digitize function to determine which bucket each wait time falls into.

Count the number of wait times in each bucket and generate bucket labels.

***Input Format***

The first line contains an integer  $n$ , the number of customer wait times recorded.

The second line contains  $n$  space-separated floating-point numbers representing the wait times (in minutes).

***Output Format***

The first line of output is the text:

Wait Time Buckets and Counts:

Each subsequent line prints the bucket range and the number of wait times in that bucket, formatted as:

<bucket\_range>: <count>

where <bucket\_range> is the lower and upper bound of the bucket (inclusive lower bound, exclusive upper bound), for example:

0-5: 3

5-10: 2

10-15: 1



The output uses the default string formatting of Python's print() function (no extra spaces, no special formatting beyond the specified lines).

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 10

2.0 3.0 7.0 8.0 12.0 14.0 18.0 19.0 21.0 25.0

Output: Wait Time Buckets and Counts:

0-5: 2

5-10: 2

10-15: 2

15-20: 2

20-25: 1

### **Answer**

```
# You are using Python
import numpy as np
import math
n=int(input())
m=list(map(float,input().split()))
m=np.array(m)
l=np.max(m)
nm=math.ceil(l/5)
print("Wait Time Buckets and Counts:")
for i in range(nm):
    lower=i*5
    upper=lower+5
    count=np.sum((m>=lower)&(m<upper))
    print(f"{lower}-{upper}:{count}")
```

**Status :** Correct

**Marks :** 10/10

## **4. Problem Statement**

You're analyzing the daily returns of a set of financial assets over a period

of time. Each day is represented as a row in a 2D array, where each column represents the return of a specific asset on that day.

Your task is to identify which days had all positive returns across every asset using numpy, and output a boolean array indicating these days.

### ***Input Format***

The first line of input consists of two integer values, rows and cols, separated by a space.

Each of the next rows lines consists of cols float values representing the returns of the assets for that day.

### ***Output Format***

The first line of output prints: "Days where all asset returns were positive:"

The second line of output prints: the boolean array `positive_days`, indicating True for days where all asset returns were positive and False otherwise.

Refer to the sample output for the formatting specifications.

### ***Sample Test Case***

Input: 3 4

0.01 0.02 0.03 0.04  
0.05 0.06 0.07 0.08  
-0.01 0.02 0.03 0.04

Output: Days where all asset returns were positive:  
[ True True False]

### ***Answer***

```
# You are using Python
import numpy as np
r,c=map(int,input().split())
m=[]
for i in range(r):
    m.append(list(map(float,input().split())))
a=np.array(m)
r=[]
```

```

for i in a:
    p=True
    for j in i:
        if j<=0:
            p=False
            break
    r.append(p)
print("Days where all asset returns were positive:")
print(['I',*r,])

```

**Status :** Correct

**Marks :** 10/10

## 5. Problem Statement

A company conducted a customer satisfaction survey where each respondent provides their RespondentID and an optional textual Feedback. Sometimes, respondents submit their ID without any feedback or with empty feedback.

Your task is to process the survey responses using pandas to replace any missing or empty feedback with the phrase "No Response". Finally, print the cleaned survey responses exactly as shown in the sample output.

### **Input Format**

The first line contains an integer  $n$ , the number of survey responses.

Each of the next  $n$  lines contains:

A RespondentID (a single alphanumeric string without spaces),

Followed optionally by a Feedback string, which may be empty or missing.

If no feedback is provided after the RespondentID, treat it as missing.

### **Output Format**

Print the line:

Survey Responses with Missing Feedback Filled:

Then print the cleaned survey data as a table with two columns: RespondentID

and Feedback.

The table should have the headers exactly as:

RespondentID Feedback

Print each respondent's data on a new line, aligned to match the output produced by `pandas.DataFrame.to_string(index=False)`.

For any missing or empty feedback, print "No Response" in the Feedback column.

Maintain the spacing and alignment exactly as shown in the sample outputs.

Refer to the sample output for the formatting specifications.

### **Sample Test Case**

Input: 4

101 Great service

102

103 Loved it

104

Output: Survey Responses with Missing Feedback Filled:

RespondentID	Feedback
--------------	----------

101	Great service
-----	---------------

102	No Response
-----	-------------

103	Loved it
-----	----------

104	No Response
-----	-------------

### **Answer**

# You are using Python

**Status : Wrong**

**Marks : 0/10**