

Module Interface Specification for Slope Stability Analysis Program (SSP)

Henry Frankis and Brooks MacLachlan

November 20, 2018

1 Revision History

Date	Version	Notes
11/12/18	1.0	Initial updates based on template

2 Symbols, Abbreviations and Acronyms

See Section [2](#) of the Software Requirements Specification (SRS) document, available in [the GitHub repository for the project](#).

Contents

1	Revision History	i
2	Symbols, Abbreviations and Acronyms	ii
3	Introduction	1
4	Notation	1
5	Numerical Algorithms	2
6	Module Decomposition	2
7	MIS of the Control Module	3
7.1	Module	3
7.2	Uses	3
7.3	Syntax	3
7.3.1	Exported Constants	3
7.3.2	Exported Data Types	4
7.3.3	Exported Access Programs	4
7.4	Semantics	4
7.4.1	State Variables	4
7.4.2	Environment Variables	4
7.4.3	Assumptions	4
7.4.4	Access Routine Semantics	4
7.4.5	Local Functions	4
8	MIS of the Input Module	4
8.1	Module	4
8.2	Uses	5
8.3	Syntax	5
8.3.1	Exported Constants	5
8.3.2	Exported Data Types	5
8.3.3	Exported Access Programs	6
8.4	Semantics	7
8.4.1	State Variables	7
8.4.2	Environment Variables	7
8.4.3	Assumptions	7
8.4.4	Access Routine Semantics	7
8.4.5	Local Functions	11

9	MIS of the Output Module	11
9.1	Module	11
9.2	Uses	11
9.3	Syntax	11
9.3.1	Exported Constants	11
9.3.2	Exported Data Types	11
9.3.3	Exported Access Programs	11
9.4	Semantics	11
9.4.1	State Variables	11
9.4.2	Environment Variables	11
9.4.3	Assumptions	12
9.4.4	Access Routine Semantics	12
9.4.5	Local Functions	12
10	MIS of the Genetic Algorithm Module	12
10.1	Module	12
10.2	Uses	12
10.2.1	Imported Access Programs	12
10.3	Syntax	13
10.3.1	Exported Constants	13
10.3.2	Exported Data Types	13
10.3.3	Exported Access Programs	13
10.4	Semantics	13
10.4.1	State Variables	13
10.4.2	Environment Variables	13
10.4.3	Assumptions	13
10.4.4	Access Routine Semantics	13
10.4.5	Local Functions	14
11	MIS of the Kinematic Admissibility Module	14
11.1	Module	14
11.2	Uses	14
11.3	Syntax	14
11.3.1	Exported Constants	14
11.3.2	Exported Data Types	15
11.3.3	Exported Access Programs	15
11.4	Semantics	15
11.4.1	State Variables	15
11.4.2	Environment Variables	15
11.4.3	Assumptions	15
11.4.4	Access Routine Semantics	15
11.4.5	Local Functions	16

12 MIS of the Slip Weighting Module	16
12.1 Module	16
12.2 Uses	16
12.3 Syntax	16
12.3.1 Exported Constants	16
12.3.2 Exported Data Types	17
12.3.3 Exported Access Programs	17
12.4 Semantics	17
12.4.1 State Variables	17
12.4.2 Environment Variables	17
12.4.3 Assumptions	17
12.4.4 Access Routine Semantics	17
12.4.5 Local Functions	17
13 MIS of the Slip Slicing Module	18
13.1 Module	18
13.2 Uses	18
13.3 Syntax	18
13.3.1 Exported Constants	18
13.3.2 Exported Data Types	18
13.3.3 Exported Access Programs	18
13.4 Semantics	18
13.4.1 State Variables	18
13.4.2 Environment Variables	18
13.4.3 Assumption	18
13.4.4 Access Routine Semantics	19
13.4.5 Local Functions	19
14 MIS of the Morgenstern-Price Calculation Module	19
14.1 Module	19
14.2 Uses	19
14.3 Syntax	19
14.3.1 Exported Constants	19
14.3.2 Exported Data Types	20
14.3.3 Exported Access Programs	20
14.4 Semantics	20
14.4.1 State Variables	20
14.4.2 Environment Variables	20
14.4.3 Assumptions	20
14.4.4 Access Routine Semantics	20
14.4.5 Local Functions	21

15 MIS of the Slice Property Calculation Module	22
15.1 Module	22
15.2 Uses	22
15.3 Syntax	22
15.3.1 Exported Constants	22
15.3.2 Exported Data Types	22
15.3.3 Exported Access Programs	22
15.4 Semantics	23
15.4.1 State Variables	23
15.4.2 Environment Variables	23
15.4.3 Assumptions	23
15.4.4 Access Routine Semantics	23
15.4.5 Local Functions	25
16 MIS of the Sequence Data Structure Module	25
16.1 Module	25
16.2 Uses	25
16.3 Syntax	25
16.3.1 Exported Constants	25
16.3.2 Exported Data Types	25
16.3.3 Exported Access Programs	25
16.4 Semantics	25
16.4.1 State Variables	25
16.4.2 Environment Variables	25
16.4.3 Assumptions	26
16.4.4 Access Routine Semantics	26
16.4.5 Local Functions	26
16.4.6 Considerations	26
17 MIS of the Plotting Module	26
17.1 Module	26
17.2 Uses	26
17.3 Syntax	26
17.3.1 Exported Constants	26
17.3.2 Exported Data Types	27
17.3.3 Exported Access Programs	27
17.4 Semantics	27
17.4.1 State Variables	27
17.4.2 Environment Variables	27
17.4.3 Assumptions	27
17.4.4 Access Routine Semantics	27
17.4.5 Local Functions	27
17.4.6 Considerations	27

18 MIS of the Random Number Generation Module	28
18.1 Module	28
18.2 Uses	28
18.3 Syntax	28
18.3.1 Exported Constants	28
18.3.2 Exported Data Types	28
18.3.3 Exported Access Programs	28
18.4 Semantics	28
18.4.1 State Variables	28
18.4.2 Environment Variables	28
18.4.3 Assumptions	28
18.4.4 Access Routine Semantics	28
18.4.5 Local Functions	29
18.4.6 Considerations	29
19 Appendix	31
19.1 Parameter Tables	31
19.1.1 Layer Parameters	31
19.1.2 Piezometric Parameter	31
19.1.3 Search Range Parameters	32
19.1.4 Solution Parameters	32
19.1.5 Internal Force Parameters	33
19.1.6 Angle Parameters	33

3 Introduction

The following document details the Module Interface Specifications for SSP, a program for determining the critical slip surface and corresponding factor of safety for a given sloped mass of soil. The document is intended to ease understanding of the design of SSP and should be used as a resource for any maintenance of SSP.

Complementary documents include the System Requirement Specifications and Module Guide. The full documentation and implementation can be found at [the GitHub repository for the project](#).

4 Notation

The structure of the MIS for modules comes from [Hoffman and Strooper \(1995\)](#), with the addition that template modules have been adapted from [Ghezzi et al. \(2003\)](#). The mathematical notation comes from Chapter 3 of [Hoffman and Strooper \(1995\)](#). For instance, the symbol $:=$ is used for a multiple assignment statement and conditional rules follow the form $(c_1 \Rightarrow r_1 | c_2 \Rightarrow r_2 | \dots | c_n \Rightarrow r_n)$. For quantifiers, this document uses the word “with” to specify constraints on the bound variable.

The following table summarizes the primitive data types used by SSP.

Data Type	Notation	Description
character	char	a single symbol or digit
boolean	\mathbb{B}	a value from the set {true, false}
real	\mathbb{R}	any number in $(-\infty, \infty)$
integer	\mathbb{Z}	a number without a fractional component in $(-\infty, \infty)$

The specification of SSP uses some derived data types: sequences, strings, and tuples. Sequences are ordered lists of elements of the same data type, denoted by brackets enclosing the type of the data elements. If a sequence has fixed dimensions, the notation of the type will include the dimensions in superscript. Strings are sequences of characters. Tuples contain a list of values, potentially of different types, each associated with a field identifier. When a tuple is referenced in this document, a link to an appendix section that specifies the fields of the tuple will be provided. In addition, SSP uses functions, which are defined by the data types of their inputs and outputs. Local functions are described by giving their type signature followed by their specification.

5 Numerical Algorithms

Morgenstern-Price (Section 14)

The non-linear nature of the systems of equations in the Morgenstern-Price solver algorithm requires that the equations for the factor of safety (IM1), the interslice normal-to-shear force ratio (IM2), and the interslice normal forces (IM3) are solved iteratively, with an initial guess for two of the values, typically the factor of safety and interslice normal-to-shear force ratio.

Genetic Algorithm (Section 10)

SSP uses a genetic algorithm to find the coordinates of the critical slip surface vertices that minimize the factor of safety, as described in IM4. The genetic algorithm generates a set of initial potential slip surfaces, and subsequent generations are created by merging and mutating slip surfaces with low factors of safety from the previous generation. The minimum factor of safety after several generations is assumed to correspond to the critical slip surface.

[This section is not on the template. I've left it in for now because the information does seem useful, but maybe this is not the right place for it? Maybe this should go to an appendix? —BM]

6 Module Decomposition

The following table is taken directly from the Module Guide document for this project.

Level 1	Level 2
Hardware-Hiding	
	Control
	Input
	Output
Behaviour-Hiding	Genetic Algorithm
	Kinematic Admissibility
	Slip Weighting
	Slip Slicing
	Morgenstern-Price Calculation
	Slice Property Calculation
Software Decision	Sequence Data Structure
	Random Number Generation
	Plotting

Table 1: Module Hierarchy

7 MIS of the Control Module

7.1 Module

Control

7.2 Uses

Input (Section 8), Output (Section 9), GenAlg (Section 10), Sequence (Section 16)

7.3 Syntax

7.3.1 Exported Constants

N/A

7.3.2 Exported Data Types

N/A

7.3.3 Exported Access Programs

Name	In	Out	Exceptions
Control	string	-	-

7.4 Semantics

7.4.1 State Variables

N/A

7.4.2 Environment Variables

N/A

7.4.3 Assumptions

The access program is called with a string parameter.

7.4.4 Access Routine Semantics

`control(fname):`

- transition:

Modifies the state of the Input Module, Genetic Algorithm Module, and Output Module.

7.4.5 Local Functions

N/A

8 MIS of the Input Module

8.1 Module

Input

8.2 Uses

Sequence (Section 16)

8.3 Syntax

8.3.1 Exported Constants

N/A

8.3.2 Exported Data Types

`coord` = tuple of ($x : \mathbb{R}$, $y : \mathbb{R}$)

`coords` = [`coord`]

`paramsLayers` = tuple of (`strat` : `coords`, $\phi : \mathbb{R}$, $\text{coh} : \mathbb{R}$, $\text{gam} : \mathbb{R}$, $\text{gams} : \mathbb{R}$) (Appendix 19.1.1)

`paramsPiez` = tuple of (`piez` : `coords`, $\text{gamw} : \mathbb{R}$) (Appendix 19.1.2)

`paramsSearch` = tuple of (`Xext`, `Xetr`, $\text{Ylim} : [\mathbb{R}]^{1 \times 2}$) (Appendix 19.1.3)

`paramsSoln` = tuple of (`ltor`, `ftype`, `evnslc`, `cncvu`, `obtu` : \mathbb{B}) (Appendix 19.1.4)

8.3.3 Exported Access Programs

Name	In	Out	Exceptions
load_params	string	-	fileNotExist, badFileExtension, unexpectedInput
verify_params	-	-	badSlopeGeometry, badEffAngleFriction, badCohesion, badDryUnitWeight, badSatUnitWeight, badPiezGeometry, badWatUnitWeight
strat	-	coords	-
slopeX	-	$[\mathbb{R}]$	-
slopeY	-	$[\mathbb{R}]$	-
phi	-	\mathbb{R}	-
coh	-	\mathbb{R}	-
gam	-	\mathbb{R}	-
gams	-	\mathbb{R}	-
piez	-	coords	-
piezX	-	$[\mathbb{R}]$	-
piezY	-	$[\mathbb{R}]$	-
gamw	-	\mathbb{R}	-
xExt	-	$[\mathbb{R}]^{1 \times 2}$	-
xEtr	-	$[\mathbb{R}]^{1 \times 2}$	-
yLim	-	$[\mathbb{R}]^{1 \times 2}$	-
ltor	-	\mathbb{B}	-
ftype	-	\mathbb{B}	-
evnslc	-	\mathbb{B}	-
cncvu	-	\mathbb{B}	-
obtu	-	\mathbb{B}	-

8.4 Semantics

8.4.1 State Variables

slope : paramsLayers
piez : paramsPiez
search : paramsSearch
soln : paramsSoln

8.4.2 Environment Variables

in_file : String

- *in_file* represents a file stored in the file system of the hardware running SSP.

8.4.3 Assumptions

- load_params is called before any of the other access programs.
- The guesses for potential minimum and maximum x and y values of the critical slip surface, as described in *in_file*, lie within the boundaries of the given slope geometry.

8.4.4 Access Routine Semantics

load_params(*fname*):

- transition:

$slope, piez, search, soln := slope', piez', search', soln'$

where $slope'$, $piez'$, $search'$, and $soln'$ are populated based on the contents of *in_file*.

- exceptions:

$exc := (fname \text{ does not exist in file system} \Rightarrow \text{fileNotExist}$
 $| fname[(|fname| - 5)..(|fname| - 1)] = \text{"out"} \Rightarrow \text{badFileExtension}$
 $| in_file \text{ is not formatted correctly} \Rightarrow \text{unexpectedInput})$

verify_params():

- exceptions:

$exc := (\neg(\forall(i : \mathbb{Z} | i \in [0..|slope.strat| - 2] : slope.strat[i].x - slope.strat[i + 1].x \leq 0)) \Rightarrow \text{badSlopeGeometry}$
 $| \neg(0 < slope.phi < 90) \Rightarrow \text{badEffAngleFriction})$

$$\begin{aligned}
& | \neg(0 < \text{slope.coh}) \Rightarrow \text{badCohesion} \\
& | \neg(0 < \text{slope.gam}) \Rightarrow \text{badDryUnitWeight} \\
& | \neg(0 < \text{slope.gams}) \Rightarrow \text{badSatUnitWeight} \\
& | \neg(\forall(i : \mathbb{Z} | i \in [0..|\text{piez.piez}| - 2] : \text{piez.piez}[i].x - \text{piez.piez}[i + 1].x \leq 0)) \\
& \vee \text{piez.piez}[0].x \neq \text{slope.strat}[0].x \\
& \vee \text{piez.piez}[|\text{piez.piez}| - 1].x \neq \text{slope.strat}[|\text{slope.strat}| - 1].x \\
& \Rightarrow \text{badPiezGeometry}
\end{aligned}$$

strat():

- output:

$$\text{out} := \text{slope.strat}$$

slopeX():

- output:

$$\begin{aligned}
& \text{out} := \text{slope.strat}[0].x || \text{slope.strat}[1].x || \\
& \dots || \text{slope.strat}[|\text{slope.strat}| - 1].x
\end{aligned}$$

slopeY():

- output:

$$\begin{aligned}
& \text{out} := \text{slope.strat}[0].y || \text{slope.strat}[1].y || \\
& \dots || \text{slope.strat}[|\text{slope.strat}| - 1].y
\end{aligned}$$

phi():

- output:

$$\text{out} := \text{slope.phi}$$

coh():

- output:

$$\text{out} := \text{slope.coh}$$

gam():

- output:

$out := slope.gam$

`gams()`:

- output:

$out := slope.gams$

`piez()`:

- output:

$out := piez.piez$

`piezX()`:

- output:

$out := piez.piez[0].x || piez.piez[1].x ||$
 $\dots || piez.piez[|piez.piez| - 1].x$

`piezY()`:

- output:

$out := piez.piez[0].y || piez.piez[1].y ||$
 $\dots || piez.piez[|piez.piez| - 1].y$

`gamw()`:

- output:

$out := piez.gamw$

`xExt()`:

- output:

$out := search.Xext$

xEtr():

- output:

out := search.Xetr

yLim():

- output:

out := search.Ylim

ltor():

- output:

out := soln.ltor

ftype():

- output:

out := soln.ftype

evnslc():

- output:

out := soln.evnslc

cncvu():

- output:

out := soln.cncvu

obtu():

- output:

out := soln.obtu

8.4.5 Local Functions

N/A

9 MIS of the Output Module

9.1 Module

Output

9.2 Uses

Sequence (Section 16), Plot (Section 17)

9.3 Syntax

9.3.1 Exported Constants

N/A

9.3.2 Exported Data Types

N/A

9.3.3 Exported Access Programs

Name	In	Out	Exceptions
verify_output	\mathbb{R}	-	negativeFS
output	\mathbb{R} , coords, coords, coords, string	-	-

9.4 Semantics

9.4.1 State Variables

N/A

9.4.2 Environment Variables

out_file : String

- *out_file* represents a file stored in the file system of the hardware running SSP.

screen : $[\mathbb{Z}]$

- *screen* represents the colour values for each pixel on the screen of the hardware running SSP.

9.4.3 Assumptions

N/A

9.4.4 Access Routine Semantics

verify_output(*Fs*):

- exceptions:

$exc := Fs < 0 \Rightarrow \text{negativeFS}$

output(*Fs*, *crit_slip*, *G*, *X*, *fname*):

- transition:

out_file is created at path *fname* || “.out”. The outputs of xEtr(), xExt(), yLim(), ftype(), *Fs*, *crit_slip*, *G*, and *X* are written to *out_file*. *screen* is modified to display the outputs of plot(*crit_slip.x*, *crit_slip.y*), plot(*G.x*, *G.y*), and plot(*X.x*, *X.y*).

9.4.5 Local Functions

N/A

10 MIS of the Genetic Algorithm Module

10.1 Module

GenAlg

10.2 Uses

10.2.1 Imported Access Programs

Input (Section 8), MorgPriceSolver (Section 14), Slicer (Section 13), KinAdm (Section 11), SlipWeighter (Section 12), Sequence (Section 16), Rand (Section 18)

10.3 Syntax

10.3.1 Exported Constants

MIN_GENS = 100

NUM_SLIPS = 20

REL_DIFF = 0.00005

10.3.2 Exported Data Types

slip = tuple of (surf : coords, Fs : \mathbb{R} , G : coords, X : coords, wt : \mathbb{R})

slips = [slip]

10.3.3 Exported Access Programs

Name	In	Out	Exceptions
genetic_alg	-	\mathbb{R} , coords, coords, coords	-

10.4 Semantics

10.4.1 State Variables

N/A

10.4.2 Environment Variables

N/A

10.4.3 Assumptions

N/A

10.4.4 Access Routine Semantics

genetic_alg():

- output:

$out := \text{weighter}(slip_surfs)[0].surf, \text{weighter}(slip_surfs)[0].Fs, \text{weighter}(slip_surfs)[0].G,$
and $\text{weighter}(slip_surfs)[0].X$, where $slip_surfs$, of type slips, is developed by:

- * using `rand` to randomly generate coordinates for `NUM_SLIPS` potential slip surfaces, where the entry and exit x-coordinate for each slip surface are computed according to `generate_slips(xEtr)` and `generate_slips(xExt)`. Corresponding y-coordinates are determined by interpolating on the slope geometry.
- * using `kinAdm` to verify that the geometry of each potential slip surface is physically realizable. If any are not, new slip surfaces are randomly generated until `NUM_SLIPS` valid slip surfaces have been generated,
- * using `slicer` to redefine each slip surface's coordinates based on the desired number of slices
- * using `morg_price` to determine the Fs , G , and X fields of each slip surface
- * using `weighter` to determine the wt field of each slip surface
- * using `rand` to generate a new pool of `NUM_SLIPS` slip surfaces by applying crossovers and mutations to the previous generation, with the more highly-weighted members having a greater likelihood of contributing to the subsequent generations
- * applying `kinAdm`, `slicer`, `morg_price`, and `weighter` to the new generation
- * repeating until at least `MIN_GENS` have occurred and the relative difference between subsequent generations is less than `REL_DIFF`.

10.4.5 Local Functions

`generate_slips(Xrange) : $[\mathbb{R}] \rightarrow \mathbb{R}$`

`generate_slips(Xrange) = (Xrange[0] + rand() * (Xrange[1] - Xrange[0]))`

11 MIS of the Kinematic Admissibility Module

11.1 Module

`KinAdm`

11.2 Uses

Input (Section 8), Sequence (Section 16)

11.3 Syntax

11.3.1 Exported Constants

N/A

11.3.2 Exported Data Types

N/A

11.3.3 Exported Access Programs

Name	In	Out	Exceptions
kinAdm	slip	\mathbb{B}	-

11.4 Semantics

11.4.1 State Variables

N/A

11.4.2 Environment Variables

N/A

11.4.3 Assumptions

- The *surf* field is populated for every member of the input sequence of slip data.

11.4.4 Access Routine Semantics

kinAdm(*slip_surf*):

- output:

$$\begin{aligned} out := & (\neg(\forall(i : \mathbb{Z} | i \in [0..|slip_surf.surf| - 2] : slip_surf.surf[i].x - slip_surf.surf[i + \\ & 1].x \leq 0)) \\ & \vee \neg is_on_slope(slip_surf.surf[0]) \\ & \vee \neg is_on_slope(slip_surf.surf[|slip_surf.surf| - 1]) \\ & \vee \neg is_in_slope(slip_surf.surf) \\ & \vee (cncvu() \wedge \neg(is_concave_up(slip_surf.surf))) \\ & \vee (obtu() \wedge \neg(has_no_sharp_angles(slip_surf.surf))) \\ & \Rightarrow false \\ & | else \Rightarrow true \end{aligned}$$

[Not sure if I'm allowed to use "else" here but don't know how else to express the "else" case succinctly —BM]

11.4.5 Local Functions

$\text{linSlope}(\text{point1}, \text{point2}) : \text{coord} \times \text{coord} \rightarrow \mathbb{R}$

$$\text{linSlope}(\text{point1}, \text{point2}) = \frac{\text{point2.y} - \text{point1.y}}{\text{point2.x} - \text{point1.x}}$$

$\text{is_on_slope}(\text{point}) : \text{coord} \rightarrow \mathbb{B}$

$$\begin{aligned} \text{is_on_slope}(\text{point}) = & (\exists(i : \mathbb{Z} | i \in [0..|\text{slope.strat}| - 1] : \text{point} = \text{slope.strat}[i])) \\ \vee & (\exists(i : \mathbb{Z} | i \in [0..|\text{slope.strat}| - 2] : \text{point.y} = \text{linSlope}(\text{slope.strat}[i], \text{slope.strat}[i + 1]) * \\ & \text{point.x} + \frac{\text{slope.strat}[i].y}{\text{linSlope}(\text{slope.strat}[i], \text{slope.strat}[i+1]) * \text{slope.strat}[i].x})) \end{aligned}$$

$\text{is_in_slope}(\text{surf}) : \text{coords} \rightarrow \mathbb{B}$

$$\begin{aligned} \text{is_in_slope}(\text{surf}) = & (\forall(i : \mathbb{Z} | i \in [1..|\text{surf}| - 2] : (\forall(j : \mathbb{Z} | j \in [0..|\text{slope.strat}| - 2] \wedge \text{slope.strat}[j].x \leq \\ & \text{surf}[i].x < \text{slope.strat}[j + 1].x : \text{surf}[i].y < (\text{slope.strat}[j].y + (\text{surf}[i].x - \text{slope.strat}[j].x) * \\ & \text{linSlope}(\text{slope.strat}[j], \text{slope.strat}[j + 1]))))) \end{aligned}$$

$\text{is_concave_up}(\text{surf}) : \text{coords} \rightarrow \mathbb{B}$

$$\text{is_concave_up}(\text{surf}) = (\forall(i : \mathbb{Z} | i \in [0..|\text{surf}| - 3] : \text{linSlope}(\text{surf}[i+1], \text{surf}[i+2]) \geq \text{linSlope}(\text{surf}[i], \text{surf}[i+1])))$$

$\text{distance}(\text{point1}, \text{point2}) : \text{coord} \times \text{coord} \rightarrow \mathbb{R}$

$$\text{distance}(\text{point1}, \text{point2}) = \sqrt{(\text{point1.x} - \text{point2.x})^2 + (\text{point1.y} - \text{point2.y})^2}$$

$\text{has_no_sharp_angles}(\text{surf}) : \text{coords} \rightarrow \mathbb{B}$

$$\begin{aligned} \text{has_no_sharp_angles}(\text{surf}) = & (\forall(i : \mathbb{Z} | i \in [0..|\text{surf}| - 3] : \\ & \arccos \frac{(\text{distance}(\text{surf}[i], \text{surf}[i+1]))^2 + (\text{distance}(\text{surf}[i+1], \text{surf}[i+2]))^2 - (\text{distance}(\text{surf}[i], \text{surf}[i+2]))^2}{2 * \text{distance}(\text{surf}[i], \text{surf}[i+1]) * \text{distance}(\text{surf}[i+1], \text{surf}[i+2])})) \end{aligned}$$

12 MIS of the Slip Weighting Module

12.1 Module

SlipWeighter

12.2 Uses

Sequence (Section 16)

12.3 Syntax

12.3.1 Exported Constants

N/A

12.3.2 Exported Data Types

N/A

12.3.3 Exported Access Programs

Name	In	Out	Exceptions
weighter	slips	slips	-

12.4 Semantics

12.4.1 State Variables

N/A

12.4.2 Environment Variables

N/A

12.4.3 Assumptions

- The Fs field is populated for every member of the input sequence of slip data.

12.4.4 Access Routine Semantics

weighter($slip_surfs$):

- output:

$out := slip_surfs'$ such that $slip_surfs' = assign_weights(sort_Fs(slip_surfs))$

12.4.5 Local Functions

$sort_Fs(unsorted) : slips \rightarrow slips$ $sort_Fs(unsorted) = sorted$ such that

$\forall(a : slip | a \in unsorted : \exists(b : slip | b \in sorted : b = a \wedge count(a, A) = count(b, B))) \wedge \forall(i : \mathbb{Z} | i \in [0..|unsorted| - 1] : sorted[i].Fs \leq sorted[i + 1].Fs)$

$count(a, A) : slip \times slips \rightarrow \mathbb{Z}$

$count(a, A) = +(x : slip | x \in A \wedge x = a : 1)$

$assign_weights(s) : slips \rightarrow slips$

$assign_weights(s) = s'$ such that

$s'[0].wt = s[0].Fs - s[|s| - 1].Fs$ and

$\forall(i : \mathbb{Z} | i \in [1..|s| - 1] : s'[i].wt = s'[i - 1].wt + \frac{s[i].Fs - s[|s| - 1].Fs}{+(j : \mathbb{Z} | j \in [0..|s| - 1] : s[j].Fs - s[|s| - 1].Fs)})$

13 MIS of the Slip Slicing Module

13.1 Module

Slicer

13.2 Uses

Sequence (Section 16)

13.3 Syntax

13.3.1 Exported Constants

N/A

13.3.2 Exported Data Types

N/A

13.3.3 Exported Access Programs

Name	In	Out	Exceptions
slicer	coords, \mathbb{Z}	slip	-

13.4 Semantics

13.4.1 State Variables

N/A

13.4.2 Environment Variables

N/A

13.4.3 Assumption

- The integer input to *slicer* is greater than the size of the slip input to *slicer*.

13.4.4 Access Routine Semantics

$\text{slicer}(\text{slip_surf}, \text{num_slices})$:

- output:

$\text{out} := (\text{evnslc} \Rightarrow \text{slip_surf}'$ obtained by repeatedly applying $\text{slip_surf}[\text{large_segment}(\text{slip_surf})]$
 $|| \text{midpoint}(\text{slip_surf}[\text{large_segment}(\text{slip_surf})], \text{slip_surf}[\text{large_segment}(\text{slip_surf})+1])$
 $|| \text{slip_surf}[\text{large_segment}(\text{slip_surf})+1]$ until $|\text{slip_surf}'| = \text{num_slices}$
 $|\neg \text{evnslc} \Rightarrow \text{slip_surf}'$ such that $\forall(i : \mathbb{Z} | i \in [0..|\text{slip_surf}'| - 2] : \text{slip_surf}'[i] * \frac{\text{num_slices}}{|\text{slip_surf}'|-1} \cdot (i + 1) * \frac{\text{num_slices}}{|\text{slip_surf}'|-1} = \text{subslice}(\frac{\text{num_slices}}{|\text{slip_surf}'|-1}, \text{slip_surf}[i], \text{slip_surf}[i + 1]))$

13.4.5 Local Functions

$\text{large_segment}(\text{surf}) : \text{coords} \rightarrow \mathbb{Z}$

$\text{large_segment}(\text{surf}) = \text{index}$ such that

$\forall(i : \mathbb{Z} | i \in [0..|\text{surf}| - 2] : \text{surf}[\text{index} + 1] - \text{surf}[\text{index}] \geq \text{surf}[i + 1] - \text{surf}[i])$

$\text{midpoint}(\text{point1}, \text{point2}) : \text{coord} \times \text{coord} \rightarrow \text{coord}$

$\text{midpoint}(\text{point1}, \text{point2}) = < \frac{\text{point1}.x + \text{point2}.x}{2}, \frac{\text{point1}.y + \text{point2}.y}{2} >$

$\text{subslice}(n, \text{point1}, \text{point2}) : \text{int} \times \text{coord} \times \text{coord} \rightarrow \text{coords}$

$\text{subslice}(n, \text{point1}, \text{point2}) = \text{subslices}$ such that

$\forall(i : \mathbb{Z} | i \in [0..n] : \text{subslices}[i].x = \text{point1}.x + \frac{i}{n} * (\text{point2}.x - \text{point1}.x) \wedge \text{subslices}[i].y = \text{point1}.y + \frac{i}{n} * (\text{point2}.y - \text{point1}.y))$

14 MIS of the Morgenstern-Price Calculation Module

14.1 Module

MorgPriceSolver

14.2 Uses

Input (Section 8), PropertyCalc (Section 15), Sequence (Section 16)

14.3 Syntax

14.3.1 Exported Constants

$\text{MAX_DIFF} = 0.000001$

$\text{MAX_ITER} = 20$

$\text{MIN_FS} = 0.5$

14.3.2 Exported Data Types

N/A

14.3.3 Exported Access Programs

Name	In	Out	Exceptions
morg_price	slip	slip	-

14.4 Semantics

14.4.1 State Variables

N/A

14.4.2 Environment Variables

N/A

14.4.3 Assumptions

N/A

14.4.4 Access Routine Semantics

morg_price(*slip_surf*):

- output:

out := *slip_surf*' where *slip_surf*'.*Fs*, *slip_surf*'.*G*, and *slip_surf*'.*X* satisfy the following system of equations, taken from the SRS document. The equations are presented with the symbols from the SRS document for readability, though the symbols *F_S*, *G*, and *X* correspond to *slip_surf*'.*Fs*, *slip_surf*'.*G*, and *slip_surf*'.*X*, respectively.

$$(IM1): F_S = \frac{\sum_{i=1}^{n-1} \left[R_i \prod_{c=i}^{n-1} \Psi_c \right] + R_n}{\sum_{i=1}^{n-1} \left[T_i \prod_{c=i}^{n-1} \Psi_c \right] + T_n}$$

$$\begin{aligned}
(\text{IM2}): C1_i &= \begin{cases} b_1 [G_1 + H_1] \tan(\alpha_1) & i = 1 \\ b_i [(G_i + G_{i-1}) + (H_i + H_{i-1})] \tan(\alpha_i) & 2 \leq i \leq n-1 \\ + h_i (-2 U_{t,i} \sin(\beta_i)) \\ b_n [G_{n-1} + H_{n-1}] \tan(\alpha_{n-1}) & i = n \end{cases} \\
C2_i &= \begin{cases} b_1 G_1 f_1 & i = 1 \\ b_i (f_i G_i + f_{i-1} G_{i-1}) & 2 \leq i \leq n-1 \\ b_n G_{n-1} f_{n-1} & i = n \end{cases} \\
\lambda &= \frac{\sum_{i=1}^n C1_i}{\sum_{i=1}^n C2_i} \\
(\text{IM3}): G_i &= \begin{cases} \frac{(FS)T_1 - R_1}{\Phi_i} & i=1 \\ \frac{\Psi_{i-1} \cdot G_{i-1} + (FS) \cdot T_i - R_i}{\Phi_i} & 2 \leq i \leq n-1 \\ 0 & i=0 \vee i=n \end{cases}
\end{aligned}$$

$$(\text{GD6}): X = \lambda \cdot f \cdot G$$

The solution method is to start with initial guesses $F_S = 1$ and $\lambda = 0$ and use them to compute F_S using IM1 and G using IM3, then use these values to compute a new guess for λ using IM2. This iteration continues until the absolute difference between F_S in the current iteration and in the previous iteration is less than MAX_DIFF, or until the absolute difference between λ in the current iteration and in the previous iteration is less than MAX_DIFF. When this occurs, X is computed using GD6, and $\text{slip_surf}'.Fs, \text{slip_surf}'.G, \text{slip_surf}'.X := F_S, G, X$. If MAX_ITER iterations occur, the solution is considered to be non-converging. If the solution converges but $F_S < \text{MIN_FS}$, the solution is considered to be spurious. In either case, $\text{slip_surf}'.Fs, \text{slip_surf}'.G, \text{slip_surf}'.X := 1000, [], []$.

14.4.5 Local Functions

N/A

15 MIS of the Slice Property Calculation Module

15.1 Module

PropertyCalc

15.2 Uses

Input (Section 8), Sequence (Section 16)

15.3 Syntax

15.3.1 Exported Constants

N/A

15.3.2 Exported Data Types

paramsInternalForce = tuple of (Ub, Ut, W, H : $[\mathbb{R}]$) (Appendix 19.1.5)

paramsAngles = tuple of (alpha, beta : $[\mathbb{R}]$) (Appendix 19.1.6)

15.3.3 Exported Access Programs

Name	In	Out	Exceptions
prop_calc	slip	-	-
ub	-	$[\mathbb{R}]$	-
ut	-	$[\mathbb{R}]$	-
w	-	$[\mathbb{R}]$	-
h	-	$[\mathbb{R}]$	-
alpha	-	$[\mathbb{R}]$	-
beta	-	$[\mathbb{R}]$	-
hts	-	$[\mathbb{R}]$	-

15.4 Semantics

15.4.1 State Variables

force : paramsInternalForce

angles : paramsAngles

heights : $[\mathbb{R}]$

15.4.2 Environment Variables

N/A

15.4.3 Assumptions

- prop_calc is called before any of the other access programs.

15.4.4 Access Routine Semantics

prop_calc(*slip_surf*):

- transition:

The equations used below contain symbols from the SRS document for this project for the sake of brevity. The SRS should be consulted for the definitions of these symbols.

force, *angles*, *heights* := *force*', *angles*', *soil*'*heights*' where

$\forall(i : \mathbb{Z} | i \in [1..|slip_surf| - 1]) :$

$$\begin{aligned}
 force.Ub[i] &= \ell_{b,i} \begin{cases} (y_{wt,i} - y_{slip,i}) \gamma_w, & y_{wt,i} > y_{slip,i} \\ 0, & y_{wt,i} \leq y_{slip,i} \end{cases} \\
 \wedge force.Ut[i] &= \ell_{s,i} \begin{cases} (y_{wt,i} - y_{us,i}) \gamma_w, & y_{wt,i} > y_{us,i} \\ 0, & y_{wt,i} \leq y_{us,i} \end{cases} \\
 \wedge force.W[i] &= b_i \begin{cases} (y_{us,i} - y_{slip,i}) \gamma_{Sat}, & y_{wt,i} \geq y_{us,i} \\ (y_{us,i} - y_{wt,i}) \gamma + (y_{wt,i} - y_{slip,i}) \gamma_{Sat}, & y_{us,i} > y_{wt,i} > y_{slip,i} \\ (y_{us,i} - y_{slip,i}) \gamma, & y_{wt,i} \leq y_{slip,i} \end{cases} \\
 \wedge force.H[i] &= \begin{cases} \frac{[y_{us,i} - y_{slip,i}]^2}{2} \gamma_{Sat} + [y_{wt,i} - y_{us,i}]^2 \gamma_{Sat}, & y_{wt,i} \geq y_{us,i} \\ \frac{[y_{wt,i} - y_{slip,i}]^2}{2} \gamma_{Sat}, & y_{us,i} > y_{wt,i} > y_{slip,i} \\ 0, & y_{wt,i} \leq y_{slip,i} \end{cases} \\
 \wedge angles.alpha[i] &= \arctan \left(\frac{y_{slip,i} - y_{slip,i-1}}{x_{slip,i} - x_{slip,i-1}} \right)
 \end{aligned}$$

$$\wedge \text{angles.beta}[i] = \arctan \left(\frac{y_{us,i} - y_{us,i-1}}{x_{us,i} - x_{us,i-1}} \right)$$

$$\wedge \text{heights}[i] = 0.5 * ((y_{us,i} - y_{slip,i}) + (y_{us,i+1} - y_{slip,i+1}))$$

ub():

- output:

$$out := force.Ub$$

ut():

- output:

$$out := force.Ut$$

w():

- output:

$$out := force.W$$

h():

- output:

$$out := force.H$$

alpha():

- output:

$$out := angles.alpha$$

beta():

- output:

$$out := angles.beta$$

hts():

- output:

$$out := heights$$

15.4.5 Local Functions

N/A

16 MIS of the Sequence Data Structure Module

16.1 Module

Sequence

16.2 Uses

N/A

16.3 Syntax

16.3.1 Exported Constants

N/A

16.3.2 Exported Data Types

[T] = sequence of T, where T is any type

16.3.3 Exported Access Programs

Name	In	Out	Exceptions
[$_$]	Any number of values of type T	[T]	-
-($_$)	[T], \mathbb{Z}	T	
-($_$:- $_$)	[T], \mathbb{Z} , \mathbb{Z}	[T]	-

16.4 Semantics

16.4.1 State Variables

N/A

16.4.2 Environment Variables

N/A

16.4.3 Assumptions

N/A

16.4.4 Access Routine Semantics

$[-]$ (Any number of values):

- output:

$out :=$ A sequence containing the arguments passed to the function.

$[-](list, int)$:

- output:

$out := list[int]$

$[-:](list, int1, int2)$:

- output:

$out := list[int1..int2]$

16.4.5 Local Functions

N/A

16.4.6 Considerations

This module is the sequence data type and operations on sequences implemented by Matlab.

17 MIS of the Plotting Module

17.1 Module

Plot

17.2 Uses

N/A

17.3 Syntax

17.3.1 Exported Constants

N/A

17.3.2 Exported Data Types

N/A

17.3.3 Exported Access Programs

Name	In	Out	Exceptions
plot	$[\mathbb{R}], [\mathbb{R}]$	-	-

17.4 Semantics

17.4.1 State Variables

N/A

17.4.2 Environment Variables

screen : $[\mathbb{Z}]$

- *screen* represents the colour values for each pixel on the screen of the hardware running SSP.

17.4.3 Assumptions

N/A

17.4.4 Access Routine Semantics

plot(*x*, *y*):

- transition:

Modifies *screen* to display a plot with *x* on the horizontal axis and *y* on the vertical axis.

17.4.5 Local Functions

N/A

17.4.6 Considerations

This module is the plot function implemented by Matlab.

18 MIS of the Random Number Generation Module

18.1 Module

Rand

18.2 Uses

N/A

18.3 Syntax

18.3.1 Exported Constants

N/A

18.3.2 Exported Data Types

N/A

18.3.3 Exported Access Programs

Name	In	Out	Exceptions
rand	-	\mathbb{R}	-

18.4 Semantics

18.4.1 State Variables

N/A

18.4.2 Environment Variables

N/A

18.4.3 Assumptions

N/A

18.4.4 Access Routine Semantics

rand():

- output:

out coloneqq A random number in the interval (0,1).

18.4.5 Local Functions

N/A

18.4.6 Considerations

This module is the rand function implemented by Matlab.

References

- Carlo Ghezzi, Mehdi Jazayeri, and Dino Mandrioli. *Fundamentals of Software Engineering*. Prentice Hall, Upper Saddle River, NJ, USA, 2nd edition, 2003.
- Daniel M. Hoffman and Paul A. Strooper. *Software Design, Automated Testing, and Maintenance: A Practical Approach*. International Thomson Computer Press, New York, NY, USA, 1995. URL <http://citeseer.ist.psu.edu/428727.html>.

19 Appendix

19.1 Parameter Tables

19.1.1 Layer Parameters

The elements in the structure of the containers for the parameters of different slope layers. Assumed that the parameters will be entered such that sequence progresses from the uppermost stratigraphic layer at the first index, to the lowest stratigraphic layer at the last index. $nlayer$ refers to the number of soil layers in the slope, and is defined by the input file.

Parameter	Description
$strat : [[\mathbb{R}]^{2,nvtx}]^{1,nlayer}$	Sequence of coordinate sequences describing the vertexes of each layer. The value $nvtx$ is defined by the input file, and can be different for each sequence.
$phi : [\mathbb{R}]^{1,nlayer}$	Sequence of the effective angle of friction for each stratigraphic layer.
$coh : [\mathbb{R}]^{1,nlayer}$	Sequence of the effective cohesion for each stratigraphic layer.
$gam : [\mathbb{R}]^{1,nlayer}$	Sequence of the dry unit weight of soil for each stratigraphic layer.
$gams : [\mathbb{R}]^{1,nlayer}$	Sequence of the saturated unit weight of soil for each stratigraphic layer.
$E : [\mathbb{R}]^{1,nlayer}$	Sequence of the Young's modulus for each stratigraphic layer.
$nu : [\mathbb{R}]^{1,nlayer}$	Sequence of the poissons ratio for each stratigraphic layer.

19.1.2 Piezometric Parameter

The elements in the structure for parameters relating to the piezometric surface existing on the slope. npz refers to the number of vertexes describing the piezometric surface, and is defined by the input file.

Parameter	Description
$piez : [\mathbb{R}]^{2,npz}$	Sequence of vertex coordinates describing the geometry of the water table. If there is no water table than $piez$ is an empty array.
$gamw : \mathbb{R}$	The unit weight of water.

19.1.3 Search Range Parameters

The elements in the structure for parameters relating to the range of coordinates the critical slip surface will be searched for in.

Parameter	Description
Xext : $[\mathbb{R}]^{1,2}$	Sequence of the range of x -ordinates that the exit point of the slip will be searched for in. Exit refers to the point of the slip at lower elevation that the slope mass will move towards during failure.
Xent : $[\mathbb{R}]^{1,2}$	Sequence of the range of x -ordinates that the entry point of the slip will be searched for in. Entry refers to the point of the slip at higher elevation that the slope mass will move away from during failure.
Ylim : $[\mathbb{R}]^{1,2}$	Sequence of range of y -ordinates that the slip will be searched for in. The larger value should be greater than the max y -ordinate of the slope. The smaller Ylim value is the deepest the slip surface is expected to descend to.

19.1.4 Solution Parameters

The elements in the structure for parameters relating to method in which the solution method will be approached.

Parameter	Description
ltor : \mathbb{B}	Direction the slope is expected to experience failure in. If true than the side of the slope with a greater x -ordinate value is at a lower elevation. If false than the side of the slope with a greater x -ordinate is at a higher elevation.
ftype : \mathbb{B}	Switch between functions to use for interslice shear/normal inclination function. If true then the inclination function is a constant (Spencer's method). If false then the inclination function is a half-sine (standard Morgenstern Price method).
evnslc : \mathbb{B}	Switch between method of slicing a slip surface to when preparing for analysis. If true then slice slip surface into equal x -ordinate widths. If false then slice distance between vertices into even number of slices.
cncvu : \mathbb{B}	Switch for concave slip surface admissibility criterion. If true then an admissible slip surface must be concave upwards towards the surface. If false then an admissible slip surface does not need to pass this criterion.

obtu : \mathbb{B}	Switch for angle limit slip surface admissibility criterion. If true then an admissible slip surface must have all interior angles greater than a set limit. If false then an admissible slip surface does not need to pass this criterion.
---------------------	---

19.1.5 Internal Force Parameters

The elements in the structure for parameters relating to the forces acting on a slice caused by the slope, and water in the slope acting on itself. n refers to the number of slices composing the evaluation slip surface, and is defined by the Slicer module (section 13).

Parameter	Description
Ub : $[\mathbb{R}]^{1,n}$	Sequence of the force acting on the basal surface of a slice as a result of pore water pressure within the slice. Value for each slice. From DD2 of the SRS.
Ut : $[\mathbb{R}]^{1,n}$	Sequence of the force acting on the upper surface of a slice as a result of pore water pressure standing water on the surface. Value for each slice. From DD3 of the SRS.
W : $[\mathbb{R}]^{1,n}$	Sequence of the downward force acting on the slice caused by the mass of the slice and the force of gravity. Value for each slice. From DD1 of the SRS.
H : $[\mathbb{R}]^{1,n-1}$	Sequence of the force acting into the interslice surfaces as a result of pore water pressure within the adjacent slices. Value for each interslice. From DD4 of the SRS.

19.1.6 Angle Parameters

The elements in the structure for parameters relating to the angles of the slice surfaces. n refers to the number of slices composing the slip surface, and is defined by the input *evalslip* given to the Property Sorter module (section 15).

Parameter	Description
Alpha : $[\mathbb{R}]^{1,n}$	Sequence of the angle that the basal surface of the slice makes with the horizontal. Value for each slice. From DD?? of the SRS.

Beta : $[\mathbb{R}]^{1,n}$

Sequence of the angle that the upper surface of the slice makes with the horizontal. Value for each slice. From DD?? of the SRS.
