

Cisco Packet Tracer

File Edit Options View Tools Extensions Help

Logical Physical x: 759, y: 1204

HYBRID TOPOLOGY.

S.BALAJI
192412691.

PC-PT PC7

2960-24TT Switch7

2960-24TT Switch8

PC-PT PC8

2960-24TT Switch11

2960-24TT Switch12

2960-24TT Switch13

PC-PT PC11

PC-PT PC12

PC-PT PC13

PC-PT PC9

2960-24TT Switch9

2960-24TT Switch10

PC-PT PC10

PC-PT PC14

PC-PT PC17

PC16

Physical Config Desktop Programming Attributes

Command Prompt

Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 4ms, Average = 1ms

C:\>ipconfig /all

FastEthernet0 Connection: (default port)

Connection-specific DNS Suffix...
Physical Address..... 00E0.8FA3.6D84
Link-local IPv6 Address..... FE80::2E0:8FFF:FEA3:6D84
IP Address..... 172.23.20.9
Subnet Mask..... 255.255.0.0
Default Gateway..... 0.0.0.0
DNS Servers..... 0.0.0.0
DHCP Servers..... 0.0.0.0
DHCPv6 Client DUID..... 00-01-00-01-47-18-C9-4B-00-E0-8F-A3-6D-84

Bluetooth Connection:

Connection-specific DNS Suffix...
Physical Address..... 00E0.F74C.5DCE
Link-local IPv6 Address..... ::
IP Address..... 0.0.0.0
Subnet Mask..... 0.0.0.0
Default Gateway..... 0.0.0.0
DNS Servers..... 0.0.0.0

Time: 00:39:42.772

PLAY CONTROLS:

Scenario 0

New Delete

Toggle PDU List Window

Event List Realtime Simulation

| Fire | Last Status | Source | Destination | Type | Color | Time(sec) | Periodic | Num | Ed |
|------|-------------|--------|-------------|------|-------|-----------|----------|-----|----|
| | Successful | PC1 | PC4 | ICMP | | 0.000 | N | 0 | (e |
| | Successful | PC15 | PC16 | ICMP | | 0.816 | N | 1 | (e |

Automatically Choose Connection Type