

Cisco Packet Tracer

File Edit Options View Tools Extensions Help

Logical Physical x: 1342, y: 288

RING TOPOLOGY.

PC-PT PC11

2960-24TT Switch0

2960-24TT Switch2

PC-PT PC12

2960-24TT Switch1

2960-24TT Switch4

PC-PT PC13

PC-PT PC14

S.BALAJI.  
192412691.

PC13

Physical Config Desktop Programming Attributes

Command Prompt

Approximate round trip times in milli-seconds:  
Minimum = 6ms, Maximum = 12ms, Average = 7ms

C:\>ipconfig /all

FastEthernet0 Connection: (default port)

Connection-specific DNS Suffix...  
Physical Address..... 0001.970B.4AD9  
Link-local IPv6 Address..... FE80::201:97FF:FE0B:4AD9  
IP Address..... 172.23.20.3  
Subnet Mask..... 255.255.0.0  
Default Gateway..... 0.0.0.0  
DNS Servers..... 0.0.0.0  
DHCP Servers..... 0.0.0.0  
DHCPv6 Client DUID..... 00-01-00-01-C3-71-05-5B-00-01-97-0B-4A-D9

Bluetooth Connection:

Connection-specific DNS Suffix...  
Physical Address..... 0060.2FA6.67B2  
Link-local IPv6 Address..... ::  
IP Address..... 0.0.0.0  
Subnet Mask..... 0.0.0.0  
Default Gateway..... 0.0.0.0  
DNS Servers..... 0.0.0.0

At Device Type

PC11	STP
Switch4	STP
PC13	STP
PC14	STP
Switch0	STP
Switch2	STP
Switch4	STP
PC12	STP
Switch1	DTP

Captured to: 7.412 s

Time: 01:45:41.325 PLAY CONTROLS:

Scenario 0

New Delete

Toggle PDU List Window

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Ed
	Successful	PC11	PC14	ICMP		0.000	N	0	(e

Automatically Choose Connection Type

Simulation