

Cisco Packet Tracer

File Edit Options View Tools Extensions Help

Logical Physical x: 474, y: 28

S.BALAJI 192412691 TREE TOPOLOGY.

```
graph TD
    S2[2960-24TT Switch2] --- S1[2960-24TT Switch1]
    S1 --- S0[2960-24TT Switch0]
    S0 --- S6[2960-24TT Switch6]
    S1 --- PC1[PC-PT PC1]
    S1 --- PC2[PC-PT PC2]
    S0 --- PC5[PC-PT PC5]
    S6 --- PC6[PC-PT PC6]
    S6 --- S4[2960-24TT Switch4]
    S6 --- S5[2960-24TT Switch5]
    S4 --- PC3[PC-PT PC3]
    S5 --- PC4[PC-PT PC4]
```

PC6

Physical Config Desktop Programming Attributes

Command Prompt

```
C:\>config /all
Invalid Command.

C:\>ipconfig /all

FastEthernet0 Connection:(default port)

Connection-specific DNS Suffix...:
Physical Address...: 00E0.8F20.6059
Link-local IPv6 Address...: FE80::2E0:8FFF:FE20:6059
IP Address...: 172.23.20.5
Subnet Mask...: 255.255.0.0
Default Gateway...: 0.0.0.0
DNS Servers...: 0.0.0.0
DHCP Servers...: 0.0.0.0
DHCPv6 Client DUID...: 00-01-00-01-11-09-E5-73-00-80-8F-20-60-59

Bluetooth Connection:

Connection-specific DNS Suffix...:
Physical Address...: 00E0.8F7C.8A35
Link-local IPv6 Address...: ::
IP Address...: 0.0.0.0
Subnet Mask...: 0.0.0.0
Default Gateway...: 0.0.0.0
DNS Servers...: 0.0.0.0
```

Time: 00:31:30.283 PLAY CONTROLS:

Scenario 0

New Delete

Toggle PDU List Window

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic	Num	Ed
	Successful	PC1	PC4	ICMP		0.000	N	0	(e

Automatically Choose Connection Type