```
mysql> insert into student values(1,"Anu","BCA");
Query OK, 1 row affected (0.01 sec)

mysql> insert into student values(2,"Mona","BBA");
Query OK, 1 row affected (0.01 sec)

mysql> insert into student values(3,"Vaish","BBA");
Query OK, 1 row affected (0.01 sec)

mysql> insert into student values(4,"Liya","BDes");
Query OK, 1 row affected (0.01 sec)

mysql> insert into student values(5,"Riya","BDS");
Query OK, 1 row affected (0.01 sec)

mysql> select * from student;
+--------+-------+--------+
| Rollno | Name  | Course |
+--------+-------+--------+
|      1 | Anu   | BCA    |
|      2 | Mona  | BBA    |
|      3 | Vaish | BBA    |
|      4 | Liya  | BDes   |
|      5 | Riya  | BDS    |
+--------+-------+--------+
5 rows in set (0.00 sec)

mysql> create table persdet(Rollno int, Gender varchar(2),Address varchar(20),Phone_number int);
ERROR 1050 (42S01): Table 'persdet' already exists
mysql> insert into persdet values(1,"Bengaluru",97536792);
ERROR 1136 (21S01): Column count doesn't match value count at row 1
mysql> insert into persdet values(1,"F","Bengaluru",97536792);
Query OK, 1 row affected (0.01 sec)

mysql> insert into persdet values(2,"F","Mysore",974535232);
Query OK, 1 row affected (0.01 sec)

mysql> insert into persdet values(3,"F","Mysore",97576432);
Query OK, 1 row affected (0.01 sec)

mysql> insert into persdet values(4,"F","Coimbatore",965323844);
Query OK, 1 row affected (0.04 sec)
```

```
mysql> create table persdet(Rollno int, Gender varchar(2),Address varchar(20),Phone_number int);
ERROR 1050 (42S01): Table 'persdet' already exists
mysql> insert into persdet values(1,"Bengaluru",97536792);
ERROR 1136 (21S01): Column count doesn't match value count at row 1
mysql> insert into persdet values(1,"F","Bengaluru",97536792);
Query OK, 1 row affected (0.01 sec)

mysql> insert into persdet values(2,"F","Mysore",974535232);
Query OK, 1 row affected (0.01 sec)

mysql> insert into persdet values(3,"F","Mysore",97576432);
Query OK, 1 row affected (0.01 sec)

mysql> insert into persdet values(4,"F","Coimbatore",965323844);
Query OK, 1 row affected (0.04 sec)

mysql> insert into persdet values(5,"F","Chennai",96864244);
Query OK, 1 row affected (0.04 sec)

mysql> select * from persdet;
+--------+--------+------------+--------------+
| Rollno | Gender | Address    | Phone_number |
+--------+--------+------------+--------------+
|      1 | F      | Bengaluru  |     97536792 |
|      2 | F      | Mysore     |    974535232 |
|      3 | F      | Mysore     |     97576432 |
|      4 | F      | Coimbatore |    965323844 |
|      5 | F      | Chennai    |     96864244 |
+--------+--------+------------+--------------+
5 rows in set (0.00 sec)

mysql> select student.Name,student.Course,persdet.Address from student inner join persdet on student.Rollno=persdet.Rollno;
+-------+--------+------------+
| Name  | Course | Address    |
+-------+--------+------------+
| Anu   | BCA    | Bengaluru  |
| Mona  | BBA    | Mysore     |
| Vaish | BBA    | Mysore     |
| Liya  | BDes   | Coimbatore |
| Riya  | BDS    | Chennai    |
+-------+--------+------------+
5 rows in set (0.00 sec)
```

```
mysql> insert into persdet values(6,"F","Chennai",96453344);
Query OK, 1 row affected (0.04 sec)

mysql> select student.Name,student.Course,persdet.Address from student right join persdet on student.Rollno=persdet.Rollno;
+-------+--------+------------+
| Name  | Course | Address    |
+-------+--------+------------+
| Anu   | BCA    | Bengaluru  |
| Mona  | BBA    | Mysore     |
| Vaish | BBA    | Mysore     |
| Liya  | BDes   | Coimbatore |
| Riya  | BDS    | Chennai    |
| NULL  | NULL   | Chennai    |
+-------+--------+------------+
6 rows in set (0.00 sec)

mysql> select student.Name,student.Course,persdet.Address from student left join persdet on student.Rollno=persdet.Rollno;
+-------+--------+------------+
| Name  | Course | Address    |
+-------+--------+------------+
| Anu   | BCA    | Bengaluru  |
| Mona  | BBA    | Mysore     |
| Vaish | BBA    | Mysore     |
| Liya  | BDes   | Coimbatore |
| Riya  | BDS    | Chennai    |
+-------+--------+------------+
5 rows in set (0.00 sec)

mysql>
```

```
mysql> Select * from student where course=(select course where name="vaish");
+--------+-------+--------+
| Rollno | Name  | Course |
+--------+-------+--------+
|      3 | Vaish | BBA    |
+--------+-------+--------+
1 row in set (0.00 sec)
```