```sql
CREATE TABLE departments (
  dept_id INT PRIMARY KEY,
  dept_name VARCHAR(50)
);

CREATE TABLE employees (
  emp_id INT PRIMARY KEY,
  emp_name VARCHAR(50),
  dept_id INT,
  salary INT
);

INSERT INTO departments VALUES (1,'HR'),
(2,'IT'),(
  3,'Finance'),
  (4,'Marketing');
INSERT INTO employees VALUES
(101,'Asha',1,30000),
(102,'Ravi',2,50000),
(103,'Meera',2,55000),
(104,'Kiran',3,45000),
(105,'Neha',NULL,40000);


SELECT dept_id, COUNT(*) AS total_emp, AVG(salary) AS avg_salary
FROM employees
```

```sql
SELECT dept_id, COUNT(*) AS total_emp, AVG(salary) AS avg_salary
FROM employees
GROUP BY dept_id;


SELECT dept_id, COUNT(*) AS total_emp
FROM employees
GROUP BY dept_id
HAVING COUNT(*) > 1;

SELECT emp_name, salary FROM employees ORDER BY salary DESC;


SELECT dept_id, AVG(salary) AS avg_salary
FROM employees
WHERE dept_id IS NOT NULL
GROUP BY dept_id
HAVING AVG(salary) > 40000
ORDER BY avg_salary DESC;
```

```
[illegible]
---------- ---------- ----------
      NULL          1       40000
         1          1       30000
         2          2       52500
         3          1       45000
dept_id    total_emp
---------- ----------
         2          2
emp_name                                                 salary
-------------------------------------------------- ----------
Meera                                                     55000
Ravi                                                      50000
Kiran                                                     45000
Neha                                                      40000
Asha                                                      30000
dept_id    avg_salary
---------- ----------
         2       52500
         3       45000
```