queries.sql

```sql
CREATE TABLE departments (
 dept_id INT PRIMARY KEY,
 dept_name VARCHAR(50)
);
CREATE TABLE employees (
 emp_id INT PRIMARY KEY,
 emp_name VARCHAR(50),
 dept_id INT,
 salary INT
);
INSERT INTO departments VALUES (1,'HR'),(2,'IT'),(3,'Finance'),(4,'Marketing');
INSERT INTO employees VALUES
(101,'Asha',1,30000),(102,'Ravi',2,50000),(103,'Meera',2,55000),
(104,'Kiran',3,45000),(105,'Neha',NULL,40000);

DELIMITER //
CREATE PROCEDURE GetAllEmployees()
BEGIN
 SELECT * FROM employees;
END //
CREATE PROCEDURE AddEmployee(IN p_id INT, IN p_name VARCHAR(50), IN p_dept INT, IN
BEGIN
 INSERT INTO employees VALUES (p_id, p_name, p_dept, p_sal);
END //
CREATE PROCEDURE UpdateSalary(IN p_id INT, IN p_sal INT)
BEGIN
 UPDATE employees SET salary = p_sal WHERE emp_id = p_id;

CREATE PROCEDURE DeleteEmployee(IN p_id INT)
BEGIN
 DELETE FROM employees WHERE emp_id = p_id;
END //
DELIMITER ;

CALL GetAllEmployees();
CALL AddEmployee(106,'Sana',1,35000);
CALL UpdateSalary(106,38000);
CALL DeleteEmployee(106);
CALL GetAllEmployees();
```

Output:

```
+--------+----------+---------+--------+
| emp_id | emp_name | dept_id | salary |
+--------+----------+---------+--------+
|    101 | Asha     |       1 |  30000 |
|    102 | Ravi     |       2 |  50000 |
|    103 | Meera    |       2 |  55000 |
|    104 | Kiran    |       3 |  45000 |
|    105 | Neha     |    NULL |  40000 |
+--------+----------+---------+--------+
```


```
+--------+----------+---------+--------+
| emp_id | emp_name | dept_id | salary |
+--------+----------+---------+--------+
|    101 | Asha     |       1 |  30000 |
|    102 | Ravi     |       2 |  50000 |
|    103 | Meera    |       2 |  55000 |
|    104 | Kiran    |       3 |  45000 |
|    105 | Neha     |    NULL |  40000 |
+--------+----------+---------+--------+
```