ABSTRACT

An ultra-wide band pentagon antenna is designed and simulated using CST microwave studio for detecting the tumour present in the brain. It is operating at the range 3.67 GHz to 13.2 GHz in free space. The antenna is designed using Flame Retardant (FR-4) substrate. The dimensions of the antenna are 44*30mm². For improving the bandwidth and directivity modifications is made in the patch and ground. The input radiations from the antenna are allowed to penetrate into the human head phantom with three layers namely skin-outer layer, skull-middle layer and brain-inner layer containing tumour. The receiver antenna is used to record the output response. From the output signal various statistical parameters are determined to accurately detect the tumour.

TABLE OF CONTENTS

CHAPTER			TITLE	PAGE
NO.				NO.
	ABSTRACT			
	TABLE OF CONTENTS			vi
	LIS	T OF FI	IGURES	viii
	LIS	T OF TA	ABLES	xii
	LIS	T OF A	BBREVATIONS	xiii
1	INT	RODU	CTION	1
	1.1	Brain	tumour	2
		1.1.1	Parts of the brain	3
	1.2	Types	of brain tumour	3
		1.2.1	Primary brain tumour	4
		1.2.2	Secondary brain tumour	6
	1.3	Object	tive	7
2	LITRATURE REVIEW			8
	2.1	Introd	uction	8
	2.2	Work	proposed by various authors	8
3	FUN	DAME	NTAL PARAMETERS OF ANTENNA	11
	3.1	Introd	uction	11
	3.2	Anten	na basics	11
	3.3	Anten	na parameters	11
		3.3.1	Bandwidth	12
		3.3.2	Return loss	13
		3.3.3	Gain	13
		3.3.4	Directivity	14
		3.3.5	Resonant frequency	14

	3.3.6	Impeda	nce	15
	3.3.7	Radiatio	16	
	3.3.8	VSWR	17	
	3.3.9	Polariza	ation	18
3.4	THE	ORY OF	MICROSTRIP ANTENNA	19
	3.4.1	Design	specifications	20
	3.4.2	Radiatio	on mechanisms	22
	3.4.3	Advanta	ages and disadvantages	23
	3.4.4	Applica	tions	24
		3.4.4.1	Mobile & satellite	25
			communication	
		3.4.4.2	Global positioning system	25
		3.4.4.3	Radio frequency identification	25
		3.4.4.4	WIMAX	25
		3.4.4.5	Radar application	26
		3.4.4.6	Telemedicine application	26
		3.4.4.7	Medical application of patch	26
	3.4.4	Feeding	techniques	27
		3.4.4.1	Microstrip line feeding	27
		3.4.4.2	Co-axial line feed	28
		3.4.4.3	Proximity coupled feed	29
		3.4.4.4	Aperture coupled feed	30
PRO	POSEI	D METH	ODOLOGY	32
4.1	UWB	pentagon	antenna	32
	4.1.1	Simulat	ion result	33
4.2	Modif	ied design	n of pentagon antenna	35
	4.2.1	Modifie	ed design of pentagon antenna	35
4.3	Fabric	cated antenna		
	PRO 4.1 4.2	3.3.7 3.3.8 3.3.9 3.4.1 3.4.2 3.4.3 3.4.4 3.4.4 PROPOSEI 4.1 UWB 4.1.1 4.2 Modification (A.2.1)	3.3.7 Radiation 3.3.8 VSWR 3.3.9 Polariza 3.4 THEORY OF 3.4.1 Design of the second of	3.3.9 Polarization 3.4 THEORY OF MICROSTRIP ANTENNA 3.4.1 Design specifications 3.4.2 Radiation mechanisms 3.4.3 Advantages and disadvantages 3.4.4 Applications 3.4.4.1 Mobile & satellite communication 3.4.4.2 Global positioning system 3.4.4.3 Radio frequency identification 3.4.4.4 WIMAX 3.4.4.5 Radar application 3.4.4.6 Telemedicine application 3.4.4.7 Medical application of patch 3.4.4 Feeding techniques 3.4.4.1 Microstrip line feeding 3.4.4.2 Co-axial line feed 3.4.4.3 Proximity coupled feed PROPOSED METHODOLOGY 4.1 UWB pentagon antenna 4.1.1 Simulation result 4.2 Modified design of pentagon antenna 4.2.1 Modified design of pentagon antenna

4.4		Phantom design		40	0
		4.4.1	Phantom model without tumour	4	1
		4.4.2	Phantom model with tumour	4	1
	4.5	Analy	sis of brain tumour	4:	5
5	RESULTS AND CONCLUSION			54	4
	5.1	Concl	usion	54	4
	5.2	Future	e work	54	4
	APPENDIX			5:	5
	REFERENCES			6	1

LIST OF FIGURES

Fig No	Title	Page	
		No	
1.1	Tumour development stages	2	
3.1	Antenna bandwidth	12	
3.2	Impedance of an RF antenna with frequency	15	
3. 3	Radiation Patterns in Polar and Cartesian Coordinates Showing Various Types of Lobes	17	
3.4	Types of polarization	18	
3.5	Microstrip patch antenna	19	
3.6	Rectangular mictrostrip patch antenna	22	
3.7	Side view	23	
3.8	Microstrip patch antenna with microstrip line feed	28	
3.9	Microstrip Patch antenna with coaxial line feed.	29	
3.10	Aperture coupled feed microstrip patch antenna	30	
3.11	Proximity couple feed microstrip patch antenna	31	
4.1(a)	Front view of the designed antenna	32	
4.1(b)	Back view of the designed antenna	32	
4.2	The above figure shows the patch and ground of the designed antenna.	32	
4.3	Reflection coefficient of the designed antenna	33	
4.4	Directivity of the designed antenna	33	
4.5	Gain of the designed antenna	33	
4.6	VSWR plot of the designed antenna	34	
4.7	Radiation pattern of the designed antenna	34	
4.8(a)	E-Field pattern	34	
4.8(b)	H-field pattern	34	
4.9(a)	Front view of designed antenna	35	

4.9(b)	Back view of designed antenna	35
4.10	Patch of antenna with dimensions	35
4.11	Ground and patch with dimensions	36
4.12	Reflection coefficient of the designed antenna	36
4.13	Gain of the designed antenna	37
4.14	Directivity of the designed antenna	37
4.15	VSWR plot of the designed antenna	38
4.16	Radiation pattern of the designed antenna	38
4.17(a)	E-Field pattern	38
4.17(b)	H-field pattern	38
4.18	Fabricated antenna front view	39
4.19	Fabricated antenna back view	39
4.20	Head phantom design	40
4.21	Phantom without tumour	41
4.22	Spherical shaped tumour with 24.6 mm radius	41
4.23	Head model contains 10mm tumour which is at a distance of	42
4.24	40mm from antenna Head model contains 15mm tumour	42
4.25	Head model contains 24.6mm tumour which is at a distance of 30mm from antenna.	42
4.26	Head model contains 15mm tumour which is at a distance of	43
4.27	30mm from antenna. Head model contains 10mm tumour which is at a distance of	43
4.28	15mm from antenna Head model contains 10mm tumour which is at a distance of	43
4.29	65mm from antenna Head model contains 15mm tumour which is at a distance of	44
4.30	60mm from antenna Reflection coefficient curves of head model with tumour and	44
4.31	without tumour. Mean value of the head phantom without tumour and with	47
4.32	different sized tumour Median value of the head phantom without tumour and with different sized tumour	47

4.33	Mode value of the head phantom without tumour and with	48
	different sized tumour	
4.34	Variance of the head phantom without tumour and with	48
	different sized tumour	
4.35	Standard deviation of the head phantom without tumour and	49
	with different sized tumour.	
4.36	Skewness of the head phantom without tumour and with	49
	different sized tumour	
4.37	Kurtosis of the head phantom without tumour and with	50
	different sized tumour.	
4.38	Minimum value of the head phantom without tumour and	50
	with different sized tumour.	
4.39	Maximum value of the head phantom without tumour and	51
	with different sized tumour.	
4.40	Rms value of the head phantom without tumour and with	51
	different sized tumour	
4.41	Crest factor of the head phantom without tumour and with	52
	different sized tumour.	
4.42	Covariance of the head phantom without tumour and with	52
	different sized tumour.	
4.43	Correlation coefficient of the head phantom without tumour	53
	and with different sized tumour.	

LIST OF TABLES

Table	Title	Page
No		No
4.1	Dimensions of patch and ground	32
4.2	Patch dimensions of proposed antenna	35
4.3	Ground dimensions of designed antenna	36
4.4	Electrical properties of the different layers of the head model	40
4.5	Phantom dimensions	41
4.6	Analysis with different tumours	51

LIST OF ABBREVIATIONS

MRI Magnetic resonance imaging

PET Positron emission tomography

CT Computed tomography

UWB Ultra-wide band

NET Neuroectodermal Tumour

VSWR Voltage Standing Wave Radio

RHC Right Hand Circular

LHC Left Hand Circular

RFID Radio Frequency Identification

WIMAX Worldwide Interoperability for Microwave Access

MATLAB Matrix Laboratory

RMS Root Mean Square

dB Decibel

dBi Decibel Isotropic

ISM Industrial Scientific Medical

MHz Mega Hertz

GHz Giga Hertz