DESIGN OF ULTRA WIDE BAND ANTENNA

A PROJECT REPORT

Submitted by

DIVYA SOUNDHARYA. N (211714106026)

LEKHA PRIYADHARSHINI. S (211714106069)

NIVETHITHA. P (211714106085)

in partial fulfilment for the award of the degree

of

BACHELOR OF ENGINEERING

in

ELECTRONICS AND COMMUNICATION ENGINEERING

RAJALAKSHMI INSTITUTE OF TECHNOLOGY CHENNAI

ANNA UNIVERSITY: CHENNAI 600 025

APRIL 2018

BONAFIDE CERTIFICATE

Certified that this project report "DESIGN OF ULTRA WIDE BAND ANTENNA" is the bonafide work of "DIVYA SOUNDHARYA. N (211714106026), LEKHA PRIYADHARSHINI. S (211714106069) and NIVETHITHA. P (211714106085)" who carried out the project work under my supervision.

SIGNATURE SIGNATURE

Dr. G.R. SURESH, M.E., Ph.D. Mr. L. FRANKLIN TELFER, M.E., (Ph.D.)

HEAD OF THE DEPARTMENT SUPERVISOR

Professor Assistant Professor

Department of Electronics and Department of Electronics and

Communication Engineering Communication Engineering

Rajalakshmi Institute of Technology Rajalakshmi Institute of Technology

Chennai- 600 124 Chennai- 600 124

CERTIFICATE OF EVALUATION

College Name : 2117- Rajalakshmi Institute of Technology

Branch & Semester: Electronics and Communication Engg. VIII Semester

Subject : EC6811 PROJECT WORK

TITLE OF THE PROJECT:

DESIGN OF ULTRA WIDE BAND ANTENNA

NAME OF THE STUDENTS:

DIVYA SOUNDHARYA. N 211714106026

LEKHA PRIYADHARSHINI. S 211714106069

NIVETHITHA. P 211714106085

The report on the project work submitted by the above students in partial fulfilment for the award of the degree of Bachelor of Engineering in ELECTRONICS AND COMMUNICATION ENGINEERING of Anna University, reported the work done by the above students and then evaluated.

| The University | Viva-voce was | held on | |
|----------------|---------------|---------|--|
|----------------|---------------|---------|--|

INTERNAL EXAMINER

EXTERNAL EXAMINER

ACKNOWLEDGEMENT

We wish to express our hearty and sincere gratitude to our chairman **Dr.S.MEGANATHAN**, **B.E.**, **F.I.E.**, for his sincere endeavour in educating us in his premier institution.

We wish to express our deep gratitude to our beloved chairperson **Dr.(Mrs.)THANGAM MEGANATHAN, M.A., M.Phil., Ph.D.,** for her enthusiastic motivation which helped us a lot in completing the project.

We express our thankfulness to **Dr.M.VELAN M.E., Ph.D.,** Principal, Rajalakshmi Institute of Technology for their kind support and the facilities provided to complete our work in time.

With profound sense and regards, we acknowledge with great pleasure **Dr.G.R.SURESH, M.E., Ph.D,** Head of the Department, Department of Electronics and Communication Engineering for his valuable suggestions and guidance for the development and completion of our project.

We express our sincere thanks to our guide **Mr.L.FRANKLIN TELFER, M.E., (Ph.D),** Professor, Department of Electronics and Communication Engineering, for leading us on the project.

We extend our gratitude to **Mr.K.SIVAKUMAR**, Assistant Professor (SS), project Coordinator for their timely organization of reviews and their support throughout the project work.

We also thank our review committee members **Dr.R.RAJESWARI**, professor, **Dr.G.NIRMALA**, professor, Department of Electronics and Communication Engineering for his valuable suggestions and guidance for the development and completion of our project.

Finally, we express our deep sense of gratitude to our parents, all our faculty members, technical staff and all our friends for their constant encouragement and moral support.

ABSTRACT

In this paper we propose an Ultra wide band antenna which operates on UWB range (3.1 to 10.6GHz). We use micro strip line feeding and rectangular shape as a base shape for patch. FR4 is used as a substrate material with thickness 1.57mm with copper cladding for a ground and patch as 0.035mm. Rectangular patch and defected ground structure is used to attain UWB range. The design is carried out using Computer Simulation Technology (CST) microwave studio 2014. The optimization is achieved by varying the length and width parameters. Simulation results show that the antenna works well in the UWB region and satisfies premier antenna parameters such as return loss, VSWR and radiation pattern. Finally, the proposed UWB antenna structure is fabricated and verified. The measurement shows a good agreement with the simulated results. Mainly used in the application like military, satellite, cognitive radio etc.

TABLE OF CONTENTS

| CHAPTER NO | TITLE | PAGE NO |
|------------|---------------------------|---------|
| | ABSTRACT | V |
| | LIST OF TABLES | viii |
| | LIST OF FIGURES | ix |
| | LIST OF ABBREVATIONS | X |
| 1 | INTRODUCTION | 1 |
| | 1.1 Antenna basics | 1 |
| | 1.2 Antenna parameters | 1 |
| | 1.2.1 Return loss | 1 |
| | 1.2.2 Gain | 2 |
| | 1.2.3 Directivity | 2 |
| | 1.2.4 Resonant frequency | 3 |
| | 1.2.5 Impedance | 3 |
| | 1.2.6 Bandwidth | 3 |
| | 1.2.7 Radiation pattern | 3 |
| | 1.2.8 VSWR | 4 |
| | 1.2.9 Polarization | 4 |
| | 1.3 History of UWB | 4 |
| 2 | LITERATURE REVIEW | 9 |
| 3 | METHODOLOGY | 16 |
| | 3.1 Existing model | 16 |
| | 3.2 Proposed model | 16 |
| | 3.2.1 Design of ground | 17 |
| | 3.2.2 Design of substrate | 18 |
| | 3.2.3 Design of patch | 20 |

| | 3.2.4 Design of feed | 20 |
|---|---|----|
| | 3.3 Design equation | 21 |
| | 3.4 Values of calculated specifications | 23 |
| | | |
| 4 | EXPERIMENTAL RESULTS | 24 |
| | 4.1 Antenna simulation | 24 |
| | 4.2 Return loss | 24 |
| | 4.3 VSWR | 25 |
| | 4.4 Radiation pattern | 26 |
| | 4.4.1 Directivity | 26 |
| | 4.4.2 Gain | 26 |
| | 4.5 Output frequencies | 27 |
| | 4.6 Fabricated Antenna | 33 |
| 5 | CONCLUSION | 34 |
| | 5.1 Future scope | 34 |
| | REFERENCES | 36 |

LIST OF TABLES

| TABLE NO | TABLE DESCRIPTION | PAGE NO |
|----------|---|---------|
| 3.2.1 | Specification of ground plane | 18 |
| 3.2.2 | Specification of substrate | 19 |
| 3.2.3 | Specification of patch | 20 |
| 3.4 | Variable values of proposed UWB antenna | 23 |

LIST OF FIGURES

| FIGURE NO | FIGURE DESCRIPTION | PAGE NO |
|-----------|---|---------|
| 1.1 | Equivalence of a pulse based waveform | 5 |
| 1.2 | Mask of an UWB communications system. | 6 |
| 1.3 | Impulse and frequency modulation | 7 |
| 3.1 | Geometry of proposed UWB antenna | 17 |
| 3.2 | Design of ground in CST | 18 |
| 3.3 | Design of substrate in CST | 19 |
| 3.4 | Design of patch in CST | 20 |
| 3.5 | Design of feed in CST | 21 |
| 4.1 | Simulation in CST | 24 |
| 4.2 | Return loss | 25 |
| 4.3 | VSWR | 25 |
| 4.4 | Far field gain at 4.917GHz | 27 |
| 4.5 | Far field directivity at 4.917GHz | 28 |
| 4.6 | Far field gain at 4.917GHz in 3Dimension | 28 |
| 4.7 | Far field gain at 6.1009GHz | 29 |
| 4.8 | Far field directivity at 6.1009GHz | 29 |
| 4.9 | Far field gain at 6.1009GHz in 3Dimension | 30 |
| 4.10 | Far field gain at 10.407GHz | 31 |
| 4.11 | Far field directivity at 10.407GHz | 32 |
| 4.12 | Far field gain at 10.407GHz in 3Dimension | 32 |
| 4.13 | Far field gain at 13.476GHz | 32 |
| 4.14 | Far field directivity at 13.476GHz | 33 |
| 4.15 | Far field gain at 13.476GHz in 3Dimension | 34 |
| 4.16 | Fabricated Antenna of proposed model | 34 |

LIST OF ABBREVIATIONS

UWB Ultra Wide Band

CST Computer Simulation Technology

VSWR Voltage Standing Wave Ratio

FR-4 Flame Retardant

dBi Decibel over Isotropic

dBd Dipole over Dipole

IEEE Institute of Electrical & Electronics Engineering

RF Radio Frequency