1.Progarm to reverse the given string without changing the delimiters or special symbols

Input="Vision,tranz It : Solutions" Output="snoitu,loStI zn : artnoisiV"

ExpenseTracker > src > main > Main > main(String[]) : void

```java
package main;

public class Main {
    public static void main(String[] args) {
        String input = "Vision,tranz It :  Solutions";
        char[] a = input.toCharArray();
        int l = 0;
        int r = input.length()-1;
        while(l<r) {
            if(Character.isLetter(a[l]) && Character.isLetter(a[r])) {
                char temp = a[l];
                a[l] = a[r];
                a[r] = temp;
                l++;
                r--;
            }
            else if(!Character.isLetter(a[l])) {
                l++;
            }
            else {
                r--;
            }
        }
        System.out.print(String.valueOf(a));
    }
}
```

<terminated> Main [Java Application] C:\Program Files\Java\jdk-23\bin\ja

```
snoitu,loStI zn :  artnoisiV
```

Outline

- main
- Main
  - main(String[]) : void

**2.Program to count the characters which has lower followed by higher -Input="accept VanBanAnn" Output=6**

ExpenseTracker > src > main > Main

```java
package main;

public class Main {
    public static void main(String[] args) {
        String s = "accept VanBanAnn";
        int lowerCount = 0;
        boolean flag = false;
        for(int i=0;i<s.length();i++) {
            char c = s.charAt(i);
            if(Character.isUpperCase(c)) {
                flag = true;
            }
            else if(flag && Character.isLowerCase(c)) {
                lowerCount++;
            }
        }
        System.out.print(lowerCount);
    }
}
```

```
<terminated> Main [Java Application] C:\Program Files\Java\jdk-23\bin\j
6
```

# 3.Program to reverse either odd or even position based on the input inp1="chennaicitys" inp2=“even" Output:shtncainieyc

ExpenseTracker > src > main > Main

```java
package main;

public class Main {
    public static void main(String[] args) {
        String s = "chennaicitys";
        String type = "even";
        char[] c = s.toCharArray();
        int n = s.length();
        int pos = 0;
        if(type.equals("even")) pos = 0;
        else pos = 1;
        int l = 0;
        int r = s.length()-1;
        while(l<=r){
            if(l%2==pos){
                char a = c[l];
                c[l] = c[r];
                c[r] = a;
            }
            l++;
            r--;
        }
        System.out.print(String.valueOf(c));
    }
}
```

<terminated> Main [Java Application] C:\Program Files\Java\jdk-23\bin\ja

```
shtncainieyc
```

Outline

- main
- Main
  - main(String[]) : void

# 4.Program to print the highest frequency followed by lowest

ExpenseTracker > src > main > Main

```java
package main;

public class Main {
    public static void main(String[] args) {
        String a = "engineering";
        int[] freq = new int[26];
        for (char c : a.toCharArray()) {
            freq[c - 'a']++;
        }
        char[] arr = a.toCharArray();
        for (int i = 0; i < arr.length - 1; i++) {
            for (int j = 0; j < arr.length - i - 1; j++) {
                int f1 = freq[arr[j] - 'a'];
                int f2 = freq[arr[j + 1] - 'a'];
                if (f1 < f2 || (f1 == f2 && arr[j] > arr[j + 1])) {
                    char temp = arr[j];
                    arr[j] = arr[j + 1];
                    arr[j + 1] = temp;
                }
            }
        }
        System.out.println(String.valueOf(arr));
    }
}
```

<terminated> Main [Java Application] C:\Program Files\Java\jdk-23\bin\ja

```
eeennnggiir
```

Outline

- main
- Main
  - main(String[]) : void

5.Program to decrypt the given string  input="a5b4c10"  Output="aaaaabbbbcccccccccc"

ExpenseTracker > src > main > Main

```java
package main;

public class Main {
    public static void main(String[] args) {
        String s = "a5b4c10";
        StringBuilder sb = new StringBuilder();
        int i = 0;
        while(i<s.length()) {
            char c = s.charAt(i);
            i++;
            StringBuilder num = new StringBuilder();
            while(i<s.length() && Character.isDigit(s.charAt(i))) {
                num.append(s.charAt(i));
                i++;
            }
            int freq = Integer.parseInt(num.toString());
            for(int j=0;j<freq;j++) {
                sb.append(c);
            }
        }
        System.out.print(sb.toString());
    }
}
```

<terminated> Main [Java Application] C:\Program Files\Java\jdk-23\bin\j

```
aaaaabbbbcccccccccc
```

Outline

main

Main

6.Program to encrypt the given sstring input="aaaaabbbbbbcccccddeee" output=a5b6c64d2e3

ExpenseTracker ▸ src ▸ main ▸ Main ▸

```java
package main;

public class Main {
    public static void main(String[] args) {
        String str = "aaaaabbbbbbcccccddeee";
        StringBuilder res = new StringBuilder();
        int count = 1;
        for(int i=1;i<=str.length();i++) {
            if(i<str.length() && str.charAt(i)==str.charAt(i-1)) {
                count++;
            }
            else {
                res.append(str.charAt(i-1)).append(count);
                count = 1;
            }
        }
        System.out.print(res);
    }
}
```

<terminated> Main [Java Application] C:\Program Files\Java\jdk-23\bin\ja

```
a5b6c6d2e3
```

7.Word reverse  Input="indian institute of technology"  Output="naidni etutitsni fo ygolonhcet

ExpenseTracker > src > main > Main

```java
package main;

public class Main {
    public static void main(String[] args) {
        String s = "indian institue of technology";
        String[] str = s.split(" ");
        for(int i=0;i<str.length;i++){
            char[] c = str[i].toCharArray();
            int l = 0;
            int r = c.length-1;
            while(l<r){
                char temp = c[l];
                c[l++] = c[r];
                c[r--] = temp;
            }
            str[i] = new String(c);
        }
        System.out.print(String.join(" ",str));
    }
}
```

<terminated> Main [Java Application] C:\Program Files\Java\jdk-23\bin\ja

```
naidni eutitsni fo ygolonhcet
```

Outline

# 8.To remove the palindrome from given String

ExpenseTracker > src > main > Main

```java
package main;

public class Main {
    public static void main(String[] args) {
        String a = "In India Malayam is best dad and mom";
        String[] arr = a.split(" ");
        StringBuilder sb = new StringBuilder();
        for(String word:arr) {
            boolean flag = palindromeOrNot(word);
            if(flag) {
                sb.append(word).append(" ");
            }
        }
        System.out.print(sb.toString());
    }
    public static boolean palindromeOrNot(String word) {
        StringBuilder sb = new StringBuilder(word);
        sb.reverse();
        if(word.equals(sb.toString())) {
            return false;
        }
        return true;
    }
}
```

<terminated> Main [Java Application] C:\Program Files\Java\jdk-23\bin\j

```
In India Malayam is best and
```

Outline

- main
- Main
  - main(String[]) : void

9.The program should find the minimum number in the given string and return (print) the word associated with that minimum number.

ExpenseTracker > src > main > Main > main(String[]) : void

```java
package main;

public class Main {
    public static void main(String[] args) {
        String str = "laptop 100;mobile 21;tv 123;headphones 10";
        String str1 = str.replaceAll(";", " ");
        String[] arr = str1.split(" ");
        int min = Integer.MAX_VALUE;
        int minIndex = 0;
        String word = "";
        for(int i=0;i<arr.length;i++){
            if(i%2==1 && Integer.parseInt(arr[i])<min) {
                min = Integer.parseInt(arr[i]);
                minIndex = i;
            }
        }
        word = arr[minIndex-1];
        System.out.print(word);
    }
}
```

<terminated> Main [Java Application] C:\Program Files\Java\jdk-23\bin\j

```
headphones
```