



Report on

RELIABILITY PREDICTION

OF

Camera Model No.: HC-IPC-DI3212DVZK-N5-O
(CCTV CAMERA)

as per Telcordia SR-332, Issue 4



CENTRE FOR RELIABILITY,
STQC Directorate
Government of India
Ministry of Electronics and Information Technology (MeitY)
Thiruvananthapuram, Chennai - 600041
Ph: (044) 24547700/01/89
TeleFax: (044) 24543713
E-mail: cfr@stqc.gov.in

TERMS AND CONDITIONS

1. This report refers only to the sample actually subjected to Design Reliability Analysis.
2. The analysis report provided is solely based on a theoretical estimation for predicting design reliability.
3. The accuracy and validity of the design reliability prediction cannot be guaranteed due to its theoretical nature.
4. The analysis report should be used for informational purposes only and should not be solely relied upon for making critical decisions.
5. The analysis report issued by the Centre is not to be used for any legal purposes and shall not be produced in the court of Law.
6. The analysis report shall not be misused knowingly or unknowingly.
7. The analysis report must be reproduced in full and in no case, this should partially be re-produced.
8. The report shall not be regarded in any way diminishing the contractual requirements between the buyers and sellers.
9. The Centre provides the services solely for the benefit of the Client. As the sole intended beneficiary, only the Client has a right to enforce this agreement.
10. The report provided by the Centre to the client is for the benefit and guidance of the Client only and not intended for communication to a broader audience.
11. The Centre and the Client have arrived at the extent and depth of testing that can reasonably be achieved in the light of Client's other constraints and the product's design reliability.
12. The Centre shall have no liability for any damages to the Client or consequential damages (including lost profits) of the Client or any third party, even if the Centre has been advised of the possibility of such damages.
13. The reports shall not in any way be construed as approval of any product by the Centre.
14. The conditions are subject to change/modification without any prior notice.
15. The Centre does not endorse the intellectual property risks, if any, claimed by the client for the product.
16. The responsibility of confirming the correctness of the performance of the product is of the client and NOT that of the Centre. The Centre has only checked the design Reliability/Failure of the product assuming that the performance/functionality are correct and appropriate.
17. In case of any disputes, the decision of the Director, CFR, Chennai shall be final and binding.

CENTRE FOR RELIABILITY, CHENNAI STQC DIRECTORATE MINISTRY OF ELECTRONICS & INFORMATION TECHNOLOGY GOVERNMENT OF INDIA	Report No. CFR/2026/10TE20260 1267 Page 1 of 9
Reliability Prediction Report on Camera Model No.: HC-IPC-DI3212DVZK-N5-O	Date of Issue 12-06-2026

1.0 SCOPE

- 1.1** Service request no. : 2602330
- 1.2** Name & Address of the Client : Hi-Focus Electronics India Pvt Ltd
3, Sunguvar Agraharam St,
Chindatripet, Chintadripet, Chennai,
Tamil Nadu 600002.
- 1.3** Description : **CCTV CAMERA**
Make : Hi-Focus Electronics India Pvt Ltd
Model No. : HC-IPC-DI3212DVZK-N5-O
Serial No. : HFP25100543120377
- 1.4** Project : Received Date : 11-05-2026
Completed Date : 12-06-2026
- 1.5** (a) Standard/ Analysis / Test Procedure Ref. : Telcordia SR-332, Issue 4
(b) Scope : Reliability Prediction by Parts Count Method

Approved by

Issued by

CENTRE FOR RELIABILITY, CHENNAI STQC DIRECTORATE MINISTRY OF ELECTRONICS & INFORMATION TECHNOLOGY GOVERNMENT OF INDIA	Report No. CFR/2026/10TE20260 1267 Page 2 of 9
Reliability Prediction Report on Camera Model No.: HC-IPC-DI3212DVZK-N5-O	Date of Issue 12-06-2026

2.0 INTRODUCTION

This report presents the results of Reliability Prediction Analysis performed on **Camera Model No.: HC-IPC-DI3212DVZK-N5-O** as per Telcordia SR-332, Issue 4 as depicted in Figure 1.0, 2.0, 3.0, 4.0, 5.0, and 6.0. This exercise was performed under **Ground, Fixed, Controlled (GB)** environment as requested by **Hi-Focus Electronics India Pvt Ltd.**

Design Reliability Prediction is the process of quantitatively assessing whether a proposed or actual equipment design will meet a specified reliability requirement. Design Reliability Prediction has various applications in the design and development process including substantiating quantitative design comparisons with competitive products, selecting warranty periods, advertising and marketing. It provides guidance, relative to expected inherent reliability of a given design.



Figure 1.0 (a & b) Front & Top view of camera



Figure 2.0 (a) Markings on camera

Approved by

Issued by

**Reliability Prediction Report on
Camera Model No.: HC-IPC-DI3212DVZK-N5-O**

**Date of Issue
12-06-2026**



Figure 3.0 (a & b) Front & Rear View of PCB 1




Figure 4.0 (a & b) Front & Rear View of PCB 2



Figure 5.0 (a) Motorized Lens



Figure 6.0 (a & b) IR Board & LEDs

Approved by

Issued by

CENTRE FOR RELIABILITY, CHENNAI STQC DIRECTORATE MINISTRY OF ELECTRONICS & INFORMATION TECHNOLOGY GOVERNMENT OF INDIA	Report No. CFR/2026/10TE20260 1267 Page 4 of 9
Reliability Prediction Report on Camera Model No.: HC-IPC-DI3212DVZK-N5-O	Date of Issue 12-06-2026

3.0 APPLICABLE DOCUMENTS AND TOOLS

Telcordia SR-332, Issue 4 - Reliability Prediction Procedure for Electronic Equipment

4.0 RELIABILITY PREDICTION OBJECTIVES

Objectives of this analysis are to estimate the Mean Time between Failure (MTBF) of **Camera Model No.: HC-IPC-DI3212DVZK-N5-O** using Telcordia SR-332, Issue 4 and to obtain quantitative design information as applicable. The main objectives are:

- a. Provide an estimate of the steady-state failure rates for device design based on generic reliability parameters and obtain feasibility evaluation.
- b. Provide feedback for designers.
- c. Identify potential problem areas during design review.
- d. Provide MTBF of the system and sub-assemblies and failure rate of system/sub-assemblies/ Components.

5.0 SR-332, Method 1: Unit Steady-State Failure Rate Parts Count Method - ASSUMPTIONS

Reliability Prediction using SR-332, Method 1: Unit Steady-State Failure Rate Parts Count Method for reliability prediction operates under the following assumptions: assumes a serial relationship between parts of the system, in which, failure of any part constitutes system failure. The model also assumes that

- a. At the device level, it is assumed that no detailed reliability data is available. Predictions are based on generic reliability parameters.
- b. Predictions are made using generic reliability parameters as specified in the relevant sections of SR-332, which are applied to estimate steady state failure rates.
- c. At the unit level, failure rate predictions are based solely on the failure rates of the individual devices that compose the unit, without considering interactions between devices.
- d. This method primarily estimates steady-state failure rates and does not specifically account for infant mortality failures (early-life failures) or wear out failures (end-of-life failures). It assumes a constant failure rate.

Approved by

Issued by

CENTRE FOR RELIABILITY, CHENNAI STQC DIRECTORATE MINISTRY OF ELECTRONICS & INFORMATION TECHNOLOGY GOVERNMENT OF INDIA	Report No. CFR/2026/10TE20260 1267 Page 5 of 9
Reliability Prediction Report on Camera Model No.: HC-IPC-DI3212DVZK-N5-O	Date of Issue 12-06-2026

6.0 SR-332, Method I: Unit Steady-State Failure Rate Parts Count Method: Factors

Method I: Unit Steady-State Failure Rate Using the Parts Count Method primarily estimates reliability by calculating the steady-state failure rate of a device using a set of generic parameters. It takes into account the following factors:

- 6.0.1 Number of component of each Type
- 6.0.2 Mean Generic Steady-State Failure Rate
- 6.0.3 Temperature factor
- 6.0.4 Environmental factor
- 6.0.5 Quality factor
- 6.0.6 Electrical Stress Factor

Approved by

Issued by

CENTRE FOR RELIABILITY, CHENNAI STQC DIRECTORATE MINISTRY OF ELECTRONICS & INFORMATION TECHNOLOGY GOVERNMENT OF INDIA	Report No. CFR/2026/10TE20260 1267 Page 6 of 9
Reliability Prediction Report on Camera Model No.: HC-IPC-DI3212DVZK-N5-O	Date of Issue 12-06-2026

7.0 ENVIRONMENTAL CONDITIONS

7.1 STORAGE AND OPERATIONAL ENVIRONMENT

The Reliability Prediction has been performed using **Ground, Fixed, Controlled (GB)** Environment based on the operational conditions of **Camera Model No.: HC-IPC-DI3212DVZK-N5-O**.

GROUND, FIXED, CONTROLLED (GB):

The environment represents a stationary, land-based installation located in a protected or climate-controlled facility. It is characterized by low vibration and shock stresses, low atmospheric variations, and low temperature-cycling stresses, with the understanding that a building or ruggedized enclosure provides consistent protection from weather and contaminants.

TEMPERATURE

Reliability Prediction has been performed on **Camera Model No.: HC-IPC-DI3212DVZK-N5-O** at the **Ambient Temperature of 40 °C for Ground, Fixed, Controlled (GB) Environment**.

7.2 QUALITY LEVEL : Level- 1

The unit has been evaluated under the commercial-grade component Quality level-1 as mentioned by the client in bill of material. The components used in the unit were procured without undergoing thorough device qualification or lot-to-lot controls by the equipment manufacturer.

Approved by

Issued by

CENTRE FOR RELIABILITY, CHENNAI STQC DIRECTORATE MINISTRY OF ELECTRONICS & INFORMATION TECHNOLOGY GOVERNMENT OF INDIA	Report No. CFR/2026/10TE20260 1267 Page 7 of 9
Reliability Prediction Report on Camera Model No.: HC-IPC-DI3212DVZK-N5-O	Date of Issue 12-06-2026

8.0 REPORTS

Report includes the following information-

- a) Components/ Parts descriptions
- b) Failure Rate
- c) Pi (π) Factors
- d) Parameters details

Refer Annexure- I.

Approved by

Issued by

CENTRE FOR RELIABILITY, CHENNAI STQC DIRECTORATE MINISTRY OF ELECTRONICS & INFORMATION TECHNOLOGY GOVERNMENT OF INDIA	Report No. CFR/2026/10TE202601 267 Page 8 of 9
Reliability Prediction Report on Camera Model No.: HC-IPC-DI3212DVZK-N5-O	Date of Issue 12-06-2026

9.0 System Analysis Summary

The overall estimated MTBF and Failure Rate as per Telcordia SR-332 of **Camera Model No.: HC-IPC-DI3212DVZK-N5-O**, submitted for reliability prediction analysis by **Hi-Focus Electronics India Pvt Ltd** are summarized as follows:

SYSTEM: Camera Model No.: **HC-IPC-DI3212DVZK-N5-O**

Environment	Ambient Temperature	Failure Rate (Failures/Million Hours)	MTBF (Hrs)
Ground, Fixed, Controlled (GB)	40°C	4.172301	239675.91

- Design reliability prediction analysis was carried out based on the failure rates of components used in the camera (refer Annexure I), following a physical verification of components and in accordance with Telcordia SR-332, Issue 4.
- The camera contains three (03) nos of synchronous/stepper/shutter motors. However, failure rate data for these motors is not available in the Telcordia standard or in the reliability prediction software used. Therefore, for the purpose of the design reliability prediction, the failure rate for each motor has been conservatively assumed as one (1) FIT.
- MTBF (Mean Time Between Failures) calculations have been performed using the component details—such as type, quantity, electrical and environmental parameters, stress levels, and quality grades—as provided by the client in their submitted Bill of Materials.

Approved by

Issued by

10.0 Abbreviation Used:

- a) MTBF : Mean Time Between Failure
- b) λG : Base failure rate for the generic part (Ground fixed base rate)
- c) σG : Standard deviation or uncertainty in base failure rate (generic)
- d) πQ : Quality factor (related to part/process quality level)
- e) πE : Environmental factor (based on the operating environment, e.g., ground benign, airborne)
- f) πT : Temperature factor (influenced by ambient/operating temperature)
- g) πS : Stress factor (e.g., voltage or power stress ratio)
- h) λSS : Subsystem or system-level failure rate (or stress-adjusted failure rate)
- i) σSS : Standard deviation or uncertainty in system/subsystem failure rate

- End of Report -

Approved by

Issued by

Annexure - I

Approved by

Issued by



Reliability Prediction Report

Name	CCTV CAMERA	Calculation Model	Telcordia Issue 4
Description	Make : HI-FOCUS Model Number: HC-IPC-DI3212DVZK-N5-O Serial Number : HFP25100543120377 Job No : 10TE202601267	Environment	Ground, Fixed, Controlled (GB)
Quantity	1	Ambient Temperature, Celsius	40.00
Reference Designator		Operating Profile	Telecommunications
		Failure Rate Units	Failures/Million Hours
		Failure Rate	4.172301
		MTBF Units	Hours
		MTBF	239675.91

PARTS

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.1	R0402RXX330XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R3,R7,R8,R10,R11,R12,R13	33Ω±1%-0402-(-55°C~155°C)	7	0.000173	0.001211	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 33, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40
1.2	R0402RXX472XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R5,R15,R28,R36,R65,R72,R90,R91	4.7K±1%-0402-(-55°C~155°C)	8	0.000172	0.001374	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 4.7, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40
1.3	R0402RXX330XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R8,R20,R21,R42,R43,R57,R58	33Ω±1%-0402-(-55°C~155°C)	7	0.000173	0.001211	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 33, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.4	R0402RXX202XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R74,R94	2K $\pm$ 1%-0402-(-55°C~155°C)	2	0.000190	3.801525E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 2, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.5	R0402RXX223XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R24	22K $\pm$ 1%-0402-(-55°C~155°C)	1	0.000205	2.052850E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 22, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.6	R0402RXX102XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R70,R95	1K $\pm$ 1%-0402-(-55°C~155°C)	2	0.000190	3.801525E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 1, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.7	R0402RXX105XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R27	1M $\pm$ 1%-0402-(-55°C~155°C)	1	0.000205	2.052850E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 1, Resistance Units: Mohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.8	R0402RXX103XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R7,R11,R29,R30, R39,R93	10K $\pm$ 1%-0402-(-55°C~155°C)	6	0.000175	0.001048	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 10, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.9	R0402RXX104XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R31,R89,R96	100K $\pm$ 1%-0402-(-55°C~155°C)	3	0.000183	5.501810E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 100, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.10	R0402RXX241XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R38	240 Ω $\pm$ 1%-0402-(-55°C~155°C)	1	0.000205	2.052850E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 240, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.11	R0402JXX0000P 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R32,R34,R44	0 Ω $\pm$ 5%-0402-(-55°C~155°C)	3	0.000152	4.562529E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 0, Resistance Units: ohm, Applied Power: 0.001, Rated Power: 0.0625, Percentage: 1.6	Applied Power: 0.001, Rated Power: 0.0625, Percentage: 1.6	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.53301804, λ G: 0.08, σ G: 0.02, λ SS: 0.12792433, σ SS: 0.031981083, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.12	R0402RXX183XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R33,R37,R69,R88	18K $\pm$ 1%-0402-(-55°C~155°C)	4	0.000179	7.177196E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 18, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.13	R0402RXX152XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R92	1.5K $\pm$ 1%-0402-(-55°C~155°C)	1	0.000205	2.052850E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 1.5, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.14	R0402RXX332XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R18	3.3K $\pm$ 1%-0402-(-55°C~155°C)	1	0.000205	2.052850E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 3.3, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.15	R0402RXX473XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R87	47K $\pm$ 1%-0402-(-55°C~155°C)	1	0.000205	2.052850E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 47, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.16	R0402RXX751XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R35	750 Ω ±1%-0402-(-55°C~155°C)	1	0.000205	2.052850E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 750, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.17	R0402RXX153XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R73	15K±1%-0402-(-55°C~155°C)	1	0.000205	2.052850E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 15, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.18	R0402RXX471XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R706,C1401	470 Ω ±1%-0402-(-55°C~155°C)	2	0.000190	3.801525E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 470, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.19	R0402RXX474XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R41,R1419	470K±1%-0402-(-55°C~155°C)	2	0.000190	3.801525E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 470, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.20	R0402RXX472XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R45,R52,R63,R86,R87,R90,R93,R124,R150,R191,R220,R227,R274,R277,R703,R712,R737,R742,R746,R803,R809,R812,R815,R818,R822,R823,R824,R859,R860,R863,R897,R1301,R1402	4.7K±1%-0402-(-55°C~155°C)	33	0.000163	0.005374	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 4.7, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40
1.21	R0402RXX330XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R5,R6,R10,R11,R17,R18,R25,R61,R94,R101,R153,R157,R253,R517,R518,R804,R811,R825,R857,R858,R861,R864,R865,R866,R867,R868	33Ω±1%-0402-(-55°C~155°C)	26	0.000164	0.004263	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 33, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40
1.22	R0402RXX202XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R20,R91,R99,R140,R181,R183,R186,R188,R246,R896,R1403	2K±1%-0402-(-55°C~155°C)	11	0.000169	0.001861	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 2, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40
1.23	R0402RXX223XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R141,R724	22K±1%-0402-(-55°C~155°C)	2	0.000190	3.801525E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 22, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.24	R0402RXX222XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R78,R603	2.2K±1%-0402-(-55°C~155°C)	2	0.000190	3.801525E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 2.2, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.25	R0402RXX102XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R21,R23,R27,R133,R134,R138,R147,R149,R151,R171,R217,R248,R345,R734,R744,R748,R830,R1003,R1005	1K±1%-0402-(-55°C~155°C)	19	0.000166	0.003146	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 1, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.26	R0402RXX103XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R3,R29,R50,R100,R130,R143,R145,R219,R236,R238,R239,R247,R601,R602,R709,R722,R736,R738,R740,R741,R831,R1013,R1015,R1016,R1201,R2621	10K±1%-0402-(-55°C~155°C)	26	0.000164	0.004263	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 10, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.27	R0402RXX104XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R721,R801	100K±1%-0402-(-55°C~155°C)	2	0.000190	3.801525E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 100, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.28	R0402RXX241XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R1007,R1008	240 Ω ±1%-0402-(-55°C~155°C)	2	0.000190	3.801525E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 240, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.29	CR-05JL7---10R	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R113,R114,R115,R116,R120,R262,R899	10 Ω ±5%-0805-(-55°C~155°C)	7	0.000156	0.001091	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 10, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.125, Percentage: 8	Applied Power: 0.01, Rated Power: 0.125, Percentage: 8	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.57926223, λ G: 0.08, σ G: 0.02, λ SS: 0.13902294, σ SS: 0.034755734, Temperature: 40
1.30	CR-05FL7---10K	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R117,R118	10K±1%-0805-(-55°C~155°C)	2	0.000171	3.426031E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 10, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.125, Percentage: 8	Applied Power: 0.01, Rated Power: 0.125, Percentage: 8	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.57926223, λ G: 0.08, σ G: 0.02, λ SS: 0.13902294, σ SS: 0.034755734, Temperature: 40
1.31	CR-05FL7--100R	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R178	100 Ω ±1%-0805-(-55°C~155°C)	1	0.000185	1.850080E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 100, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.125, Percentage: 8	Applied Power: 0.01, Rated Power: 0.125, Percentage: 8	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.57926223, λ G: 0.08, σ G: 0.02, λ SS: 0.13902294, σ SS: 0.034755734, Temperature: 40
1.32	CR-05JL7---0R	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R8,R35,R107,R112	0 Ω ±5%-0805-(-55°C~155°C)	4	0.000147	5.890311E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 0, Resistance Units: ohm, Applied Power: 0.001, Rated Power: 0.125, Percentage: 0.8	Applied Power: 0.001, Rated Power: 0.125, Percentage: 0.8	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.52750338, λ G: 0.08, σ G: 0.02, λ SS: 0.12660081, σ SS: 0.031650203, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.33	R0402JXX0000P 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R2,R13,R16,R76, R160,R166,R240 ,R637,R646,R64 7,R650,R651,R6 65,R723,R735,R 739,R750,R756, R766,R819,R826 ,R827,R833,R10 01,R1002,R1203 ,R1423,R1599,R 1705,R1723	0Ω±5%-0402-(- 55°C~155°C)	30	0.000135	0.004062	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 0, Resistance Units: ohm, Applied Power: 0.001, Rated Power: 0.0625, Percentage: 1.6	Applied Power: 0.001, Rated Power: 0.0625, Percentage: 1.6	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.53301804, λG: 0.08, σG: 0.02, λSS: 0.12792433, σSS: 0.031981083, Temperature: 40
1.34	R0402RXX100XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R121,R229,R230 ,R231,R233,R23 4,R235,R2622	10Ω±1%-0402-(- 55°C~155°C)	8	0.000172	0.001374	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 10, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40
1.35	R0402RXX101XF 16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R14,R19,R24,R2 8,R814,R817,R1 404	100Ω±1%-0402- (-55°C~155°C)	7	0.000173	0.001211	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 100, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40
1.36	CR-03FL7---75R	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R290,R291,R421 ,R422	75Ω±1%-0603-(- 55°C~155°C)	4	0.000535	0.002139	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 75, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.01, Percentage: 100	Applied Power: 0.01, Rated Power: 0.01, Percentage: 100	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 1.9155408, λG: 0.08, σG: 0.02, λSS: 0.4597298, σSS: 0.11493245, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.37	R0402RXX183XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R84,R729,R1110	18K $\pm$ 1%-0402-(-55°C~155°C)	3	0.000183	5.501810E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 18, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.38	R0402RXX333XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R743,R745	33K $\pm$ 1%-0402-(-55°C~155°C)	2	0.000190	3.801525E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 33, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.39	R0402RXX152XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R237	1.5K $\pm$ 1%-0402-(-55°C~155°C)	1	0.000205	2.052850E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 1.5, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.40	R0402RXX332XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R142,R170,R224,R717,R832,R898	3.3K $\pm$ 1%-0402-(-55°C~155°C)	6	0.000175	0.001048	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 3.3, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.41	R0402RXX224XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R128	220K±1%-0402-(-55°C~155°C)	1	0.000205	2.052850E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 220, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40
1.42	R0402RXX201XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R139	200Ω±1%-0402-(-55°C~155°C)	1	0.000205	2.052850E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 200, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40
1.43	R0402RXX153XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R155,R212,R218,R704,R720,R725,R732,R747	15K±1%-0402-(-55°C~155°C)	8	0.000172	0.001374	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 15, Resistance Units: Kohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40
1.44	R0402RWX2R2XF16LTA	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R273,R286,R287,R289	2.2Ω±1%-0402-(-55°C~155°C)	4	0.000179	7.177196E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 2.2, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.64274964, λG: 0.08, σG: 0.02, λSS: 0.15425991, σSS: 0.038564978, Temperature: 40
1.45	RL1206FR-070R51L	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R123,R127,R131,R132	510mΩ±1%-1206-(-55°C~155°C)	4	0.000154	6.140516E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 0.51, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.25, Percentage: 4	Applied Power: 0.01, Rated Power: 0.25, Percentage: 4	Level I	λG: 0.08, σG: 0.02, πQ: 3, πE: 1, πT: 1, πS: 0.54991036, λG: 0.08, σG: 0.02, λSS: 0.13197849, σSS: 0.032994621, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.46	RS-05FL7---OR2	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R81	200mR $\pm$ 1%-0805-(-55°C~155°C)	1	0.000280	2.804510E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 0.2, Resistance Units: ohm, Applied Power: 0.05, Rated Power: 0.125, Percentage: 40	Applied Power: 0.05, Rated Power: 0.125, Percentage: 40	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.87809543, λ G: 0.08, σ G: 0.02, λ SS: 0.2107429, σ SS: 0.052685726, Temperature: 40
1.47	CR0402FF56R0G	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R1014,R1017	56R $\pm$ 1%-0402-(-55°C~155°C)	2	0.000190	3.801525E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 56, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.48	CR0402FF6800G	Resistor	Fixed	Film (Carbon, Oxide, Metal)	R1018,R1019,R1020,R1021	680R $\pm$ 1%-0402-(-55°C~155°C)	4	0.000179	7.177196E-004	Type: Film (Carbon, Oxide, Metal), Quality Level: Level I, Resistance: 680, Resistance Units: ohm, Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Applied Power: 0.01, Rated Power: 0.0625, Percentage: 16	Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, π S: 0.64274964, λ G: 0.08, σ G: 0.02, λ SS: 0.15425991, σ SS: 0.038564978, Temperature: 40
1.49	CC0805KKX5R7BB106	Capacitor	Ceramic	General	C1	10uF $\pm$ 10%-16V-X5R-0805	1	0.000102	1.016686E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 16, Percentage: 20.625	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 16, Percentage: 20.625	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.29987937, λ G: 0.1, σ G: 0.01, λ SS: 0.08996381, σ SS: 0.008996381, Temperature: 40
1.50	CC0402KRX7R7BB104	Capacitor	Ceramic	General	C2	100nF $\pm$ 10%-16V-X7R-0402	1	0.000102	1.016686E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 16, Percentage: 20.625	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 16, Percentage: 20.625	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.29987937, λ G: 0.1, σ G: 0.01, λ SS: 0.08996381, σ SS: 0.008996381, Temperature: 40
1.51	CC0402JRNPO9BN100	Capacitor	Ceramic	General	C81	10pF $\pm$ 5%-50V-NP0-0402	1	0.000055	5.526646E-005	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 2.9, Rated Voltage: 50, Percentage: 5.8	AC Peak Voltage: 0, Applied DC Voltage: 2.9, Rated Voltage: 50, Percentage: 5.8	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.16329449, λ G: 0.1, σ G: 0.01, λ SS: 0.048988348, σ SS: 0.0048988348, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.52	CC0402KRX7R9BB102	Capacitor	Ceramic	General	C47	1nF±10%-50V-X7R-0402	1	0.000048	4.815829E-005	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 1.2, Rated Voltage: 50, Percentage: 2.4	AC Peak Voltage: 0, Applied DC Voltage: 1.2, Rated Voltage: 50, Percentage: 2.4	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.14204662, λ G: 0.1, σ G: 0.01, λ SS: 0.042613985, σ SS: 0.0042613985, Temperature: 40
1.53	0402X105K6R3CT	Capacitor	Ceramic	General	C30,C31,C32,C58	1uF±10%-6.3V-X5R-0402	4	0.000090	3.589336E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 1.2, Rated Voltage: 6.3, Percentage: 19.0476190476	AC Peak Voltage: 0, Applied DC Voltage: 1.2, Rated Voltage: 6.3, Percentage: 19.0476190476	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.28109921, λ G: 0.1, σ G: 0.01, λ SS: 0.084329762, σ SS: 0.0084329762, Temperature: 40
1.54	CC0402KRX7R7BB104	Capacitor	Ceramic	General	C14,C33,C34,C38,C54,C56,C59,C60,C61,C62,C63,C64,C70,C80,C88,C89,C93,C99,C457	100nF±10%-16V-X7R-0402	19	0.000093	0.001760	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 16, Percentage: 20.625	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 16, Percentage: 20.625	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.29987937, λ G: 0.1, σ G: 0.01, λ SS: 0.08996381, σ SS: 0.008996381, Temperature: 40
1.55	0402B103K500CT	Capacitor	Ceramic	General	C11,C13,C20,C44	10nF±10%-50V-X7R-0402	4	0.000045	1.813783E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 1.2, Rated Voltage: 50, Percentage: 2.4	AC Peak Voltage: 0, Applied DC Voltage: 1.2, Rated Voltage: 50, Percentage: 2.4	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.14204662, λ G: 0.1, σ G: 0.01, λ SS: 0.042613985, σ SS: 0.0042613985, Temperature: 40
1.56	0402X225M6R3CT	Capacitor	Ceramic	General	C12	2.2uF±20%-6.3V-X5R-0402	1	0.000288	2.876279E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 2.9, Rated Voltage: 6.3, Percentage: 46.0317460317	AC Peak Voltage: 0, Applied DC Voltage: 2.9, Rated Voltage: 6.3, Percentage: 46.0317460317	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.84984745, λ G: 0.1, σ G: 0.01, λ SS: 0.25495424, σ SS: 0.025495424, Temperature: 40
1.57	CL05A475MQ5NRNC	Capacitor	Ceramic	General	C3,C6,C7,C9,C15,C17,C19,C21,C23,C25,C27,C36	4.7uF±20%-6.3V-X5R-0402	12	0.000264	0.003173	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 2.9, Rated Voltage: 6.3, Percentage: 46.0317460317	AC Peak Voltage: 0, Applied DC Voltage: 2.9, Rated Voltage: 6.3, Percentage: 46.0317460317	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.84984745, λ G: 0.1, σ G: 0.01, λ SS: 0.25495424, σ SS: 0.025495424, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.58	0402X224K100 NT	Capacitor	Ceramic	General	C86,C104	220nF±20%-10V-X5R-0402	2	0.000163	3.259277E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 10, Percentage: 33	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 10, Percentage: 33	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.4980773, λ G: 0.1, σ G: 0.01, λ SS: 0.14942319, σ SS: 0.014942319, Temperature: 40
1.59	CL10A106KP8N NNC	Capacitor	Ceramic	General	C39,C57,C71,C436	10uF±10%-10V-X5R-0603	4	0.000319	0.001277	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 5, Rated Voltage: 10, Percentage: 50	AC Peak Voltage: 0, Applied DC Voltage: 5, Rated Voltage: 10, Percentage: 50	Level I	π Q: 3, π E: 1, π T: 1, π S: 1, λ G: 0.1, σ G: 0.01, λ SS: 0.3, σ SS: 0.03, Temperature: 40
1.60	CL10A226MQ8 NRNC	Capacitor	Ceramic	General	C37,C40,C42,C51,C55,C79,C90,C92,C94,C96,C103,C105,C107,C232,C233	22uF±20%-6.3V-X5R-0603	15	0.000342	0.005126	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 6.3, Percentage: 52.380952381	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 6.3, Percentage: 52.380952381	Level I	π Q: 3, π E: 1, π T: 1, π S: 1.1025427, λ G: 0.1, σ G: 0.01, λ SS: 0.33076281, σ SS: 0.033076281, Temperature: 40
1.61	CC0402JRNPO9 BN100	Capacitor	Ceramic	General	C825	10pF±5%-50V-NPO-0402	1	0.000057	5.710925E-005	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.16873936, λ G: 0.1, σ G: 0.01, λ SS: 0.050621808, σ SS: 0.0050621808, Temperature: 40
1.62	CC0402JRNPO9 BN180	Capacitor	Ceramic	General	C815,C822,C824	18pF±5%-50V-NPO-0402	3	0.000054	1.631020E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.16873936, λ G: 0.1, σ G: 0.01, λ SS: 0.050621808, σ SS: 0.0050621808, Temperature: 40
1.63	CC0402JRNPO9 BN101	Capacitor	Ceramic	General	C181,C991	100pF±5%-50V-NPO-0402	2	0.000063	1.269350E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 5, Rated Voltage: 50, Percentage: 10	AC Peak Voltage: 0, Applied DC Voltage: 5, Rated Voltage: 50, Percentage: 10	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.19398004, λ G: 0.1, σ G: 0.01, λ SS: 0.058194013, σ SS: 0.0058194013, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.64	CC0402KRX7R9BB102	Capacitor	Ceramic	General	C182,C1408,C1417	1nF±10%-50V-X7R-0402	3	0.000054	1.631020E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.16873936, λ G: 0.1, σ G: 0.01, λ SS: 0.050621808, σ SS: 0.0050621808, Temperature: 40
1.65	0402B332K500CT	Capacitor	Ceramic	General	C73	3.3nF±10%-50V-X7R-0402	1	0.000057	5.710925E-005	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.16873936, λ G: 0.1, σ G: 0.01, λ SS: 0.050621808, σ SS: 0.0050621808, Temperature: 40
1.66	CC1206KKX7RD BB102	Capacitor	Ceramic	General	C30,C89,C126,C158,C167,C168,C284,C327	1nF±10%-2KV-X7R-1206	8	0.000041	3.262902E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 5, Rated Voltage: 2000, Percentage: 0.25	AC Peak Voltage: 0, Applied DC Voltage: 5, Rated Voltage: 2000, Percentage: 0.25	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.13006122, λ G: 0.1, σ G: 0.01, λ SS: 0.039018367, σ SS: 0.0039018367, Temperature: 40
1.67	0402N221J500CT	Capacitor	Ceramic	General	C171,C173,C705,C716,C731	220pF±5%-50V-NP0-0402	5	0.000054	2.676154E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.16873936, λ G: 0.1, σ G: 0.01, λ SS: 0.050621808, σ SS: 0.0050621808, Temperature: 40
1.68	1206B104K201NT	Capacitor	Ceramic	General	C159,C166	100nF±10%-200V/250V-X7R-1206	2	0.000113	2.253547E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 48, Rated Voltage: 200, Percentage: 24	AC Peak Voltage: 0, Applied DC Voltage: 48, Rated Voltage: 200, Percentage: 24	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.3443833, λ G: 0.1, σ G: 0.01, λ SS: 0.10331499, σ SS: 0.010331499, Temperature: 40
1.69	1206B105K101CT	Capacitor	Ceramic	General	C161,C163	1uF±10%-100V-X7R-1206	2	0.000301	6.028542E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 48, Rated Voltage: 100, Percentage: 48	AC Peak Voltage: 0, Applied DC Voltage: 48, Rated Voltage: 100, Percentage: 48	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.92127196, λ G: 0.1, σ G: 0.01, λ SS: 0.27638159, σ SS: 0.027638159, Temperature: 40
1.70	CC0805KKX5R7BB106	Capacitor	Ceramic	General	C58,C62	10uF±10%-16V-X5R-0805	2	0.000912	0.001824	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 12, Rated Voltage: 16, Percentage: 75	AC Peak Voltage: 0, Applied DC Voltage: 12, Rated Voltage: 16, Percentage: 75	Level I	π Q: 3, π E: 1, π T: 1, π S: 2.7870955, λ G: 0.1, σ G: 0.01, λ SS: 0.83612864, σ SS: 0.083612864, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.71	VZH221M1ETR-0810	Capacitor	Electrolytic	Aluminum	CE4	220uF±20%-25V-105°C-Φ8*10mm	1	0.002730	0.002730	Type: Aluminum, Quality Level: Level I, Capacitance: 220, Capacitance Units: uF, AC Peak Voltage: 0, Applied DC Voltage: 12, Rated Voltage: 25, Percentage: 48	AC Peak Voltage: 0, Applied DC Voltage: 12, Rated Voltage: 25, Percentage: 48	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.95313379, λ G: 0.73, σ G: 0.17, λ SS: 2.087363, σ SS: 0.48609823, Temperature: 40
1.72	0603N821J500CT	Capacitor	Ceramic	General	C282,C283,C325,C326	820pF±5%-50V-NPO-0603	4	0.000054	2.154621E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.16873936, λ G: 0.1, σ G: 0.01, λ SS: 0.050621808, σ SS: 0.0050621808, Temperature: 40
1.73	0402X105K6R3CT	Capacitor	Ceramic	General	C208,C739,C801,C821	1uF±10%-6.3V-X5R-0402	4	0.000352	0.001408	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 6.3, Percentage: 52.380952381	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 6.3, Percentage: 52.380952381	Level I	π Q: 3, π E: 1, π T: 1, π S: 1.1025427, λ G: 0.1, σ G: 0.01, λ SS: 0.33076281, σ SS: 0.033076281, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.74	CC0402KRX7R7BB104	Capacitor	Ceramic	General	C28,C47,C50,C53,C57,C68,C88,C91,C145,C172,C175,C176,C180,C207,C711,C715,C719,C726,C733,C738,C741,C747,C751,C753,C802,C804,C808,C810,C813,C814,C817,C818,C819,C820,C823,C827,C829,C830,C831,C832,C835,C836,C838,C850,C852,C853,C854,C855,C858,C859,C860,C983,C984,C992,C995,C1002,C1003,C1004,C1006,C1012,C1013,C1014,C1015,C1016,C1017,C1018,C1019,C1020,C1021,C1022,C1023,C1024,C1025,C1026,C1028,C1029,C1030,C1031,C1032,C1033,C1034,C1035,C1036,C1037,C1038,C1039,C1040,C1041,C1102	100nF±10%-16V-X7R-0402	89	0.000141	0.012546	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 5, Rated Voltage: 16, Percentage: 31.25	AC Peak Voltage: 0, Applied DC Voltage: 5, Rated Voltage: 16, Percentage: 31.25	Level I	πQ: 3, πE: 1, πT: 1, πS: 0.4635922, λG: 0.1, σG: 0.01, λSS: 0.13907766, σSS: 0.013907766, Temperature: 40
1.75	0402B103K500CT	Capacitor	Ceramic	General	C183,C280,C281,C601,C1042	10nF±10%-50V-X7R-0402	5	0.000054	2.676154E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 50, Percentage: 6.6	Level I	πQ: 3, πE: 1, πT: 1, πS: 0.16873936, λG: 0.1, σG: 0.01, λSS: 0.050621808, σSS: 0.0050621808, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.76	0402X225M6R3 CT	Capacitor	Ceramic	General	C186,C1461	2.2uF±20%-6.3V-X5R-0402	2	0.000361	7.214727E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 6.3, Percentage: 52.380952381	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 6.3, Percentage: 52.380952381	Level I	πQ: 3, πE: 1, πT: 1, πS: 1.1025427, λG: 0.1, σG: 0.01, λSS: 0.33076281, σSS: 0.033076281, Temperature: 40
1.77	0805X226M100 CT	Capacitor	Ceramic	General	C36	22uF±20%-10V-0805	1	0.000338	3.384465E-004	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 5, Rated Voltage: 10, Percentage: 50	AC Peak Voltage: 0, Applied DC Voltage: 5, Rated Voltage: 10, Percentage: 50	Level I	πQ: 3, πE: 1, πT: 1, πS: 1, λG: 0.1, σG: 0.01, λSS: 0.3, σSS: 0.03, Temperature: 40
1.78	UL1J470M0810 VG	Capacitor	Electrolytic	Aluminum	CE5	47uF±20%-63V-105°C-Φ8*10mm	1	0.005369	0.005369	Type: Aluminum, Quality Level: Level I, Capacitance: 47, Capacitance Units: uF, AC Peak Voltage: 0, Applied DC Voltage: 48, Rated Voltage: 63, Percentage: 76.1904761905	AC Peak Voltage: 0, Applied DC Voltage: 48, Rated Voltage: 63, Percentage: 76.1904761905	Level I	πQ: 3, πE: 1, πT: 1, πS: 1.8749302, λG: 0.73, σG: 0.17, λSS: 4.1060971, σSS: 0.9562144, Temperature: 40
1.79	UT1E101M0607 VG	Capacitor	Electrolytic	Aluminum	CE3	100uF±20%-25V-105°C-Φ6.3*7.7mm	1	0.002730	0.002730	Type: Aluminum, Quality Level: Level I, Capacitance: 100, Capacitance Units: uF, AC Peak Voltage: 0, Applied DC Voltage: 12, Rated Voltage: 25, Percentage: 48	AC Peak Voltage: 0, Applied DC Voltage: 12, Rated Voltage: 25, Percentage: 48	Level I	πQ: 3, πE: 1, πT: 1, πS: 0.95313379, λG: 0.73, σG: 0.17, λSS: 2.087363, σSS: 0.48609823, Temperature: 40
1.80	CL05A475MQ5 NRNC	Capacitor	Ceramic	General	C209,C805,C807,C809,C811,C816,C828,C857,C1402,C1403	4.7uF±20%-6.3V-X5R-0402	10	0.000344	0.003442	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 6.3, Percentage: 52.380952381	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 6.3, Percentage: 52.380952381	Level I	πQ: 3, πE: 1, πT: 1, πS: 1.1025427, λG: 0.1, σG: 0.01, λSS: 0.33076281, σSS: 0.033076281, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.81	CL10A106KP8N NNC	Capacitor	Ceramic	General	C109,C704,C714,C728,C735,C746,C812,C826,C851,C856,C985,C989,C993,C1001,C1027	10uF±10%-10V-X5R-0603	15	0.000310	0.004649	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 5, Rated Voltage: 10, Voltage: 5, Rated Voltage: 10, Percentage: 50	AC Peak Voltage: 0, Applied DC Voltage: 5, Rated Voltage: 10, Percentage: 50	Level I	π Q: 3, π E: 1, π T: 1, π S: 1, λ G: 0.1, σ G: 0.01, λ SS: 0.3, σ SS: 0.03, Temperature: 40
1.82	CL21A106KAYN NNE	Capacitor	Ceramic	General	C63,C92,C156,C177,C178,C179,C743	10uF±10%-25V-X5R-0805	7	0.000290	0.002028	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 12, Rated Voltage: 25, Voltage: 12, Rated Voltage: 25, Percentage: 48	AC Peak Voltage: 0, Applied DC Voltage: 12, Rated Voltage: 25, Percentage: 48	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.92127196, λ G: 0.1, σ G: 0.01, λ SS: 0.27638159, σ SS: 0.027638159, Temperature: 40
1.83	CL10A226MQ8 NRNC	Capacitor	Ceramic	General	C29,C70,C706,C710,C717,C730,C732,C737,C750,C803	22uF±20%-6.3V-X5R-0603	10	0.000344	0.003442	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 6.3, Voltage: 3.3, Rated Voltage: 6.3, Percentage: 52.380952381	AC Peak Voltage: 0, Applied DC Voltage: 3.3, Rated Voltage: 6.3, Percentage: 52.380952381	Level I	π Q: 3, π E: 1, π T: 1, π S: 1.1025427, λ G: 0.1, σ G: 0.01, λ SS: 0.33076281, σ SS: 0.033076281, Temperature: 40
1.84	HCM1206X7R10 3K102PT	Capacitor	Ceramic	General	C169	10nF±10%-1000V-X7R-1206	1	0.000044	4.356988E-005	Type: General, Quality Level: Level I, AC Peak Voltage: 0, Applied DC Voltage: 0, Rated Voltage: 1000, Voltage: 0, Rated Voltage: 1000, Percentage: 0	AC Peak Voltage: 0, Applied DC Voltage: 0, Rated Voltage: 1000, Percentage: 0	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.1287349, λ G: 0.1, σ G: 0.01, λ SS: 0.038620471, σ SS: 0.0038620471, Temperature: 40
1.85	C1402-1009-211	Connection	Multi-Pin		J2	193-F093K230-B06	1	0.001597	0.001597	Quality Level: Level I, Number of Pins: 10		Level I	λ G: 0.4, σ G: 0.1, π Q: 3, π E: 1, π T: 1, λ SS: 1.2, σ SS: 0.3, Temperature: 40
1.86	510-628-11	Connection	Multi-Pin		J6	2*10*0.8mm-5.2mm	1	0.003194	0.003194	Quality Level: Level I, Number of Pins: 20		Level I	λ G: 0.8, σ G: 0.2, π Q: 3, π E: 1, π T: 1, λ SS: 2.4, σ SS: 0.6, Temperature: 40
1.87	11-1832002-330	Connection	Multi-Pin		J4	2*1.25mm	1	0.000319	3.193856E-004	Quality Level: Level I, Number of Pins: 2		Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, λ SS: 0.24, σ SS: 0.06, Temperature: 40
1.88	1.25T-1-WT-4A	Connection	Multi-Pin		J2	4*1.25mm	1	0.000639	6.387712E-004	Quality Level: Level I, Number of Pins: 4		Level I	λ G: 0.16, σ G: 0.04, π Q: 3, π E: 1, π T: 1, λ SS: 0.48, σ SS: 0.12, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.89	60076-5007-1001	Connection	Multi-Pin		J5	50*0.5mm- Flip-Latch	1	0.007985	0.007985	Quality Level: Level I, Number of Pins: 50		Level I	λ G: 2, σ G: 0.5, π Q: 3, π E: 1, π T: 1, λ SS: 6, σ SS: 1.5, Temperature: 40
1.90	1.25T-1-LT-10A	Connection	Multi-Pin		J6	10*1.25mm	1	0.001597	0.001597	Quality Level: Level I, Number of Pins: 10		Level I	λ G: 0.4, σ G: 0.1, π Q: 3, π E: 1, π T: 1, λ SS: 1.2, σ SS: 0.3, Temperature: 40
1.91	1.25T-1-LT-8A	Connection	Multi-Pin		J11	8*1.25mm	1	0.001278	0.001278	Quality Level: Level I, Number of Pins: 8		Level I	λ G: 0.32, σ G: 0.08, π Q: 3, π E: 1, π T: 1, λ SS: 0.96, σ SS: 0.24, Temperature: 40
1.92	1.25T-1-LT-6A	Connection	Multi-Pin		J3	6*1.25mm	1	0.000958	9.581568E-004	Quality Level: Level I, Number of Pins: 6		Level I	λ G: 0.24, σ G: 0.06, π Q: 3, π E: 1, π T: 1, λ SS: 0.72, σ SS: 0.18, Temperature: 40
1.93	1.25T-1-LT-2A	Connection	Multi-Pin		J8	2*1.25mm	1	0.000319	3.193856E-004	Quality Level: Level I, Number of Pins: 2		Level I	λ G: 0.08, σ G: 0.02, π Q: 3, π E: 1, π T: 1, λ SS: 0.24, σ SS: 0.06, Temperature: 40
1.94	1.25T-1-LT-12A	Connection	Multi-Pin		J5	12*1.25mm	1	0.001916	0.001916	Quality Level: Level I, Number of Pins: 12		Level I	λ G: 0.48, σ G: 0.12, π Q: 3, π E: 1, π T: 1, λ SS: 1.44, σ SS: 0.36, Temperature: 40
1.95	510-627-11	Connection	Multi-Pin		J2	2*10*0.8mm-5.2mm	1	0.003194	0.003194	Quality Level: Level I, Number of Pins: 20		Level I	λ G: 0.8, σ G: 0.2, π Q: 3, π E: 1, π T: 1, λ SS: 2.4, σ SS: 0.6, Temperature: 40
1.96	60076-5007-1001	Connection	Multi-Pin		J9	50*0.5mm- Flip-Latch	1	0.007985	0.007985	Quality Level: Level I, Number of Pins: 50		Level I	λ G: 2, σ G: 0.5, π Q: 3, π E: 1, π T: 1, λ SS: 6, σ SS: 1.5, Temperature: 40
1.97	1.25T-1-LT-6A	Connection	Multi-Pin		J1	6*1.25mm	1	0.000958	9.581568E-004	Quality Level: Level I, Number of Pins: 6		Level I	λ G: 0.24, σ G: 0.06, π Q: 3, π E: 1, π T: 1, λ SS: 0.72, σ SS: 0.18, Temperature: 40
1.98	NRS3015T2R2M NGH	Inductor	Coil	Chip/Ceramic Filter	L702,L703,L704	2.2uH-1.48A	3	0.000462	0.001386	Type: Chip/Ceramic Filter, Quality Level: Level I		Level I	λ G: 0.1, σ G: 0.07, π Q: 3, π E: 1, π T: 1, λ G: 0.1, σ G: 0.07, λ SS: 0.3, σ SS: 0.21, Temperature: 40
1.99	HXNR4030B-4R7M	Inductor	Coil	Chip/Ceramic Filter	L3,L705	4.7uH-2A	2	0.000499	9.980442E-004	Type: Chip/Ceramic Filter, Quality Level: Level I		Level I	λ G: 0.1, σ G: 0.07, π Q: 3, π E: 1, π T: 1, λ G: 0.1, σ G: 0.07, λ SS: 0.3, σ SS: 0.21, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.100	0.47mH-1.8A	Inductor	Coil	Chip/Ceramic Filter	L2	0.47mH-1.8A	1	0.000581	5.806969E-004	Type: Chip/Ceramic Filter, Quality Level: Level I		Level I	λ G: 0.1, σ G: 0.07, π Q: 3, π E: 1, π T: 1, λ G: 0.1, σ G: 0.07, λ SS: 0.3, σ SS: 0.21, Temperature: 40
1.101	RS1M-F1-0002	Semiconductor	Diode	General Purpose, Si	D25	1000V-1A-SMA	1	0.000801	8.012066E-004	Type: General Purpose, Si, Quality Level: Level I, Operating Current: 0.2, Rated Current: 1, Percentage: 20, Operating Voltage: 50, Rated Voltage: 1000, Percentage: 5	Rated Current: 1, Percentage: 20, Operating Voltage: 50, Rated Voltage: 1000, Percentage: 5	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.41895155, λ G: 0.33, σ G: 0.23, λ SS: 0.41476203, σ SS: 0.28907657, Temperature: 40
1.102	P0080SB-LV1	Semiconductor	Diode	General Purpose, Si	D16,D17,D31,D85,D1401,D1403	6.5V-4KV-SMB	6	0.004517	0.027101	Type: General Purpose, Si, Quality Level: Level I, Operating Current: 0.001, Rated Current: 100, Percentage: 0.001, Operating Voltage: 3.3, Rated Voltage: 6.5, Percentage: 50.7692307692	Rated Current: 100, Percentage: 0.001, Operating Voltage: 3.3, Rated Voltage: 6.5, Percentage: 50.7692307692	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.23566226, λ G: 4.6, σ G: 3.3, λ SS: 3.2521391, σ SS: 2.3330563, Temperature: 40
1.103	1SS355	Semiconductor	Diode	General Purpose, Si	D18,D21,D22,D801	80V-0.1A-SOD323	4	0.000454	0.001818	Type: General Purpose, Si, Quality Level: Level I, Operating Current: 0.01, Rated Current: 0.1, Percentage: 10, Operating Voltage: 5, Rated Voltage: 80, Percentage: 6.25	Rated Current: 0.1, Percentage: 10, Operating Voltage: 5, Rated Voltage: 80, Percentage: 6.25	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.31348618, λ G: 0.33, σ G: 0.23, λ SS: 0.31035132, σ SS: 0.21630546, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.104	SCD310H	Semiconductor	Diode	General Purpose, Si	D3,D24	100V-3A-2010/SMAF	2	0.001014	0.002028	Type: General Purpose, Si, Quality Level: Level I, Operating Current: 1, Rated Current: 3, Percentage: 33.333333333, Operating Voltage: 12, Rated Voltage: 100, Percentage: 12	Rated Current: 3, Percentage: 33.333333333, Operating Voltage: 12, Rated Voltage: 100, Percentage: 12	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.61672421, λ G: 0.33, σ G: 0.23, λ SS: 0.61055697, σ SS: 0.42553971, Temperature: 40
1.105	SBR6100CTL-13	Semiconductor	Diode	Voltage Regulator, Zener	D15	100V-6A-DPAK	1	0.017551	0.017551	Type: Voltage Regulator, Zener, Quality Level: Level I, Actual Zener Current or Power: 1, Rated Zener Current or Power: 6, Percentage: 16.666666667	Rated Zener Current or Power: 6, Percentage: 16.666666667	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.44932896, λ G: 9.3, σ G: 2.8, λ SS: 12.536278, σ SS: 3.7743633, Temperature: 40
1.106	BV-SMBJ58C2H	Semiconductor	Diode	TVS Surge Suppressor	D23,D27	58V-10us/700us-85MAX-SMB	2	0.002390	0.004781	Type: TVS Surge Suppressor, Quality Level: Level I, Average Forward Current: 0.2, Rated Forward Current: 21.37, Percentage: 0.93589143659	Rated Forward Current: 21.37, Percentage: 0.93589143659	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.24102391, λ G: 2.55, σ G: 0.81, λ SS: 1.8438329, σ SS: 0.5856881, Temperature: 40
1.107	BV-SMBJ20CAI	Semiconductor	Diode	General Purpose, Si	D7	20V-10/1000uS-800W-30V@8/20us-SMB	1	0.006982	0.006982	Type: General Purpose, Si, Quality Level: Level I, Operating Current: 1, Rated Current: 30, Percentage: 3.333333333, Operating Voltage: 12, Rated Voltage: 30, Percentage: 40	Rated Current: 30, Percentage: 3.333333333, Operating Voltage: 12, Rated Voltage: 30, Percentage: 40	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.25837757, λ G: 4.6, σ G: 3.3, λ SS: 3.5656104, σ SS: 2.5579379, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.108	TUSD03FB	Semiconductor	Diode	TVS Surge Suppressor	D12,D13	3.3V-8/20uS-350W-Max19V-SOD323	2	0.002327	0.004655	Type: TVS Surge Suppressor, Quality Level: Level I, Average Forward Current: 0.001, Rated Forward Current: 8, Percentage: 0.0125	Rated Forward Current: 8, Percentage: 0.0125	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.23465534, λ G: 2.55, σ G: 0.81, λ SS: 1.7951133, σ SS: 0.57021246, Temperature: 40
1.109	MB6F	Semiconductor	Diode	General Purpose, Si	Z1,Z2	Glass Passivated Single-Phase Bridge Rectifier	2	0.003924	0.007848	Type: General Purpose, Si, Quality Level: Level I, Operating Current: 0.4, Rated Current: 0.5, Percentage: 80, Operating Voltage: 48, Rated Voltage: 600, Percentage: 8	Rated Current: 0.5, Percentage: 80, Operating Voltage: 48, Rated Voltage: 600, Percentage: 8	Level I	π Q: 3, π E: 1, π T: 1, π S: 2.3869109, λ G: 0.33, σ G: 0.23, λ SS: 2.3630417, σ SS: 1.6469685, Temperature: 40
1.110	S8050-H-F2-0000HF	Semiconductor	Transistor	Field Effect, Silicon	Q2	40V-0.5A-SOT23	1	0.004336	0.004336	Type: Field Effect, Silicon, Application Type: Switch, Quality Level: Level I, Dissipated Power: 0.01, Rated Power: 0.3, Percentage: 3.333333333	Rated Power: 0.3, Percentage: 3.333333333	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.32627979, λ G: 3.44, σ G: 0.75, λ SS: 3.3672075, σ SS: 0.73412954, Temperature: 40
1.111	S8550	Semiconductor	Transistor	Field Effect, Silicon	Q3	40V-0.5A-SOT23	1	0.004336	0.004336	Type: Field Effect, Silicon, Application Type: Switch, Quality Level: Level I, Dissipated Power: 0.01, Rated Power: 0.3, Percentage: 3.333333333	Rated Power: 0.3, Percentage: 3.333333333	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.32627979, λ G: 3.44, σ G: 0.75, λ SS: 3.3672075, σ SS: 0.73412954, Temperature: 40
1.112	S8050-H-F2-0000HF	Semiconductor	Transistor	Field Effect, Silicon	Q2,Q5,Q9	40V-0.5A-SOT23	3	0.003921	0.011762	Type: Field Effect, Silicon, Application Type: Switch, Quality Level: Level I, Dissipated Power: 0.01, Rated Power: 0.3, Percentage: 3.333333333	Rated Power: 0.3, Percentage: 3.333333333	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.32627979, λ G: 3.44, σ G: 0.75, λ SS: 3.3672075, σ SS: 0.73412954, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.113	MMBTA42LT1G	Semiconductor	Transistor	Field Effect, Silicon	Q16	300V/160V-0.5A-SOT23	1	0.004336	0.004336	Type: Field Effect, Silicon, Application Type: Switch, Quality Level: Level I, Dissipated Power: 0.01, Rated Power: 0.3, Percentage: 3.3333333333	Rated Power: 0.3, Percentage: 3.3333333333	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.32627979, λ G: 3.44, σ G: 0.75, λ SS: 3.3672075, σ SS: 0.73412954, Temperature: 40
1.114	FDS86242	Semiconductor	Transistor	Field Effect, Silicon	Q12	150V-4.1A-SOP8	1	0.010453	0.010453	Type: Field Effect, Silicon, Application Type: Switch, Quality Level: Level I, Dissipated Power: 1, Rated Power: 2.5, Percentage: 40	Rated Power: 2.5, Percentage: 40	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.78662786, λ G: 3.44, σ G: 0.75, λ SS: 8.1179995, σ SS: 1.7699127, Temperature: 40
1.115	YJS2305A-F2-0000HF	Semiconductor	Transistor	Field Effect, Silicon	Q7	20V-5.4A-SOT23-6L	1	0.007293	0.007293	Type: Field Effect, Silicon, Application Type: Switch, Quality Level: Level I, Dissipated Power: 0.3, Rated Power: 1.2, Percentage: 25	Rated Power: 1.2, Percentage: 25	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.54881164, λ G: 3.44, σ G: 0.75, λ SS: 5.6637361, σ SS: 1.2348262, Temperature: 40
1.116	ZM930P06T	Semiconductor	Transistor	Field Effect, Silicon	Q6	60V-3A-SOT23	1	0.008907	0.008907	Type: Field Effect, Silicon, Application Type: Switch, Quality Level: Level I, Dissipated Power: 0.5, Rated Power: 1.5, Percentage: 33.3333333333	Rated Power: 1.5, Percentage: 33.3333333333	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.67032005, λ G: 3.44, σ G: 0.75, λ SS: 6.9177029, σ SS: 1.5082201, Temperature: 40
1.117	BSS138W-F2-0000HF	Semiconductor	Transistor	Field Effect, Silicon	Q2601	50V-0.34A-SOT323	1	0.004199	0.004199	Type: Field Effect, Silicon, Application Type: Switch, Quality Level: Level I, Dissipated Power: 0.01, Rated Power: 0.15, Percentage: 6.6666666667	Rated Power: 0.15, Percentage: 6.6666666667	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.31600413, λ G: 3.44, σ G: 0.75, λ SS: 3.2611626, σ SS: 0.71100929, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.118	-	Optical Device	Other	Single LED / LCD Segment	IR1,IR2,IR3,IR4,IR5,IR6,IR7,IR8,IR9,IR10,IR11,IR12,IR13,IR14,IR15,IR16,IR17,IR18	Night Mode	18	0.000917	0.016507	Type: Single LED / LCD Segment, Quality Level: Level I		Level I	π Q: 3, π E: 1, π T: 1, λ G: 0.25, σ G: 0.18, λ SS: 0.75, σ SS: 0.54, Temperature: 40
1.119	-	Optical Device	Isolators, Dual / Couplers	Light Sensitive Resistor	LDR1	Ambient Light Sensor, Light Dependent Resistor	1	0.123111	0.123111	Type: Light Sensitive Resistor, Quality Level: Level I		Level I	π Q: 3, π E: 1, π T: 1, λ G: 21, σ G: 15, λ SS: 63, σ SS: 45, Temperature: 40
1.120	[HFD42/4.5-3SR(825)]-DC5V-HF	Relay	General Purpose		K1	HFD42/4.5-3SR(825)	1	0.009483	0.009483	Quality Level: Level I, Contact Current: 1, Rated Current: 4, Percentage: 25	Contact Current: 1, Rated Current: 4, Percentage: 25	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.72252735, λ G: 1.9, σ G: 1.9, λ SS: 4.1184059, σ SS: 4.1184059, Temperature: 40
1.121	TSTP6650K-180BH-8.4	Switch	Pushbutton		SW2	DC12V-50mA-4PIN-6*6*5mm	1	0.007842	0.007842	Quality Level: Level I, Contact Current: 0.01, Rated Current: 0.05, Percentage: 20	Contact Current: 0.01, Rated Current: 0.05, Percentage: 20	Level I	π Q: 3, π E: 1, π T: 1, π S: 0.67705687, λ G: 1.99, σ G: 1.4, λ SS: 4.0420295, σ SS: 2.8436389, Temperature: 40
1.122	K-F-24.000M-9-2020-4085-80	Miscellaneous	Crystal Oscillator		X803	24M $\pm$ 20ppm-(-40°C-85°C)-3.2*2.5	1	0.015628	0.015628	Oscillator Type: Quartz Controlled, Quality Level: Level I		Level I	π Q: 3, π E: 1, π T: 1, λ G: 3.2, σ G: 1.5, λ SS: 9.6, σ SS: 4.5, Temperature: 40
1.123	SF32WK32768D31T002	Miscellaneous	Crystal Oscillator		X802	32.768K $\pm$ 20ppm-(-40°C-85°C)-3.2*1.5	1	0.015628	0.015628	Oscillator Type: Quartz Controlled, Quality Level: Level I		Level I	π Q: 3, π E: 1, π T: 1, λ G: 3.2, σ G: 1.5, λ SS: 9.6, σ SS: 4.5, Temperature: 40
1.124	YT30028FB.IR-JZ-DK-	Rotating Device				Lens-Electric Zoom	2	1.000000	2.000000				
1.125	IR0109	Rotating Device				Day and Night Mode	1	1.000000	1.000000				
1.126	ETA5052S2G	Integrated Circuit	Analog		U2	[ETA5052S2G/ETA5052V0S2G]-SOT23-6	1	0.031289	0.031289	Quality Level: Level I, Number of Transistors: 565		Level I	π Q: 3, π E: 1, π T: 1, λ G: 5.3630921, σ G: 3.7917061, λ SS: 16.089276, σ SS: 11.375118, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.127	LP3981AB5F]-SOT23-5	Integrated Circuit	Analog		U3,U7	[LP3981AB5F]-SOT23-5	2	0.026871	0.053741	Quality Level: Level I, Number of Transistors: 565		Level I	π Q: 3, π E: 1, π T: 1, λ G: 5.3630921, σ G: 3.7917061, λ SS: 16.089276, σ SS: 11.375118, Temperature: 40
1.128	[TP10-2-VR]-VSSOP8	Integrated Circuit	Analog		U4	[TP10-2-VR]-VSSOP8	1	0.031289	0.031289	Quality Level: Level I, Number of Transistors: 565		Level I	π Q: 3, π E: 1, π T: 1, λ G: 5.3630921, σ G: 3.7917061, λ SS: 16.089276, σ SS: 11.375118, Temperature: 40
1.129	[TPM16050-S6TR/TMI8113]-SOT23-6	Integrated Circuit	Analog		U5	[TPM16050-S6TR/TMI8113]-SOT23-6	1	0.031289	0.031289	Quality Level: Level I, Number of Transistors: 565		Level I	π Q: 3, π E: 1, π T: 1, λ G: 5.3630921, σ G: 3.7917061, λ SS: 16.089276, σ SS: 11.375118, Temperature: 40
1.130	SGM431XN3LG	Integrated Circuit	Analog		U13,U15	[LTL431APTSLT1G]-SOT23	1	0.031289	0.031289	Quality Level: Level I, Number of Transistors: 565		Level I	π Q: 3, π E: 1, π T: 1, λ G: 5.3630921, σ G: 3.7917061, λ SS: 16.089276, σ SS: 11.375118, Temperature: 40
1.131	TL2845BDR-8	Integrated Circuit	Analog		U12	[TL2845BDR-8/SA2845SATR/SAP2845SATR]-SOP8	1	0.031289	0.031289	Quality Level: Level I, Number of Transistors: 565		Level I	π Q: 3, π E: 1, π T: 1, λ G: 5.3630921, σ G: 3.7917061, λ SS: 16.089276, σ SS: 11.375118, Temperature: 40
1.132	DIO54335TST6]-SOT23-6-dioo	Integrated Circuit	Analog		U709	[DIO54335TST6]-SOT23-6	1	0.028473	0.028473	Quality Level: Level I, Number of Transistors: 456		Level I	π Q: 3, π E: 1, π T: 1, λ G: 4.8804343, σ G: 3.450467, λ SS: 14.641303, σ SS: 10.351401, Temperature: 40
1.133	ETA3485S2F]-SOT23-5-ETA	Integrated Circuit	Analog		U702,U703,U706	[ETA3485S2F]-SOT23-5	3	0.022631	0.067893	Quality Level: Level I, Number of Transistors: 456		Level I	π Q: 3, π E: 1, π T: 1, λ G: 4.8804343, σ G: 3.450467, λ SS: 14.641303, σ SS: 10.351401, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.134	ETA5053V180D F1E]-1.8V-DFN1*1-ETA	Integrated Circuit	Analog		U710	[ETA5053V180D F1E]-1.8V-DFN1*1	1	0.031289	0.031289	Quality Level: Level I, Number of Transistors: 565		Level I	π Q: 3, π E: 1, π T: 1, λ G: 5.3630921, σ G: 3.7917061, λ SS: 16.089276, σ SS: 11.375118, Temperature: 40
1.135	LP3981AB5F]-SOT23-5	Integrated Circuit	Analog		U707	[LP3981AB5F]-SOT23-5	1	0.031289	0.031289	Quality Level: Level I, Number of Transistors: 565		Level I	π Q: 3, π E: 1, π T: 1, λ G: 5.3630921, σ G: 3.7917061, λ SS: 16.089276, σ SS: 11.375118, Temperature: 40
1.136	TMI5302]-TSOT23-6	Integrated Circuit	Analog		U6	[TMI5302]-TSOT23-6	1	0.035814	0.035814	Quality Level: Level I, Number of Transistors: 768		Level I	π Q: 3, π E: 1, π T: 1, λ G: 6.1386501, σ G: 4.3400256, λ SS: 18.41595, σ SS: 13.020077, Temperature: 40
1.137	SD4924STR]-SO8	Integrated Circuit	Analog		U10	[SD4924STR]-SOP8	1	0.031289	0.031289	Quality Level: Level I, Number of Transistors: 565		Level I	π Q: 3, π E: 1, π T: 1, λ G: 5.3630921, σ G: 3.7917061, λ SS: 16.089276, σ SS: 11.375118, Temperature: 40
1.138	EL357N(B)(TA)-VG	Integrated Circuit	Analog		U11	[EL357N(B)(TA)(BMS)-G]-SO6	1	0.031289	0.031289	Quality Level: Level I, Number of Transistors: 565		Level I	π Q: 3, π E: 1, π T: 1, λ G: 5.3630921, σ G: 3.7917061, λ SS: 16.089276, σ SS: 11.375118, Temperature: 40
1.139	TP8485E-SR	Integrated Circuit	Analog		U20	[TP8485E-SR/SIT3088EESA]-SOP8	1	0.031289	0.031289	Quality Level: Level I, Number of Transistors: 565		Level I	π Q: 3, π E: 1, π T: 1, λ G: 5.3630921, σ G: 3.7917061, λ SS: 16.089276, σ SS: 11.375118, Temperature: 40
1.140	MS41908M	Integrated Circuit	Analog		U36	[MS41908M]-QFN44	1	0.031289	0.031289	Quality Level: Level I, Number of Transistors: 565		Level I	π Q: 3, π E: 1, π T: 1, λ G: 5.3630921, σ G: 3.7917061, λ SS: 16.089276, σ SS: 11.375118, Temperature: 40

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)

SI No	Part Number	Category	Subcategory	Type	Reference Designator	Description	Quantity (n)	Failure Rate	n * Failure Rate	Part Data	Stress Data	Quality	π Factors
1.141	IMX307LQR-C	Integrated Circuit	Digital		U1	[IMX307LQR-C]-2.0MP-1/2.8-LGA110	1	0.031007	0.031007	Quality Level: Level I, Technology: CMOS, Number of Gates: 5000000		Level I	π Q: 3, π E: 1, π T: 1, λ G: 6.9374105, σ G: 2.5470825, λ SS: 20.812232, σ SS: 7.6412476, Temperature: 40
1.142	W25N01GVZEIG	Integrated Circuit	ROM, PROM, EPROM		U1101	[W25N01GVZEIG]-WS0N8 (8x6mm)-3V3	1	0.249449	0.249449	Quality Level: Level I, Technology: CMOS, Number of Bits: 1, Bit Units: Gb		Level I	π Q: 3, π E: 1, π T: 1, λ G: 42.756504, σ G: 30.228848, λ SS: 128.26951, σ SS: 90.686545, Temperature: 40
1.143	NT5CB256M16ER-FL	Integrated Circuit	RAM		U1001	[NT5CB256M16ER-FL]-FBGA96	1	0.115747	0.115747	Quality Level: Level I, Technology: Dynamic NMOS/CMOS, Number of Bits: 4, Bit Units: Gb		Level I	π Q: 3, π E: 1, π T: 1, λ G: 20.379802, σ G: 13.601017, λ SS: 61.139406, σ SS: 40.80305, Temperature: 40
1.144	C5-36GW	Integrated Circuit	Microprocessor		U801	[C5-36GW]-BGA307	1	0.154317	0.154317	Quality Level: Level I, Technology: CMOS, Bus Width in Bits: 32		Level I	π Q: 3, π E: 1, π T: 1, λ G: 24.604507, σ G: 20.224777, λ SS: 73.81352, σ SS: 60.674332, Temperature: 40
1.145	S16403	Inductor	Transformer	Power (> 1W)	T1	[S16403]100M POE-1 channel	1	0.023018	0.023018	Type: Power (> 1W), Quality Level: Level I		Level I	λ G: 5, σ G: 2, π Q: 3, π E: 1, π T: 1, λ G: 5, σ G: 2, λ SS: 15, σ SS: 6, Temperature: 40
1.146	GEP13	Inductor	Transformer	Power (> 1W)	T2	GEP13-127 μ H	1	0.023018	0.023018	Type: Power (> 1W), Quality Level: Level I		Level I	λ G: 5, σ G: 2, π Q: 3, π E: 1, π T: 1, λ G: 5, σ G: 2, λ SS: 15, σ SS: 6, Temperature: 40
1.147	BA301N	Miscellaneous	Surge Arrestor SMD / Gas Discharge Tube			Operational Amplifier	1	0.002596	0.002596	Quality Level: Level I		Level I	π Q: 3, π E: 1, λ G: 0.49, σ G: 0.28, λ SS: 1.47, σ SS: 0.84
1.148	[ML414H-IV01E]-3V	Miscellaneous	Battery		BAT801	Rechargeable, 1mAh	1	0.104891	0.104891	Battery Type: Lithium, Quality Level: Level I		Level I	π Q: 3, π E: 1, λ G: 25, σ G: 7.5, λ SS: 75, σ SS: 22.5
1.149	Fuse-4A	Miscellaneous	Fuse		FU1	[6125SB4A250V-G]-4A-250V 6125	1	0.001964	0.001964	Fuse Type: $\leq$ 30A, Quality Level: Level I		Level I	π Q: 3, π E: 1, λ G: 0.4, σ G: 0.19, λ SS: 1.2, σ SS: 0.57

Tested and Prepared By: Shantanu Paria (TMB) and Anupam Anand (Scientist B)

Reviewed By: Shubham Kumar (Scientist D)

Approved By: V. Jambulingam (Head Reliability)