```java
public class Main

  {

      public static void main(String[] ar

      {

          int n, a = 0, b = 0;

          Scanner s = new Scanner(System.

          System.out.println("Author:Asa
          System.out.print("Enter no. of

          n = s.nextInt();

          int x[] = new int[n];

          int odd[] = new int[n];

          int even[] = new int[n];

          System.out.println("Enter all t

          for(int y = 0; y < n; y++)

          {

              x[y] = s.nextInt();

          }
```

Author:Asa venkatsai ID:51834542
Enter no. of elements you want in arr

```java
1  public class Main
2  {
3      public static void main (String[] ar
4          System.out.println("Author:Asa v
5          int A=1;
6          for (int b=1;b<=5;b++)
7          {
8              for (int c=1;c<=b;c++)
9              {
10                 System.out.print(A);
11                 A++;
12             }
13             System.out.println();
14         }
15     }
16 }
```

Terminal

Author:Asa venkatsai
SAP ID:51834542
1
23
456
78910

```java
import java.util.Scanner;

    public class Main

    {

        public static void main(String[]

        {

            int c;

            String temp;

            Scanner s = new Scanner(Syst

            System.out.println("Author:
            System.out.print("Enter numb

            c = s.nextInt();

            String names[] = new String[

            Scanner s1 = new Scanner(Sys

            System.out.println("Enter al

            for(int a = 0; a < c; a++)

            {

                names[a] = s1.nextLine()
```

Terminal