ascending.java

Saved

```java
import java.util.Scanner;
public class Ascending
{
    public static void main(String[] args)
    {
        int n, temp;
        Scanner s = new Scanner(System.in);
        System.out.println("Name:G.vyshanvi,Sap id :51834743");
        System.out.print("Enter no. of elements you want in array:");
        n = s.nextInt();
        int a[] = new int[n];
        System.out.println("Enter all the elements:");
        for (int i = 0; i < n; i++)
        {
            a[i] = s.nextInt();
        }
        for (int i = 0; i < n; i++)
        {
            for (int j = i + 1; j < n; j++)
            {
                if (a[i] > a[j])
                {
                    temp = a[i];
                    a[i] = a[j];
                    a[j] = temp;
                }
            }
        }
        System.out.print("Ascending Order:");
        for (int i = 0; i < n - 1; i++)
        {
            System.out.print(a[i] + ",");
        }
        System.out.print(a[n - 1]);
    }
}
```

Try Dcoder's keyboard



vyshu.file.java

Saved

```java
import java.util.Arrays;

public class Main
{
    private static int[] mergeArray(int[] array1, int[] array2)
    {
        System.out.println("Name:G.vyshnavi,SAP ID:51834743");
        int[] mergedArray = new int[array1.length + array2.length];

        int a=0, b=0, c=0;

        while (a < array1.length)
        {
            mergedArray[c] = array1[a];
            a++;
            c++;
        }

        while (b < array2.length)
        {
            mergedArray[c] = array2[b];
            b++;
            c++;
        }

        Arrays.sort(mergedArray);

        return mergedArray;
    }

    public static void main(String[] args)
    {
        int[] array1 = new int[] {12, -7, 18, 9, 37, -1, 21};

        int[] array2 = new int[] {27, 8, 71, -9, 18};

        int[] mergedArray = mergeArray(array1, array2);
```

Make public

Array 1 : "+Arrays.toString(array





abstract.java

Saved

```java
abstract class Student{
 abstract void reading();
 abstract void listening();
 abstract void writing();
 abstract void walking();
 abstract void drawing();
}
 class Jahnavi_V extends Student{
  void reading(){
   System.out.println("Student is reading...");
  }
  void listening(){
   System.out.println("Student is listening...");
  }
  void writing(){
   System.out.println("Student is writing...");
  }
  void walking(){
   System.out.println("Student is walking...");
  }
  void drawing(){
   System.out.println("Student is drawing...");
  }
 }
 class Jahnavi{
  public static void main(String args[]){
   System.out.println("Name :G.vyshnavi,Sap id :51834743");
   Student s=new Jahnavi_V();
   s.reading();
   s.listening();
   s.writing();
   s.walking();
   s.drawing();
  }
  }
```

Try Dcoder's keyboard



patterns.file.java

Saved

```java
import java.lang.Math;
public class Main
{
    public static void main(String[] args)
    {
      System.out.println("Name:G.vyshnavi,Sap id:51834743");
       char ch=' ';
       for(int i=4;i>=1;i--)
       {
          int k=(int)Math.pow(2,i-1);
          if(i==4)
            ch='*';
          else if(i==3)
            ch='&';
          else if(i==2)
            ch='%';
          for(int j=i;j<=4;j++)
          {
             System.out.print(" ");
          }
          for(int j=1;j<=k+2;j++)
          {
             if(j==1 || j==k+2 && i!=1)
             {
                System.out.print("#");
             }
             else if(i!=1)
             {
                System.out.print(ch);
             }
          }
          System.out.println();
       }

    }
}
```

Try Dcoder's keyboard