Flattening a nested linked list

May 3, 2020

0.1 Flattening a nested linked list

Suppose you have a linked list where the value of each node is a sorted linked list (i.e., it is a *nested* list). Your task is to *flatten* this nested list—that is, to combine all nested lists into a single (sorted) linked list.

First, we'll need some code for generating nodes and a linked list:

```
In [2]: # Helper code
        # A class behaves like a data-type, just like an int, float or any other built-in ones.
        # User defined class
        class Node:
            def __init__(self, value): # <-- For simple LinkedList, "value" argument will be an
                self.value = value
                self.next = None
            def __repr__(self):
                return str(self.value)
        # User defined class
        class LinkedList:
            def __init__(self, head): # <-- Expects "head" to be a Node made up of an int or Lin
                self.head = head
            For creating a simple LinkedList, we will pass an integer as the "value" argument
            For creating a nested LinkedList, we will pass a LinkedList as the "value" argument
            def append(self, value):
                # If LinkedList is empty
                if self.head is None:
                    self.head = Node(value)
                    return
                # Create a temporary Node object
```

node = self.head

```
# Iterate till the end of the currrent LinkedList
while node.next is not None:
    node = node.next

# Append the newly creataed Node at the end of the currrent LinkedList
node.next = Node(value)

'''We will need this function to convert a LinkedList object into a Python list of a
def to_list(self):
    out = []  # <-- Declare a Python list
    node = self.head # <-- Create a temporary Node object

while node: # <-- Iterate untill we have nodes available
    out.append(int(str(node.value))) # <-- node.value is actually of type Node,
    node = node.next

return out</pre>
```

0.1.1 Exercise - Write the two function definitions below

Now, in the cell below, see if you can solve the problem by implementing the flatten method.

Hint: If you first create a merge method that merges two linked lists into a sorted linked list, then there is an elegant recursive solution.

```
In [8]: def merge(list1, list2):
            # TODO: Implement this function so that it merges the two linked lists in a single,
            The arguments list1, list2 must be of type LinkedList.
            The merge() function must return an instance of LinkedList.
            merged = LinkedList(None)
            if list1 is None:
                return list2
            if list2 is None:
                return list1
            list1_elt = list1.head
            list2_elt = list2.head
            while list1_elt is not None or list2_elt is not None:
                if list1 elt is None:
                    merged.append(list2_elt)
                    list2_elt = list2_elt.next
                elif list2_elt is None:
                    merged.append(list1_elt)
                    list1_elt = list1_elt.next
                elif list1_elt.value <= list2_elt.value:</pre>
                    merged.append(list1_elt)
```

```
list1_elt = list1_elt.next
else:
    merged.append(list2_elt)
    list2_elt = list2_elt.next
return merged

''' In a NESTED LinkedList object, each node will be a simple LinkedList in itself'''
class NestedLinkedList(LinkedList):
    def flatten(self):
        # TODO: Implement this method to flatten the linked list in ascending sorted order return self._flatten(self.head)
    def _flatten(self, node):
        if node.next is None:
            return merge(node.value, None)
        return merge(node.value, self._flatten(node.next))
```

0.1.2 Test - Let's test your function

Here's some code that will generate a nested linked list that we can use to test the solution:

Structure of the nested linked list to be tested nested_linked_list should now have 2 nodes. The head node is a linked list containing 1, 3, 5. The second node is a linked list containing 2, 4

Calling flatten should return a linked list containing 1, 2, 3, 4, 5.

0.1.3 Solution

First, let's implement a merge function that takes in two linked lists and returns one sorted linked list. Note, this implementation expects both linked lists to be sorted.

```
In [4]: def merge(list1, list2):
            merged = LinkedList(None)
            if list1 is None:
                return list2
            if list2 is None:
                return list1
            list1_elt = list1.head
            list2_elt = list2.head
            while list1_elt is not None or list2_elt is not None:
                if list1_elt is None:
                    merged.append(list2_elt)
                    list2 elt = list2 elt.next
                elif list2_elt is None:
                    merged.append(list1_elt)
                    list1_elt = list1_elt.next
                elif list1_elt.value <= list2_elt.value:</pre>
                    merged.append(list1_elt)
                    list1_elt = list1_elt.next
                else:
                    merged.append(list2_elt)
                    list2_elt = list2_elt.next
            return merged
```

Let's make sure merge works how we expect:

```
In [5]: ''' Test merge() function'''
        linked_list = LinkedList(Node(1))
        linked_list.append(3)
        linked_list.append(5)
        second_linked_list = LinkedList(Node(2))
        second_linked_list.append(4)
        merged = merge(linked_list, second_linked_list)
        node = merged.head
        while node is not None:
            #This will print 1 2 3 4 5
            print(node.value)
            node = node.next
        # Lets make sure it works with a None list
        merged = merge(None, linked_list)
        node = merged.head
        while node is not None:
```

```
#This will print 1 3 5
print(node.value)
node = node.next

1
2
3
4
5
1
3
5
```

5

Now let's implement flatten recursively using merge.

```
In [7]: ''' In a NESTED LinkedList object, each node will be a simple LinkedList in itself'''
        class NestedLinkedList(LinkedList):
            def flatten(self):
                return self._flatten(self.head) # <-- self.head is a node for NestedLinkedList
            ''' A recursive function '''
            def _flatten(self, node):
                # A termination condition
                if node.next is None:
                    return merge(node.value, None) # <-- First argument is a simple LinkedList
                # _flatten() is calling itself untill a termination condition is achieved
                return merge(node.value, self._flatten(node.next)) # <-- Both arguments are a sa
In [8]: ''' Test flatten() function'''
        nested_linked_list = NestedLinkedList(Node(linked_list))
        nested_linked_list.append(second_linked_list)
        flattened = nested_linked_list.flatten()
        node = flattened.head
        while node is not None:
            #This will print 1 2 3 4 5
            print(node.value)
            node = node.next
1
2
3
4
```

0.1.4 Computational Complexity

Lets start with the computational complexity of merge. Merge takes in two lists. Let's say the lengths of the lists are N_1 and N_2 . Because we assume the inputs are sorted, merge is very efficient. It looks at the first element of each list and adds the smaller one to the returned list. Every time through the loop we are appending one element to the list, so it will take $N_1 + N_2$ iterations until we have the whole list.

The complexity of flatten is a little more complicated to calculate. Suppose our NestedLinkedList has N linked lists and each list's length is represented by $M_1, M_2, ..., M_N$.

We can represent this recursion as:

 $merge(M_1, merge(M_2, merge(..., merge(M_{N-1}, merge(M_N, None)))))$

Let's start from the inside. The inner most merge returns the *nth* linked list. The next merge does $M_{N-1} + M_N$ comparisons. The next merge does $M_{N-2} + M_{N-1} + M_N$ comparisons.

Eventually we will do N comparisons on all of the M_N elements. We will do N-1 comparisons on M_{N-1} elements.

This can be generalized as:

$$\sum_{n}^{N} n * M_{n}$$

In []: