Más Siguiente blog»

Crear un blog Acceder

I.T. - As Built

I'm an IT Professional with over 10 years experience. I've worked as a contractor for SMBs, LAN Admin for large enterprise and a mix of everything in between. In my current role, I'm an IT Team Leader for a market research company. The main purpose of this site though is to try and give something back to the online community which has been by far the most valuable of all my tools over the years. I hope you find something helpful!

Wednesday, July 14, 2010

Installing Zabbix agent daemon on Linux 2.6.x based system

Just a simple HowTo of installing the Zabbix agent daemon.

Create the zabbix user and required directories:

- # useradd zabbix
- # mkdir /var/log/zabbix
- # mkdir /etc/zabbix
- # mkdir /usr/src/zabbix

Download and extract the Zabbix agent precompiled binaries for Linux 2.6.x kernel (in this case the x64 version)

- # cd /usr/src/zabbix
- # wget http://www.zabbix.com/downloads/1.8.2/zabbix_agents_1.8.2.linux2_6.x64.tar.gz
- # tar zxvf zabbix_agents_1.8.2.linux2_6.x64.tar.gz
- # cp /usr/src/zabbix/sbin/zabbix_agentd /usr/local/bin

Create a basic zabbix_agentd.conf in /etc/zabbix. Here is an example:

- # This is config file for zabbix_agentd
- # To get more information about ZABBIX, go http://www.zabbix.com

#

- # List of comma delimited IP addresses (or hostnames) of ZABBIX servers.
- # No spaces allowed. First entry is used for sending active checks.
- # Note that hostnames must resolve hostname->IP address and
- # IP address->hostname.

Server=111.222.333.444

Server port for sending active checks

ServerPort=10051

Unique hostname. Required for active checks.

Hostname=myhostname.mydomain.com

Listen port. Default is 10050

ListenPort=10050

- # IP address to bind agent
- # If missing, bind to all available IPs

#ListenIP=127.0.0.1

- # Number of pre-forked instances of zabbix_agentd.
- # Default value is 5
- # This parameter must be between 1 and 16

Seguidores (0)
Seauir

Sequir Sequir Blog Archive ▼ 2010 (9) ▼ July (9) P2V conversion of Slackware 11

Cannot add ESX host to HA cluster

Installing Zabbix agent daemon on Linux 2.6.x base...

Pacemaker crm status reporting error with migrated...

Setting up Octopus to control World of Warcraft on...

Bandwidth limiting using iptables

CentOS Web Server from Source (mostly)

Slackware 11.0 and VMTools

DNS Update on a Linux Machine

About Me dthomo View my complete profile

1 de 3

StartAgents=3 # How often re

How often refresh list of active checks. 2 minutes by default.

RefreshActiveChecks=1800

Disable active checks. The agent will work in passive mode listening server.

DisableActive=0

Enable remote commands for ZABBIX agent. By default remote commands disabled.

EnableRemoteCommands=1

Specifies debug level

#0 - debug is not created

1 – critical information

#2 - error information

#3 - warnings

#4 - information (default)

#5 - for debugging (produces lots of information)

DebugLevel=4

Name of PID file

PidFile=/etc/zabbix/zabbix_agentd.pid

Name of log file.

If not set, syslog will be used

LogFile=/var/log/zabbix/zabbix_agentd.log

Maximum size of log file in MB. Set to 0 to disable automatic log rotation. LogFileSize=5

Spend no more than Timeout seconds on processing

Must be between 1 and 30

Timeout=30

USER-DEFINED MONITORED PARAMETERS

Format: UserParameter=,

Note that shell command must not return empty string or EOL only

Set permissions for the files/directories

chown -R zabbix:zabbix /var/log/zabbix # chown -R zabbix:zabbix /etc/zabbix

Start the daemon

/usr/local/bin/zabbix_agentd

You may want to add this line to your /etc/rc.d/rc.local as well to ensure the daemon starts after a reboot

Posted by dthomo at 5:11 PM

G+1 Recommend this on Google

No comments:

Post a Comment

2 de 3 18/10/2016 18:55

Enter your comment	
Comment as: Select profile Publish Preview	
Newer Post Home	Older Post

Subscribe to: Post Comments (Atom)

 $\label{eq:awesome lnc.} \mbox{Awesome Inc. template. Powered by Blogger.}$

3 de 3