Script	Run it in directory
a count more house	·
accept_mesh.m	s4_terrain
accepts anchors_carretera.msh as the definite mesh, skipping further	
processing with MeshLab. To be run instead of	
simplificar+MeshLab+juntar_mallas	
add_dat_to_geo.m	s1_mesh
Reads the .dat files created by SASPlanet while splitting a satellite	
image and creates a grid that can be saved as grid.geo or appended to	
salida\joined.geo.	
This script also created a list of background images	
(s1_mesh\list_bi.txt) ready to be included in the Venue.xml.	
NOTE: this script internally calls addgrid, so addgrid.hlg is	
overwritten.	
addgrid.m	s1_mesh
Creates a grid with .geo format. Two possibilities:	
addgrid(numx,numz) You want to view the available elevation	
data using a numx X numz grid	
addgrid(xmin,xmax,zmin,zmax,step) Creates a grid with the	
specified limits and line separation.	
specified filling and fille separation.	
If another parameter is added to the command, no matter its	
value, the list of points and lines created will be explicit (instead	
of using a "for loop").	
addgrid creates a file called addgrid.hlg ready to be opened with	
SASPLanet to get the satellite images for that area.	a7 walla b
add_sobject.m	s7_walls_b
Creates a list of SObjects to be inserted by hand in the Venue.xml.	
add_sobject(num_points) Parameter is the maximum number	
of points used by one SObject. Longer SObjects will be splitted.	
addt.m	s1_mesh
Opens joined geo and replaces the last occurrence of a Plane Surface	
followed by a Spline with the code to define that surface as Transinite	
btb_a_coor.m	base directory
Returns the terrestrial coordinates of a BTB point	
> [mapeo] = textread('mapeo.txt', '%f');	
<pre>> x=2380.47; > z=-2350.67;</pre>	
<pre>> z=-2350.67; > [longitud altura latitud]=BTB_a_coor(x,0,z,mapeo)</pre>	
btb06.m	venue
Creates the points in both borders of the road, where the road and the	, cliuc
terrain will be linked (they are called anchors). Parameter is the	
separation between anchors on right and left side. It will affect the	
1 1	
mesh created by mallado_regular	

coor_a_btb.m	base directory
Returns the BTB coordinates of a point given the terrestrial	
coordinates	
> [mapeo]=textread('mapeo.txt','%f');	
<pre>> longit= -73.67; > latit= 41.47;</pre>	
<pre>> latit= 41.47, > [x1 y1 z1]=coor_a_BTB(longit, latit, elevation, mapeo)</pre>	
corregir.m	s3_road
For a given road, compares the elevation profile assigned using	
dar_altura and that obtained from elevation data (from lamalla.mat),	
and changes the terrain elevation data (lamalla.mat) to fit the	
elevation profile set with dar_altura.	
corregir also accepts a kml file as a parameter and uses its coordinates	
and altitude to change lamalla.mat. This could be useful if we have a	
kml with altitudes we trust, but dangerous as those altitudes could	
have an offset respect to the elevation data available.	
corregir('file.kml')	
creartrack1.m	s3_road
Gets elevation values for a road from its coordinates and elevation	
data (lamalla.mat)	
create_hlg	s1_mesh
Creates file s1_mesh\sasplanet.hlg (open it with SASPlanet) with the	
boundary coordinates (box) of anchors_carretera.msh (run	
trocea_malla before using create_hlg)	0.41
create_sons	father's root
Creates the folder's structure for several sons in a multi-track project.	directory
create_sons(number_of_sons)	
Creates son01, son02, etc. folders in the same folder where the	
father is located	
create_sons('c:\temp\kmls',keep_names) Creates one son for each kml located inside the directory used	
as first parameter. If keep_names is 0, folders will be named	
son01, son02, etc. If keep_names is 1, folders will keep the	
name of their respective kmls	
cut lamalla.m	s2_elevation
Reduces the size of lamalla.mat. Useful if data comes for a too big	s2_elevation_b
zone.	52_00 (40001_0
cut_lamalla([xmin xmax],[zmin zmax])	
	<u> </u>

dar_altura.m	s3_road
Softens the output from creartrack1 and gives the nodes of the track	
their elevation and slope to fit that curve.	
dar_altura(smooth_factor,pos_slope,neg_slope,step,interactive)	
- smooth is a smoothing factor, the bigger the smoother	
 pos_slope and neg_slope are the maximum and minimum 	
slopes allowed (1 means 45 degrees)	
- the final elevation profile is constructed using one point	
each "step" meters. Use a small value to preserve the	
profile's details, and a big value to smooth them. 25m is	
used if omitted	
- If interactive==0, the script doesn't give the user the option	
to edit the profile by hand and exists	
fix_project.m	s1 mesh\salida
This script reads tracks' point coordinates contained in joined.geo and	SI_IIIesii (suita
creates new files porcentajes.mat and anchors.mat for all the tracks in	
the project. This way may be a project where tracks and terrain are	
not correctly linked any more can be fixed. After running this script,	
all the steps from juntar_mallas to the end must be redone.	
ı v	
This script won't work correctly if sons have been added or removed	
since joined.geo was created.	
Make a backup before using this script.	0.1
importakml.m	s0_import
Reads a kml file and from it creates a mapping between terrestrial and	
BTB coordinates.	
importakml(kml_file)	
All the original points of the kml will be converted to nodes of	
the road	
importakml(kml_file,'decimate',factor)	
Keeps 1 from every "factor" points of the kml as nodes of the	
road. For example if the kml has 100 points and factor==2, the	
road will have 50 nodes.	
<pre>importakml_old(kml_file,tolerance) Uses the old "approach".</pre>	
An <i>ideal</i> smooth road with a huge amount of nodes that follows	
the coordinates of the kml file (using akima splines). Finally	
some nodes are removed. A node is removed if removing it	
doesn't deviate the road more than "tolerance" meters from the	
"ideal path"	
join_all.m	s9_join
Final step of the process. Joins all the tracks, terrain, pacenotes and	
walls, creating a file called Venue.xml. To open this file good luck	
and WP.zip Xpack are needed.	
join_geos.m	s1_mesh
Joins the anchors_carretera.geo files created with mallado_regular for	SI_IIICSII
all the projects, creating file joined.geo inside s1_mesh\salida folder.	
This file should be edited with gmsh.	
	c4 toppoin
juntar_mallas.m Pands i ply a ply and p ply from s4 torrain\salida and joins them in	s4_terrain
Reads i.ply, c.ply and n.ply from s4_terrain\salida and joins them in	
one single mesh (files anchors_contaltura.txt and elements.txt)	

leehgt.m Creates lamalla.mat from a .hgt file (1 degree x 1 degree) leehgt(fichero,latitud,longitud) Data extension is from latittud to latitud+1 and from longitud to longitud+1	s2_elevation s2_elevation_b
<pre>leehgt2.m The same as leehgt, but joins 2 adjacent .hgt files leehgt2(file1, latit1, longit1, file2, latit2, longit2) if latit1==latit2, longit1 should be <longit2 <latit2<="" be="" if="" latit1="" longit1="=longit2," pre="" should=""></longit2></pre>	s2_elevation s2_elevation_b
leer_gridfloat.m Creates lamalla.mat from gridfloat file. First parameter is the .hdt and second one is .flt	s2_elevation s2_elevation_b
leetif.m Creates lamalla.mat from a geotiff file listc.m Reads salida\joined.geo and creates a file called listc.geo with the id numbers of all the Plane Surfaces created inside joined.geo after its creation (last line of joined.geo after its creation is the reference used by listc)	s2_elevation s2_elevation_b s1_mesh
make_grid.m Creates several files containing a regular grid of points with terrestrial coordinates. Those files should be "raised" with BTBLofty or a similar application and save with a different name: grid001.kml should be saved in the same folder as grid001_relleno.kml make_grid(xmin, xmax, zmin, zmax, step, file_size) Parameters are x and z minimum and maximum values, and distance between points of the grid. Maximum file_size depends upon the application to be used. 5000 is recommended for BTBLofty. Another possibility for make_grid is creating a kml route and asking	s2_elevation s2_elevation_b
make_grid ('limits.kml', step) mallado_regular.m Creates a terrain mesh on both sides of the road. Position of road borders (anchors) is taken from btb06 output. Besides the road a terrain of a specified width will be created, splitted in the transversal direction into the desired number of panels. Terrain width (meters) is the first parameter and the number of panels is the second one. If you want to try a regular pattern (tranfinite) for all the driveable zone, use 1 as 3 rd parameter. Otherwise use just 2 parameters	s1_mesh

muro_pegado.m	s7_walls_b
Creates walls on both sides of the road (from start to end). List of	
walls can be found in salida folder and should be inserted by hand	
inside the Venue.xml file (updating the total walls count, if needed)	
muro_pegado(tam_wall,offset)	
Parameters are the limit of points per wall and the displacement	
in meters in the outside direction from the road border (the	
width specified as btb06 parameter is used to compute border	
position)	
pacenotes.m	pacenotes
Gets the track shape from a driveline.ini file. Output from thius script	
will be used by pacenotes_2	
pacenotes_a.m	pacenotes
Gets the track shape from anchors created by btb06. Output from this	pacenoces
script will be used by pacenotes2_a	no cor stas
pacenotes2.m	pacenotes
Creates a new pacenotes.ini file using the old one and the output from	
pacenotes.m	
pacenotes2(sensibility,distance)	
Parameters are the sensibility for curve detection and the	
distance you want to move the pacenotes to the start of the road.	
10 means 50m.	
pacenotes2_a.m	pacenotes
Creates a list of pacenotes in BTB format ready to be inserted inside	r moorio cos
the Venue.xml. Join.all looks for this pacenotes and if they exist,	
includes them inside Venue.xml. Parameters are the same as	
pacenotes2	
1	.10 .14
partir_track.m	s10_plit
Splits a track into several segments. Reads split points from	
pos_nodes.txt	
plot_lamalla.m	s2_elevation
Plots the contents of salida\lamalla.mat as a surface.	s2_elevation_b
poner_muro.m	s7_walls
Creates walls in the boundary between driveable and non-driveable	
zones. Walls are automatically included inside Venue.xml by join_all	
procesar_elementstxt_mt.m	s10_split
Creates the terrain in BTB format from the mesh created by	pro_spiit
· ·	
juntar_mallas and the output from partir_track.	
By default terrain is splitted using a 10x10 grid, but user can choose	
another grid size.	
procesar_elementstxt_mt(cells_x,cells_z,do_mapping)	
Will split the terrain using a cells_x X cells_z grid, and If	
do_mapping is 1, terrain will be created with background	
images blending (see add_dat_to_geo).	
procesar_nodostxt.m	s4_terrain
Nodes of anchors_carretera.msh mesh receive a elevation value taken	
from lamalla.mat, if possible, or lamalla2.mat	
	1

	1 1 4
process_sons.m	base directory
This script processes all the sons in a multitrack project. It should be	of father
first edited to set the desired values for the parameters of the scripts	
called.	2 1 4
raise_kml.m	s2_elevation
Calls a Google Earth API to get elevation values for the	s2_elevation_b
gridXXX.kml files inside s2_elevation\salida folder. Output files will	
be named gridXXX_relleno.kml and will be ready to be processed	
with read_grid	
This script needs Google Earth and Python27 installed in the system,	
Read instructions for installation inside documentation folder.	
read_grid.m	s2_elevation
Reads the gridXXX_relleno files and created lamalla.mat, with all the	s2_elevation_b
elevation info collected	
readkml.m	s1_mesh
Translates a route from a kml file to a curve in gmsh format and BTB	
coordinates. Output file is written in salida folder, with the same	
name as input, but .geo extension.	
readkml('file.kml',curve)	
Second parameter can be "t", for adding straight lines, "s" for	
adding a spline, or "st" for adding both. Not using a second	
parameter means adding no curve (just points).	
readkml bat.m	s1_mesh
Calles readkml for all the .kml files found in the specified folder.	
readkml_bat('d:\folder',curve)	
simplificar.m	s1_mesh
Splits anchors_carretera.msh in three parts that should be processed	_
with MeshLab: intocables.ply, conducibles.ply and noconducibles.ply	
Also creates a folder nc_splitted with a separate .ply file for each	
surface of the non-driveable zone, so it is possible to simplify them	
individually.	
split_track.m	s10_split
Selects the points for splitting a track into several segments. Writes	STO_SPIRE
those points in file pos_nodes.txt, allowing the user to change them	
before running partir_track	
start.m	
Calls importakml to process s0_import\road.kml	
Calls make_grid with s2_elevation\limits.kml as parameter	
Calls make_grid with s2_elevation_b\limits_b.kml as parameter	
Default steps for make_grid are 25 and 75m, respectively. By default	
each gridXXX.kml is limited to 5000 points	
start	
start(step,step_b,file_size)	
Parameters are the steps in meters used by make_grid and the number	
of points per kml.	
	c4 townsin
terrain_noise.m Adds a random value to the elevation of the nodes of the terrain.	s4_terrain
Random value will be in the range specified. Use this script just	
before join_all	
terrain_noise([ymin ymax])	

trocea_malla.m	s1_mesh
Splits anchors_carretera.msh into 2 parts: list of mesh nodes	
(nodos.txt) and triangles (elements.txt)	
vercontorno.m	s2_elevation
Shows a contour plot using the terrain elevation data (lamalla.mat)	s2_elevation_b
and the road position (output from btb06)	