

Absolutely. Here are **simple JavaScript examples for beginners**, especially useful if you're learning JavaScript for **test automation / Playwright**.

1. Print a message

JavaScript

```
console.log("Hello World");  
console.log("Welcome to JavaScript");
```

Open the browser **Developer Tools** → **Console** to see the output.

2. Variables

JavaScript

```
let name = "Bala";  
let age = 30;  
  
console.log(name);  
console.log(age);
```

You can also combine them:

JavaScript

```
console.log("My name is " + name);  
console.log("My age is " + age);
```

3. Numbers and calculations

JavaScript

```
let price = 100;  
let quantity = 3;  
  
let total = price * quantity;  
  
console.log(total);
```

Output:

300

Try:

JavaScript

```
let a = 20;
let b = 5;

console.log(a + b); // Addition
console.log(a - b); // Subtraction
console.log(a * b); // Multiplication
console.log(a / b); // Division
```

4. String operations

JavaScript

```
let firstName = "Bala";
let lastName = "Murthy";

let fullName = firstName + " " + lastName;

console.log(fullName);
```

You can also use template literals:

JavaScript

```
console.log(`My name is ${firstName} ${lastName}`);
```

5. If condition

JavaScript

```
let age = 25;

if (age >= 18) {
  console.log("Eligible to vote");
} else {
  console.log("Not eligible to vote");
}
```

This is very important for **test validations**.

6. Multiple conditions

JavaScript

```
let marks = 75;

if (marks >= 90) {
  console.log("Grade A");
} else if (marks >= 70) {
  console.log("Grade B");
} else if (marks >= 50) {
  console.log("Grade C");
} else {
  console.log("Fail");
}
```

7. Boolean values

JavaScript

```
let isLoggedIn = true;

console.log(isLoggedIn);
```

Example:

JavaScript

```
if (isLoggedIn) {
  console.log("User is logged in");
} else {
  console.log("User is not logged in");
}
```

8. Arrays

An array stores multiple values.

JavaScript

```
let browsers = ["Chrome", "Firefox", "Edge"];

console.log(browsers);
console.log(browsers[0]);
```

```
console.log(browsers[1]);  
console.log(browsers[2]);
```

Output:

```
Chrome  
Firefox  
Edge
```

Remember: **array indexes start from 0.**

9. Loop through an array

JavaScript

```
let browsers = ["Chrome", "Firefox", "Edge"];  
  
for (let i = 0; i < browsers.length; i++) {  
  console.log(browsers[i]);  
}
```

This is particularly useful in automation when you need to process multiple elements.

10. Simple `for` loop

JavaScript

```
for (let i = 1; i <= 5; i++) {  
  console.log(i);  
}
```

Output:

```
1  
2  
3  
4  
5
```

11. Function

A function is a reusable block of code.

JavaScript

```
function greet() {  
    console.log("Hello");  
}  
  
greet();
```

12. Function with parameters

JavaScript

```
function greet(name) {  
    console.log("Hello " + name);  
}  
  
greet("Bala");  
greet("John");
```

Output:

```
Hello Bala  
Hello John
```

13. Function returning a value

JavaScript

```
function add(a, b) {  
    return a + b;  
}  
  
let result = add(10, 20);  
  
console.log(result);
```

Output:

```
30
```

14. Comparing values

JavaScript

```
let age = 25;

console.log(age == 25);
console.log(age === 25);
console.log(age > 18);
console.log(age < 18);
```

The result is `true` or `false`.

For automation, you'll frequently use:

JavaScript

```
actualValue === expectedValue
```

15. Simple email validation

This is a good beginner **tester-oriented** example:

JavaScript

```
function validateEmail(email) {

    if (email.includes("@")) {
        console.log("Valid email");
    } else {
        console.log("Invalid email");
    }
}

validateEmail("bala@gmail.com");
validateEmail("bala.com");
```

16. Get a value from an HTML input

HTML:

HTML

```
<input id="username" type="text">
<button onclick="getValue()">Get Value</button>

<script>
```

```
function getValue() {  
    let username = document.getElementById("username").value;  
    console.log(username);  
}  
</script>
```

If you enter:

Bala

and click the button, the browser console will show:

Bala

17. Change HTML text using JavaScript

HTML

```
<h1 id="message">Hello</h1>  
  
<button onclick="changeMessage()">Click Me</button>  
  
<script>  
function changeMessage() {  
    document.getElementById("message").innerText = "Welcome to JavaScript";  
}  
</script>
```

When you click the button, **Hello** changes to **Welcome to JavaScript**.

18. Simple age validation — useful for your insurance examples

JavaScript

```
function validateAge(age) {  
  
    if (age === "") {  
        console.log("Age is mandatory");  
    } else if (age < 18) {  
        console.log("Applicant is not eligible");  
    } else if (age > 60) {  
        console.log("Applicant is not eligible");  
    } else {  
        console.log("Applicant is eligible");  
    }  
}
```

```
}  
  
}  
  
validateAge(25);  
validateAge(15);  
validateAge(65);
```

Beginner practice order

I recommend learning these in this order:

Variables → **Data Types** → **Operators** → **if/else** → **Loops** → **Arrays** → **Functions** → **Objects** → **DOM** → **Events** → **Validation**

Once these are comfortable, you can move into JavaScript specifically for **Playwright automation**, such as:

JavaScript

```
page.locator()  
page.click()  
page.fill()  
page.textContent()  
page.getAttribute()
```

and then into **TypeScript for Playwright**.