Status	Finished
Started	Friday, 30 October 2026, 1:29 AM
Completed	Friday, 30 October 2026, 1:33 AM
Duration	4 mins 16 secs
Grade	**12.00** out of 15.00 (**80**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

a. {'rec', 1, ('cse', 'ece'),True}

b. {'rec', 1, ('cse', 'ece')} ✓

c. Error

d. {'rec', True, ('cse', 'ece')}

Question **2**

Correct

Mark 1.00 out of 1.00

What will be printed when the following code executes?

```
a = ("Python Programming")
```

```
print type(a)
```

```

```

a. str

b. <class 'str'> ✓

c. <class 'tuple'>

d. <class 'int'>

Question **3**

Incorrect

Mark 0.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

a. ['8', '30', '3', '2']

b. ['2', '3', '30', '8']

c. ['2', '3', '8', '30']

d. ['30', '8', '3', '2'] ✗

Question **4**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

a. (55,78,64,25)

b. Error ✓

c. (12)

d. 12

Question **5**

Correct

Mark 1.00 out of 1.00

Write the Output of the following Code?

t = (15,83,83,52,60,45,52,85,100)

print(min(t)+max(t)+t.count(52))

a. 2

b. 100

c. Error

d. 117 ✓

Question **6**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. False

b. True ✓

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
False

b. True
False

c. True ✓
True

d. False
True

Question **8**

Correct

Mark 1.00 out of 1.00

Which of the following options will not result in an error when performed on tuples in Python where tupl=(5,2,7,0,3)?

a. tupl[1]=2

b. tupl.sort()

c. tupl.append(2)

d. tupl1=tupl+tupl ✓

Question **9**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (30, 40, 50)(40, 50, 60, 70, 80)

b. (30, 40, 50) (10, 20, 30, 40)

c. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

d. (10, 20, 30, 40) (40, 50, 60, 70, 80)

Question **10**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
False

b. True ✓
True

c. False
True

d. True
False

Question **11**

Correct

Mark 1.00 out of 1.00

Select all the correct options to remove "ECE" from the set.

```
sampleSet = {"ECE", "R&A", "MCT"}
```

a. remove.sampleSet("ECE")

b. sampleSet.discard("ECE") ✓

c. sampleSet.delete("ECE")

d. del.sampleSet("ECE")

Question **12**

Incorrect

Mark 0.00 out of 1.00

What will be the output of below Python code?

```
tupl=("python","programming","Computer")
print(tupl[-3:0])
```

a. ()

b. Computer

c. (Computer) ✗

d. Error

Question **13**

Correct

Mark 1.00 out of 1.00

What will set1|set2 do?

```
If set1={"a","b",3}
set2={3,7}
```

a. A new set will be created with the unique elements of set1 and set2.

b. Elements of set1 will get appended to set2

c. A new set will be created with the elements of both set1 and set2 ✓

d. Elements of set2 will get appended to set1

Question **14**

Incorrect

Mark 0.00 out of 1.00

Which of the following Python code will create a set?

(i) set1=set((0,9,0))
(ii) set1=set([0,2,9])
(iii) set1={}

a. iii
b. All of the above
c. i,ii
d. ii ✗

Question **15**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

a. A tuple is unordered
b. We can change the tuple once created
c. A tuple maintains the order of items ✓
d. None of these