Fail-Closed Flood Evacuation Decision Support: Gauge-Held-Out Forecasting and a Constraint Shield for Learned Route Proposals

Anonymous Author(s)
Affiliation withheld for double-blind review

***Abstract*—Flood evacuation tools usually treat forecasting, decision making and routing as separate problems, and they are often evaluated in ways that hide their failure modes. We present a flood decision-support system in which every stage either produces an auditable result or hands control to a human operator. The forecasting stage predicts whether streamflow will exceed a gauge's 95th-percentile flow within three days. Trained on 242 CAMELS-IND gauges and tested on 49 gauges held out in both space and time (2015–2020), an XGBoost model reached a balanced accuracy of 0.898 and ROC-AUC of 0.965, against 0.765 and 0.765 for a persistence baseline; its precision of 0.328 remains the main weakness. The decision stage maps risk to monitor, human-review or automated-response actions and falls back to review whenever data, model or database health checks fail. The routing stage places a constraint shield, formulated as a quadratic unconstrained binary optimization (QUBO) feasibility filter followed by a deterministic validator, after an adaptive route proposer. Across 90 seeded scenarios with injected road closures and shelter overload, the shield raised the proposer's safe-route rate from 68.3% to 93.3% under four closures and eliminated capacity violations. It did not outperform flood-aware A*, and we report that result directly. We also show that a gate based on mean source reliability fails to trigger on most single-source failures.**

***Index Terms*—flood forecasting, evacuation routing, safe reinforcement learning, shielding, QUBO, human-in-the-loop, digital twin**

I. Introduction

Floods are among the most damaging natural hazards in India, and during a monsoon event the questions an emergency officer must answer change by the hour: will this river cross its warning level in the next few days, should evacuation start now or wait for review, and which roads and shelters are still usable? Machine-learning forecasters have become good at the first question, even in basins without long records [1], and graph search answers the last one quickly. What is less settled is how these pieces should be joined so that a wrong or stale input cannot silently turn into a dispatch order.

Learned route policies make this concern sharper. Reinforcement learning (RL) has been applied to evacuation planning for storm surge [2] and wildfire [3], and it can anticipate congestion that a shortest-path search ignores. A policy trained with reward penalties, however, still has no guarantee that it will avoid a closed bridge or a full shelter at run time. The safe-RL literature addresses this with *shields* that block unsafe actions before they reach the environment [4], [5]. To our knowledge, this idea has not been evaluated in a flood-evacuation setting alongside the forecasting and gating stages that feed it.

This paper describes and evaluates such a pipeline, built as an open full-stack prototype. Our contributions are:

1) A fail-closed decision chain in which a hazard-monotone risk score drives a three-way policy (monitor, human review, automated response), and any failed data, model or database health check downgrades automation to review.
2) A proposer-agnostic constraint shield for evacuation routes, with closures, shelter capacity, vehicles and accessibility encoded as QUBO penalties, plus a deterministic validator that re-checks the final plan.
3) A leakage-controlled evaluation of three-day flood-exceedance forecasting on CAMELS-IND gauges that are unseen in both space and time, reported against a persistence baseline.
4) A seeded stress test of the shield and of reliability gating, including results that do not favour our design.

We make no claim of quantum speed-up. The QUBO form is used because it expresses hard constraints as penalties that any binary solver can consume. In this prototype it is solved classically.

II. Related Work

Flood forecasting. Tree ensembles, support vector machines and neural networks are widely used for flood susceptibility and prediction [6]. Nearing *et al.* showed that a model trained on thousands of gauges forecasts extreme floods in ungauged basins with skill comparable to an operational physical system [1]. Graph-based models that encode river topology have since reported longer warning lead times [7]. For India, CAMELS-IND provides daily forcing, streamflow and catchment attributes for 228 peninsular catchments [8], and INDOFLOODS catalogues historical flood events [9]. Many published models are validated with random row splits. When neighbouring days from the same gauge fall on both sides of the split, accuracy is inflated, so we hold out whole gauges and later years.

Evacuation routing and learning. Classical formulations use shortest paths, network flows or vehicle routing, with Dijkstra [10], A* [11] and k-shortest paths [12] as building blocks. Deep Q-networks and policy-gradient methods such as PPO [13] have been used to learn evacuation policies [2], [3]. Shielding [4] and related constrained-RL methods [5] correct




Fig. 1. Fail-closed pipeline. Shaded blocks can stop or downgrade automation. The dashed link carries source reliability and health checks to the policy. Every block writes to the audit log.

a policy's action at run time instead of relying on the reward to discourage violations.

Binary optimization. Assignment and routing constraints can be written as Ising or QUBO models [14] and solved by simulated annealing [15], quantum annealing [16] or the Quantum Approximate Optimization Algorithm (QAOA) [17]. We use the QUBO form for its constraint encoding, not for any expected hardware advantage.

Explanation and digital twins. SHAP attributes a prediction to its inputs [18], and TreeSHAP computes exact values for tree ensembles [19]. Feature attributions cannot by themselves tell an officer that a route was rejected because a bridge is closed, so we pair them with explicit constraint traces. Practitioners co-designing a flood digital twin ranked data provenance and transparent "what-if" runs above visual realism [20]. This finding shaped our rule that simulated data is always labelled as simulated.

III. System Overview

Fig. 1 shows the pipeline. A FastAPI backend runs one function, `run_pipeline(mode, observations)`, in both live mode, which uses Open-Meteo weather and river discharge data, and simulation mode, which uses a digital twin of the Delhi Yamuna corridor and five reservoirs. Live and simulated snapshots are stored separately in MongoDB, so a synthetic tick can never appear on the live dashboard. A React interface reads every displayed value from this state.

A. Forecasting Stage

For gauge g on day t, the target is

$$y_{g,t} = \mathbf{1}\Big[\max_{h\in\{1,2,3\}} Q_{g,t+h} \;\geq\; q_g^{95}\Big], \tag{1}$$

where Q is observed streamflow and q_g^{95} is the gauge's 95th-percentile flow over the training years 1980–2008 only. The model uses 50 inputs: lagged and accumulated rainfall (up to 90 days), temperature, humidity, evapotranspiration, four soil-moisture layers, lagged and rolling streamflow, seasonality, and static catchment attributes such as area, slope, aridity and land cover. Hydrological signatures in CAMELS-IND are excluded because they are computed over the full record, including the test years. Future rainfall is also excluded.

B. Risk and Gated Decision Policy

The live risk engine combines a model prior p_{ML} with two hazard terms:

$$p = \mathrm{clip}\left(0.16 + 0.50\,\sigma_R + 0.20\,h_S + 0.14\,p_{\mathrm{ML}},\, 0,\, 1\right), \tag{2}$$

with $\sigma_R = 1/(1+e^{-(R-38)/12})$ for 24-h rainfall R in mm, and h_S the mean of $\mathrm{clip}((s-70)/30, 0, 1)$ over river and dam stages s, each expressed as a percentage of its danger level. The coefficients are fixed design choices rather than learned values, and a unit test checks that p never falls as rainfall rises. The policy returns MONITOR for $p < 0.50$ and HUMAN REVIEW for $0.50 \leq p < 0.60$. It returns AUTOMATED RESPONSE for $p \geq 0.60$ only when the data-quality, model-health and database-health checks all pass; otherwise the action is downgraded to review and the reason is logged. Thresholds live in a single configuration module served over the API, so the interface and backend cannot disagree.

C. Route Proposer and Constraint Shield

The routing study uses a 15-node network with three population zones, nine junctions, three shelters and 22 roads. Each road carries a travel time, flood depth index and congestion level. Candidate routes come from Yen's k-shortest paths on two graphs: the open-road graph and a graph that still contains closed roads. Including closed roads imitates a learned policy that has not yet seen a closure. The proposer ranks candidates by $w_T T + w_H H$, where T is travel time and H is hazard exposure, adjusted by group priority. It updates w_T and w_H online from a reward that penalises hazard and infeasibility. This is a lightweight adaptive policy, not a trained deep PPO agent. The shield treats it as a black box, so a trained agent can replace it without changing the interface.

Let $x_k \in \{0,1\}$ select candidate k for a group. The shield builds

$$E(\mathbf{x}) = \sum_k c_k x_k + P_1\Big(1 - \sum_k x_k\Big)^2 + P_2 \sum_k v_k x_k, \tag{3}$$

where $c_k = T_k + 5H_k$ is the route cost, the second term enforces a one-hot choice, and v_k counts violations of four hard constraints: closed roads, remaining shelter seats, available vehicles and accessibility for vulnerable groups. The penalties are set so that $P_2 > \max_k c_k$, which guarantees that a feasible route always has lower energy than an infeasible one. Candidates with $v_k > 0$ are removed before solving. The remaining one-hot problem is solved by simulated annealing, and a QAOA-inspired classical sampler is run alongside for comparison. A deterministic validator then re-checks the chosen route against the current graph version, shelter seats, vehicles, accessibility and data freshness. If the graph changed during solving, the result is discarded.

D. Reliability Gating and Explanations

Each data source (weather, flood sensor, radar, road database and citizen reports) has a reliability value set by its status. For example, live sources start at 0.88–0.94, a stale road feed drops to 0.40, and a drifting sensor drops to 0.48. Automatic dispatch

is blocked when the mean reliability falls below 0.60 or when a cross-source conflict score reaches 0.55. In the present prototype, the conflict score comes from a scripted scenario (Section V-C) rather than being estimated from data. Every recommendation carries two explanations: attribution bars over travel time, hazard, congestion, shelter seats, reliability and priority, and a trace listing each rejected candidate with the constraint it broke. For the flood forecaster, TreeSHAP is computed on the same booster that produced the displayed probability.

IV. Experimental Setup

Forecasting. The data cover 242 CAMELS-IND gauges. Training uses 1,641,197 gauge-days from 1980–2008 and validation uses 349,645 gauge-days from 2009–2014, all from gauges seen in training. The primary test set contains 52,994 gauge-days from 2015–2020 at 49 gauges, 20% of the total, that were held out with a group split (seed 42) and never used for training or tuning. Seven candidate models (logistic regression, random forest, histogram gradient boosting and four XGBoost [21] configurations) were compared on validation balanced accuracy. The decision threshold, 0.45, was also chosen on validation. The test set was used once.

Metrics. Floods occur on few days, so accuracy is misleading. We report the balanced accuracy

$$\mathrm{BA} = \tfrac{1}{2}\Big(\frac{TP}{TP+FN} + \frac{TN}{TN+FP}\Big), \tag{4}$$

together with precision, recall, F1, ROC-AUC and the area under the precision–recall curve (PR-AUC), which is sensitive to false alarms on rare events. For routing, let $s_i^{(1)}$ and $s_i^{(2)}$ be 1 when the initial and the re-planned route of scenario i pass every hard check and 0 otherwise. The safe-route rate over N scenarios is

$$S = \frac{100}{N}\sum_{i=1}^{N} \tfrac{1}{2}\big(s_i^{(1)} + s_i^{(2)}\big). \tag{5}$$

We also report the travel time of the final route, the number of plans that exceed shelter capacity and the wall-clock re-planning latency.

Routing. Each scenario draws flood depths, congestion, shelter occupancy and group sizes from a fixed seed ($42+17i$, $i = 0, \ldots, 29$). A route is planned, road R5 is then closed, and Shelter A receives 50% of its capacity as new arrivals. The route is then re-planned. A plan is *safe* if both the initial and re-planned routes avoid closed roads and satisfy capacity, vehicle and accessibility checks. We compare six methods: static shortest path by distance, flood-aware A*, a risk-aware greedy search, the proposer alone, the proposer with the shield solved by simulated annealing, and the proposer with the shield solved by the QAOA-inspired sampler. The stress test repeats the 30 scenarios with 0, 2 and 4 additional random closures (90 scenarios per method). It also varies the flood-severity setting over 0.20, 0.35, 0.50 and 0.65. Latencies were measured on a consumer laptop and include only the Python planning code.

TABLE I
Three-day exceedance forecasting on 49 unseen gauges, 2015–2020

Method	BA	Recall	Prec.	F1	ROC-AUC	PR-AUC
Persistence	0.765	0.538	**0.789**	**0.640**	0.765	0.449
XGBoost (all days)	**0.898**	**0.902**	0.328	0.481	**0.965**	**0.737**
XGBoost (onsets)	0.857	0.813	0.177	0.290	0.940	0.369

BA = balanced accuracy; threshold 0.45 (set on validation); n = 52,994.

Reproducibility. Every routing and gating number in this paper comes from one script that runs the prototype's own planning engine with fixed seeds and writes its results to a single file, and a build step fails if any number in the text differs from that file or from the stored forecasting evaluation. The forecasting split, the selected model and its threshold are stored with the model, so the test-set figures can be recomputed without retraining. Latencies are the only values that change from run to run, and we report them as indicative.

V. Results

A. Forecasting on Unseen Gauges

Table I summarises test performance. Floods occur on 5.5% of test days, so a model that always predicts "no flood" would be 94.5% accurate. For this reason we report balanced accuracy and precision–recall measures. The model found 90.2% of flood windows at gauges it had never seen, compared with 53.8% for persistence. Its ranking quality was also higher, with a PR-AUC of 0.737 against 0.449. The cost is false alarms: precision is 0.328, and its F1 score is lower than persistence. When we keep only windows in which the river was below threshold on day t, a stricter onset test, recall falls to 0.813 and PR-AUC to 0.369. On validation, the seven candidates were close (balanced accuracy 0.899–0.911), so the choice of model mattered less than the features and the split.

Table II lists the validation results that drove model selection. Logistic regression, fitted on a 500,000-row subsample, was only 0.012 below the selected model in balanced accuracy. The tree ensembles differed by at most 0.006, and depth had almost no effect. The selected configuration, the later of two depth-6 XGBoost fits, had the highest balanced accuracy and PR-AUC on validation. Every candidate had a validation precision between 0.391 and 0.420, so the low precision comes from the task and the threshold rule and appears in every model family.

B. Routing Benchmark

Table III reports the base setting (30 scenarios, no extra closures). Without the shield, the proposer chose an unsafe route in 10% of plans, and 0.2 capacity violations per scenario, all caused by Shelter A filling up. It behaved like the static and greedy baselines because, after the overload, all three still preferred the nearest shelter. The shield removed these violations at a cost of 1.2 minutes of extra travel time (17.8 vs. 16.6 min). Flood-aware A* reached the same safety and travel time with a re-planning latency about 15 times lower.

TABLE II
VALIDATION RESULTS OF THE SEVEN CANDIDATES (2009–2014, n = 349,645)

Model	Rows	BA	Recall	Prec.	PR-AUC
Logistic regression	sub	0.899	0.916	0.391	0.751
Random forest	sub	0.905	0.924	0.403	0.781
Hist. gradient boosting	full	0.909	0.930	0.408	0.791
XGBoost, depth 4	full	0.909	0.934	0.401	0.790
XGBoost, depth 6 (earlier fit)	full	0.909	0.925	0.420	0.792
XGBoost, depth 8	full	0.909	0.927	0.416	0.793
XGBoost, depth 6 (selected)	full	**0.911**	**0.936**	0.404	**0.796**

sub = 500,000-row training subsample; full = all 1,641,197 training rows.

TABLE III
ROUTING BENCHMARK, 30 SEEDED SCENARIOS (MEAN ± S.D.)

Method	Safe (%)	Clear. (min)	Cap. viol.	Re-plan (ms)
Static shortest path	90.0 ± 20.0	16.63	0.20	0.19
Flood-aware A*	100.0 ± 0.0	17.81	0.00	0.17
Risk-aware greedy	90.0 ± 20.0	16.63	0.20	1.22
Proposer only	90.0 ± 20.0	16.63	0.20	2.50
Proposer + shield (SA)	100.0 ± 0.0	17.81	0.00	2.68
Proposer + shield (QI)	100.0 ± 0.0	17.82	0.00	3.00

SA = simulated annealing; QI = QAOA-inspired classical sampler.

The simulated-annealing and QAOA-inspired solvers selected the same routes in all but a few cases, so the solver has little effect at this problem size.

Fig. 2 shows that the shield matters most when the network is degraded. With four extra closures, the proposer alone fell to 68.3% safe routes because it kept favouring short routes through roads that had just closed. With the shield, it reached 93.3%, the same as flood-aware A*. The remaining 6.7% are scenarios in which no feasible route existed after the closures, so no method could succeed. The flood-severity setting had no measurable effect: across all four values, safe-route rates and capacity violations were identical, and travel times differed by at most 0.01 minutes. The generated flood depths never crossed the 0.75 closure threshold, so closures, not severity, drove the outcome. This exposes a weakness of our scenario generator that we did not see before running the sweep.

Table IV gives the full sweep. Static shortest path and the risk-aware greedy search behaved identically at every closure level and fell to 86.67% at four closures. The proposer alone looked faster under heavy closures, with a travel time of 20.47 minutes against 25.27 for the shielded version, but only because some of its routes ran over closed roads. A shorter time on an unsafe route is not a usable result, so travel time should be compared only between methods with the same safe-route rate. Among those, the shield and flood-aware A* were within 0.01 minutes of each other at every level.

A separate ablation on 20 scenarios with a different seed stride ($42 + 19i$) gave the same picture: 92.5% safe routes without the shield and 100% with it, and mean travel time rose from 16.6 to 17.6 minutes. Capacity violations fell from 0.15 per scenario to zero. The shielded pipeline needed slightly more time to re-plan, 2.8 against 2.2 ms in that run, because it scores and filters every candidate before choosing one.




Fig. 2. Safe-route rate as initial road closures increase (30 seeded scenarios per bar).

TABLE IV
SAFE-ROUTE RATE (%) AND TRAVEL TIME (MIN) AGAINST INITIAL CLOSURES (FLOOD SEVERITY 0.35, 30 SCENARIOS EACH)

	0 closures		2 closures		4 closures	
Method	Safe	Time	Safe	Time	Safe	Time
Static shortest path	90.00	16.63	93.33	18.50	86.67	24.46
Flood-aware A*	100.00	17.81	100.00	19.31	93.33	25.28
Risk-aware greedy	90.00	16.63	93.33	18.50	86.67	24.46
Proposer only	90.00	16.63	86.67	19.07	68.33	20.47
Proposer + shield (SA)	100.00	17.81	100.00	19.31	93.33	25.27
Proposer + shield (QI)	100.00	17.82	100.00	19.32	93.33	25.28

C. Reliability Gating

We injected each failure type into the base scenario and recorded whether automatic dispatch stayed enabled (Table V). Only a communications failure, which degrades two sources at once, or three simultaneous failures pushed the mean reliability below 0.60. A complete weather-API outage left the mean at 0.662 and dispatch enabled. Averaging lets four healthy sources hide one failed source, which is the wrong behaviour for a safety gate. A minimum-based or source-weighted rule would block this case. The scripted sensor-conflict scenario (flood sensor reporting a flooded road that the road database still lists as open, conflict score 0.71) did block dispatch, as designed.

VI. DISCUSSION AND LIMITATIONS

Three lessons follow from the results. First, a shield is necessary when routes come from a learned or adaptive proposer, but it is not a source of better routes. It brought the proposer back to the level of a well-weighted classical search and no further. The case for a learned proposer therefore has to rest on situations that A* cannot represent, such as congestion that builds over time or many groups competing for the same roads, and our current benchmark does not model either. Second, forecast skill on unseen gauges is high when measured by recall and ranking, but its low precision means

TABLE V
FAILURE INJECTION AND AUTOMATIC-DISPATCH GATE (THRESHOLD 0.60)

Injected failure	Mean reliability	Auto dispatch
None	0.810	allowed
Weather API outage	0.662	allowed
Delayed radar	0.744	allowed
Flood-sensor drift	0.724	allowed
Stale road database	0.746	allowed
Conflicting citizen reports	0.780	allowed
Shelter failure	0.810	allowed
Communications failure	0.586	**blocked**
Delayed radar + sensor drift	0.658	allowed
Sensor drift + stale roads	0.660	allowed
Weather + drift + stale roads	0.512	**blocked**

that automatic evacuation on the forecast alone would produce many false alarms. Routing the forecast into human review rather than direct action is therefore the right default. Third, how a reliability gate aggregates its inputs matters as much as its threshold.

The study has clear limits. The routing network is small and synthetic. Source reliabilities are fixed per status rather than calibrated from data, and the conflict score is scripted. The forecaster is evaluated as a separate service: the live risk score in (2) still uses an earlier model trained on INDOFLOODS as its prior, and replacing it with the gauge forecaster is ongoing work. No field trial or user study with emergency officers has been carried out. Finally, the QAOA-inspired sampler is a classical heuristic and should not be read as evidence about quantum hardware.

We also note threats to the validity of the comparison. All routing methods were run on the same seeded scenarios, so differences between them are not caused by scenario sampling, but they share any bias of the scenario generator, including the flood depths that never crossed the closure threshold. The simulated-annealing and QAOA-inspired solvers pick from the same small feasible set, so their near-identical results say little about either solver. The forecasting gauges are in peninsular India, while the live system serves the Yamuna corridor in the north, so the reported skill may not transfer to that basin. Finally, the safe-route rate is binary per route: it records whether a hard constraint was broken but not how long a group would spend on a hazardous road.

Future work will move the routing benchmark to the Delhi road graph used by the live system. We will also replace the proposer with a trained PPO agent behind the same shield, change the gate to a minimum-based rule, and estimate conflict scores from paired observations.

VII. CONCLUSION

We built and evaluated a flood decision-support pipeline that is designed to fail towards human review. On gauges unseen in space and time, a three-day exceedance forecaster detected 90.2% of flood windows, against 53.8% for persistence, but with low precision. A QUBO-encoded constraint shield removed every capacity violation from an adaptive route proposer and raised its safe-route rate under heavy closures from 68.3% to 93.3%, matching but not beating flood-aware A*. A mean-based reliability gate missed most single-source failures. We report these weaker results because they show which parts of such a system need further work.

ACKNOWLEDGMENT

The authors thank the CAMELS-IND and INDOFLOODS dataset authors, Open-Meteo, and the OpenStreetMap contributors for openly available data. In line with the IEEE policy on AI-generated content, the authors disclose that Claude (Anthropic) was used to help edit and restructure the text of all sections and to draft the plotting and experiment scripts. The experiments use the authors' own software and can be reproduced with fixed seeds. The authors checked every number, claim and reference and take full responsibility for the content.

REFERENCES

[1] G. Nearing *et al.*, "Global prediction of extreme floods in ungauged watersheds," *Nature*, vol. 627, pp. 559–563, 2024.
[2] C. Liu *et al.*, "Effective storm surge risk assessment and deep reinforcement learning based evacuation planning: A case study of Daya Bay Petrochemical Industrial Zone," *Nat. Hazards Earth Syst. Sci.*, vol. 25, pp. 4767–4786, 2025.
[3] B. Raei, R. Safarzadeh, and X. Wang, "Congestion-aware multi-agent reinforcement learning for wildfire evacuation routing," *Int. Arch. Photogramm. Remote Sens. Spatial Inf. Sci.*, vol. XLIX-M-1-2026, pp. 41–50, 2026.
[4] M. Alshiekh, R. Bloem, R. Ehlers, B. Könighofer, S. Niekum, and U. Topcu, "Safe reinforcement learning via shielding," in *Proc. AAAI Conf. Artif. Intell.*, vol. 32, no. 1, 2018, pp. 2669–2678.
[5] J. García and F. Fernández, "A comprehensive survey on safe reinforcement learning," *J. Mach. Learn. Res.*, vol. 16, pp. 1437–1480, 2015.
[6] A. Mosavi, P. Ozturk, and K.-W. Chau, "Flood prediction using machine learning models: Literature review," *Water*, vol. 10, no. 11, Art. no. 1536, 2018.
[7] N. Kirschstein and Y. Sun, "The merit of river network topology for neural flood forecasting," in *Proc. 41st Int. Conf. Mach. Learn. (ICML)*, Vienna, Austria, 2024.
[8] N. K. Mangukiya *et al.*, "CAMELS-IND: Hydrometeorological time series and catchment attributes for 228 catchments in Peninsular India," *Earth Syst. Sci. Data*, vol. 17, pp. 461–491, 2025.
[9] S. K. Kuntla and M. Saharia, "INDOFLOODS: A comprehensive database for flood events in India enhanced with catchment attributes," *Bull. Amer. Meteorol. Soc.*, 2025.
[10] E. W. Dijkstra, "A note on two problems in connexion with graphs," *Numer. Math.*, vol. 1, no. 1, pp. 269–271, 1959.
[11] P. E. Hart, N. J. Nilsson, and B. Raphael, "A formal basis for the heuristic determination of minimum cost paths," *IEEE Trans. Syst. Sci. Cybern.*, vol. 4, no. 2, pp. 100–107, 1968.
[12] J. Y. Yen, "Finding the k shortest loopless paths in a network," *Manage. Sci.*, vol. 17, no. 11, pp. 712–716, 1971.
[13] J. Schulman, F. Wolski, P. Dhariwal, A. Radford, and O. Klimov, "Proximal policy optimization algorithms," arXiv:1707.06347, 2017.
[14] A. Lucas, "Ising formulations of many NP problems," *Front. Phys.*, vol. 2, Art. no. 5, 2014.
[15] S. Kirkpatrick, C. D. Gelatt, and M. P. Vecchi, "Optimization by simulated annealing," *Science*, vol. 220, no. 4598, pp. 671–680, 1983.
[16] A. R. Cadeliña *et al.*, "D-Wave implementation of quantum annealing for optimal resource allocation in disaster response operation of Marikina City," *ECTI Trans. Comput. Inf. Technol.*, vol. 18, no. 1, pp. 24–33, 2024.
[17] E. Farhi, J. Goldstone, and S. Gutmann, "A quantum approximate optimization algorithm," arXiv:1411.4028, 2014.
[18] S. M. Lundberg and S.-I. Lee, "A unified approach to interpreting model predictions," in *Adv. Neural Inf. Process. Syst. 30*, 2017, pp. 4765–4774.
[19] S. M. Lundberg *et al.*, "From local explanations to global understanding with explainable AI for trees," *Nat. Mach. Intell.*, vol. 2, no. 1, pp. 56–67, 2020.

[20] H. Underhill, L. McEwen, and T. Coulthard, "'That's the dream, right?': Reflections on the co-design of an environmental digital twin by flood risk management professionals," *Front. Environ. Sci.*, vol. 13, Art. no. 1724250, 2026.

[21] T. Chen and C. Guestrin, "XGBoost: A scalable tree boosting system," in *Proc. 22nd ACM SIGKDD Int. Conf. Knowl. Discov. Data Min.*, 2016, pp. 785–794.