One-Hot-Preserving QAOA with Transferable Angles for Flood Shelter Assignment

Nandhakumar T
Department of Information Technology
Sona College of Technology
Salem, Tamil Nadu, India
nandhakumartm93@gmail.com

Balakarthikeyan B S
Department of Artificial Intelligence and Data Science
Sona College of Technology
Salem, Tamil Nadu, India
balasan2626@gmail.com

Gowthaman J
Department of Artificial Intelligence and Data Science
Sona College of Technology
Salem, Tamil Nadu, India
gowthamanjanadhran@gmail.com

Abhishek S
Department of Artificial Intelligence and Data Science
Sona College of Technology
Salem, Tamil Nadu, India
abisheksengodan18@gmail.com

***Abstract*—Shelter assignment after a flood disruption is a small capacity-constrained assignment problem that is often proposed for quantum optimization, yet mixer studies use equality constraints on random graphs and train new angles for every instance. We study the Quantum Approximate Optimization Algorithm (QAOA) on 12-qubit flood digital-twin instances by exact statevector simulation. A ring-XY mixer, which keeps every group assigned to exactly one shelter while capacity stays a penalty, placed 0.188 $\pm$ 0.020 of its probability on the optimal plan at depth 4 over 5 optimizer seeds, against at most 0.048 for the transverse-field mixer (Holm-adjusted $p \leq 8.0 \times 10^{-6}$); a Grover mixer was not significantly different after correction for four depths but tended to fall behind, and a mixer confined to the fully feasible subspace reached 0.444, at the price of preparing a superposition of feasible plans. Angles fixed on 30 development instances and applied unchanged to 30 new instances reached $P_{\mathrm{opt}} = 0.306$, above per-instance COBYLA training (0.163), the best of five training seeds (0.242) and L-BFGS-B (0.225). Switching off the cost scaling made the transferred angles collapse to 0.029, so the shared energy scale is what makes transfer work. On 50 instances on OpenStreetMap road networks of 6 Indian cities they matched per-instance training and raised success within 32 shots from 74.9% to 89.9%. Exhaustive search solves these instances in 0.90 ms; we claim no quantum advantage.**

***Index Terms*—QAOA, XY mixer, parameter transfer, QUBO, evacuation planning**

I. Introduction

When a flood closes roads and fills shelters, an emergency officer must decide again which shelter each evacuation group should go to. The decision couples travel time, flood exposure along the route and the seats left at each shelter. As a binary program it is a capacity-constrained assignment problem, the kind that is routinely encoded as a quadratic unconstrained binary optimization (QUBO) problem [1], [2] and offered as an application for near-term quantum optimization [3], [4].

Three questions are usually left open in such proposals. First, does the circuit respect the constraints or only penalise their violation? The original QAOA [5] explores all 2^n bit-strings, most of which are not plans, whereas the quantum alternating operator ansatz [6] keeps the state inside a feasible subspace [7]–[9]. Mixer comparisons use equality constraints, while shelter capacity is an inequality; the ring-XY mixer studied here preserves only the one-hot equality, so capacity stays a penalty. Second, must the angles be trained again for every disruption? In an evacuation the instance changes with every closure, and per-instance training costs thousands of circuit evaluations. Third, how does the result compare with ordinary classical methods on instances of realistic shape?

We answer these questions on instances generated by the digital twin of a flood decision-support prototype. Our contributions are:

1) A shelter-assignment QUBO built from twin state, with a pairwise capacity encoding, a penalty bound, and a cost shift and scaling that place all instances on one energy scale; we measure how often the encoding is exact.
2) A controlled comparison of the transverse-field, one-hot-preserving ring-XY, Grover and feasible-subspace mixers under mean-energy and conditional value-at-risk (CVaR) training at depths 1–4, replicated over 5 optimizer seeds with paired significance tests and a penalty-weight sweep.
3) An angle-transfer protocol, with its one-time cost and a test of the energy scaling it relies on: one angle set per depth, chosen on development instances, is applied unchanged to new disruption instances and to instances on real city road networks and on larger instances, and matches or outperforms per-instance training at no per-instance cost.
4) A gate-level noise study and a comparison with exhaustive search, a greedy rule and tuned simulated annealing, with a scaling run to 18 qubits.

All results come from classical simulation; we make no claim of quantum speed-up.

II. Related Work

Formulations. Lucas gave Ising forms for many NP-hard problems [1], and Glover *et al.* describe how assignment and capacity constraints become quadratic penalties [2]. Shelter location and allocation for flood evacuation has long been studied with integer programming [10], and quantum annealing has been applied to disaster resource allocation [3].

Mixers. QAOA alternates a cost unitary and a mixing unitary for p layers [5]; a recent review covers its variants [11]. Hadfield *et al.* generalised the mixer so that it preserves hard constraints [6]. Wang *et al.* analysed ring and complete XY mixers for one-hot constraints [7], Fuchs *et al.* gave general constructions of constraint-preserving mixers [8] and optimal mixers restricted to a subspace [12], and Grover mixers move the complexity from the mixer into the preparation of the feasible superposition [9]. Applied studies pair XY mixers with warm starts for vehicle routing [13] and build coverage-preserving mixers for personnel rostering [14].

Training and transfer. Angles can be interpolated from depth p to $p{+}1$ [15], CVaR objectives raise the probability of good samples [16], and warm starts use classical solutions [17]. Optimal angles concentrate across instances of one family [18] and transfer between random graphs [19]; for weighted Max-Cut, rescaling the weights lets one parameter set serve many instances [20]. On hardware, QAOA performance falls with size and depth [21], and practical advantage in optimization has not been shown [4].

Research gap. The mixer studies above handle equality constraints, the transfer studies use unconstrained MaxCut with the standard mixer, and the disaster-response work solves a penalty QUBO on an annealer. To our knowledge, angle transfer has not been tested for one-hot-preserving mixers on instances with a penalised capacity inequality, nor on instances that change with a disruption, and no evacuation study compares mixers against an exact optimum, classical baselines and a gate-level noise model together.

III. Problem Formulation

A. Instances from the Digital Twin

The twin models a corridor with three population zones, nine junctions and three shelters joined by 22 roads. Every road carries a travel time, a flood-depth index and a congestion level drawn from a seed. Shelters have capacities of 120, 90 and 70 people with an initial occupancy of 15–45%, and groups have 8–22 people. Each instance applies the disruption used in the twin's routing benchmark: road R5 closes and Shelter A receives arrivals equal to half its capacity. For group g and shelter s we take the best open path under the twin's flood- and congestion-weighted edge cost and define

$$c_{gs} = T_{gs} + 5H_{gs}, \tag{1}$$

where T_{gs} is travel time in minutes and H_{gs} the mean flood index along the path. The pair (g, s) is *forbidden* if no open path exists, the shelter has failed, or the group alone exceeds the remaining seats R_s. With G groups, binary variables x_{gs} give $n = 3G$ qubits. A plan is feasible if every group has exactly one shelter, no forbidden pair is used and $\sum_g n_g x_{gs} \le R_s$ for each shelter, where n_g is the group size.

B. QUBO with Pairwise Capacity

The capacity constraint is an inequality, which normally needs slack qubits [2]. We use a pairwise encoding instead. Let $\mathcal{O} = \{(g, h, s) : n_g + n_h > R_s\}$ be the pairs of groups that cannot share shelter s and $\mathcal{F}$ the forbidden pairs. With shifted costs $c'_{gs} = c_{gs} - \min_{s'} c_{gs'}$,

$$E(\mathbf{x}) = \sum_{g,s} c'_{gs} x_{gs} + P\Big[\sum_{g}\Big(1 - \sum_{s} x_{gs}\Big)^2 + \sum_{(g,s)\in\mathcal{F}} x_{gs} + \sum_{(g,h,s)\in\mathcal{O}} x_{gs}x_{hs}\Big]. \tag{2}$$

Lemma 1: With $P = 1 + \sum_g \max_s c'_{gs}$, every bitstring that breaks a one-hot, forbidden-pair or pairwise-capacity term has higher energy than every bitstring that breaks none of them.

Proof. Since $c'_{gs} \ge 0$, a bitstring with no violated term has energy at most $P - 1$, while a violated term adds at least P to a non-negative cost. ∎

On one-hot states the shift subtracts the constant $\sum_g \min_s c_{gs}$, so the optimal plan is unchanged. We then divide the Hamiltonian by $\Delta = P - 1$, which maps the energies of all penalty-free plans into $[0, 1]$ for every instance. This scaling later allows angles to be shared between instances (Section IV-A). The pairwise encoding misses overloads by three or more groups whose pairs all fit, so a penalty-free plan can still be infeasible; every sampled plan is therefore re-checked exactly before use.

IV. QAOA Variants and Training

For depth p and angles $\boldsymbol{\theta} = (\boldsymbol{\gamma}, \boldsymbol{\beta})$, QAOA prepares

$$|\psi(\boldsymbol{\theta})\rangle = \prod_{k=1}^{p} e^{-i\beta_k B}\, e^{-i\gamma_k \hat{E}/\Delta}\, |\psi_0\rangle, \tag{3}$$

where $\hat{E}$ is diagonal with entries $E(\mathbf{x})$. Substituting $x_q = (1 - Z_q)/2$ turns (2) into an Ising Hamiltonian with one R_Z rotation per qubit and one two-qubit ZZ rotation per non-zero coupling.

Transverse-field (X) mixer. $B = \sum_q X_q$ and $|\psi_0\rangle = |+\rangle^{\otimes n}$; constraints act only through the penalties.

Ring-XY mixer. For each group g with qubits a_g, b_g, c_g,

$$B_{\mathrm{XY}} = \sum_{g} \sum_{(u,v)\in\{(a_g,b_g),(b_g,c_g),(c_g,a_g)\}} \tfrac{1}{2}\big(X_u X_v + Y_u Y_v\big). \tag{4}$$

Each term swaps amplitude between $|01\rangle$ and $|10\rangle$, so a one-hot group stays one-hot [7]. The start state $|W_3\rangle^{\otimes G}$, with $|W_3\rangle = (|100\rangle + |010\rangle + |001\rangle)/\sqrt{3}$, is the uniform superposition of the 3^G one-hot plans [22]. The one-hot penalty is then constant and is dropped. The three ring terms are applied in a fixed order, as in a first-order Trotter step.

Grover mixer. $B_{\mathrm{GM}} = |\psi_0\rangle\langle\psi_0|$ with the same start state, so $e^{-i\beta B_{\mathrm{GM}}} = I + (e^{-i\beta} - 1)|\psi_0\rangle\langle\psi_0|$ [9]. It mixes all

one-hot plans in one step, but each layer needs the inverse state preparation, a phase controlled on all n qubits and the preparation again, which is far deeper than the 12 XY rotations of the ring mixer.

Feasible-subspace mixer. The ring-XY and Grover mixers keep the state among one-hot plans, so capacity still acts only through the penalty. As a reference for a mixer that respects every constraint, we also run a Grover mixer whose start state is the uniform superposition of the fully feasible plans [9], [12]. Its probability of a feasible plan is 1 by construction, but preparing that state requires knowing the feasible set, which is as hard as the problem itself in general; it is a bound on what constraint handling can give, not a practical circuit.

Objectives and training. We minimise either $\langle \hat{E} \rangle$ or the CVaR with $\alpha = 0.1$ [16]. Sorting bitstrings by energy, $E_{(1)} \le E_{(2)} \le \dots$, with probabilities $\pi_{(k)}$ and cumulative mass $\Pi_k = \sum_{j \le k} \pi_{(j)}$,

$$\mathrm{CVaR}_\alpha = \frac{1}{\alpha} \sum_k E_{(k)} \, \min\big(\pi_{(k)},\ \max(0,\ \alpha - \Pi_{k-1})\big). \quad (5)$$

Angles are optimised by COBYLA [23] with at most 250 evaluations per start, depth by depth: at each depth p we start from two random points ($\gamma_k \sim U(0,\pi)$, $\beta_k \sim U(0,\pi/2)$) and, for $p > 1$, from the optimum of depth $p-1$ interpolated to p layers [15], and keep the best result.

A. Angle Transfer

Per-instance training must be repeated after every disruption. Since the scaled Hamiltonians of all instances share the energy range $[0, 1]$, we test whether trained angles carry over. Let $\Theta_p = \{\boldsymbol{\theta}_j^{(p)} : j \in \mathcal{D}\}$ be the angles trained on the development instances. We fix

$$\boldsymbol{\theta}_p^\star = \arg\max_{\boldsymbol{\theta} \in \Theta_p} \ \frac{1}{|\mathcal{D}|} \sum_{j \in \mathcal{D}} P_{\mathrm{opt}}(j; \boldsymbol{\theta}), \quad (6)$$

the trained angle set that works best on average across the development instances, and apply it to new instances without any evaluation on them. We choose among whole trained sets instead of averaging angles coordinate by coordinate, because angles trained on different instances sit in different basins of the periodic landscape; their coordinate-wise median gave $P_{\mathrm{opt}} = 0.001$ in a leave-one-out test.

V. Experimental Setup

Instances. The development set $\mathcal{D}$ has 30 instances from twin seeds $42 + 17i$, $i = 0, \dots, 29$, using the first four groups ($G = 4$, $n = 12$); all are feasible, with on average 45.0 feasible plans among the 81 one-hot plans, and in 12 of them capacity changes the optimal plan. The held-out set has 30 new instances from $i = 30, \dots, 59$, which were used for nothing but the final transfer test. For a test across networks we built 60 further instances (50 feasible, 22 capacity-bound) on the OpenStreetMap road graphs of 6 flood-prone Indian cities (Delhi, Chennai, Mumbai, Kolkata, Guwahati and Patna), using each city's mapped zones, shelters and road flood-exposure proxy and the same edge weights and travel-time rule as the prototype's live router. The road data are real; demand is not mapped, so group sizes and seats follow the twin's distributions, and the disruption closes the most flood-exposed road on any zone–shelter path and sends half a shelter's capacity to the first shelter.

Simulation. The simulator stores the 2^n amplitudes in double precision; the cost unitary is one elementwise phase, the X mixer applies R_X qubit by qubit, and each XY term rotates the precomputed amplitude pairs whose target bits are 01 and 10. One evaluation at 12 qubits takes under 10 ms on a laptop. All random choices use fixed seeds.

Metrics. P_{opt} is the probability of measuring an optimal plan, P_{feas} that of a feasible plan, and success@$N = 1 - (1 - P_{\mathrm{opt}})^N$ the chance that one of $N = 32$ shots is optimal. We count objective evaluations, each of which is a batch of circuit executions on hardware.

Replication and statistics. Per-instance training was repeated with 5 optimizer seeds for the X/mean, XY/mean and XY/CVaR variants; seed 0 reproduces the main run. Mixers are compared per instance with the two-sided Wilcoxon signed-rank test, Holm-corrected over the four depths, and with 95% bootstrap intervals over instances.

Baselines. Uniform sampling of the 81 one-hot plans ($P_{\mathrm{opt}} = 0.0169$); exhaustive search; a greedy rule that places the largest group first in its cheapest shelter with seats left; and simulated annealing [24] on (2) with 20 restarts of 200 sweeps. For the X mixer we also swept the penalty λP with $\lambda \in \{0.25, 0.5, 1, 2\}$.

TABLE I
Mixers and objectives at depth 4 (30 instances, 12 qubits)

Variant	P_{opt}	95% CI	seeds	P_{feas}	s@32 %	Evals
X, mean	0.040	0.031–0.051	0.040 ± 0.005	0.547	63.7	2046
XY, mean	0.215	0.153–0.283	0.188 ± 0.020	0.795	88.4	2513
XY, CVaR	0.149	0.126–0.178	0.139 ± 0.013	0.664	98.1	1281
Grover, mean	0.139	0.121–0.156	–	0.815	96.9	2033
Grover, CVaR	0.117	0.106–0.127	–	0.563	96.2	918

CI: 95% bootstrap over instances, main run. seeds: mean ± s.d. over 5 optimizer seeds. s@32: success@32. Evals: cumulative to $p = 4$.

VI. Results

A. Mixers, Objectives and Penalties

Table I and Fig. 1 give the main comparison. The XY mixer reached $P_{\mathrm{opt}} = 0.215$ at $p = 4$ in the main run and 0.188 ± 0.020 over 5 seeds (range 0.168–0.215), against 0.035–0.048 for the X mixer. It was better on 25–29 of 30 instances at every depth (Holm-adjusted $p \le 8.0 \times 10^{-6}$), and the ranking held for every seed. Its feasibility stayed between 0.722 and 0.795 at every depth, whereas the X mixer began with $P_{\mathrm{feas}} = 0.074$ and spent its layers recovering feasibility.

The Grover mixer reached 0.139 at $p = 4$, and its difference from XY was not significant at any depth (Holm-adjusted $p \ge 0.19$). Non-significance is not equivalence, and the data lean towards XY: at $p = 4$ XY was ahead on 20 of 30 instances, with a mean difference of 0.076 (paired 95% bootstrap interval




Fig. 1. Probability of the optimal plan (left) and of any feasible plan (right) against depth, main run. The dotted line is uniform sampling of one-hot plans.

0.018–0.141) and an unadjusted signed-rank $p = 0.047$ that does not survive the Holm correction; at $p = 2$ and 3 the interval includes zero. It spread probability more evenly over instances, so its success@32 was higher than that of XY with the mean objective. The ring-XY circuit has the two-qubit gate count per layer of the X variant: 2.0 capacity couplings plus 12 XY rotations, against 14.0 ZZ couplings, about 28 CNOTs per layer with all-to-all connectivity.

CVaR training lowered the XY mixer's mean P_{opt} to 0.149 but raised success@32 from 88.4% to 98.1%, because it removed the instances with very small P_{opt}: the worst instance rose from 0.002 to 0.074. Those instances were all capacity-bound.

A natural objection is that the X mixer was handicapped by its penalty. Lowering the penalty to $\lambda = 0.25$ raised its P_{opt} by 2.6× to 0.104 ($\lambda \in \{0.25, 0.5, 1, 2\}$), at a feasibility of only 0.401, still about half of the XY result. The other direction shows what the capacity penalty still costs the XY mixer: the feasible-subspace mixer reached $P_{\text{opt}} = 0.444$ at $p = 4$ (0.145 at $p = 1$) and beat XY on 26 of 30 instances ($p = 4.4e-06$), with every plan feasible.

B. Angle Transfer to New Disruptions

In a leave-one-out test on the development set, where (6) was evaluated without the target instance, the transferred angles gave $P_{\text{opt}} = 0.292$ at $p = 4$ with no evaluation on the target, above per-instance training (0.215) and equal to the best of 5 training seeds per instance (0.297), which costs 12,552 evaluations per instance. Only 2 distinct angle sets were ever selected.

Table II gives the held-out test. Applied unchanged to the 30 new instances, the fixed XY angles reached $P_{\text{opt}} = 0.306$ at $p = 4$, 1.9× the 0.163 of per-instance training with 2,496 evaluations, and were better on 24 of 30 instances ($p = 1.7 \times 10^{-4}$). Success within 32 shots rose from 79.7% to 99.99%. Refining the fixed angles with 30 evaluations raised P_{opt} to 0.356. CVaR angles transferred as well (0.250 against 0.138, better on 29 of 30). Transfer did not rescue the X mixer (0.036 against 0.028). To test whether the energy scaling is

TABLE II
HELD-OUT TRANSFER: 30 NEW INSTANCES, ANGLES FIXED ON THE DEVELOPMENT SET

		trained per instance		fixed	fixed	s@32 %	
Variant	p	P_{opt}	evals	P_{opt}	+30	trained	fixed
XY, mean	1	0.040	278	0.089	0.110	55.5	89.6
XY, mean	2	0.072	996	0.162	0.226	71.8	95.4
XY, mean	3	0.120	1,746	0.246	0.272	76.8	99.8
XY, mean	4	0.163	2,496	0.306	0.356	79.7	100.0
XY, CVaR	1	0.059	310	0.063	0.115	80.7	75.7
XY, CVaR	2	0.092	826	0.108	0.145	93.6	88.7
XY, CVaR	3	0.126	1,246	0.180	0.178	97.9	99.6
XY, CVaR	4	0.138	1,590	0.250	0.252	97.9	99.8
X, mean	4	0.028	2,032	0.036	0.040	50.3	63.6

Fixed angles need 0 evaluations per new instance; +30 = refined with 30 evaluations.

what makes transfer work, we repeated training, selection by (6) and the held-out test with the scaling switched off and with a different normalisation, division by the standard deviation of the penalty-free plan energies. Without scaling the fixed angles reached only 0.029 on the new instances, although training without scaling still reached 0.270 per instance on the development set; with the other normalisation they reached 0.282, close to the 0.306 of ours. Transfer therefore needs a common energy scale, not our particular one.

The per-instance baseline stops at 250 evaluations per start, so we also tried stronger ones on the held-out instances at $p = 4$. The best of five COBYLA seeds (0.242, 12,485 evaluations per instance) and L-BFGS-B with finite-difference gradients (0.225, 3,330) stayed below the fixed angles, so their advantage is not only a weak optimizer; COBYLA started from the fixed angles with the full budget did improve on them (0.385with 814 evaluations, $p = 0.0019$). The fixed angles are not free: training the 30 development instances took 75,392 evaluations and choosing by (6) another 3,600, 78,992 in all, which per-instance training would spend on about 32 disruptions. For a sequence of disruptions, training moves offline and each new instance needs only sampling, or a warm start where time allows.

C. Transfer to Real Road Networks

The city instances differ from the twin in network, travel times (mean cost 47 minutes per pair) and disruption, yet the angles fixed on the twin carried over (Table III). For the XY mixer with the mean objective, the fixed angles reached $P_{\text{opt}} = 0.202$ on the 50 city instances, not significantly different from per-instance training (0.213, $p = 0.74$) with 2,488 evaluations, against uniform sampling at 0.0123. They were more reliable: per-instance training left 8 instances with $P_{\text{opt}} < 0.01$, the fixed angles 1, so success within 32 shots rose from 74.9% to 89.9% ($p = 0.01$). CVaR angles transferred better than per-instance CVaR training (0.194 against 0.111, $p = 7.9 \times 10^{-6}$), and the X mixer stayed far behind (0.047 fixed, 0.037 trained).

D. Transfer to Larger Instances and Under Noise

The angles in (6) were selected on 12-qubit instances only. We applied them unchanged to 10 new twin instances

TABLE III
FIXED ANGLES AGAINST PER-INSTANCE TRAINING AT $p = 4$: HELD-OUT TWIN INSTANCES AND OPENSTREETMAP CITY INSTANCES

	twin, 30 new		cities, 50		cities, s@32 %
Variant	trained	fixed	trained	fixed	trained fixed
XY, mean	0.163	0.306	0.213	0.202	74.9 89.9
XY, CVaR	0.138	0.250	0.111	0.194	86.6 89.8
X, mean	0.028	0.036	0.037	0.047	55.8 70.1

Entries are mean P_{opt} unless marked; fixed angles use 0 evaluations per instance.

TABLE IV
ANGLES FIXED AT 12 QUBITS, APPLIED AT 15 AND 18 QUBITS ($p = 4$, NEW INSTANCES)

				trained		fixed			s@32 %
G (n)	obj.	inst.	unif.	mean	<.01	mean	min	tr.	fix.
5 (15)	mean	10	0.0049	0.138	3	0.216	0.176	63	100
5 (15)	CVaR	10	0.0049	0.130	0	0.190	0.078	98	99
6 (18)	mean	10	0.0016	0.060	6	0.079	0.056	39	92

<.01: instances with $P_{\mathrm{opt}} < 0.01$. Fixed angles use 0 evaluations per instance.

with five groups (15 qubits) and 10 with six groups (18 qubits), and compared them with per-instance training under the same procedure as before (Table IV). The fixed angles stayed at least 0.176 at 15 qubits and 0.056 at 18 qubits, far above uniform one-hot sampling, while per-instance training collapsed below 0.01 on 3 and 6 of the instances. In mean P_{opt}, at 15 qubits the fixed angles were higher on average but not significantly so ($p = 0.105$, Wilcoxon); at 18 qubits the fixed angles were higher on average but not significantly so ($p = 0.557$, Wilcoxon). A sampler fails on exactly these collapsed instances, so success within 32 shots rose from 63.2% to 99.9% at 15 qubits and from 39.1% to 91.5% at 18 qubits. Under two-qubit noise the advantage persisted: at $\epsilon = 0.01$ the fixed angles kept $P_{\mathrm{opt}} = 0.182$ against 0.108 for per-instance angles (better on 8 of 10 instances). With ten instances per size, the test shows that the angles do not break as the problem grows, not that the gain is stable.

E. Encoding Exactness

In every one of the 30 development instances, some infeasible one-hot plan had zero penalty, because three groups whose pairs fit overloaded a shelter together. The minimiser of (2) was nevertheless the true optimum in 93.3% of instances, because such plans were usually costlier than the optimum. The encoding is therefore approximate, and every sample must be verified exactly.

F. Sensitivity to Gate Noise

We simulated gate-level noise by quantum trajectories on the first 10 instances. In each of 200 runs per circuit every two-qubit gate, including the capacity couplings, the XY rotations and the W-state preparation, fails with probability ϵ and then applies one of the 15 non-identity two-qubit Pauli operators. Table V compares this with a global depolarising model, in which the circuit returns its ideal state with probability $F = (1-\epsilon)^{N_2}$ and a uniformly random bitstring otherwise:

$$P^{\epsilon}_{\mathrm{opt}} = F\,P_{\mathrm{opt}} + (1-F)\,n_{\mathrm{opt}}/2^n. \tag{7}$$

TABLE V
P_{opt} AT DEPTH 4 UNDER TWO-QUBIT NOISE (10 INSTANCES)

	X mixer		XY mixer	
ϵ	traj.	global	traj.	global
0.001	0.045	0.044	0.162	0.161
0.005	0.038	0.036	0.128	0.121
0.01	0.033	0.028	0.105	0.086
0.02	0.023	0.016	0.058	0.043

traj. = mean over 200 Pauli-error trajectories; global = model (7).

At $\epsilon = 0.01$, of the order reported for current superconducting processors, the XY mixer kept $P_{\mathrm{opt}} = 0.105$, 3.2× the X mixer's 0.033. The global model is pessimistic (0.086), since many Pauli errors barely change the output distribution.

G. Classical Baselines and Scaling

Exhaustive search over the 81 one-hot plans took 0.90 ms per instance. The greedy rule found a feasible plan in 100.0% of instances and the optimum in 93.3%. Simulated annealing with 20 restarts reached the optimum in 80.0% and a feasible plan in 90.0% in 128 ms; a single short run of 60 sweeps reached only 10.0%. Training one QAOA configuration to $p = 4$ took several seconds of simulation, so at this size QAOA is not competitive on time and the comparison concerns solution quality per circuit.

A scaling run on ten instances per size, $G = 2, \ldots, 6$ at $p = 2$, kept XY above uniform one-hot sampling at every size (0.006 at 18 qubits) while the X mixer fell below it from 12 qubits on; one training run at 18 qubits took 99.4 s against 8.14 ms for exhaustive search.

VII. DISCUSSION AND LIMITATIONS

Three findings bear on moving such problems to hardware. First, the one-hot constraint belongs in the mixer: the ring-XY mixer beat the transverse-field mixer on almost every instance and seed, and a tuned penalty did not close the gap. Capacity is the remaining gap: a mixer confined to the feasible subspace roughly doubled P_{opt}, but its state preparation needs the feasible set, so a practical circuit that respects capacity remains open. Second, transfer needs a common energy scale: without one the fixed angles collapsed, and with ours or another normalisation a single angle set per depth served new disruptions better than per-instance training, including stronger optimizers, at a one-time cost that pays back after about 32 disruptions. Third, classical methods solve these instances exactly in milliseconds, and the pairwise capacity encoding admits infeasible penalty-free plans, so a classical verifier must check every sample.

The study has clear limits. The main results are noiseless and the noise model ignores single-qubit and correlated errors, so the probabilities are upper bounds for hardware. The twin

is synthetic and the city instances use real roads but sampled demand and one disruption pattern, so transfer to recorded events and to other disruption types remains untested, and shelter accessibility never constrained the plan. Better angles than ours exist, as the warm start shows, and no exhaustive angle search was run; the size test stops at 18 qubits with ten instances per size, and the comparison with the Grover mixer has too few instances to show equivalence. Circuits were not compiled or routed for hardware.

Threats to validity remain. All variants used the same budget and starts, so the mixer comparison is fair, but absolute P_{opt} values depend on that budget, and success@N assumes independent shots. A deployed verifier can check feasibility but, unlike our exhaustive reference, not optimality. Future work will test transfer on recorded events, compare slack-variable capacity encodings and run the fixed-angle XY circuit on hardware.

VIII. Conclusion

On shelter-assignment instances drawn from a flood digital twin, a ring-XY mixer that keeps every group assigned to exactly one shelter gave QAOA a significantly higher probability of the optimal plan than the transverse-field mixer across instances and optimizer seeds. Capacity still enters only as a penalty, and a mixer confined to the feasible subspace showed how much is left to gain. Angles fixed on development instances reached $P_{\mathrm{opt}} = 0.306$ on new disruption instances with no per-instance evaluations, above per-instance training with COBYLA or L-BFGS-B, because the cost scaling puts every instance on one energy scale; without it they collapsed. On real road networks of 6 cities they matched per-instance training and found the optimum within 32 shots far more often. Exhaustive search solves the same instances in about a millisecond, so these results identify formulation and training choices for future hardware experiments, not a present-day advantage.

Acknowledgment

The authors thank the OpenStreetMap contributors and Open-Meteo for openly available data used by the digital twin. In line with the IEEE policy on AI-generated content, the authors disclose that Claude (Anthropic) was used to help edit and restructure the text of all sections and to draft the simulation, experiment and plotting scripts. All experiments use the authors' own software and can be reproduced with fixed seeds. The authors checked every number, claim and reference and take full responsibility for the content.

References

[1] A. Lucas, "Ising formulations of many NP problems," *Front. Phys.*, vol. 2, Art. no. 5, 2014, doi: 10.3389/fphy.2014.00005.

[2] F. Glover, G. Kochenberger, and Y. Du, "Quantum bridge analytics I: A tutorial on formulating and using QUBO models," *4OR*, vol. 17, no. 4, pp. 335–371, 2019, doi: 10.1007/s10288-019-00424-y.

[3] A. R. Cadeliña *et al.*, "D-Wave implementation of quantum annealing for optimal resource allocation in disaster response operation of Marikina City," *ECTI Trans. Comput. Inf. Technol.*, vol. 18, no. 1, pp. 24–33, 2024, doi: 10.37936/ecti-cit.2024181.253577.

[4] A. Abbas *et al.*, "Challenges and opportunities in quantum optimization," *Nat. Rev. Phys.*, vol. 6, pp. 718–735, 2024, doi: 10.1038/s42254-024-00770-9.

[5] E. Farhi, J. Goldstone, and S. Gutmann, "A quantum approximate optimization algorithm," arXiv:1411.4028, 2014.

[6] S. Hadfield, Z. Wang, B. O'Gorman, E. G. Rieffel, D. Venturelli, and R. Biswas, "From the quantum approximate optimization algorithm to a quantum alternating operator ansatz," *Algorithms*, vol. 12, no. 2, Art. no. 34, 2019, doi: 10.3390/a12020034.

[7] Z. Wang, N. C. Rubin, J. M. Dominy, and E. G. Rieffel, "XY mixers: Analytical and numerical results for the quantum alternating operator ansatz," *Phys. Rev. A*, vol. 101, no. 1, Art. no. 012320, 2020, doi: 10.1103/PhysRevA.101.012320.

[8] F. G. Fuchs, K. O. Lye, H. M. Nilsen, A. J. Stasik, and G. Sartor, "Constraint preserving mixers for the quantum approximate optimization algorithm," *Algorithms*, vol. 15, no. 6, Art. no. 202, 2022, doi: 10.3390/a15060202.

[9] A. Bärtschi and S. Eidenbenz, "Grover mixers for QAOA: Shifting complexity from mixer design to state preparation," in *Proc. IEEE Int. Conf. Quantum Comput. Eng. (QCE)*, 2020, pp. 72–82, doi: 10.1109/QCE49297.2020.00020.

[10] H. D. Sherali, T. B. Carter, and A. G. Hobeika, "A location-allocation model and algorithm for evacuation planning under hurricane/flood conditions," *Transp. Res. B, Methodol.*, vol. 25, no. 6, pp. 439–452, 1991, doi: 10.1016/0191-2615(91)90037-J.

[11] K. Blekos *et al.*, "A review on quantum approximate optimization algorithm and its variants," *Phys. Rep.*, vol. 1068, pp. 1–66, 2024, doi: 10.1016/j.physrep.2024.03.002.

[12] F. G. Fuchs and R. Pariente Bassa, "LX-mixers for QAOA: Optimal mixers restricted to subspaces and the stabilizer formalism," *Quantum*, vol. 8, Art. no. 1535, 2024, doi: 10.22331/q-2024-11-25-1535.

[13] R. S. do Carmo, M. C. S. Santana, F. F. Fanchini, V. H. C. de Albuquerque, and J. P. Papa, "Warm-starting QAOA with XY mixers: A novel approach for quantum-enhanced vehicle routing optimization," arXiv:2504.19934, 2025.

[14] A. Gupta and S. R. Hassan, "Constraint-preserving QAOA for personnel rostering: Coverage-preserving and guarded-XY mixer constructions," arXiv:2607.09145, 2026.

[15] L. Zhou, S.-T. Wang, S. Choi, H. Pichler, and M. D. Lukin, "Quantum approximate optimization algorithm: Performance, mechanism, and implementation on near-term devices," *Phys. Rev. X*, vol. 10, no. 2, Art. no. 021067, 2020, doi: 10.1103/PhysRevX.10.021067.

[16] P. K. Barkoutsos, G. Nannicini, A. Robert, I. Tavernelli, and S. Woerner, "Improving variational quantum optimization using CVaR," *Quantum*, vol. 4, Art. no. 256, 2020, doi: 10.22331/q-2020-04-20-256.

[17] D. J. Egger, J. Mareček, and S. Woerner, "Warm-starting quantum optimization," *Quantum*, vol. 5, Art. no. 479, 2021, doi: 10.22331/q-2021-06-17-479.

[18] F. G. S. L. Brandão, M. Broughton, E. Farhi, S. Gutmann, and H. Neven, "For fixed control parameters the quantum approximate optimization algorithm's objective function value concentrates for typical instances," arXiv:1812.04170, 2018.

[19] A. Galda, X. Liu, D. Lykov, Y. Alexeev, and I. Safro, "Transferability of optimal QAOA parameters between random graphs," in *Proc. IEEE Int. Conf. Quantum Comput. Eng. (QCE)*, 2021, pp. 171–180, doi: 10.1109/QCE52317.2021.00034.

[20] R. Shaydulin, P. C. Lotshaw, J. Larson, J. Ostrowski, and T. S. Humble, "Parameter transfer for quantum approximate optimization of weighted MaxCut," *ACM Trans. Quantum Comput.*, vol. 4, no. 3, Art. no. 19, 2023, doi: 10.1145/3584706.

[21] M. P. Harrigan *et al.*, "Quantum approximate optimization of non-planar graph problems on a planar superconducting processor," *Nat. Phys.*, vol. 17, pp. 332–336, 2021, doi: 10.1038/s41567-020-01105-y.

[22] A. Bärtschi and S. Eidenbenz, "Deterministic preparation of Dicke states," in *Fundamentals of Computation Theory* (LNCS, vol. 11651). Cham, Switzerland: Springer, 2019, pp. 126–139, doi: 10.1007/978-3-030-25027-0_9.

[23] M. J. D. Powell, "A direct search optimization method that models the objective and constraint functions by linear interpolation," in *Advances in Optimization and Numerical Analysis*, S. Gomez and J.-P. Hennart, Eds. Dordrecht, The Netherlands: Kluwer, 1994, pp. 51–67, doi: 10.1007/978-94-015-8330-5_4.

[24] S. Kirkpatrick, C. D. Gelatt, and M. P. Vecchi, "Optimization by simulated annealing," *Science*, vol. 220, no. 4598, pp. 671–680, 1983, doi: 10.1126/science.220.4598.671.