# Implementing a Sensor Observation Service for Wi-Fi tracking data

Matthijs Bon Xander den Duijn Balazs Dukai





## Implementing a Sensor Observation Service for Wi-Fi tracking data

by

Matthijs Bon Xander den Duijn Balazs Dukai

GEO1007 course during the MSc programme Geomatics for the built environment at the Delft University of Technology,

Project duration: April 16, 2016 – June 9, 2016

to be presented on Friday May 20, 2016.



## Preface

Matthijs Bon Xander den Duijn Balazs Dukai Delft, January 2013

## Contents

1	Introduction	1
	1.1 Problem description	1
	1.2 Objectives	
	1.3 Methods	
2	Functionality	5
	2.1 52North application	5
	2.1.1 Database model	
3	Technical Description	7
	3.1 Preprocessing (of the wifilog data)	7
	3.2 Filling the tables	
	3.2.1 'Simple' tables	7
	3.2.2 FeatureOfInterest	7
	3.2.3 Series	7
	3.2.4 Observation	7
	3.2.5 ComplexValue	7
4	Status of the application	9
5	Conclusions and recommendations	11
Α		13

### Introduction

This report describes the process and results of the assignment for the GEO1007 course in the MSc Geomatics programme. For this assignment, the authors chose one of seven topics. The chosen topic focusses on implementing a Sensor Observation Service to publish the tracking data derived from the geomatics synthesis project on a server and test it in a SOS client, such as the 52 North application.

A Sensor Observation Service (SOS) is a service standardized by the Open Geospatial Consortium (OGC). The standard defines a web service interface for the discovery and retrieval of real time or archived data produced by all kinds of sensors like mobile or stationary as well as in-situ or remote sensors (OGC, 2016). A sensor can measure multiple things, e.g. a meteorological sensor can observe properties such as temperature, wind speed, humidity. The SOS standard focusses mainly on the observations of these sensors.

In this project, the focus lies on the Wi-Fi network of the TU Delft campus. The wireless access points (AP) used in the Wi-Fi network can be seen as sensors, and the devices registered by the APs can be seen as the measurement. Each devices can be identified by its unique mac address, but also other properties can be measured, i.e. the received signal strength and the signal to noise ratio (SNR). These are all observations that can be retrieved using a SOS. In the next sections the research question, objectives, methods and tools will be discussed.

#### 1.1. Problem description

Implementing a SOS from Wi-Fi tracking data is a topic that has little to no scientific literature. So far sensor observations services are most commonly used with sensors that observe natural or meteorological properties, such as temperature. Using it for publishing Wi-Fi tracking data is uncommon and will require much trial and error.

During this project, the research will be guided by the following question:

How can the 52North web application be used to publish and visualize the WiFi tracking data from the TU Delft eduroam network?

This research question can be divided into the following subjects which need to be addressed:

- · Research the 52North database model for a SOS
- · Setting up the SOS server
- · Testing the SOS client

These questions can be answered once the goals and objectives have been established.

#### 1.2. Objectives

To answer the research question and sub questions, the purpose of the research has to be clearly defined. The purpose of the research is captured into two main objectives:

2 1. Introduction

MUST	SHOULD
Automatically transform the raw WiFi-logs from the PostgreSQL database to an SOS-compliant data model.	Functionality to download raw WiFi-logs or trajectories.
Time series tracking data (subset WiFi-logs with time range) in the client	
COULD	WONT
	Push notification to the user when new data is available
	Push new data to the user. When subscribing, the user can decide to either receive the raw WiFi-logs or the trajectories.

Table 1.1: MoSCoW Rules

- To provide a method for publishing WiFi-based tracking data through an SOS service and visualize the data in a client. The user can view and subset the data in the client and eventually download it. This allows a quick, preliminary data filtering which speeds up the data analysis work flow.
- To set up a SES service which pushes newly added tracking data to the client/user.

To dive deeper into the steps that need to be taken to answer the research question, the objectives can be divided into sub-goals:

- Automatically transform the raw WiFi-logs from the PostgreSQL database to an SOS-compliant data model.
- Functionality to download raw WiFi-logs or trajectories.
- Time series tracking data (subset WiFi-logs with time range) in the client

Finally, to structure the objectives and goals and to define the scope of the project, the objectives are grouped using the MoSCoW rules (see Table 1.1). To achieve these goals, implementation of the SOS Core Profile is necessary, comprising the mandatory operations: GetCapabilities, DescribeSensor, GetObservation.

#### 1.3. Methods

Publishing the Wi-Fi tracking data using the SOS can be done using different methods. For this project multiple tools are used, these are listed below.

- PostgreSQL
- Python
- GeoServer
- Apache Tomcat
- 52North Application

The 52North application was used as a guide for the implementation of the SOS on the server. This application is very well documented on their website. An work flow combining Python and PostgreSQL is used to automate as much of the SQL that is needed for the implementation i.e. limiting the manual work.

#### **Occupancy vs Movement**

1.3. Methods

This project aligns with the Synthesis project of the MSc Geomatics programme. During that project, we focus on movement in and between buildings. The first idea was to publish this movement data using the SOS, but this soon became rather difficult. Because the SOS uses time series to organize the data, there are limitations on the use of the data. When consider the access points as sensors in the SOS, one observation can include a mac address, SNR and RSSI. The time series organize these measurements in a way that one access point can have multiple observations, but one observation (mac address in this case) can not be tracked. Another way of looking at this would be to consider each mac address as sensor and each observation is the access point that it connects to. The first method will consider the data as occupancy information, whereas the second method will consider it movement data, in which tracking one person over time is possible. Because the time in this project is limited, the decision was made to see the access points as sensors, i.e. considering not movement but occupancy.

# 2

## **Functionality**

The following chapter describes the OGC SOS standard implementation by the 52°North organization. The OGC SOS 2.0 standard was adopted in 2012 which serves the basis of the 52°North SOS 4.x implementation. Firstly the functionalities of the implementation are detailed, then the underlying data model is described.

#### 2.1. 52North application

The 52°North SOS 4.x supports the requriements of the SOS 2.0 specification, implementing all of its extensions and their operations:

- 1. Core
  - · GetCapabilities, GetObservation, DescribeSensor
- 2. Enhanced
  - · GetFeatureOfInterest, GetObservaitonById
- 3. Transactional
  - InsertSensor, UpdateSensorDescription, DeleteSensor, InsertObservation
- 4. Result Handling
  - InsertResultTemplate, InsertResult, GetResultTemplate, GetResult

Additionally, 52°North SOS 4.x offers the following main features:

- SOS API
- Persistence framework to easily change the underlying database management system and database model (*Hibernate* and *Hibernatespatial*)
- Administration GUI
- · Installer GUI
- Bundle including SWC REST-API and JavaScript SOS Client
- RESTFul binding extension

6 2. Functionality

Table name	Description
codespace	contains the {codespace} and {codespacename} for the identifiers of Procedure, Observable
featureOfInterest	the geometries of the observations
featureOfInterestType	the type of the geometries of the observations
observableProperty	parameters that are observed
series	describes a series, a combination of featureOfInterest, observableProperty and procedure
observation	contains the observations
observationHasOffering	relates the offerings to the observations
offering	needed for structuring the data in a SOS server
procedure	the processes thorough which the observed values were generated
procedureDescriptionFormat	the format in which procedures shall be described
unit	units of a measurement
textvalue	contains the measured values, which are of type OM_TextObservation
observationConstellation	look-up table to check if the observation type of the InsertObservation,request is valid for t
observationType	stores the observation types
	Table 2.1: Tables in the Core database model
Table name	Description
featureRelation	hierarchy of features
offeringAllowedFeatureType	look-up table for the feature types which are valid for the offering
offeringAllowedObservationTy <sub>l</sub>	pe look-up table for the observation types which are valid for the offering
resultTemplate	holds the result template information which are necessary for the result handling opera-
validProcedureTime	stores the procedure description

Table 2.2: Tables in the Transactional database model

#### 2.1.1. Database model

The 52°North SOS 4.x database model is divided into two major profile, **Core** and **Transactional** profile. The Core database model implements the OGC SOS 2.0 *Core* and *Extended* profiles, while the Transactional database model extends the Core model to implement the OGC SOS 2.0 *Transactional* and *Result Handling* profiles.

In the Core database model, the following tables (Table 2.1) are relevant for disseminating Wi-Fi tracking data:

In the Transactional database model, the following tables are relevant for disseminating Wi-Fi tracking data:

## **Technical Description**

#### 3.1. Preprocessing (of the wifilog data)

#### 3.2. Filling the tables

#### 3.2.1. 'Simple' tables

#### codespace

FeatureOfInterest::codeSpace is the codespace attribute for the identifier (*gml:identifier*) of the access points. As the GML 3.2. schema defines the *gml:identifier* is a "special identifier is assigned to an object by the maintaining authority with the intention that it is used in references to the object." Furthermore, the attribute *codeSpace* is of type *anyURI*. In the present case the Technical University Delft is the maintaining authority of the campus WLAN and with it the access points. Because there is no official repository that contains the identifiers of the access points, we defined the codespace as *tudelft-wlan*.

#### name and codespacename

Codespacename refers to the codespace for the *name* of the *featureOfInterest*. FeatureOfInterest:name refers to *gml:name* in the GML 3.2 schema. In the case of the TU Delft WLAN the access point names equal to the access point identifiers, thus they have the same codespace as well.

#### hibernatediscriminator

According to the SensorObservationService documentation provided by 52North's wiki page, four tables require the attribute 'hibernatediscriminator'. The wiki page describes this attribute as 'only needed for internal purposes', but this is rather unclear. Because there is no clear description on the value of this attribute, the value 'F' is chosen, as indicator for a 'False' value.

3.2.2. FeatureOfInterest

**3.2.3. Series** 

3.2.4. Observation

3.2.5. ComplexValue

## Status of the application

The application that was created during the course of this project is almost finished. The steps that needed to be taken to get from the raw Wi-Fi data to the SOS on the geoserver have all been taken, but some debugging is still to be done to have a final working application.

Setting up the geoserver was the easy part. The webapp that 52°North provided could be imported directly into the geoserver running on the local machines. The configuration of the 52°North SOS was slightly harder. The original Wi-Fi tracking data is on a remote server on the TU Delft campus, but the encoding for that server is in 'LATIN1', which is unsupported by the 52°North SOS. It required a new database with new encoding to get the SOS tables in the database. Filling the tables with the tracking data took most of the time, but using the 52°North application as a guide ensured that the correct attributes were used in the tables.

Finally, the 52°North webapp could be used to do sample queries on the database to check if the database model was correct. This worked and showed that the database model was correct. Figure 4.1 shows such a sample query and the result from the database.

SELECT DISTINCT identifier AS "Identifier",  ST_ASTEXT(geom) AS "Geometry",  ST_SRID(geom) AS "SRID"  FROM featureofinterest;					
	Identifier character varying(255)	Geometry text	SRID integer		
1	A-23-0-052	POINT(4.37550578727327 51.9988856445979)	4326		
2	A-36-0-132	POINT(4.37346394905794 51.9988525836389)	4326		
3	A-20-0-007	POINT(4.37355252109371 52.0022144047065)	4326		
4	campus				
5	A-134-0-111	POINT(4.37142624632561 52.0008242350308)	4326		

Figure 4.1: Test queries on the database

Additionally, sample requests can also be sent. These sample requests can be generated by the 52°North webapp test client. Such requests are GetCapabilities and GetFeatureOfInterest. The screenshots of these requests are depicted in appendix A.

From the bindings that are available to send the request (JSON, KVP, SOAP and POX), only the KVP (Key Value Pairs) seemed to work. Unfortunately the other bindings would result in errors. Without deeper understanding about SOS and these bindings, we were not able to debug the errors and create valid requests.

# 

## Conclusions and recommendations



```
vesos:GetFeatureOfInterestResponse xmlns:sos="http://www.opengis.net/sos/2.0" xmlns:xmi="http://www.opengis.net/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/samplingPatial/2.0" xmlns:qmi="http://www.opengis.net/samplingPatial/2.0" xmlns:qmi="http://www.opengis.net/samplingPatial/2.0" xmlns:qmi="http://www.opengis.net/samplingPatial/2.0" xmlns:qmi="http://www.opengis.net/samplingPatial/2.0" xmlns:qmi="http://www.opengis.net/samplingPatial/2.0" xmlns:qmi="http://www.opengis.net/samplingPatial/2.0" xmlns:qmi="http://www.opengis.net/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/gmi/description" xmlns:qmi="http://www.opengis.net/def/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/def/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/def/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/def/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/def/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/def/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/def/samplingSpatial/2.0" xmlns:qmi="http://www.opengis.net/def/crs/SPSC/0/4326">xmlns:qmi="http://www.opengis.net/def/crs/SPSC/0/4326">xmlns:qmi="http://www.opengis.net/def/crs/SPSC/0/4326">xmlns:qmi="http://www.opengis.net/def/crs/SPSC/0/4326">xmlns:qmi="http://www.opengis.net/def/crs/SPSC/0/4326">xmlns:qmi="http://www.opengis.net/def/crs/SPSC/0/4326">xmlns:qmi="http://www.opengis.net/def/crs/SPSC/0/4326">xmlns:qmi="http://www.opengis.net/def/crs/SPSC/0/4326">xmlns:qmi="http://www.opengis.net/def/crs/SPSC/0/4326">xmlns:qmi="http://www.opengis.net/def/crs/SPSC/0/4326">xmlns:qmi="http://www.opengis.net/def/crs/SPSC/0/4326">xmlns:qmi="http://www.opengis.net/def/crs/SPSC/0/4326">xmlns:qmi="http://www
```

Figure A.1: Sample request: GetFeatureOfInterest

Figure A.1 shows a sample request. The request that was sent to the SOS was http://localhost:8080/52n-sos-webapp/service?service=SOS&request=GetFeatureOfInterest&version=2.0.0

```
vossCapabilities wmlns:sos="http://www.opengis.net/sos/2.0" xmlns:xsis="http://www.vd.org/199/xlink" xmlns:fas="http://www.vd.org/199/xlink" xmlns:fas="http://www.opengis.net/fcs/2.0" versions="2.0.0" xsis:schemalocation="http://www.opengis.net/os/2.0" http://schemas.opengis.net/os/2.0 http://schemas.opengis.net/os/2.0/sosGetCapabilities.xdd http://www.opengis.net/os/2.0 http://schemas.opengis.net/os/2.0/sosGetCapabilities.xdd http://schemas.opengis.net/os/2.0 http://schemas.opengis.net/os/2.0/sosGetCapabilities.xdd http://schemas.opengis.net/os/2.0/sosGetCapabilities.xdd http://schemas.opengis.net/os/2.0 http://schemas.opengis.net/osoGetCapabilities.xdd http://schemas.openg
```

Figure A.2: Sample request: GetCapabilities

Figure A.2 shows a sample request. The request that was sent to the SOS was http://localhost:8080/52n-sos-webapp/service?service=SOS&request=GetFeatureOfInterest&version=2.0.0