

SOME CLASSIC CONCURRENCY PROBLEMS

AN INTRODUCTION

Joseph Kehoe¹

¹Department of Computing and Networking
SETU, Carlow Campus

Concurrency, 2023

MUTUAL EXCLUSION

MUTUAL EXCLUSION Prevent threads simultaneous access of a variable

- 1 Use a Mutex;
- 2 Use a Semaphore initialised to 1;
- 3 Use a buffered channel of size 1.

- Generalise mutual exclusion solution to allow a maximum of N threads access a critical section
 - Critical section is a block of code that we need to restrict concurrent access to
 - Only N threads can be in critical section at any one time ($N > 0$)
- We must show that Deadlock cannot occur under any circumstances
- We should also show fairness

Use a semaphore (initialised to N) or a buffered Channel (of size N)

- Two threads must reach a certain point before either can continue
 - Each must signal the other that it has arrived and
 - Wait until it gets a signal that its partner has also arrived
- We must show that Deadlock cannot occur under any circumstances
- We should also show fairness

Use Mutexes or Semaphores or Channels

- Rendezvous only works for two threads
- A barrier works for N threads
 - When first N-1 threads arrive at barrier they are blocked
 - When the Nth thread arrives they all continue

Hints on next slide!

- 1 We will need to keep track of the number of threads who have reached the barrier

do it now!

- 1 Break into groups. Each group must come up with a solution!