

Class 10: Structural Bioinformatics (Part 1)

Michael McClellan (PID: A169692395)

Table of contents

The PDB Database	1
2. Visualizing with Mol-star	3
3. Using the bio3d package in R	5
Molecular visualization in R	6
Predicting functional motions of a single structure	6

The PDB Database

The main repository of biomolecular structure data is called the Protein Data Bank (PDB for short). It is the second oldest database (after GenBank).

What is currently in the PDB? We can access current composition stats here.

```
stats <- read.csv("Data Export Summary.csv", row.names = 1)
stats
```

	X.ray	EM	NMR	Multiple.methods	Neutron	Other
Protein (only)	171,959	18,083	12,622	210	84	32
Protein/Oligosaccharide	10,018	2,968	34	10	2	0
Protein/NA	8,847	5,376	286	7	0	0
Nucleic acid (only)	2,947	185	1,535	14	3	1
Other	170	10	33	0	0	0
Oligosaccharide (only)	11	0	6	1	0	4
Total						
Protein (only)	202,990					
Protein/Oligosaccharide	13,032					
Protein/NA	14,516					
Nucleic acid (only)	4,685					
Other	213					
Oligosaccharide (only)	22					

Q1: What percentage of structures in the PDB are solved by X-Ray and Electron Microscopy.

```
x <- stats$X.ray
# Substitute comma for nothing
```

```
y <- (gsub(",", "", x))  
  
#convert to numeric  
sum(as.numeric(y))
```

```
[1] 193952
```

Turn this snippet into a function so I can use it any time I have this comma problem (i.e. the other columns of this stats table)

```
comma.sum <- function(x) {  
  # Substitute comma for nothing  
  y <- (gsub(",", "", x))  
  
  # convert to numerica  
  return(sum(as.numeric(y)))  
}
```

```
xray.sum <- comma.sum(stats$X.ray)  
em.sum <- comma.sum(stats$EM)  
total.sum <- comma.sum(stats$Total)
```

```
xray.sum/total.sum * 100
```

```
[1] 82.37223
```

```
em.sum/total.sum * 100
```

```
[1] 11.30648
```

```
(em.sum + xray.sum)/total.sum * 100
```

```
[1] 93.6787
```

Q2: What proportion of structures in the PDB are protein?

```
comma.sum(stats$Total[1]) / total.sum * 100
```

[1] 86.2107

Q3: Type HIV in the PDB website search box on the home page and determine how many HIV-1 protease structures are in the current PDB?

SKIPPED

2. Visualizing with Mol-star

Explore the HIV-1 protease structure with PDB code: 1HSG Mol-star homepage at: <https://molstar.org/viewer/>.




Figure 1: Figure 1. A first view of HIV-Pr




Figure 2: Figure 2. Molecular surface showing binding cavity



Figure 3: Figure 3. The catalytically important ASP 25 amino acids and drug interacting HOH 308

3. Using the bio3d package in R

The Bio3D package is focused on structural bioinformatics analysis and allows us to read and analyze PDB (and related) data.

```
library(bio3d)
```

```
pdb <- read.pdb("1hsg")
```

Note: Accessing on-line PDB file

```
pdb
```

```
Call: read.pdb(file = "1hsg")

Total Models#: 1
  Total Atoms#: 1686, XYZs#: 5058 Chains#: 2 (values: A B)

Protein Atoms#: 1514 (residues/Calpha atoms#: 198)
Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)

Non-protein/nucleic Atoms#: 172 (residues: 128)
Non-protein/nucleic resid values: [ HOH (127), MK1 (1) ]

Protein sequence:
PQITLWQRPLVTIKIGGQLKEALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYD
QILIEICGHKAIGTVLVGPTPVNIIGRNLLTQIGCTLNFPQITLWQRPLVTIKIGGQLKE
ALLDTGADDTVLEEMSLPGRWKPKMIGGIGGFIKVRQYDQILIEICGHKAIGTVLVGPTP
VNIIGRNLLTQIGCTLNF

+ attr: atom, xyz, seqres, helix, sheet,
      calpha, remark, call
```

```
attributes(pdb)
```

```
$names
[1] "atom" "xyz" "seqres" "helix" "sheet" "calpha" "remark" "call"

$class
[1] "pdb" "sse"
```

We can see atom data with `pdb$atom`:

```
head(pdb$atom)
```

	type	eleno	elety	alt	resid	chain	resno	insert	x	y	z	o	b
1	ATOM	1	N	<NA>	PRO	A	1	<NA>	29.361	39.686	5.862	1	38.10
2	ATOM	2	CA	<NA>	PRO	A	1	<NA>	30.307	38.663	5.319	1	40.62
3	ATOM	3	C	<NA>	PRO	A	1	<NA>	29.760	38.071	4.022	1	42.64
4	ATOM	4	O	<NA>	PRO	A	1	<NA>	28.600	38.302	3.676	1	43.40
5	ATOM	5	CB	<NA>	PRO	A	1	<NA>	30.508	37.541	6.342	1	37.87
6	ATOM	6	CG	<NA>	PRO	A	1	<NA>	29.296	37.591	7.162	1	38.40

	segid	elesy	charge
1	<NA>	N	<NA>
2	<NA>	C	<NA>
3	<NA>	C	<NA>
4	<NA>	O	<NA>
5	<NA>	C	<NA>
6	<NA>	C	<NA>

```
head(pdbseq(pdb))
```

1	2	3	4	5	6
"P"	"Q"	"I"	"T"	"L"	"W"

Molecular visualization in R

We can make quick 3D viz with the `view.pdb()` function:

```
library(bio3dview)
library(NGLVieweR)

# view.pdb(pdb, backgroundColor = "lightblue", colorScheme = "sse") |>
# setSpin()
```

```
sel <- atom.select(pdb, resno=25)

# view.pdb(pdb, cols = c("green", "orange"), highlight = sel, highlight.style =
"spacefill") |>
# setRock()
```

Predicting functional motions of a single structure

We can finish off today with a bioinformatics prediction of the functional motions of a protein.

We will run a Normal Mode Analysis (NMA).

```
adk <- read.pdb("6s36")
```

```
Note: Accessing on-line PDB file
PDB has ALT records, taking A only, rm.alt=TRUE
```

```
adk
```

```
Call: read.pdb(file = "6s36")

Total Models#: 1
  Total Atoms#: 1898, XYZs#: 5694 Chains#: 1 (values: A)

  Protein Atoms#: 1654 (residues/Calpha atoms#: 214)
  Nucleic acid Atoms#: 0 (residues/phosphate atoms#: 0)

  Non-protein/nucleic Atoms#: 244 (residues: 244)
  Non-protein/nucleic resid values: [ CL (3), HOH (238), MG (2), NA (1) ]


Protein sequence:
  MRIILLGAPGAGKGTQAQFIMEKYGIPQISTGDMRLRAAVKSGSELGKQAKDIMDAGKLV
  DELVIALVKERIAQEDCRNGFLLDGFPR TIPQADAMKEAGINVDYVLEFDVPDELIVDKI
  VGRRVHAPSGRVYHVKNPPKVEGKDDVTGEELTTRKDDQEETVRKRLVEYHQM TAPLIG
  YYSKEAEAGNTKYAKVDGTPVAEVRADLEKILG

+ attr: atom, xyz, seqres, helix, sheet,
      calpha, remark, call
```

```
m <- nma(adk)
```

```
Building Hessian...      Done in 0.014 seconds.
Diagonalizing Hessian... Done in 0.481 seconds.
```

```
plot(m)
```



```
# view.nma(m)
```

We can write out a trajectory of the predicted dynamics and view this in Mol-star.

```
mktrj(m, file = "nma.pdb")
```